

LOGIX INSULATED CONCRETE FORMS

DESIGN MANUAL

VERSION 2013

Publication History

List of changes from previous version 2013 includes

| | Changes |
|---|---|
| Section 2, Installation Guide | <ul style="list-style-type: none"> Section 2.7.7 - T-WALLS Added 10" and 12" size LOGIX T-walls to table Revised Section 2.7.7 to include LOGIX T-wall |
| Section 5, CAD Drawings - LOGIX ICF Forms | <ul style="list-style-type: none"> 5.1.23 LOGIX T-Wall Added 10" and 12" size LOGIX T-walls |
| Section 5, CAD Drawings - Residential | <ul style="list-style-type: none"> New drawing 5.5.6, LOGIX 6.25" Below- & Above-grade Wall W/ Brick Ledge New drawing 5.8.8, Gable End Wood Framed Connection Revised drawing 5.10.8, Brick Ledge Stirrup Detail, to include 10" Brick Ledge New drawing 5.10.21, Overhead Garage Door New drawing 5.10.22, Radon Barrier Slab New drawing 5.10.23, Pool Detail Forming for Coping Option 1 New drawing 5.10.24, Pool Detail Forming for Coping Option 2 New drawing 5.10.25, Pool Detail of Inlet/Outlet Fixture New drawing 5.10.26, Pool Detail at Footing New drawing 5.10.27, Pool Skimmer New drawing 5.10.28, Brick Ledge with Timber Post |
| Section 5, CAD Drawings - Commercial | <ul style="list-style-type: none"> New drawing 5.2.12, Foundation W/ Tie Xtenders Supporting Stone Veneer Revised drawing 5.9.7, Brick Ledge Stirrup Detail, to include 10" Brick Ledge New drawing 5.9.42, Concrete Encased Steel Column New drawing 5.9.43, Brick Ledge Shelf Angle |
| Section 6, US Engineering | <ul style="list-style-type: none"> Lintel Tables 4A to 4E, 5A to 5E Added note to clarify factored loads Minor editorial change Corrected note in Lintel Tables that referred to "Figure 8". Changed to read "Figure 4" |
| Section 6, Canadian Engineering | <ul style="list-style-type: none"> Lintel Tables 4A to 4E, 5A to 5E Added note to clarify factored loads |
| Section 6, US & Canadian Engineering | <ul style="list-style-type: none"> 6.4, Footing Width Tables Added notes to clarify footing size, and applicable uses |
| Section 7, Evaluation Reports (US) | <ul style="list-style-type: none"> 7.1.1, ICC-ES Updated to 2009 I-Codes 7.1.4, State of Florida Certificate of Approval Updated to 2010 Florida Building Code |

**LOGIX INSULATED CONCRETE FORMS
DESIGN MANUAL
VERSION 2012**

Publication History Cont'd

| | Changes |
|--|--|
| Section 7, Evaluation Reports (Canada) | <ul style="list-style-type: none">• 7.2.2, Ontario Ruling of the Minister Document no longer applicable due to ICFs now included in National Building Code. Document is available in the LOGIX Technical Library website• Minor Editorial Change: Section numbers changed to reflect removal of Section 7.2.2, Ontario Ruling of the Minister |

1.0 – SYSTEM OVERVIEW

TABLE OF CONTENTS

| | |
|---|--------|
| 1.1 – APPLICATION & USE | P. 1-3 |
| 1.2 – PRODUCT SPECIFICATION TABLE | P. 1-5 |

1.0 – SYSTEM OVERVIEW

1.1 – APPLICATION & USE





LOGIX Insulated Concrete Forms are used to create solid reinforced concrete walls that are pre-insulated for use both above and below grade. LOGIX walls are particularly effective for residential, light commercial, institutional, and industrial buildings, providing excellent insulation as well as thermal mass and structural strength. LOGIX walls offer a 4-hour fire resistance rating.

LOGIX Insulated Concrete Forms are based on the simple concept of modular interlocking blocks. These “blocks” or “forms” are made of expanded polystyrene (EPS) panels, held together with high-density polypropylene webs. LOGIX leads the industry in builder friendliness, featuring thick 2-3/4 inch (70 mm) foam in each panel. In fact, LOGIX XRV Panels can provide EPS panels as thick as 8 inches (203 mm). This not only adds insulating value, it also makes the block tougher and more resistant to normal jobsite handling.

LOGIX forms are dry stacked using a running bond. Reinforcing steel is inserted in the wall cavity as required, and the forms are filled with concrete to form a monolithic insulated wall.

LOGIX forms are generally 48 inches (1220 mm) in length and 16 inches (406 mm) in height. They come in a range of concrete core thicknesses, from 4 inch (102 mm) to 12 inch (305 mm), to accommodate most design requirements. In addition, LOGIX Xtenders can increase the core thickness to virtually any width wider than 12 inches (305 mm).

1.1 – APPLICATION & USE CONTINUED



LOGIX is available in a wide variety of special form units and accessories, including corners, transitions, ledges, panel systems, pilasters, Flex Bars, and Knock-down forms permit the LOGIX system to be adapted to many different situations. Most LOGIX forms are also available in 8 inch (203 mm) height for additional design flexibility.

The plastic webs that hold the LOGIX forms together are made from recycled plastic. In addition to form support, the webs are designed to conveniently hold reinforcing steel in place prior to concrete placement, and act as a fastening surface for wall finish materials. The outer face of the web is 14-3/8 inch (365 mm) high and 1-1/4 inch (32 mm) wide, and is embedded in the foam 1/2 inch (13 mm) deep to comply with EIFS siding manufacturer standards.

LOGIX offers solid products and quality service from seven key manufacturing locations situated throughout North America. Our products are designed to perform better in the field, providing trouble-free, profitable installations time after time. Our commitment to product quality and continual innovation is backed up by over 50 years of ICF manufacturing experience.

1.2 – PRODUCT SPECIFICATION TABLE

LOGIX manufactures both assembled and unassembled insulated concrete form units. LOGIX assembled forms, known as “LOGIX PRO”, are delivered to the job site as assembled form blocks. LOGIX unassembled forms (or knock-down forms), known as “LOGIX KD”, are delivered to the job site in components that make up the form blocks - the form panels and KD Connectors. LOGIX KD are assembled on the job site.

Below is a summary of the types of LOGIX PRO and LOGIX KD forms available.

LOGIX PRO (assembled form blocks)

| | DESCRIPTION |
|------------------------------------|--|
| LOGIX Pro | White in color |
| LOGIX Pro Platinum ³ | Offers higher R-value ¹ than LOGIX Pro. Grey in color. |
| LOGIX Pro TX | LOGIX Pro with termite resistant additive Preventol ² . White in color. |
| LOGIX Pro Platinum ³ TX | LOGIX Pro Platinum with Preventol. Grey in color. |

LOGIX KD (unassembled form blocks)

| | DESCRIPTION |
|-----------------------------------|---|
| LOGIX KD | White in color |
| LOGIX KD Platinum ³ | Offers higher R-value ¹ than LOGIX KD. Grey in color. |
| LOGIX KD TX | LOGIX KD with termite resistant additive Preventol ² . White in color. |
| LOGIX KD Platinum ³ TX | LOGIX KD Platinum with Preventol. Grey in color. |

Notes:

1. See Section 8.5 for LOGIX R-values.
2. Preventol is an effective termite resistant additive.
3. Care should be taken to protect exposed foam surfaces from reflected sunlight and prolonged solar exposure until wall cladding or finish material is applied. Shade exposed foam areas, or remove sources of reflective surfaces, where heat build up onto exposed foam might occur. For more information refer to BASF Technical Leaflet N-4 Neopor, “Recommendations for packaging, transporting, storing and installing building insulation products made from Neopor EPS foam.” (The BASF Technical Leaflet is attached to every bundle of LOGIX Platinum forms delivered to a job site).

1.2 – PRODUCT SPECIFICATION TABLE CONT'D

STRAIGHT FORMS

SYSTEM OVERVIEW

| LOGIX FORM PANELS | STANDARD | | | | | TAPER TOP | | | | | BRICK LEDGE | | | | | TRANSITION | | | | |
|-------------------------|----------|-------|------|------|------|-----------|-------|------|------|------|-------------|--------|--------|--------|--------|------------|--------|--------|--------|--------|
| | | | | | | | | | | | | | | | | | | | | |
| STANDARD | | | | | | | | | | | | | | | | | | | | |
| Conc. Core Thickness | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 |
| Width Top ¹ | 9.5 | 11.75 | 13.5 | 15.5 | 17.5 | 9.5 | 11.75 | 13.5 | 15.5 | 17.5 | 13.375 | 15.625 | 17.375 | 19.375 | 21.375 | 11.25 | 13.5 | 15.25 | 17.25 | 19.25 |
| Width Bot. ¹ | 9.5 | 11.75 | 13.5 | 15.5 | 17.5 | 9.5 | 11.75 | 13.5 | 15.5 | 17.5 | 9.5 | 11.75 | 13.5 | 15.5 | 17.5 | 9.5 | 11.75 | 13.5 | 15.5 | 17.5 |
| Form Type ² | KD/P | KD/P | KD/P | KD/P | KD | KD | KD/P | KD/P | KD/P | KD | KD/P | KD/P | KD/P | KD/P | KD | KD/P | KD/P | KD/P | KD | KD |
| TAPER TOP | | | | | | | | | | | | | | | | | | | | |
| Conc. Core Thickness | | | | | | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 |
| Width Top ¹ | | | | | | 9.5 | 11.75 | 13.5 | 15.5 | 17.5 | 13.375 | 15.625 | 17.375 | 19.375 | 21.375 | 11.25 | 13.5 | 15.25 | 17.25 | 19.25 |
| Width Bot. ¹ | | | | | | 9.5 | 11.75 | 13.5 | 15.5 | 17.5 | 9.5 | 11.75 | 13.5 | 15.5 | 17.5 | 9.5 | 11.75 | 13.5 | 15.5 | 17.5 |
| Form Type ² | | | | | | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD |
| BRICK LEDGE | | | | | | | | | | | | | | | | | | | | |
| Conc. Core Thickness | | | | | | | | | | | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 |
| Width Top ¹ | | | | | | | | | | | 17.25 | 19.5 | 21.25 | 23.25 | 25.25 | 15.125 | 17.375 | 19.125 | 21.125 | 23.125 |
| Width Bot. ¹ | | | | | | | | | | | 9.5 | 11.75 | 13.5 | 15.5 | 17.5 | 9.5 | 11.75 | 13.5 | 15.5 | 17.5 |
| Form Type ² | | | | | | | | | | | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD |
| TRANSITION | | | | | | | | | | | | | | | | | | | | |
| Conc. Core Thickness | | | | | | | | | | | | | | | | 4 | 6.25 | 8 | 10 | 12 |
| Width Top ¹ | | | | | | | | | | | | | | | | 13 | 15.25 | 17 | 19 | 21 |
| Width Bot. ¹ | | | | | | | | | | | | | | | | 9.5 | 11.75 | 13.5 | 15.5 | 17.5 |
| Form Type ² | | | | | | | | | | | | | | | | KD | KD | KD | KD | KD |

1. Width at Top and Bottom is measured from outside face to outside face of forms.

2. "KD" and "P" denotes LOGIX KD (unassembled forms) and LOGIX PRO (assembled forms), respectively.

www.logixcf.com

Good. Solid. Green.™

1 – 6

LOGIX®
INSULATED CONCRETE FORMS

1.2 – PRODUCT SPECIFICATION TABLE CONT'D

STRAIGHT FORMS with XRV

| LOGIX FORM PANELS | XRV4 | | | | | XRV5 | | | | | XRV6 | | | | | XRV7 | | | | | XRV8 | | | | |
|----------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| STANDARD | | | | | | | | | | | | | | | | | | | | | | | | | |
| Conc. Core Thickness | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 |
| Width Top¹ | 10.75 | 13 | 14.75 | 16.75 | 18.75 | 11.75 | 14 | 15.75 | 17.75 | 19.75 | 12.75 | 15 | 16.75 | 18.75 | 20.75 | 13.75 | 16 | 17.75 | 19.75 | 21.75 | 14.75 | 17 | 18.75 | 20.75 | 22.75 |
| Width Bot.¹ | 10.75 | 13 | 14.75 | 16.75 | 18.75 | 11.75 | 14 | 15.75 | 17.75 | 19.75 | 12.75 | 15 | 16.75 | 18.75 | 20.75 | 13.75 | 16 | 17.75 | 19.75 | 21.75 | 14.75 | 17 | 18.75 | 20.75 | 22.75 |
| Form Type² | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD |
| TAPER TOP | | | | | | | | | | | | | | | | | | | | | | | | | |
| Conc. Core Thickness | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 |
| Width Top¹ | 10.75 | 13 | 14.75 | 16.75 | 18.75 | 11.75 | 14 | 15.75 | 17.75 | 19.75 | 12.75 | 15 | 16.75 | 18.75 | 20.75 | 13.75 | 16 | 17.75 | 19.75 | 21.75 | 14.75 | 17 | 18.75 | 20.75 | 22.75 |
| Width Bot.¹ | 10.75 | 13 | 14.75 | 16.75 | 18.75 | 11.75 | 14 | 15.75 | 17.75 | 19.75 | 12.75 | 15 | 16.75 | 18.75 | 20.75 | 13.75 | 16 | 17.75 | 19.75 | 21.75 | 14.75 | 17 | 18.75 | 20.75 | 22.75 |
| Form Type² | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD |
| BRICK LEDGE | | | | | | | | | | | | | | | | | | | | | | | | | |
| Conc. Core Thickness | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 |
| Width Top¹ | 14.625 | 16.875 | 18.625 | 20.625 | 22.625 | 15.625 | 17.875 | 19.625 | 21.625 | 23.625 | 16.625 | 18.875 | 20.625 | 22.625 | 24.625 | 17.625 | 19.875 | 21.625 | 23.625 | 25.625 | 18.625 | 20.875 | 22.625 | 24.625 | 26.625 |
| Width Bot.¹ | 10.75 | 13 | 14.75 | 16.75 | 18.75 | 11.75 | 14 | 15.75 | 17.75 | 19.75 | 12.75 | 15 | 16.75 | 18.75 | 20.75 | 13.75 | 16 | 17.75 | 19.75 | 21.75 | 14.75 | 17 | 18.75 | 20.75 | 22.75 |
| Form Type² | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD |
| TRANSITION | | | | | | | | | | | | | | | | | | | | | | | | | |
| Conc. Core Thickness | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 |
| Width Top¹ | 12.5 | 14.75 | 16.5 | 18.5 | 20.5 | 13.5 | 15.75 | 17.5 | 19.5 | 21.5 | 14.5 | 16.75 | 18.5 | 20.5 | 22.5 | 15.5 | 17.75 | 19.5 | 21.5 | 23.5 | 16.5 | 18.75 | 20.5 | 22.5 | 24.5 |
| Width Bot.¹ | 10.75 | 13 | 14.75 | 16.75 | 18.75 | 11.75 | 14 | 15.75 | 17.75 | 19.75 | 12.75 | 15 | 16.75 | 18.75 | 20.75 | 13.75 | 16 | 17.75 | 19.75 | 21.75 | 14.75 | 17 | 18.75 | 20.75 | 22.75 |
| Form Type² | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD |































1. Width at Top and Bottom is measured from outside face to outside face of forms.
2. "KD" and "P" denotes LOGIX KD (unassembled forms) and LOGIX PRO (assembled forms), respectively.

SYSTEM OVERVIEW

1.2 – PRODUCT SPECIFICATION TABLE CONT'D

XRV FORMS

SYSTEM OVERVIEW

| LOGIX FORM PANELS | XRV4 | | | | | XRV5 | | | | | XRV6 | | | | | XRV7 | | | | | XRV8 | | | | |
|-------------------------|---|-------|----|----|----|---|-------|----|----|----|---|-------|----|----|----|---|-------|----|----|----|---|-------|----|----|----|
| |  | | | | |  | | | | |  | | | | |  | | | | |  | | | | |
| |  | | | | |  | | | | |  | | | | |  | | | | |  | | | | |
| Conc. Core Thickness | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 |
| Width Top ¹ | 12 | 14.25 | 16 | 18 | 20 | 13 | 15.25 | 17 | 19 | 21 | 14 | 16.25 | 18 | 20 | 22 | 15 | 17.25 | 19 | 21 | 23 | 16 | 18.25 | 20 | 22 | 24 |
| Width Bot. ¹ | 12 | 14.25 | 16 | 18 | 20 | 13 | 15.25 | 17 | 19 | 21 | 14 | 16.25 | 18 | 20 | 22 | 15 | 17.25 | 19 | 21 | 23 | 16 | 18.25 | 20 | 22 | 24 |
| Form Type ² | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD |
| |  | | | | |  | | | | |  | | | | |  | | | | |  | | | | |
| Conc. Core Thickness | | | | | | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 |
| Width Top ¹ | | | | | | 14 | 16.25 | 18 | 20 | 22 | 15 | 17.25 | 19 | 21 | 23 | 16 | 18.25 | 20 | 22 | 24 | 17 | 19.25 | 21 | 23 | 25 |
| Width Bot. ¹ | | | | | | 14 | 16.25 | 18 | 20 | 22 | 15 | 17.25 | 19 | 21 | 23 | 16 | 18.25 | 20 | 22 | 24 | 17 | 19.25 | 21 | 23 | 25 |
| Form Type ² | | | | | | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD |
| |  | | | | |  | | | | |  | | | | |  | | | | |  | | | | |
| Conc. Core Thickness | | | | | | | | | | | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 |
| Width Top ¹ | | | | | | | | | | | 16 | 18.25 | 20 | 22 | 24 | 17 | 19.25 | 21 | 23 | 25 | 18 | 20.25 | 22 | 24 | 26 |
| Width Bot. ¹ | | | | | | | | | | | 16 | 18.25 | 20 | 22 | 24 | 17 | 19.25 | 21 | 23 | 25 | 18 | 20.25 | 22 | 24 | 26 |
| Form Type ² | | | | | | | | | | | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD |
| |  | | | | |  | | | | |  | | | | |  | | | | |  | | | | |
| Conc. Core Thickness | | | | | | | | | | | | | | | | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 |
| Width Top ¹ | | | | | | | | | | | | | | | | 18 | 20.25 | 22 | 24 | 26 | 19 | 21.25 | 23 | 25 | 27 |
| Width Bot. ¹ | | | | | | | | | | | | | | | | 18 | 20.25 | 22 | 24 | 26 | 19 | 21.25 | 23 | 25 | 27 |
| Form Type ² | | | | | | | | | | | | | | | | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD |
| |  | | | | |  | | | | |  | | | | |  | | | | |  | | | | |
| Conc. Core Thickness | | | | | | | | | | | | | | | | | | | | | 4 | 6.25 | 8 | 10 | 12 |
| Width Top ¹ | | | | | | | | | | | | | | | | | | | | | 20 | 22.25 | 24 | 26 | 28 |
| Width Bot. ¹ | | | | | | | | | | | | | | | | | | | | | 20 | 22.25 | 24 | 26 | 28 |
| Form Type ² | | | | | | | | | | | | | | | | | | | | | KD | KD | KD | KD | KD |

1. Width at Top and Bottom is measured from outside face to outside face of forms.

2. "KD" and "P" denotes LOGIX KD (unassembled forms) and LOGIX PRO (assembled forms), respectively.

Good. Solid. Green.™

www.logixicf.com

1 – 8

LOGIX®
INSULATED CONCRETE FORMS

CORNER FORMS

| | Left Hand Corner Form | Right Hand Corner Form |
|-----------------------------------|--------------------------|-----------------------------|
| 4 inch Concrete Core Thickness | <p>Form height = 16"</p> | <p>(dimensions similar)</p> |
| Form Type ¹ | KD/P | KD/P |
| 6.25 inch Concrete Core Thickness | <p>Form height = 16"</p> | <p>(dimensions similar)</p> |
| Form Type ¹ | KD/P | KD/P |
| 8 inch Concrete Core Thickness | <p>Form height = 16"</p> | <p>(dimensions similar)</p> |
| Form Type ¹ | KD/P | KD/P |
| 10 inch Concrete Core Thickness | <p>Form height = 16"</p> | <p>(dimensions similar)</p> |
| Form Type ¹ | KD/P | KD/P |
| 12 inch Concrete Core Thickness | <p>Form height = 16"</p> | <p>(dimensions similar)</p> |
| Form Type ¹ | KD | KD |







1. "KD" and "P" denotes LOGIX KD (unassembled forms) and LOGIX PRO (assembled forms), respectively.

1.2 – PRODUCT SPECIFICATION TABLE CONT'D

45° CORNER FORMS

Left Hand 45° Form

Right Hand 45° Form

| SYSTEM OVERVIEW | 4 inch Concrete Core Thickness | Left Hand 45° Form | Right Hand 45° Form |
|-----------------|-----------------------------------|---|--|
| | |  |  |
| | Form Type ¹ | KD/P | KD/P |
| | 6.25 inch Concrete Core Thickness |  |  |
| | Form Type ¹ | KD/P | KD/P |
| | 8 inch Concrete Core Thickness |  |  |
| | Form Type ¹ | KD/P | KD/P |

1. "KD" and "P" denotes LOGIX KD (unassembled forms) and LOGIX PRO (assembled forms), respectively.

HALF HEIGHT FORMS

| HALF HEIGHT STANDARD FORMS¹ | | |
|-----------------------------------|--------------------------------------|-----------------------------------|
| 4 inch Concrete Core Thickness | 6.25 inch Concrete Core Thickness | 8 inch Concrete Core Thickness |
| | | |







| | | HALF HEIGHT CORNER FORMS ¹ | | HALF HEIGHT 45° FORMS ¹ | |
|-------------------------|-----------|---------------------------------------|---------------------|------------------------------------|---------------------|
| | | Left Hand 45° Form | Right Hand 45° Form | Left Hand 45° Form | Right Hand 45° Form |
| Concrete Core Thickness | 4 inch | | | | |
| | 6.25 inch | | | | |
| | 8 inch | | | | |

1. Height of forms for Half Height Forms = 8 inches

ACCESSORIES

S Y S T E M O V E R V I E W

LOGIX ACCESSORIES

| | | |
|---|--|---|
|  |  |  |
| Flex Bars | Height Adjuster | End Cap |
|  |  |  |
| Pilaster | Horizontal & Vertical Hooks | Xtender |

2.0 – INSTALLATION GUIDE

TABLE OF CONTENTS

| | |
|--|---------|
| 2.1 – INTRODUCTION | P. 2-5 |
| 2.2 – USEFUL TOOLS & MATERIALS..... | P. 2-6 |
| 2.3 – ACCURATE FOOTINGS & SLABS..... | P. 2-8 |
| 2.3.1 – LOGIX FOOTING WITH FLEX BARS & XTENDERS | P. 2-9 |
| 2.4 – WALL LAYOUT | P. 2-10 |
| 2.5 – PRODUCT HANDLING & PLACEMENT..... | P. 2-11 |
| 2.6 – JOBSITE EFFICIENCY | P. 2-13 |
| 2.7 – LOGIX WALL CONSTRUCTION | P. 2-15 |
| 2.7.1 – THE FIRST COURSE | P. 2-17 |
| 2.7.2 – THE SECOND COURSE..... | P. 2-19 |
| 2.7.3 – ADDITIONAL COURSES | P. 2-21 |
| 2.7.4 – EXTENDED BRICK LEDGE..... | P. 2-23 |
| 2.7.5 – KNOCK-DOWN FORMS..... | P. 2-26 |
| 2.7.6 – LOGIX XRV PANELS..... | P. 2-29 |
| 2.7.7 – TEE WALLS..... | P. 2-31 |
| 2.7.8 – GABLE WALLS | P. 2-33 |
| 2.7.9 – RADIUS WALLS..... | P. 2-35 |
| 2.8 – REINFORCEMENT | P. 2-37 |
| 2.8.1 – BASIC PRINCIPLES OF REINFORCEMENT ... | P. 2-37 |
| 2.8.2 – HORIZONTAL REINFORCEMENT | P. 2-38 |
| 2.8.3 – VERTICAL REINFORCEMENT | P. 2-39 |
| 2.8.4 – LINTELS | P. 2-40 |
| 2.9 – WINDOW & DOOR BUCKS | P. 2-41 |
| 2.9.1 – TREATED PLYWOOD BUCK..... | P. 2-42 |
| 2.9.2 – SOLID WOOD BUCK..... | P. 2-43 |
| 2.9.3 – VINYL BUCK SYSTEM | P. 2-44 |
| 2.9.4 – RADIUS OPENINGS..... | P. 2-45 |
| 2.9.5 – METAL JAMBS | P. 2-47 |


2.0 – INSTALLATION GUIDE

| | |
|--|----------------|
| 2.10 – ADDITIONAL FORM SUPPORT | P. 2-48 |
| 2.11 – WALL BRACING & ALIGNMENT SYSTEM..... | P. 2-50 |
| 2.12 – FLOOR CONNECTIONS..... | P. 2-52 |
| 2.12.1 – LEDGER WITH ANCHOR | |
| BOLTS & JOIST HANGERS..... | P. 2-53 |
| 2.12.2 – STEEL ANGLE IRON LEDGER | P. 2-54 |
| 2.12.3 – BRICK LEDGE FOR TOP & BOTTOM CHORD | |
| BEARING SYSTEMS..... | P. 2-56 |
| 2.12.4 – LEDGER WITH SIMPSON | |
| BRACKET & JOIST HANGERS | P. 2-57 |
| 2.12.5 – McMILLAN JOIST HANGERS | P. 2-60 |
| 2.12.6 – TRANSITION LEDGE | P. 2-61 |
| 2.12.6.1 – TRANSITION LEDGE | |
| WITH TAPER TOP FORMS..... | P. 2-62 |
| 2.12.6.2 – TRANSITION LEDGE WITH | |
| LOGIX TRANSITION FORMS | P. 2-63 |
| 2.12.6.3 – TRANSITION LEDGE | |
| WITH CORNER BLOCKS | P. 2-64 |
| 2.12.7 – TAPER TOP WITH SILL PLATE | P. 2-66 |
| 2.12.8 – CONCRETE FLOOR SYSTEMS | P. 2-67 |
| 2.12.8.1 – PRECAST CONCRETE FLOORS | P. 2-68 |
| 2.12.8.2 – HAMBRO FLOOR SYSTEM..... | P. 2-69 |
| 2.12.8.3 – STEEL COMPOSITE FLOOR SYSTEM | P. 2-70 |
| 2.13 – ROOF CONNECTIONS | P. 2-71 |
| 2.13.1 – INSET SILL PLATE | P. 2-72 |
| 2.13.2 – TOP MOUNTED SILL PLATE..... | P. 2-73 |
| 2.14 – SERVICE PENETRATIONS..... | P. 2-74 |

2.0 – INSTALLATION GUIDE

| | |
|--|-----------------|
| 2.15 – CONCRETE PLACEMENT | P. 2-75 |
| 2.16 – ELECTRICAL INSTALLATIONS..... | P. 2-81 |
| 2.17 – PLUMBING INSTALLATIONS | P. 2-82 |
| 2.18 – INTERIOR & EXTERIOR FINISHES..... | P. 2-83 |
| 2.18.1 – VAPOR & AIR BARRIERS..... | P. 2-83 |
| 2.18.2 – INTERIOR DRYWALL | P. 2-84 |
| 2.18.3 – EXTERIOR SIDING | P. 2-86 |
| 2.18.4 – STEEL PANEL SIDING | P. 2-87 |
| 2.18.5 – WOOD SIDING..... | P. 2-88 |
| 2.18.6 – EIFS | P. 2-89 |
| 2.18.7 – TRADITIONAL STUCCO (CEMENT-BASED) | P. 2-90 |
| 2.18.8 – CEMENT COMPOSITE SIDING | P. 2-90 |
| 2.18.9 – BRICK VENEER..... | P. 2-91 |
| 2.18.10 – BELOW GRADE WATERPROOFING, DAMPPROOFING & PARGING..... | P. 2-92 |
| 2.18.10.1 – BELOW GRADE WATERPROOFING | P. 2-93 |
| 2.18.10.2 – ABOVE GRADE PARGING | P. 2-95 |
| 2.18.11 – ADDITIONAL SUPPORT FOR GRAB BARS, & OTHER HEAVY FIXTURES | P. 2-96 |
| 2.18.12 – HOLDING POWER OF SCREWS FASTENED TO LOGIX FURRING TABS..... | P. 2-97 |
| 2.19 – COURSE HEIGHT TABLE..... | P. 2-98 |
| 2.20 – RADIUS WALLS | P. 2-99 |
| 2.21 – TALL WALLS | P. 2-108 |
| 2.22 – TILT-UP WALL CONSTRUCTION | P. 2-110 |
| 2.23 – SUPPORTING PRODUCTS..... | P. 2-114 |

2.1 – INTRODUCTION



For builders who want a competitive edge, LOGIX offers solid products and friendly local service. Our products are designed to perform better in the field, providing trouble-free, profitable installations time after time. Our technical team is ready to respond to your queries with practical advice on quick and efficient installation. With contractor training provided through our numerous regional technical support offices, help is always close at hand. We are the most experienced ICF manufacturers in North America, manufacturing top quality products at our nine plants located throughout the United States and Canada.

For more information, or to contact a LOGIX representative, visit our website at www.logixicf.com and click "Contact Us". You can also register online to receive LOGIX updates.

This manual will be updated regularly. Current updates will be available at www.logixicf.com.

You can count on LOGIX. The ICF wall system that's built to last.


2.2 – USEFUL TOOLS & MATERIALS



- Pruning saw
- Cordless drill
- Screws
- Hot knife
- Electric chainsaw



- Fiberglass-reinforced tape
- Step ladder
- Rebar bender/cutter
- Internal vibrator
- Contractor-grade foam gun



- Low expansion foam adhesive
- Approved scaffold planks
- Transit or laser
- 48" (1220mm) level
- Bolt cutters
- String line


2.2 – USEFUL TOOLS & MATERIALS

CONTINUED



- Chalk line
- Wall alignment system (safety compliant)
- 36 inch (914 mm) plastic zip ties
- Concrete embedments
- Window and door buck material
- Sleeves for wall penetrations

2.3 – ACCURATE FOOTINGS & SLABS



The first step to a successful LOGIX installation is an accurate footing or slab. This means a footing or slab that is:

- Code compliant
- Designed in accordance with construction drawings and specifications
- Designed taking into account soil conditions, seismic area, number of stories, building loads, and water tables.



see section 6.0 – Engineering





STEP 1: Level footings with $\pm 1/4$ inch (± 6 mm).

STEP 2: Place footing dowels or keyways as required per plan specification or local building codes.

STEP 3: Once footing dowels are installed, cap all dowels for safety compliance.

The ideal increment for step footing is 16 inches (406 mm). Using LOGIX Half-height forms, Height Adjusters or Flex Bars it is possible to achieve 8 inch (203 mm), 4 inch (102 mm) or 2 inch (51 mm) footing increments, respectively.

2.3.1 – LOGIX FOOTING WITH FLEX BARS & XTENDERS



Building a footing with LOGIX can be done using LOGIX Flex Bars and Double Brick ledge.

STEP 1: Place the Double Brick Ledge upside down along the footing locations. With the Double Brick Ledge placed upside down the female interlocks will be at the top of the block. This means for the next course male/male LOGIX Flex Bars will be used.

STEP 2: Place the 2nd course using the male/male LOGIX Flex Bars.

STEP 3: Continue building the wall with LOGIX blocks for the remaining courses.

Be sure to add required reinforcement while placing courses, and install bracing as typically required.

To secure the courses of LOGIX Flex Bars in a LOGIX wall use zip ties to firmly connect the course below and above the LOGIX Flex Bars, and add additional form support where needed.

As an alternative to using Double Brick Ledge forms, LOGIX Standard form panels can be used with LOGIX Xtenders. LOGIX Xtenders increase the LOGIX concrete core thickness beyond 12 inches (305mm) to any footing width required.

2.4 – WALL LAYOUT



Accurate wall layout is critical to ensure a complete and profitable LOGIX project.

STEP 1: Verify that wall layout is in accordance with plans and specifications.

STEP 2: To ensure accurate 90° corners, use methods such as:

- Equal diagonal measurements
- 3-4-5 triangle
- Surveying

STEP 3: To ensure accurate 45° corners, use LOGIX 45° corner form units.


STEP 4: Snap chalk lines on footings or slab according to plan.

STEP 5: Make sure the outside face of the forms line up with the overall building dimensions.

Wall layout of radius or other corner angles is easily achieved with LOGIX.



2.5 – PRODUCT HANDLING & PLACEMENT



There are several methods to efficiently handle LOGIX forms. Unlike most ICF systems, the consistent 2-3/4 inch (70 mm) panel thickness on LOGIX forms means that handling damage is minimized. LOGIX XRV panels can also provide thicker panels up to 8 inches (203 mm)

- LOGIX Standard Forms arrive stacked on disposable skids.
- The forms are strapped together for easy handling.
- Unloading can be accomplished manually or using alternate lifting equipment.
- Standard forms can be moved by two people using two 2x4s
- Corner forms come in bundles of four or twelve, and can easily be carried by one or two people.
- Specialized dollies are another convenient way to move LOGIX bundles.
- When transporting forms on an open trailer, position the forms so the wind travels through the webs to minimize drag.
- When tying forms down on an open trailer, ensure the forms are well secured and avoid form damage from strapping materials.
- If job site conditions require form protection, LOGIX bundle bags can be ordered.

2.5 – PRODUCT HANDLING & PLACEMENT

CONTINUED



- LOGIX forms are produced to the tightest tolerance in the industry, with a length tolerance of $\pm 1/8$ inch (± 3 mm), and a height tolerance of $\pm 1/16$ inch (± 2 mm).

When forms are unloaded, it is necessary to measure forms to determine uniform length and height. It is suggested to measure 2 forms per skid. In the unlikely event that forms are out of spec, please contact the local LOGIX representative immediately.

2.6 – JOBSITE EFFICIENCY




An efficient jobsite means a faster and safer installation, and ultimately a higher quality finished project.

- Keep all materials and tools outside of the footing area until the chalk lines have been snapped and the wall layout is complete. Generally, construction is accomplished from within the perimeter of the structure.
 - When wall layout is complete, place forms at least 7 feet (2.134 m) inside the perimeter of the footings or slab to accommodate the wall alignment system.
 - Space skids of standard forms around the inside of the entire perimeter.
- ALERT:** When placing courses of forms, always take forms from the closest skid. This will eliminate the effects of normal manufacturing variations between skids.
- Periodic checking of dimensions ensures accurate wall construction.



2.6 – JOBSITE EFFICIENCY

CONTINUED



- Additional materials that should be located within the perimeter:
 - Window and door bucks
 - Rebar (straight or pre-bent)
 - Alignment system
 - Approved scaffold planks
 - Tools

2.7 – LOGIX WALL CONSTRUCTION



BARS
The spaces between the lines.

INTERLOCK


LINES
The lines between the bars allow cuts to be easily made that will allow the interlock to function consistently between courses. Cuts should always be made straight and square on the lines. Cutting anywhere but along these marks will create a stacked vertical joint.

INTERLOCK
The mechanism that holds successive courses of forms together.

WEB
polypropylene ties that holds the form unit together. The web also acts as the placement mechanism for reinforcing steel and the attachment surface for finish materials. There are six webs in each form unit.

2.7 – LOGIX WALL CONSTRUCTION


CONTINUED



When a form is cut, it can be identified using bars and webs. For example, a cut form with three bars, two webs, and three bars will be referred to as a "3-2-3".

By establishing a logical form pattern that takes into account the building dimensions, maximum efficiency will be achieved. It is important that the building dimensions have a tolerance of $\pm 1/2$ " inch (13 mm) or a stacked vertical joint will result. Such joints are acceptable if dimensions necessitate but will require additional form support on both sides of the form.

When building dimensions are based on 4 feet (1.219 m) increments, it is suggested to use all left or all right hand corners in each courses, alternating between subsequent courses.



2.7.1 – THE FIRST COURSE




STEP 1: Always place forms units with protruding interlock facing up.

STEP 2: Begin at a corner. Set corner block to chalk line.

STEP 3: Continue placing forms along the chalk line.

STEP 4: Secure forms end-to-end in the first course to maintain building dimensions.



STEP 5: When the forms are within 4 feet (1.219 m) or less of the second corner, place the second corner form.

STEP 6: Cut a standard form to fit the space left between the corner and the previous form. At this point, determine if adjustments are needed to the building dimensions so the cut can be made on a line.

If adjustments are needed, alter chalk lines accordingly.

If more than 3 bars are extending beyond any web, additional form support is required on both faces of the form.



2.7.1 – THE FIRST COURSE

CONTINUED



STEP 7: Continue around the wall in this manner until the first course is complete and dimensions are verified.

Leave the first course of forms in place across door openings and low windows until forms have been placed and building dimensions have been verified to maintain the interlock pattern above openings.

STEP 8: Place necessary rebar in first course as specified and according to local code.

STEP 9: Prior to starting the second course, install additional form support if required.

2.7.2 – THE SECOND COURSE



STEP 1: Starting at the original corner, place appropriate corner form to create a 16" (406mm) offset.

STEP 2: Fasten every corner end-to-end to adjoining forms using zip ties or adhesive foam.

STEP 3: Continue placing forms around the wall, working in the same direction as first course.


STEP 4: It is necessary to seat every form to the form below to minimize interlock settling during concrete placement.

STEP 5: All webs should line up vertically, except where building dimensions are other than 8 inch (203 mm) increments.

STEP 6: After completion of second course, place necessary rebar as specified and according to local code.

STEP 7: Place Form Lock in the second course, overlapping the lengths by roughly 8 inch (203 mm). Align the points of the zigzag pattern in the Form Lock directly above the webs.


STEP 8: Confirm that the wall is straight and level. If adjustment is required, shim or trim the bottom of the wall until level is achieved.



2.7.2 – THE SECOND COURSE

CONTINUED




STEP 9: Use foam adhesive to fasten the straightened and levelled wall to the footing or slab. Insert the  nozzle 1 inch (25 mm) at the base of every other web along the chalk line and inject foam between the block and the footing.

When vertical joints are less than 8 inches (203 mm) apart, additional form support is required.

It is important to note that at this point the wall pattern has been established. Course number 1 will be the pattern for all odd numbered courses (3, 5, 7, etc.). Course number 2 will be the pattern for all even numbered courses.

Wall alignment system to be installed at some point between the second and fourth courses, at no more than 7 feet (2.134 m) intervals. See **Section 2.11 - Wall Bracing & Alignment System** for further details.

INSTALLATION GUIDE



2.7.3 – ADDITIONAL COURSES



STEP 1: Fasten every corner end-to-end to adjoining forms using zip ties or adhesive foam.

STEP 2: Install Form Lock every fourth or fifth course after the second course.



STEP 3: After completion of each course, place necessary rebar as specified and according to local code.

STEP 4: Secure forms end-to-end in the top course to maintain building dimensions.

STEP 5: Secure top course to the forms below on both sides to prevent tipping during concrete placement.

STEP 6: If additional stories are planned, the interlock needs to be protected prior to concrete placement.

Female/female LOGIX Flex Bars can be used on the top of the wall to protect the interlocks during the pour.



STEP 7: Check building dimensions. Check corners for plumb.

STEP 8: Ensure straight walls by placing a string line at the top course set off from the wall using 3/4 inch (19 mm) pieces of wood placed in the corners. Check for straightness by running another 3/4 inch (19 mm) piece of wood between the string and wall.

2.7.3 – ADDITIONAL COURSES



CONTINUED

When vertical joints are less than 8 inches (203 mm) apart additional form support is required.

If you need to stack identical corners in subsequent courses, you will need to provide additional form support where the stacked joints are created.

Hold all reinforcement back 2 inches (51 mm) from door and window buck material to ensure proper concrete coverage.

2.7.4 – EXTENDED BRICK LEDGE



Brick Ledge forms come only in straight units, so mitered cuts on site must be made to create corners with these blocks. Two methods can be used:

1. Freehand miter cutting.
2. Using a template.

On a 6.25 inch (159 mm) LOGIX Brick Ledge always start a miter cut in the middle of the first web beyond the corner form.

When making any miter cut in a Brick Ledge form to create a 90° corner always angle the saw and make sure you follow this edge during the ENTIRE course of making the cut.


Extending a Brick Ledge block two webs beyond the corner block and making the cut will create a remaining piece that can be used for an inside corner elsewhere in the layout.

STEP 1: The first portion of the cut is vertical, then angle to the tip of the corner block below, always keeping the tip of the saw following the inside edge.

STEP 2: After making the miter cut, cut the far side of the block so it is flush with the inside edge of the corner form.

2.7.4 – EXTENDED BRICK LEDGE

CONTINUED



STEP 3: Place the second Brick Ledge in place to cut on the opposing side of the corner.

STEP 4: Cut the second Brick Ledge miter in a manner similar to the first miter.


When cutting the inside panel of the second mitered block, make the cut so it butts against the opposing panel.



STEP 5: Securely tape and foam the mitered corner, applying several rows of tape.

STEP 6: Install rebar in the Brick Ledge, making sure to install two 90° pieces extending 2 feet (0.610 m) in either direction.


Butt joints are preferred for rebar in outer edge of Brick Ledge.



STEP 7: Install long stirrups in each brick ledge cavity, including the every corner. See **Section 5** for stirrup details.


2.7.4 – EXTENDED BRICK LEDGE

CONTINUED



STEP 8: Remove foam from the corner cavity area to facilitate the flow of concrete into the corner cavity.

2.7.5 – KNOCK-DOWN FORMS



LOGIX Knock-down forms (LOGIX KD) are designed to offer the same benefits as the LOGIX solid forms (LOGIX PRO). However, LOGIX KD forms also


- reduce shipping costs and inventory requirements
- accommodates tilt-up wall panel construction
- allows hassle-free assembly of forms around complex rebar patterns (i.e. stirrup or rebar cage pattern in walls)
- allows custom block configurations (i.e. Taper Top-Brick Ledge, Transition block-Transition block, etc...)

PRODUCT DESCRIPTION

LOGIX KD forms consists of two expanded polystyrene (EPS) foam panels measuring 16 inches (406 mm) tall x 48 inches (1220 mm) wide x 2.75 inches (70 mm) thick. The panels are connected using KD Connectors, snap-in polypropylene ties spaced 8 inches (203 mm) on center to form the ICF. The KD Connectors are available in varying sizes that create 6.25, 8, 10 and 12 inch (159, 203, 254 and 305 mm) thick concrete walls. Corner panels are also available.

2.7.5 – KNOCKDOWN FORMS


CONTINUED



PRODUCT HANDLING

There are several methods to efficiently handle LOGIX KD forms. The high foam density and consistent 2-3/4 inch (70 mm) panel thickness on LOGIX KD means that handling damage is minimized. In addition, LOGIX XRV panels provide panel thickness up to 8 inches (203 mm). See next section for information on LOGIX XRV panels.

The forms arrive on-site unassembled. KD Connectors and panels arrive on-site packaged in boxes and bundled in stacks, respectively.



ASSEMBLING AND INSTALLATION

The KD Connectors connect to the polypropylene furring tabs embedded in the form panels. The furring tabs are spaced at 8 inches (203 mm) on center and act as solid attachment areas for drywall, cladding and other wall attachments. A top and bottom KD Connector is required for each furring tab.


To assemble the forms simply snap into place the top and bottom KD Connectors with the rebar slots facing upwards. This will accommodate two layers of rebar.

As the forms are assembled on-site they are stacked in place to form the walls. Stacking the blocks, including required tools, are the same when using LOGIX Pro forms.

INSTALLATION GUIDE

2.7.5 – KNOCKDOWN FORMS

CONTINUED



In addition, LOGIX recommends the following:


- Use foam adhesive, 2x4s, steel stud angles or other system that will keep the first course in place and properly aligned during the initial concrete pour.
- Zip tie adjacent forms at the fixed ends of the ties.
- Install bracing every 6 ft.
- Provide additional form support at corners of 12" LOGIX KD forms.

CORNER FORM SUPPORT



For any type of ICF knock-down system it is good practice to provide additional form support at the corners for 12" LOGIX KD forms.

To ensure a safe and proper concrete pour the following corner form support is recommended:

- Using 2.5 inch (64 mm) wood screws to fasten 2x6 vertically to the embedded furring tabs on both sides of the corner.
- For outside corners wrap steel strapping around the corners. For the bottom third of the concrete pour height evenly space two strappings for each course. Then one strap per course for the remaining pour height. Using 1.5 inch (38 mm) wood screws the bands should attach to at least two furring tabs that extend beyond the 2x6 on both sides of the corner.
- For inside corners apply typical bracing as required.



2.7.6 – LOGIX XRV PANELS



LOGIX XRV Panels are most useful for buildings in areas requiring higher energy savings or higher insulation values, such as places with extreme temperature swings or extremely cold climates. The LOGIX XRV Panels can provide R-values ranging from R-28 to R-66* by increasing the foam panel thickness from 2.75 inches (70 mm) to 8 inches (203 mm).

LOGIX XRV Panels are available in thicknesses of 4, 5, 6, 7 and 8 inches (102, 127, 152, 178 and 203 mm) and can be used to build walls with concrete cores of 4, 6.25, 8, 10 and 12 inches (102, 159, 203, 254 and 305 mm) thick. LOGIX XRV Panels employ the same tight fitting and secure interlock system found in LOGIX Pro (assembled forms) and the same furring tabs found in LOGIX KD forms. Thus LOGIX XRV Panels can be used in conjunction with LOGIX Pro and LOGIX KD.

STUCCO FINISHES

Cement or acrylic based stucco finishes should be applied according to manufacturer's installation instructions. When attaching wire mesh non-corrosive screws are recommended along with the minimum screw lengths listed below.

| Minimum Fastener Lengths |
|-----------------------------|
| 4" LOGIX XRV Panels - 2.75" |
| 5" LOGIX XRV Panels - 3.75" |
| 6" LOGIX XRV Panels - 4.75" |
| 7" LOGIX XRV Panels - 5.75" |
| 8" LOGIX XRV Panels - 6.75" |

Long screws and accessories for stucco applications are available through Wind-Lock at www.wind-lock.com.

*R-values include LOGIX ICF with minimum 4" concrete wall thickness and airfilm.

www.logixicf.com

Good. Solid. Green.™

2 – 29


LOGIX
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 11/10

2.7.6 – LOGIX XRV PANELS

CONTINUED



In addition, plastic or fibre mesh can be attached to a base coat applied over the LOGIX XRV Panel surface that has been prepared by rasping the surface.

CORNERS


Corners with LOGIX XRV Panels can be created with butt joints or miter cuts. The cuts should be made so that the embedded furring tabs are close to the corner edges. This will provide fastening points for form support and other corner attachments.

Make sure to add additional form support around the corners prior to placing concrete, and avoid placing concrete directly in the corners of LOGIX XRV Panels.




When applying stucco finishes attaching a corner bead or wrapping a plastic or fibre mesh in a base coat around the corners can add strength to the corners.

VERSATILITY

LOGIX is versatile enough to offer a choice of panel thickness, core thickness and web type. For a list of LOGIX KD and XRV combinations see **Section 8.1**.



2.7.7 – TEE WALLS



Wall T-junctions can be constructed using LOGIX T-walls, or by field-cutting LOGIX Standard forms.

LOGIX T-WALLS

LOGIX T-walls arrive to the job site assembled or disassembled.

When assembled LOGIX T-walls provide sizes that are commonly used in construction.

| LOGIX T-wall Sizes | Description |
|--------------------|--------------------------------|
| 4 to 6 | 4" connected to 6.25" LOGIX |
| 4 to 8 | 4" connected to 8" LOGIX |
| 4 to 10 | 4" connected to 10" LOGIX* |
| 4 to 12 | 4" connected to 12" LOGIX* |
| 6 to 6 | 6.25" connected to 6.25" LOGIX |
| 6 to 8 | 6.25" connected to 8" LOGIX |
| 6 to 10 | 6.25" connected to 10" LOGIX* |
| 6 to 12 | 6.25" connected to 12" LOGIX* |

*Assembled without diagonal ties

Each T-wall size comes in two different shapes so that a running bond pattern is created when the T-wall forms are stacked.

Installation of LOGIX T-walls is straightforward. As with all LOGIX forms, the T-walls are stacked in the usual running bond pattern, and follows the same basic installation instructions detailed in Section 2 of the LOGIX Design Manual.

FIELD-CUT T-WALLS

Each course of the through wall must have continuous horizontal bar or a minimum of 3 feet (0.914 m) length of rebar at proposed Tee. A pre-bent 90° rebar is required at every course of rebar.

2.7.7 – TEE WALLS

CONTINUED



STEP 1: Complete the first course of the "Through" (continuous) wall.

STEP 2: Use a felt-tip marker to mark the through wall where the Tee wall will butt against it.

STEP 3: Remove the foam from the Through wall where the Tee intersects, to the thickness of the concrete core.

STEP 4: Butt the first course of the Tee up against the Through wall.

STEP 5: Tie the first Tee wall web to the Through wall rebar using a zip tie or tie wire. A short length of rebar should be placed behind the face of the web that is being tied to stiffen it.


STEP 6: Additional exterior form support should be installed as required at every course.

STEP 7: Continue building the walls, following these steps at every course.


STEP 8: When the entire wall has been checked for plumb and square, apply foam adhesive to the entire butt joint.

Another option for building a Tee wall is to construct the entire Through wall first. This method requires pre-planning to ensure there is adequate reinforcements at every course to allow the Tee wall to be attached securely. All other steps above need to be applied.

INSTALLATION GUIDE



For full size CAD drawing see
Section 5, CAD Drawings



For full size CAD drawing see
Section 5, CAD Drawings






www.logixcf.com

Good. Solid. Green.™

2-32

LOGIX®
INSULATED CONCRETE FORMS

2.7.8 – GABLE WALLS



Gable walls can be constructed efficiently and with minimal job site waste using LOGIX Flex Bars.

The preferred method to construct a gable end is on the floor to be installed as a one-piece unit.

STEP 1: Lay the first course of LOGIX blocks for the gable wall.

STEP 2: Snap a chalk line for the sloped gable cuts and cut the LOGIX blocks to match the required gable slope at the ends of the wall. Save the remaining cut blocks for later use.


Gable cuts can be made with a pruning, reciprocating or other type of saw.

STEP 3: Place the 2nd course with female/female LOGIX Flex Bars. Cut the LOGIX Flex Bars to match the required gable slope at the ends of the wall. Save the remaining cut Flex Bars. They can be used for the end of the gable wall when placing another course of Flex Bars.

STEP 4: Lay the 3rd course of LOGIX blocks upside down so that the male interlocks of the LOGIX blocks match the female interlocks of the LOGIX Flex Bars from the previous second course. Use the saved cut pieces from the first course for the ends of the gable wall. These pieces when placed upside down will match the gable slope.

2.7.8 – GABLE WALLS

CONTINUED



STEP 5: Place the 4th course with male/male LOGIX Flex Bars. Cut the LOGIX Flex Bars to match the required gable slope at the ends of the wall. Save the remaining cut Flex Bars. They can be used for the end of the gable wall when placing another course of Flex Bars.

STEP 6: Continue the process to complete the gable wall.

- Zip tie successive courses of LOGIX blocks, and ensure that webs align vertically between courses.
- Screw 1x4s along the cut gable slope on both sides of the wall. Pieces of plywood can then be screwed into the 1x4s to help contain the concrete during placement.
- Check rebar is in place prior to concrete placement, and all necessary and roof attachment hardware is available, as it must be installed during or immediately after the pour.
- Use appropriate lifting equipment to place the sloped gable wall in place on the squared wall.
- Ensure that appropriate wall alignments and scaffolding system is in place for safe installation.

Another option for constructing a gable wall is to assemble the gable in place. Set the pitch for the gable by marking the first course appropriately. Subsequent courses should follow this pattern.



2.7.9 – RADIUS WALLS

Radius walls are easy to achieve with LOGIX.

STEP 1: Cut forms into 8 inch (203 mm) increments with web in center of each section.

STEP 2: Mark the inside and outside diameter of the curved wall on the footing or slab.

STEP 3: From the center of the circle, snap a radius line to the outside diameter line. This becomes your center radius for the next step.

STEP 4: On the outside diameter line, snap a radius line 4" (102mm) on each side of the center radius.

STEP 5: Set on of the 8 inch (203 mm) form sections, centering the web on the center radius. Line up the outside corners of the form section with the outside radius lines.

STEP 6: Mark the form section at the outside radius lines, and cut angles accordingly.

STEP 7: This form section now becomes a template, form which you can cut the other sections. Mark and cut all form section accordingly.

2.7.9 – RADIUS WALLS

CONTINUED

STEP 8: Zip ties, tape, or foam can now be used to connect all the form section into the wall. Repeat the steps for each course of radius wall.

STEP 9: This process will result in vertically stacked joints, and additional form support will be required prior to concrete placement.

2.8 – REINFORCEMENT

2.8.1 – BASIC PRINCIPLES OF REINFORCEMENT



Reinforcing steel (rebar) strengthens concrete walls to help minimize cracking and buckling under load due to backfill, wind, and other loads. Rebar also helps control cracking due to temperature swings and shrinkage.

A non-contact splice is typically the splice of choice in LOGIX walls except in heavily reinforced walls or in cases of narrow wall cavities.



Reinforcement around windows and doors needs to be installed as required.

Reinforcing steel must meet the requirements of ASTM A615, ASTM A996, or ASTM A706 for low-alloy steel. Minimum of Grade 40 (300MPa).

Reinforcing steel in a LOGIX wall must have minimum 3/4 inch (19 mm) concrete cover.



see section 6.0 – Engineering



Refer to LOGIX Design Manual for reinforcing tables or refer to EB118.

It is the responsibility of the installer to verify table rebar specifications with local building codes and engineer specs.

2.8.2 – HORIZONTAL REINFORCEMENT




STEP 1: Horizontal rebar, sized as required, should be placed in the wall as each course is installed.

STEP 2: Hold the reinforcement back from door and window openings by 2" (51mm).

STEP 3: Maintain the proper overlap splice length of 40d (40 x bar diameter) or 24 inch lap length, whichever is greater, or as otherwise specified when placing horizontal rebar. A non-contact lap splice is recommended.

STEP 4: The notch pattern on the LOGIX web allows for horizontal rebar to be alternated in location, course by course. This allows ideal support and positioning for vertical steel. Vertical rebar diameter will dictate horizontal offset from course to course.



2.8.3 – VERTICAL REINFORCEMENT



STEP 1: Install vertical rebar, as required, after all courses and horizontal reinforcement have been placed.

STEP 2: Place vertical reinforcement under windows, if required.

STEP 3: Place vertical rebar on each side of every opening as required.




STEP 4: Cold joints between upper floor walls and lower floor walls need to be reinforced with a lap length of 40d or 24 inch (610 mm) lap length, whichever is greater (unless otherwise specified).



It is the responsibility of the installer to verify table rebar specifications to comply with local building codes and engineer specs.

2.8.4 – LINTELS



Appropriate lintel rebar should be placed in the proper sequence directly above doors and windows to carry loads over these openings.

STEP 1: Before placing forms across the top of door or window openings, rest the bottom lintel bar on buck material. This provides easier access to rebar for fast lintel steel installs. Check to make sure the bottom lintel steel has enough clearance. It should be 1-1/2 to 2-1/2 inches (38 to 64 mm) from buck material.

STEP 2: Install a course of forms across the top of the buck.


STEP 3: Install Form Lock across the entire length of the course. In some cases it may be require to install top lintel rebar before installing Form Lock, in order to achieve necessary concrete cover.

STEP 4: Suspend the top lintel rebar 1-1/2 to 2-1/2 inches (38 to 64 mm) below the top of the form.

STEP 5: Use stirrups to hang the bottom lintel rebar from the top steel, making sure the bottom rebar is 1-1/2 to 2-1/2 inches (38 to 64 mm) above the buck material.

Consistent stirrup dimensions will maximize efficiency.

The top and bottom lintel rebar must extend 24 inches (610mm) beyond both sides of window and door opening.



For more lintel reinforcement details see Section 6.0 Engineering.

2.9 – WINDOW & DOOR BUCKS



Bucks provide attachment surfaces for windows and doors while holding back concrete from these openings during concrete placement. Mark the center and edges of openings as you place courses and cut blocks as needed.

Refer to the rough opening (R/O) dimensions for windows and doors. Provide for openings in the wall taking into consideration the thickness of the chosen buck material. See window and door manufacturer info for R/O dimensions.



Bucks can be made from vinyl or lumber. Pre-building lumber bucks saves time on the job site.

Cross bracing is required for all window and door bucks approximately 18 inches (457 mm) on center to help withstand the pressures of concrete placement.

Window and door openings within 4 feet (1.220 m) of corners require additional horizontal strapping from corner to across the opening.



Prior to placing window or door buck, confirm that bottom lintel rebar has been installed.



For more CAD drawings
see Section 5.9 CAD Drawings.

2.9.1 – TREATED PLYWOOD BUCK



Following are several methods for building bucks. Regardless of the method chosen, pre-planning is required to optimize chosen finish materials.

STEP 1: Rip 3/4 inch (19 mm) treated plywood to full form width.

STEP 2: Rip treated 2x4 diagonally on table saw at 180° angle.


STEP 3: Assemble buck with appropriate fasteners with 2x4s creating a dovetail detail.

STEP 4: Assemble buck sides and top with access holes cut in bottom piece for placement of concrete. Two 2x4s can also be used for the bottom to allow concrete placements.

STEP 5: Place pre-assembled buck in opening and fasten in place with foam adhesive. The buck can also be installed in opening as separate pieces.

STEP 6: Install temporary cross bracing to withstand concrete pressure. Attaching screws through the buck and into closest webs can provide additional buck support.

NOTE: Pressure treated wood for window bucks are normally required only if the bottom of the window buck frame is located at or below ground level. Check with local building codes to determine if your area requires pressure treated window bucks.



For full size CAD drawing see
Section 5, CAD Drawings


2.9.2 – SOLID WOOD BUCK



STEP 1: Choose appropriate wood product based on the dimension of the forms:

- 4" (102mm) form: 9.5" (241mm)
- 6.25" (159mm) form: 11.75" (298mm)
- 8" (203mm) form: 13.5" (343mm)
- 10" (254mm) form: 15.5" (394mm)

STEP 2: Cut top piece of buck to fit the width of the opening.



STEP 3: Cut sides of buck, remembering that the top piece rests on the side pieces.

STEP 4: Cut two 2x4s for the bottom to allow concrete placement.

STEP 5: Assemble buck and place in opening.

STEP 6: Once the buck is in place, it must be centered and secured. This can be done by attaching 1x4s to the edges of the buck, extending the edge of the 1x4 over the foam to hold the buck firmly in place. Alternately, the buck can be secured with foam adhesive and tape.

STEP 7: Solid wood bucks will require additional concrete anchors to create a permanent attachment to the concrete.

2.9.3 – VINYL BUCK SYSTEM




STEP 1: Cut the top piece of the vinyl buck to the width of the opening.

STEP 2: Install the top piece of vinyl buck over the forms so that it seats fully against forms. For additional support, the vinyl buck can be attached to the forms with foam adhesive after being properly cleaned with acetone.


STEP 3: Cut and install the bottom piece of the vinyl buck. Create appropriate holes for concrete placement and consolidation.

STEP 4: Cut and install the side pieces of the vinyl buck to seat against the top piece, resting on the bottom piece. Use foam adhesive for additional support if desired.

STEP 5: Install cross bracing as required.



2.9.4 – RADIUS OPENINGS



Radius windows and doors can be assembled at the site with shortened pieces of vinyl or lumber buck material.

STEP 1: Create the template for the radius opening with OSB or plywood that matches door or window rough opening.

STEP 2: Using template, draw outline of radius on wall, allowing for buck material thickness. Cut accordingly.

STEP 3: Cut buck material into approximately 4 inch (102 mm) widths to create radius buck.

STEP 4: Cut side and bottom buck pieces. Leave openings in the bottom piece for concrete placement and consolidation.

STEP 5: Assemble buck pieces in the opening in the following order:

- bottom
- sides
- radius top

2.9.4 – RADIUS OPENINGS CONTINUED


STEP 6: Once the buck is in place, it must be centered and secured. This can be done by attaching 1x4s to the edges of the buck, extending the edge of the 1x4 over the foam to hold the buck firmly in place. Alternately, the buck can be secured with foam adhesive and tape. Insert the radius template in opening to provide additional support.

STEP 7: Solid wood bucks will require additional concrete anchors to create a permanent attachment to the concrete.

2.9.5 – METAL JAMBS

Metal jambs are typically used in commercial applications. Many metal jamb companies will pre-bend jambs to fit LOGIX forms. Contact your local LOGIX representative for more details.


2.10 – ADDITIONAL FORM SUPPORT



The time spent prior to concrete placement pays huge dividends in job efficiency, accuracy, and profitability. The following items should be completed.

- Horizontal wood strapping is required on both the inside and outside of the wall when:
- The offset between joints is less than 8 inches (203 mm) between courses.
- There are more than 3 foam bar beyond a web.
- Vertical joints are directly on top of each other.
- Window or door openings occur less than 4 feet (1.220 m) from a corner. (Run strapping across opening to corner).
- Temporary wood straps are required around window and door openings to maintain straightness.
- Cross bracing with 2x4 supports is required inside window and door bucks to hold bucks in place and prevent sagging or bowing.
- Foam adhesive can be used on wood and plastic bucks to provide additional buck support.

INSTALLATION GUIDE



2.10 – ADDITIONAL FORM SUPPORT

CONTINUED



- Foam adhesive should be used to secure all Height Adjusters, and FleX Bars.
- All outside corners should be reinforced with tape or wood strapping.
- The top course should be secured with adhesive foam or zip ties.
- Sloped walls should be properly foamed and braced.
- Radius walls should be secured with foam adhesive and flexible strapping material.
- Forms in all lintels should be secured end-to-end with zip ties.
- The middle of large openings should be vertically braced to prevent tipping.
- All forms should be firmly seated to prevent settling.

2.11 – WALL BRACING & ALIGNMENT SYSTEM



A bracing system provides support for the wall and acts as an alignment system to keep the walls straight and plumb during concrete placement. Typically, the wall alignment system is installed on the inner side of the LOGIX wall.

There are a number of proprietary systems available. However, each bracing unit typically consists of a vertical upright steel channel with slots for attaching screws to the LOGIX webs, a turnbuckle arm, and a scaffold bracket.



Normally, wall bracing systems are installed after placing 2 to 4 courses of LOGIX forms (depending on wind and other conditions). Attach the bracing system to the webs using #10 screws with a hex head. Screws should be snug, but not tight.

Place bracing units no more than 2 feet (0.610 m) from each corner or wall end, and every 7 feet (2.134 m) or less thereafter in accordance with OSHA/OHSA requirements. Bracing units should also be placed on either side of every door and window opening.




STEP 1: Attach the upright steel channel to the LOGIX webs with a screw in each course. The screws should be snug but not tight. Always place screws near the top of the slots to accommodate settling at the interlock during concrete placement.

STEP 2: Attach a turnbuckle arm to the upright with a bolt and then secure to the floor or ground. In light or sandy soil, additional care must be taken to secure diagonal turnbuckle.

2.11 – WALL BRACING & ALIGNMENT SYSTEM

CONTINUED



STEP 3: The scaffold bracket is then inserted behind the top of the turnbuckle and secured at the bottom with an additional bolt.

STEP 4: Place the appropriate scaffolding planks and rails according to safety regulations. For requirements on toeboard and handrail configuration, consult OSHA/OHSA.

STEP 5: Prior to concrete placement, make certain walls are aligned perfectly plumb, or leaning slightly inward. The wall must not lean out at all.

STEP 6: A string line must be used to achieve straight walls.

STEP 7: Before, during and after concrete placement, the diagonal turnbuckle arm is used to adjust wall straightness to stringline.

NOTE: For tall wall bracing and alignment see **Section 3.2, Tall Wall Bracing Systems.**





INSTALLATION GUIDE

2.12 – FLOOR CONNECTIONS

Any type of floor system can be easily integrated with LOGIX. For any questions or assistance, please contact your local LOGIX representative.

2.12.1 – LEDGER WITH ANCHOR BOLTS & JOIST HANGERS



For full size CAD drawing see
Section 5, CAD Drawings

STEP 1: Place LOGIX blocks to a height allowing 2 inch (51 mm) minimum coverage over embedments.

STEP 2: Snap chalk lines directly on forms to mark the top and bottom of the proposed rim joist.


STEP 3: Cut openings between chalk lines to accommodate anchor bolts. The quantity and spacing of anchor bolts will be determined by code or engineering. Make certain that cuts are flared to facilitate proper concrete placement.

STEP 4: Pre-cut ledger to length. Pre-drill and install anchor bolts, washers and nuts as per hole layout and local code.

STEP 5: Attach ledger with screws into webs to hold in place while concrete is placed. Once concrete is cured, tighten anchor bolts.

STEP 6: Attach joist hangers to ledger according to hanger manufacturers' specs.

2.12.2 – STEEL ANGLE IRON LEDGER



For full size CAD drawing see
Section 5, CAD Drawings

When floor spans become very long or concrete topping is applied to the floor, a wood ledger may not be adequate to support floor loads. In this case a steel angle iron can be used in place of a wood ledger. The angle iron can support much more weight and also eliminates the need for joist hangers, as the floor system sits right on the angle.

To install an angle iron ledger follow the steps in **Section 2.12.1**, but use pieces of plywood to temporarily hold the bolts in place. After the pour drill and bolt on the angle iron. Local steel fabricators may be able to pre-drill your angle iron.

Another alternative is to pre-fabricate an angle iron with anchor bolts or nelson studs welded directly to the angle. The entire assembly is then cast in place. This application is described below:

STEP 1: Cut the foam out as you would with the wooden ledger then screw on 2x4 to cover the bottom of the cutout. The 2x4 temporarily supports the angle assembly so it must be installed level.

STEP 2: Sit the angle assembly on top of the 2x4 and tight up against the forms.

2.12.2 – STEEL ANGLE IRON LEDGER

CONTINUED

STEP 3: Screw strapping along the top edge of the angle to keep the assembly against the form during pour.

STEP 4: Pour concrete and cast the assembly in place.

STEP 5: After some curing place floor systems on the angle and establish layout. Once layout is complete fasten the floor joist to angle with a tech screw or by ram-set. You may decide to attach a nailing surface to the bottom leg of the angle iron to nail joists to.


NOTE: It is code in some areas for the angle assembly to be primed.

I
N
S
T
A
L
L
A
T
I
O
N
G
U
I
D
E

2.12.3 – BRICK LEDGE FOR TOP & BOTTOM CHORD BEARING SYSTEMS

The LOGIX Brick Ledge form can create a load bearing surface to support floor systems, including:

- Top chord bearing trusses
- Bottom chord bearing trusses or joists
- Cast in place concrete floors
- Pre-cast concrete floors



For full size CAD drawing see
Section 5, CAD Drawings



STEP 1: The Brick Ledge and the course above it must be foamed or otherwise secured down along the entire course to eliminate tilting or separating.

STEP 2: If the LOGIX block in the course above the Brick Ledge is of a smaller width than the Brick Ledge, additional form support will be required.

STEP 3: Install rebar in the Brick Ledge as specified. Butt joints are preferred for rebar in outer edge of Brick Ledge. Install 20 inches (508 mm) long stirrups in each Brick Ledge cavity, including the very corner.

STEP 4: As concrete is placed, install embedments as required.

2.12.4 – LEDGER WITH SIMPSON BRACKET & JOIST HANGERS




The ICFVL & ICFVL-W ledger connector system from Simpson Strong-Tie is designed for mounting steel or wood ledgers on ICF walls. The perforations in the embedded leg anchor it within the block. The exposed flange provides a structural surface for mounting either a wood or a steel ledger. The ICFVL bracket is the portion inserted into the block and embedded into the concrete. The ICFVL-W bracket is used with 1-1/2 inch (38 mm) ledger material. The ICFVL-CW bracket is used with 1-3/4 inch (44 mm) engineered wood ledgers. These brackets are installed on the ledger and attached to embedded ICFVL.

STEP 1: Place LOGIX blocks to a height allowing 2 inch (52 mm) minimum coverage over embedments.

STEP 2: Snap chalk lines directly on forms to mark the top or bottom of the proposed rim joist. For ledgers less than 10-3/8 inch (264 mm) deep, brackets should be installed to the top chalk line. For ledgers more than 10-3/8 inch (264 mm) deep, brackets should be installed to the bottom chalk line. For steel floor joists and ledgers, brackets should be centered on the proposed ledger.

STEP 3: Create vertical cuts to accommodate ICFVL bracket. Make sure these cuts are made directly opposite the thinned channels inside the form so that when inserted, the bracket will be exposed to the maximum amount of concrete. The quantity and spacing of brackets will be determined according to the table on [page 2-57](#).

2.12.4 – LEDGER WITH SIMPSON BRACKET & JOIST HANGERS CONTINUED



For full size CAD drawing see
Section 5, CAD Drawings

STEP 4: Place concrete and consolidate, ensuring brackets are fully embedded.

STEP 5: For wood or composite ledger, after proper concrete curing, the ICFVL-W or ICFVL-CW and appropriate ledger material can be installed using fasteners provided by Simpson Strong-Tie.

It is recommended to temporarily install ledger to chalk line, fastened to webs within 1 inch (25 mm) of the top edge of the ledger. This will make it easier to complete the installation. Slip ICFVL-W or ICFVL-CW underneath wood ledger and attach the screws as required.

For steel ledger, position ledger against ICFVL, level, and attach using appropriate fasteners as required by floor manufacturer.

NOTE: Industry studies show that hardened fasteners



can experience performance problems in wet environments. Accordingly, use this product in dry environments only. In addition, due to its corrosive nature, treated lumber should not be used with this product.

Use extra caution when installing the hangers on both sides of a wall. Consult your local Simpson Strongtie rep or contact Simpson Strongtie at (800) 999-5099 prior to installation.

Complete technical data is available at www.strongtie.com

2.12.4 – LEDGER WITH SIMPSON BRACKET & JOIST HANGERS CONTINUED

Simpson Strong-Tie Ledger Connector Loads & Spacings

| Ledger Type | Model No. | 6", 8" & 10" | | | | Spacing to Replace Anchor Bolts ^{3,4,6} | | | |
|---------------|---------------------------|--|--|--|--|--|-------|--------------------|-------|
| | | 4" | | 4" | | 1/2" Dia. Bolts at | | 5/8" Dia. Bolts at | |
| | | LOGIX ICF Allowable Vertical Resistance ² lbs (kN) | LOGIX ICF Allowable Vertical Resistance ² lbs (kN) | LOGIX ICF Factored Vertical Resistance lbs (kN) | LOGIX ICF Factored Vertical Resistance lbs (kN) | 12" | 24" | 12" | 24" |
| 2xD.Fir-LSPF | ICFVL w/ ICFVL-W | 1375 (6.12) | 1894 (8.42) | 1890 (8.41) | 2630 (11.70) | 4' | 4' | 3'-9" | 4' |
| | 1 3/4" LVL w/ ICFVL-CW | 1375 (6.12) | 1894 (8.42) | 1890 (8.41) | 2630 (11.70) | 4' | 4' | 3'-6" | 4' |
| (0.054") 16ga | ICFVL | 1770 (7.87) | 1894 (8.42) | 2435 (10.83) | 2630 (11.70) | 1'-3" | 2'-3" | 1' | 2' |
| (0.068") 14ga | ICFVL | 1770 (7.87) | 1894 (8.42) | 2435 (10.83) | 2630 (11.70) | 1' | 2' | 9" | 1'-6" |

| Ledger Type | Model No. | 6", 8" & 10" | | | | Spacing to Replace Anchor Bolts ^{3,4,6} | | | |
|---------------|---------------------------|--|--|--|--|--|-------|--------------------|-----|
| | | 4" | | 4" | | 2-5/8" Dia. Bolts at | | 3/4" Dia. Bolts at | |
| | | LOGIX ICF Allowable Vertical Resistance ² lbs (kN) | LOGIX ICF Allowable Vertical Resistance ² lbs (kN) | LOGIX ICF Factored Vertical Resistance lbs (kN) | LOGIX ICF Factored Vertical Resistance lbs (kN) | 12" | 24" | 12" | 24" |
| 2xD.Fir-LSPF | ICFVL w/ ICFVL-W | 1375 (6.12) | 1894 (8.42) | 1890 (8.41) | 2630 (11.70) | 1'-9" | 3'-9" | 3'-6" | 4' |
| | 1 3/4" LVL w/ ICFVL-CW | 1375 (6.12) | 1894 (8.42) | 1890 (8.41) | 2630 (11.70) | 1'-9" | 3'-6" | 2'-9" | 4' |
| (0.054") 16ga | ICFVL | 1770 (7.87) | 1894 (8.42) | 2435 (10.83) | 2630 (11.70) | -- | -- | -- | -- |
| (0.068") 14ga | ICFVL | 1770 (7.87) | 1894 (8.42) | 2435 (10.83) | 2630 (11.70) | -- | -- | -- | -- |

Allowable lateral load = 1905lbs (8.47kN) (Applicable to all form sizes).

1kN = 224.8lbs = 102Kg

1. Minimum steel ledger specification is Fy=33ksi (230MPa) and Fu=45ksi (310MPa) in accordance with CSA S136-94.

2. No load duration increase is allowed.

3. Spacing is based on vertical load only.

4. For steel ledger, spacing is based on a combination of ledger gauge & anchor bolt diameter. Spacing is closer for a 14 gauge ledger in order to achieve the equivalent bolt/ledger capacity.


5. Minimum concrete compressive strength, f_c, is 2500psi (17.25MPa).

6. The designer may specify different spacing based on the load requirements.

7. For more information contact Simpson Strongtie at www.simpsonstrongtie.com

Note: Industry studies show that hardened fasteners can experience performance problems in wet environments. Accordingly, use this product in dry environments only. In addition, due to its corrosive nature, treated lumber should not be used with Simpson Strongties.

2.12.5 – McMILLAN JOIST HANGERS



For full size CAD drawing see
Section 5, CAD Drawings

The McMillan Joist Hanger is designed to support wood floor joists to ICF walls. The perforations in the embedded leg anchor it within the block. The exposed end provides a 2.5 inch x 2.5 inch (63.5 mm x 63.5 mm) structural bearing surface for mounting wood joists with optional sizes of 1-9/16 inch (40 mm), 2-9/16 inch (65 mm) and 3-5/8 inch (92mm).

STEP 1: Determine height of floor and subtract height of floor joist.

STEP 2: Level marks with a transit or measuring tape and chalk line.

STEP 3: Screw a 2x4 ledger at chalk line to set joist hanger on.

STEP 4: Place joist hangers to floor joist layout spacing.

STEP 5: Cut two vertical slotted holes with a keyhole saw, slide joist hanger into ICF block, fasten if necessary.

STEP 6: Ensure the joist hangers are sitting straight after the placement of concrete.

NOTE: For more information contact 1-250-318-0062.




2.12.6 – TRANSITION LEDGE

A transition ledge is commonly used when the LOGIX walls will be continuing up to the roofline.

The ledge created when transitioning from a wider to a narrower wall can provide a suitable bearing surface for many types of floor systems.

For additional bearing support LOGIX Taper Top and Transition forms can be used as the top course when transitioning from a 6.25 inch (159 mm) to 4 inch (102 mm) LOGIX wall.


2.12.6.1 – TRANSITION LEDGE WITH TAPER TOP FORMS



LOGIX 6.25 inch (159 mm) Taper Top forms can be used as the top course when transitioning to a 4 inch (102 mm) wall. Alternately, 6.25 inch (159 mm) Standard forms and corner forms can be hand cut to create Taper Top forms.

LOGIX 8 inch (203 mm) Taper Top forms can be used as the top course when transitioning to 4 inch (102 mm) or a 6.25 inch (159 mm) wall.

When hand cutting Taper Top forms, be careful not to drop foam scraps into the wall cavity.



STEP 1: Set Taper Top form as the top course of the lower wall.

STEP 2: Using short lengths of #4 (10M) rebar, provide a bearing support for the unsupported edge of the upper (narrower) form.

STEP 3: Install upper form, using foam adhesive to prevent lifting or tipping at connection.

STEP 4: 1x4 lumber can be attached vertically to the outside of the forms to assist in wall alignment.

STEP 5: Right after concrete placement, trowel off the ledge while checking for level. Insert embedments as required.

2.12.6.2 – TRANSITION LEDGE WITH LOGIX TRANSITION FORMS




Figure 1a: LOGIX Transition Block





Figure 1b: LOGIX Transition Block End View



LOGIX Transition forms provide more bearing support than the LOGIX Taper Top forms. The Transition forms are available in straight units. See **Figure 1a & 1b**.

When transitioning from a thicker wall to a thinner wall (i.e., 6.25 inch (159 mm) to 4 inch (102 mm) wall) the LOGIX Transition form can provide additional bearing support for heavier loaded floor systems.

The corbel ledge of the Transition forms can support a load of up to 1300lb/ft (19kN/m) providing a total bearing seat length of 3.75 inch (95 mm).

With the corbel extending 1.75 inches (44 mm) from the face of the wall, it also adds an aesthetic crown moulding-like feature when used as the top course of an interior wall.

Creating corner forms are easily installed, and is very similar to creating corner forms with LOGIX Brick Ledge forms (see **Section 2.7.4**).

For bracing installation, refer to **Section 3**. If the bracing is placed on the corbel side of the forms, the upright vertical channel should terminate just under the corbel of the Transition form.

2.12.6.3 – TRANSITION LEDGE WITH CORNER BLOCKS

Transitioning from a wider block to a narrower block is commonly used in cases where a thinner wall becomes more economical (i.e., below grade wall to above grade wall), or to create a ledge that can support a floor or roof system, or finishes such as brick veneer.

When transitioning at corner locations using corner blocks, you might find that the interlocking knobs on the top side of the wider bottom block (bottom course) do not interlock or align with the underside of the top narrower block (top course). As a result, the top course will not sit or snap into its proper position (see **Figure 1a** & **1b**).

This occurs in transitions at corner location only, and is easily resolved by following a few simple steps outlined below.




Figure 1a. Proper alignment of top course to bottom course. Interlock aligns with underside of top course.





Figure 1b. Improper alignment of top course to bottom course. Interlock does not align with underside of top course.


2.12.6.3 – TRANSITION LEDGE WITH CORNER BLOCKS CONTINUED



Step 1

STEP 1: Cut the interlocks off the wider corner blocks (it may be necessary to cut the interlocks off the rest of the blocks on the bottom course to ensure the top course can be placed flush on top of the previous course).


As an alternative, Taper Top blocks for the bottom course can be used. The Taper Tops provide more flexibility since they can be adjusted to ensure the interlocks align with the top course.



Step 2


STEP 2: Apply foam adhesive prior to installing the top course.

STEP 3: Install the top course beginning with the corner block and continuing around the building perimeter.



Step 3

2.12.7 – TAPER TOP WITH SILL PLATE




The Taper Top form creates a greater bearing surface at the top of LOGIX walls.

STEP 1: Taper Top forms need to be foamed down or otherwise secured to the course below.

STEP 2: Trowel concrete flush with top of forms, or inset as required. Be sure to check for level.

STEP 3: Insert embedments as required.



For full size CAD drawing see
Section 5, CAD Drawings



2.12.8 – CONCRETE FLOOR SYSTEMS



Building with LOGIX will allow you to explore many concrete floor system options. Our walls are stronger and can support added weight that wood or steel frame buildings may not. Concrete floor systems are very popular in multi-residential buildings where the transmission of sound and fire are a concern. They are also growing in popularity in single-family residential applications.



2.12.8.1 – PRECAST CONCRETE FLOORS



For full size CAD drawing see
Section 5, CAD Drawings



Pre-cast floor systems are poured at the factory and shipped to site then craned in place. They are usually tensioned with steel cables cast in the concrete to provide maximum strength. Pre-cast floor are fast and can have very long clear spans.

Typically the LOGIX wall is constructed to the desired height and the pre-cast planks sit directly on the cured concrete. The planks, typically 4 feet (1.220 m) wide, are craned in place and the grooves between planks are grouted together. A 2 inch (52 mm) topping is poured over the deck to provide a smooth and level finish.

The reinforcing of the wall is tied in to the grouted grooves to secure the floor in place. The vertical reinforcing of the wall is extended past the planks to secure future levels of LOGIX.

See floor manufacturer for specific installation requirements and details.

2.12.8.2 – HAMBRO FLOOR SYSTEM



For full size CAD drawing see
Section 5, CAD Drawings

The Hambro floor system is a proprietary composite floor system that combines open web steel joists and a 2.5"-5" (64mm - 127mm) floor slab. The joists are spaced 4'-1" (1.225m) O.C. and held apart with locking bars. Then temporary plywood forms are placed between the joists and the concrete deck is poured. After sufficient cure the plywood forms are removed. Hambro is a fast and efficient concrete floor system and can span upwards of 25 feet (7.620 m).

The open joist design makes for easy mechanical and utility installation.

See Hambro for more details: www.hambrosystems.com

2.12.8.3 – STEEL COMPOSITE FLOOR SYSTEM





Composite floors are a combination of steel and concrete that is bonded together to create a very strong floor. The steel composite decking is a corrugated steel pan that has deformations that bond securely with the concrete. The steel deck is the formwork for the pour and then acts as reinforcement in the concrete. These systems are quick to install and are comparatively thin, resulting in more headroom in the finished.

It may be necessary to temporarily support the pan until the concrete has sufficiently cured.

For more info and design consult your floor manufacturer and your local design engineer.

INSTALLATION GUIDE



For full size CAD drawing see
Section 5, CAD Drawings

www.logixicf.com

Good. Solid. Green.™


2 – 7 0

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09


2.13 – ROOF CONNECTIONS



For full size CAD drawing see
Section 5, CAD Drawings

Roof connections can be attached to the LOGIX wall in a variety of ways. Several factors can affect which method to use such as area of the country and wind conditions.

2.13.1 – INSET SILL PLATE



For full size CAD drawing see
Section 5, CAD Drawings


This method of sill plate attachment is one of the most energy efficient. The LOGIX foam on each side provides an excellent thermal barrier.

STEP 1: Trowel the concrete out to a level below the top of the form equal to the depth of the sill plate. Use a site built wood trowel. Be sure to cut the trowel board to the full width of the concrete core.

STEP 2: Install embedments as required.

NOTE: For ease of concrete flow it is recommended to use either LOGIX Taper Top or Double Taper Top for the top course.

2.13.2 – TOP MOUNTED SILL PLATE



For full size CAD drawing see
Section 5, CAD Drawings

This method is typically used when additional wall height is required.

STEP 1: Trowel concrete flush with top of form and recheck for level.

STEP 2: Install embedments as required.

NOTE: For ease of concrete flow it is recommended to use either LOGIX Taper Top or Double Taper Top for the top course.

INSTALLATION GUIDE

2.14 – SERVICE PENETRATIONS

Identify and size all service and utility penetrations. Install all appropriate and properly sized sleeves where required, remembering that lightweight sleeves can be crushed during concrete placement.

List of possible service penetrations

- Dryer vent
- Water heater vent
- Water
- Sewer
- Electrical main service
- Gas line
- A/C line
- Furnace vent
- Air Exchange/HRV
- Central vacuum
- Ducting
- Bathroom vent
- Kitchen appliance venting
- Fireplace rough opening and vent
- Pet door



2.15 – CONCRETE PLACEMENT

PRE-PLACEMENT CHECKLIST

DATE:

FOREMAN:

JOB:

Prior to placing concrete in LOGIX insulated concrete forms, be certain to mark off each item on the checklist provided in this section.

- ___ 1. String line in place around the top of entire perimeter?
- ___ 2. Walls straight and plumb (not leaning out)?
- ___ 3. Top course foamed or tied down and zip tied end to end to maintain dimensions?
- ___ 4. Additional form support on all corners?
- ___ 5. Have Tee-walls been foamed and supported?
- ___ 6. Alignment - screw in every course?
- ___ 7. Scaffold planking properly secured?
- ___ 8. All handrails and toe boards installed?
- ___ 9. All bucks cross braced?
- ___ 10. All bucks secured to wall?
- ___ 11. All buck concrete anchors installed?
- ___ 12. All horizontal and vertical rebar in place?
- ___ 13. All lintel reinforcing in place?
- ___ 14. All penetrations installed?
- ___ 15. All beam pockets in place?
- ___ 16. All floor embedments installed?
- ___ 17. Are anchor bolts and hold-downs on site?
- ___ 18. Has cavity of wall been checked, and foreign material removed?
- ___ 19. Plywood, screw gun, and saw on site?
- ___ 20. Interlock protected by tape, LOGIX Flex Bars or other covering?
- ___ 21. Proper concrete mix and slump ordered?
- ___ 22. Concrete vibrator on site?
- ___ 23. Pump equipped with double-90 or reducer available?

2.15 – CONCRETE PLACEMENT CONTINUED

The most important stage of a successful LOGIX project is the concrete placement. Extra workers at this stage are important - be certain to have enough on hand during the pour to safely handle placement, consolidation, alignment, embedments, and cleanup.

Ensure straight walls by placing a string line at the top course set off from the wall using 3/4 inch (19 mm) pieces of wood placed in the corners. Check for straightness by running another 3/4" inch (19 mm) piece of wood between the string and wall. Adjust the turnbuckles as necessary to keep the wall straight during concrete placement. Walls must be perfectly straight or leaning in slightly.

During concrete placement, watch the string lines to monitor the wall for straight and plumb.

Suggested minimum compressive concrete strength of 2,900 psi (20MPa) at 28 days. For seismic areas mix design should be confirmed with local codes or by an engineer.

The following maximum aggregate sizes are recommended for use in LOGIX walls:

| | Form Cavity Size, in. (mm) | | | | |
|-------------------------------|----------------------------|------------|----------|----------|-----------|
| | 4 (102) | 6.25 (159) | 8 (203) | 10 (254) | 12* (305) |
| Max. Aggregate Size, in. (mm) | 3/8 (9.5) | 3/8 (9.5) | 3/4 (19) | 3/4 (19) | 3/4 (19) |

2.15 – CONCRETE PLACEMENT CONTINUED



Concrete slump should be 5 inch (127 mm) to 6 inches (152mm) for best results.

A pump truck with double 90° elbows or a reducer attached to a rubber extension works best to control the rate of concrete flow.

When placing concrete in 4 inch (102 mm) forms, it is recommended that the pump truck be fitted with a 3 inch (76 mm) flexible hose end.



Other methods of placement include conveyor truck, crane and bucket, and directly off the ready mix truck.


Lift height is determined by many factors, such as air temperature, concrete temperature, slump, etc. In general, lift heights should not exceed 4ft (1.220 m).

Example: on a 60° F (15° C) day with a 6 inch (152 mm) slump, the lift height should be approximately 3 feet (0.914 m). Below is a guide for a lift heights according to varying temperatures and with a 6 inch (152 mm) slump.

Consult local ready mix companies for appropriate concrete mix design.

When placing concrete below freezing or at temperatures above 100° F (38° C), it's important to protect all exposed concrete with insulation.

2.15 – CONCRETE PLACEMENT CONTINUED



Proper concrete consolidation is critical in obtaining a structurally solid wall.

Use an internal vibrator with a head size of 3/4 inch (19 mm) to 1 inch (25mm) and maximum 1 hp motor. Do not use a vibrator with a head larger than 1 inch (25 mm).

Appropriate internal vibration assures the strongest walls possible and is especially important for below grade application where the greatest loads occur.



The rule of thumb for internal vibration is fast in and slow out, always moving, with a withdrawal rate of approximately 3 inch (76 mm) per second.

| Temperature | Lift Height (6" slump) |
|-------------|------------------------|
| 40°F (4°C) | 2'-2.5" (670mm) |
| 50°F (10°C) | 2'-9" (840mm) |
| 60°F (15°C) | 3'-10.25" (920mm) |
| 70°F (21°C) | 3'-10.25" (1170mm) |
| 80°F (27°C) | 4'-4.75" (1340mm) |
| 90°F (32°C) | 4'-11.5" (1510mm) |

2.15 – CONCRETE PLACEMENT CONTINUED

STEP 1: Complete the pre-placement checklist.

STEP 2: Begin concrete placement under openings, filling those areas and consolidating.

STEP 3: Beginning no closer than 3 feet (0.914 m) from a corner, start filling the wall from the top, allowing the concrete to flow gently toward the corner. Then fill in that corner from the opposite side using the same technique.

STEP 4: Continue placing concrete around entire wall in appropriately sized lifts, using the same technique at each corner to minimize fluid pressure.

STEP 5: As the concrete is being placed, consolidation is taking place to remove air and voids to ensure structural integrity.

STEP 6: As the concrete is being placed, continually check wall alignment using string line. Adjust the wall accordingly to maintain straight and plumb using the adjustable turnbuckle.

STEP 7: Return to starting location and begin the next lift. Follow all the techniques established above.

E
D
I
C
E
I
O
N
I
N
S
T
A
L
L
A
T
I
O
N

2.15 – CONCRETE PLACEMENT CONTINUED

POST-PLACEMENT CHECKLIST

DATE:


FOREMAN:

JOB:

After placing concrete in LOGIX insulated concrete forms, be certain to mark off each item on the checklist provided in this section.

- ___ 1. Has consolidation been completed?
- ___ 2. Are walls straightened to string line?
- ___ 3. In extreme temperatures, has exposed concrete been protected?
- ___ 4. Have all anchors and embeds been installed?
- ___ 5. Has spilled concrete been disposed of?
- ___ 6. Has final check for straight and plumb been done?

2.16 – ELECTRICAL INSTALLATIONS



Electrical and plumbing installation are typically performed after concrete placement.

The exception to this rule is the placement of conduit that penetrates the wall, which must be performed before concrete placement.

Installing electrical wiring and boxes is accomplished by creating channels in the EPS foam. When installed in LOGIX walls directly against the concrete, electrical boxes will extend 1/2 inch (13 mm) beyond the foam to match the thickness of 1/2 inch (13 mm) sheetrock.

Various tools can be used to create the channels and spaces for wiring and boxes:

- Electrical chainsaw with an adjustable roller depth stop
- Hot knife
- Circular saw with a masonry blade



Make the wiring channels narrow so there will be a friction fit with the wiring. The wiring needs to remain embedded well into the foam to meet local electrical codes. Foam adhesive can be spot-applied into the channel to help hold the wiring in place.

2.17 – PLUMBING INSTALLATIONS



In most cases, buildings are designed so plumbing pipes are not carried through the LOGIX walls, except for utility entry and exit points.

However, in some cases it may be required to embed pipe in the EPS. For example, a kitchen vent tube may need to be installed vertically in the EPS foam. Pipes embedded in the foam cannot exceed 1-1/2 inch (38 mm) in diameter. Fittings embedded in the foam cannot exceed 2-1/2 inch (64 mm) diameter.

An external faucet will require the installation of a hose sleeve through the wall prior to concrete placement. This will permit replacement of the faucet or pipe should it ever be necessary.

If connecting to existing sewer lines, establish the location of the required opening and ensure clearances, since this is difficult to change.

2.18 – INTERIOR & EXTERIOR FINISHES

2.18.1 – VAPOR & AIR BARRIERS

The LOGIX wall assembly has no need for an additional vapor barrier, the solid concrete core covered with the low permeance EPS (Type II) foam insulation on the inside wall face keeps water vapor from penetrating the wall.

The fact that the inner face of EPS foam maintains a similar temperature as the inside air of the building and that a LOGIX wall has no cavity means that no condensation can occur in a LOGIX wall assembly.

The LOGIX wall assembly has no need for an air barrier (building wrap) layer as the solid concrete core and low permeance EPS (Type II) foam insulation on the outside wall face keeps air and moisture from penetrating the wall.

2.18.2 – INTERIOR DRYWALL

Drywall should be installed in the same manner on a LOGIX wall as on a stud wall, with the following time-saving exceptions:

- All webs (studs) are on 8 inch (203 mm) centers from floor to ceiling for easy attachment of any type of interior wall finish.
- The butt joints of the sheetrock do not need to fall on webs (studs) as the foam provides solid backing wherever the joints fall.
- A foam-compatible adhesive can be used to effectively fasten the sheetrock to the LOGIX wall along with screws. Always make sure to verify the local code for types and spacing for sheetrock fasteners. Typically, adhesive alone is not allowed as a fastener of sheetrock, but again check with local building codes.

Many local building codes require the application of 1/2 inch (13 mm) drywall or other suitable thermal barrier in any living space even though the EPS foam has a fire retardant component. Always verify local building code requirements.

2.18.2 – INTERIOR DRYWALL CONTINUED

Non-habitable spaces such as crawl spaces, attics, and other types of hidden areas typically do not require a thermal barrier (drywall).

Embedded furring tabs are fixed at each corner of the LOGIX 90° corner forms for solid sheetrock fastening at all corners.

2.18.3 – EXTERIOR SIDING



Siding material of some kind must be installed over the EPS foam to protect it from the UV rays of the sun. Foam left exposed to the sun will degrade on the exposed surface by slowly breaking and getting “dusty”.

NOTE: When using LOGIX Platinum Series care should be taken to protect exposed foam surfaces from reflected sunlight and prolonged solar exposure until wall cladding or finish material is applied. Shade exposed foam areas, or remove sources of reflective surfaces, where heat build up onto exposed foam might occur. For more information refer to BASF Technical Leaflet N-4 Neopor, “Recommendations for packaging, transporting, storing and installing building insulation products made from Neopor EPS foam.” (The BASF Technical Leaflet is attached to every bundle of LOGIX Platinum forms delivered to a job site).



Metal and vinyl siding can be installed directly over the top of the EPS.

Although air guns can be used, LOGIX recommends the use of screw guns when attaching exterior siding. Always follow manufacturer’s recommendations and local codes to determine the size and spacing of fasteners for all siding products.

Any type of siding that is used on a typical wood-framed building can be used on a LOGIX building.

The siding channel stock around doors and windows can be fastened to whatever type of buck material was chosen, in a similar fashion as wood framed building.

A plastic corner web is embedded in all corners as a fastening surface. See **Section 5.1.6 & 5.1.7** for further details on the plastic corner web.



2.18.4 – STEEL PANEL SIDING

Steel panel siding can be applied vertically to a LOGIX wall when the style of the panel matches the LOGIX web 8 inch (203 mm) increments for fastening purposes.

When a panel siding is chosen that doesn't fit with 8 inch (203 mm) increment for fastening, two different methods are available:

METHOD 1:

A 1/2 inch (13 mm) or 3/4 inch (19 mm) strip of wood can be attached horizontally to the webs in the wall to provide the manufacturer's specified fastener spacing.

METHOD 2:

The panels can be installed horizontally, by fastening directly into the webs.

NOTE: Although air guns can be used, LOGIX recommends the use of screw guns when attaching exterior siding. Always follow manufacturer's recommendations and local codes to determine the size and spacing of fasteners for all siding products.


2.18.5 – WOOD SIDING

Any wood siding can be attached to the LOGIX wall in the same manner as to a traditional framed building. The spacing of the web studs on 8 inch (203 mm) centers allows for industry standard spacing of fasteners. Typically, screws are used for attaching wood siding or even half-log siding to the LOGIX wall.

Although air guns can be used, LOGIX recommends a screw gun with screws in clips (Quik Drive). This is usually the fastest method for applying wood siding. Always follow manufacturer's recommendations and local codes to determine the size and spacing of fasteners for all siding products.

A good practice for installing wood siding on a wall, is to apply the siding over vertical 1 inch x 2 inch (25 mm x 51 mm) wood nailing strips with a screen at the bottom. The screen keeps insects out while the space allows air to circulate behind the siding. The air circulation helps equalize the moisture content in the wood siding, which makes for much more dimensionally stable siding and longer lasting application.

2.18.6 – EIFS



There are now acrylic-based stucco products available that are more flexible and easier to work with than traditional cement-based stucco. Collectively these products are known as EIFS (Exterior Insulation Finish Systems) and almost always require an EPS substrate.

Because LOGIX blocks are made with EPS, they are a natural fit for EIFS finishes. In addition, the webs in LOGIX blocks are embedded 1/2 inch (13 mm) deep in the EPS foam to comply with EIFS manufacturer requirements.

It is important to follow the EIFS manufacturer's application procedures.

2.18.7 – TRADITIONAL STUCCO (CEMENT-BASED)

LOGIX walls will accept traditional cement-based stucco product. Although air guns can be used, LOGIX recommends a screw gun when attaching the wire lath mesh to LOGIX walls. Use screws with a wide head or screws along with washers to best hold the mesh in place.


Consult local building codes for vertical and horizontal fastener placement requirements. The center-to-center fastener spacing requirements for nails and staples must be followed for screws as well. Again, check with local codes for all specific requirements relating to the application of stucco over EPS insulation.

2.18.8 – CEMENT COMPOSITE SIDING

Recently the new cement fiber siding products have gained popularity. This type of siding can usually be fastened directly to the LOGIX webs. Although air guns can be used, LOGIX recommends a screw gun to fasten flat-headed exterior screws at 16 inch (406 mm) centers. The screws pull the siding in tight and hold the siding securely in place. Some manufacturers may require the siding to be strapped out to allow air space behind. Vertical or shake patterns will require strapping for fastening. Always follow manufacturer's recommendations and local codes to determine the size and spacing of fasteners for all siding products.


Check with your siding manufacturer for specific requirements.

2.18.9 – BRICK VENEER



The LOGIX Brick Ledge form units are used to support a brick veneer as the exterior finish material. The Brick Ledge forms are simply placed at a level where the brick is desired to begin. The design of the form creates a reinforced concrete ledge.

With standard reinforcing, the Brick Ledge can bear up to 1300lb/ft (19kN/m) of wall.



With site-specific engineering, up to 3000lb/ft (44kN/m) of wall is attainable.

To install Brick Ledge form units, follow the instructions on **Section 2.7.4** of the guide. When reinforcing steel and concrete are in place within the wall, brick is laid on the ledge and tied back to the webs with brick ties as specified.



For full size CAD drawing see
Section 5, CAD Drawings


2.18.10 – BELOW GRADE WATERPROOFING, DAMPPROOFING & PARGING

There are many methods available to protect the “below grade” and the “just above grade” areas of the exterior of your building.

Dampproofing is used on concrete or masonry surfaces to repel water in above grade walls. The 2.75 inch (70 mm) and thicker foam panels of the LOGIX insulated concrete forms acts as dampproofing, therefore, no additional dampproofing treatment is required.

NOTE: Although dampproofing above grade walls is not typically required, check with local building codes for dampproofing requirements.

2.18.10.1 – BELOW GRADE WATERPROOFING



LOGIX recommends a rubberized “peel and stick” waterproofing membrane. The membrane is applied vertically to the wall from grade level down to and overlapping the top of the footing. It is recommended to use protection board (1/2 inch EPS or EXP foam sheets or similar) to prevent damage to the waterproofing membrane during backfilling.

Free flow drainage material with a maximum fluid density of 30 pcf (480 kg/m³) is recommended, i.e., sand or sand-gravel mix.

NOTE: Membrane should be installed within one week prior to backfill being placed. Sunlight and high temperatures may cause the membrane to begin to “sag” which may cause wrinkles in the material which may result in tears or punctures during the placement of the backfill material. Should you choose to use one of the many other types of waterproofing available be sure to follow the manufacturer’s recommended installation procedures.

STEP 1: Prep the wall and footing area to be covered by removing dirt and debris.

STEP 2: Snap chalk lines for the “grade” line.

STEP 3: Measure the height from grade line to footing. Add enough length to cover the top of the footing and cut pieces of membrane to length.

2.18.10.1 – BELOW GRADE WATERPROOFING CONTINUED



Also cut smaller 4" - 6" (102mm - 152mm) pieces to be applied as "corner caps". This will provide double ply protection in the corners.

STEP 4: Apply the "corner cap" pieces on each corner first.

STEP 5: Starting at a corner, line up the membrane so it is hanging vertically (using our vertical cut lines as a guide to keep membrane plumb). Pull back the first 8" - 10" (203mm - 254mm) of the release paper and press the membrane to the wall. Continue pulling back the release paper and pressing membrane to the wall.

STEP 6: Continue applying cut pieces of membrane around the wall, maintaining 2 inch (51 mm) overlap by using the printed marks on the membrane as a guide.

NOTE: Extreme temperatures, both cold and hot, may cause the installer to consider other types of waterproofing. Be sure to follow the manufacturer's installation process.

2.18.10.2 – ABOVE GRADE PARGING

The area that is above grade line and below the exterior siding material must be parged to protect the EPS from damage.

Parging is a coating material that is applied to give a finished appearance to the small area of wall that is above grade level but below where the siding materials will begin. LOGIX Prepcoat is the preferred option for this area.

STEP 1: Prep the wall area to be covered by removing any dirt or debris. The wall may need to be “scuffed” to reveal fresh EPS beads.

STEP 2: Mix Prepcoat dry material with water to a pasty consistency.

STEP 3: Using a trowel apply a thin, 1/16” - 1/8” (2mm - 3mm) “skim coat” of Prepcoat.

STEP 4: Pre-cut pieces of LOGIX fiber mesh 1” - 2” (25mm - 51mm) wider than the area to be parged. This will allow for an over-lap over the waterproofing membrane to create a “drip ledge”.

STEP 5: Embed the mesh in the skim coat firmly.

STEP 6: Once the area is dry to the touch apply a second coat of Prepcoat. This coat can be painted or stained if desired.

2.18.11 – ADDITIONAL SUPPORT FOR GRAB BARS, & OTHER HEAVY FIXTURES

Additional backing is recommended to support heavier wall fixtures, such as kitchen cabinetry, wall mounted fixtures, grab bars, hand rails, etc.



This can be accomplished in two ways:

METHOD 1:

Plywood board can be attached to the LOGIX wall behind the heavier cabinets in place of gypsum board, providing a thermal barrier comparable to gypsum and a strong attachment surface for heavier items and fixtures. Be certain to attach the plywood board to the LOGIX webs with a sufficient number of screws to hold heavy items in place for when loads are applied.

METHOD 2:

Create horizontal channels behind the cabinets equal in width to a 2x4 and install 2x4 backing directly to the concrete surface using sufficiently long concrete screws and a rotohammer. Attach the cabinets to the 2x4s.



For full size CAD drawing see
Section 5, CAD Drawings

2.18.12 – HOLDING POWER OF SCREWS FASTENED TO LOGIX FURRING TABS

Web fastener withdrawal and shear testing using coarse and fine thread drywall screws. Tests were conducted on furring tabs embedded 1/2 inch (52 mm) from the surface of the 2.75 inch (70 mm) LOGIX EPS panels .

| | Max. Average Withdrawal Resistance | Allowable Withdrawal Resistance ¹ | Max. Average Shear Resistance | Allowable Shear Resistance ² |
|--------------------------------|--|--|-------------------------------------|--|
| Coarse Thread Drywall Screw | 166lb (75.3kg) | 33lb (15.0kg) | 367lb (166.5kg) | 49lb (22.2kg) |
| Fine Thread Drywall Screw | 169lb (76.7kg) | 34lb (15.4kg) | 328lb (148.8kg) | 49lb (22.2kg) |

1kg = 9.81 Newtons

1. Allowable withdrawal resistance values are based on a factor of safety of 5.

2. Allowable shear resistance values are based on a factor of safety of 3.2 within defined deflection limits (for more detailed information contact info@logixcf.com)

NOTE: The numbers in this table represent resistance at failure. Good building practice mandates a minimum of a 5 to 1 safety factor in calculating fastener loading. For complete test results on additional fasteners, see **Section 8** in the LOGIX Design Manual or consult your local LOGIX representative.

2.19 – COURSE HEIGHT TABLE


COURSE HEIGHT TABLE

This table shows wall heights that are readily achieved using standard LOGIX blocks used in combination with a 4 inch (102 mm) Height Adjusters and/or 8 inch (203 mm) Half-height blocks.

INSTALLATION GUIDE

| Number of Courses | Height of Wall | Add One Height Adj. | Add One Half-height | Add One Height Adj. & One Half-height |
|-------------------|--------------------|---------------------|---------------------|---------------------------------------|
| 1 | 1' - 4" (406mm) | 1' - 8" (508mm) | 2' - 0" (610mm) | 2' - 4" (711mm) |
| 2 | 2' - 8" (813mm) | 3' - 0" (914mm) | 3' - 4" (1016mm) | 3' - 8" (1118mm) |
| 3 | 4' - 0" (1219mm) | 4' - 4" (1321mm) | 4' - 8" (1422mm) | 5' - 0" (1524mm) |
| 4 | 5' - 4" (1626mm) | 5' - 8" (1727mm) | 6' - 0" (1829mm) | 6' - 4" (1930mm) |
| 5 | 6' - 8" (2032mm) | 7' - 0" (2134mm) | 7' - 4" (2235mm) | 7' - 8" (2337mm) |
| 6 | 8' - 0" (2438mm) | 8' - 4" (2540mm) | 8' - 8" (2642mm) | 9' - 0" (2743mm) |
| 7 | 9' - 4" (2845mm) | 9' - 8" (2946mm) | 10' - 0" (3048mm) | 10' - 4" (3150mm) |
| 8 | 10' - 8" (3251mm) | 11' - 0" (3353mm) | 11' - 4" (3454mm) | 11' - 8" (3556mm) |
| 9 | 12' - 0" (3658mm) | 12' - 4" (3759mm) | 12' - 8" (3861mm) | 13' - 0" (3962mm) |
| 10 | 13' - 4" (4064mm) | 13' - 8" (4166mm) | 14' - 0" (4267mm) | 14' - 4" (4369mm) |
| 11 | 14' - 8" (4470mm) | 15' - 0" (4572mm) | 15' - 4" (4674mm) | 15' - 8" (4775mm) |
| 12 | 16' - 0" (4877mm) | 16' - 4" (4978mm) | 16' - 8" (5080mm) | 17' - 0" (5182mm) |
| 13 | 17' - 4" (5283mm) | 17' - 8" (5385mm) | 18' - 0" (5486mm) | 18' - 4" (5588mm) |
| 14 | 18' - 8" (5690mm) | 19' - 0" (5791mm) | 19' - 4" (5893mm) | 19' - 8" (5994mm) |
| 15 | 20' - 0" (6096mm) | 20' - 4" (6198mm) | 20' - 8" (6299mm) | 21' - 0" (6401mm) |
| 16 | 21' - 4" (6502mm) | 21' - 8" (6604mm) | 22' - 0" (6706mm) | 22' - 4" (6807mm) |
| 17 | 22' - 8" (6909mm) | 23' - 0" (7010mm) | 23' - 4" (7112mm) | 23' - 8" (7214mm) |
| 18 | 24' - 0" (7315mm) | 24' - 4" (7417mm) | 24' - 8" (7518mm) | 25' - 0" (7620mm) |
| 19 | 25' - 4" (7722mm) | 25' - 8" (7823mm) | 26' - 0" (7925mm) | 26' - 4" (8026mm) |
| 20 | 26' - 8" (8128mm) | 27' - 0" (8230mm) | 27' - 4" (8331mm) | 27' - 8" (8433mm) |
| 21 | 28' - 0" (8534mm) | 28' - 4" (8636mm) | 28' - 8" (8738mm) | 29' - 0" (8839mm) |
| 22 | 29' - 4" (8941mm) | 29' - 8" (9042mm) | 30' - 0" (9144mm) | 30' - 4" (9246mm) |
| 23 | 30' - 8" (9347mm) | 31' - 0" (9449mm) | 31' - 4" (9550mm) | 31' - 8" (9652mm) |
| 24 | 32' - 0" (9754mm) | 32' - 4" (9855mm) | 32' - 8" (9957mm) | 33' - 0" (10058mm) |
| 25 | 33' - 4" (10160mm) | 33' - 8" (10262mm) | 34' - 0" (10363mm) | 34' - 4" (10465mm) |

2.20 – RADIUS WALLS



LOGIX Radius Walls

| Outside Radius, ft. (m) | Form Cavity Width | | | | | | | |
|----------------------------|-------------------|---------------|---------------|----------------|-------------|-----------------|-------------|-----------------|
| | 4" (102mm) | | 6.25" (159mm) | | 8" (203mm) | | 10" (254mm) | |
| | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) |
| 3 (0.914) | 8 (203) | 13/16 (21) | 8 (203) | 1 3/32 (28) | 8 (203) | 1 19/64 (33) | 8 (203) | 1 35/64 (39) |
| 3.5 (1.067) | 8 (203) | 11/16 (17) | 8 (203) | 59/64 (23) | 8 (203) | 1 3/32 (28) | 8 (203) | 1 19/64 (33) |
| 4 (1.219) | 8 (203) | 19/32 (15) | 8 (203) | 51/64 (20) | 8 (203) | 61/64 (24) | 8 (203) | 1 1/8 (29) |
| 4.5 (1.372) | 8 (203) | 17/32 (13) | 8 (203) | 45/64 (18) | 8 (203) | 27/32 (21) | 8 (203) | 1 (25) |
| 5 (1.524) | 8 (203) | 15/32 (12) | 8 (203) | 5/8 (16) | 8 (203) | 3/4 (19) | 8 (203) | 57/64 (23) |
| 5.5 (1.676) | 8 (203) | 27/64 (11) | 8 (203) | 9/16 (14) | 8 (203) | 43/64 (17) | 8 (203) | 51/64 (20) |
| 6 (1.829) | 8 (203) | 25/64 (10) | 8 (203) | 33/64 (13) | 8 (203) | 5/8 (16) | 8 (203) | 47/64 (19) |
| 6.5 (1.981) | 8 (203) | 23/64 (9) | 8 (203) | 15/32 (12) | 8 (203) | 9/16 (14) | 8 (203) | 43/64 (17) |
| 7 (2.134) | 8 (203) | 21/64 (8) | 8 (203) | 7/16 (11) | 8 (203) | 17/32 (13) | 8 (203) | 5/8 (16) |

NOTES:

1. Field cut LOGIX Standard forms (straight forms) into widths, C, according to LOGIX Radius Walls table. For inside radius field cut additional foam, A, accordingly.
2. Secure each radius section with zip ties, tape or foam.
3. The field cuts, C, are kept at 8" (203mm), 16" (406mm), 24" (610mm) or 48" (1220mm) lengths. The field cuts, A, are determined depending on required radius. The combined field cuts, A and C, results in an outside radius which is within 1% of the design radius for radii less than 60ft (18.3m), and 1% to 2% for radii between 60ft and 100ft (18.3m to 30.5m).

2.20 – RADIUS WALLS CONTINUED

| Outside Radius, ft. (m) | Form Cavity Width | | | | | | | |
|----------------------------|-------------------|---------------|---------------|---------------|-------------|---------------|-------------|---------------|
| | 4" (102mm) | | 6.25" (159mm) | | 8" (203mm) | | 10" (254mm) | |
| | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) |
| 7.5 (2.286) | 8 (203) | 5/16 (8) | 8 (203) | 13/32 (10) | 8 (203) | 31/64 (12) | 8 (203) | 37/64 (15) |
| 8 (2.438) | 8 (203) | 9/32 (7) | 8 (203) | 3/8 (10) | 8 (203) | 29/64 (12) | 8 (203) | 35/64 (14) |
| 8.5 (2.591) | 8 (203) | 17/64 (7) | 8 (203) | 23/64 (9) | 8 (203) | 27/64 (11) | 8 (203) | 33/64 (13) |
| 9 (2.743) | 8 (203) | 1/4 (6) | 8 (203) | 11/32 (9) | 8 (203) | 13/32 (10) | 8 (203) | 31/64 (12) |
| 9.5 (2.896) | 8 (203) | 15/64 (6) | 16 (406) | 41/64 (16) | 8 (203) | 25/64 (10) | 8 (203) | 29/64 (12) |
| 10 (3.048) | 16 (406) | 29/64 (12) | 16 (406) | 39/64 (15) | 8 (203) | 23/64 (9) | 8 (203) | 7/16 (11) |
| 10.5 (3.200) | 16 (406) | 7/16 (11) | 16 (406) | 37/64 (15) | 8 (203) | 11/32 (9) | 8 (203) | 13/32 (10) |
| 11 (3.353) | 16 (406) | 27/64 (11) | 16 (406) | 35/64 (14) | 8 (203) | 21/64 (8) | 8 (203) | 25/64 (10) |
| 11.5 (3.505) | 16 (406) | 25/64 (10) | 16 (406) | 17/32 (13) | 8 (203) | 5/16 (8) | 8 (203) | 3/8 (10) |
| 12 (3.658) | 16 (406) | 3/8 (10) | 16 (406) | 1/2 (13) | 8 (203) | 19/64 (8) | 8 (203) | 23/64 (9) |
| 12.5 (3.810) | 16 (406) | 23/64 (9) | 16 (406) | 31/64 (12) | 16 (406) | 37/64 (15) | 8 (203) | 11/32 (9) |
| 13 (3.962) | 16 (406) | 11/32 (9) | 16 (406) | 15/32 (12) | 8 (203) | 9/32 (7) | 8 (203) | 21/64 (8) |
| 13.5 (4.115) | 16 (406) | 21/64 (8) | 16 (406) | 29/64 (12) | 16 (406) | 17/32 (13) | 8 (203) | 5/16 (8) |
| 14 (4.267) | 16 (406) | 21/64 (8) | 16 (406) | 7/16 (11) | 8 (203) | 1/4 (6) | 16 (406) | 39/64 (15) |
| 14.5 (4.420) | 16 (406) | 5/16 (8) | 16 (406) | 27/64 (11) | 8 (203) | 1/4 (6) | 16 (406) | 19/32 (15) |
| 15 (4.572) | 16 (406) | 19/64 (8) | 16 (406) | 13/32 (10) | 8 (203) | 15/64 (6) | 16 (406) | 37/64 (15) |
| 15.5 (4.724) | 16 (406) | 19/64 (8) | 16 (406) | 25/64 (10) | 8 (203) | 15/64 (6) | 16 (406) | 35/64 (14) |
| 16 (4.877) | 24 (610) | 27/64 (11) | 16 (406) | 3/8 (10) | 8 (203) | 7/32 (6) | 16 (406) | 17/32 (13) |
| 16.5 (5.029) | 24 (610) | 13/32 (10) | 16 (406) | 23/64 (9) | 8 (203) | 7/32 (6) | 16 (406) | 33/64 (13) |
| 17 (5.182) | 24 (610) | 13/32 (10) | 16 (406) | 23/64 (9) | 16 (406) | 27/64 (11) | 16 (406) | 1/2 (13) |
| 17.5 (5.334) | 24 (610) | 25/64 (10) | 24 (610) | 33/64 (13) | 16 (406) | 13/32 (10) | 16 (406) | 31/64 (12) |
| 18 (5.486) | 24 (610) | 3/8 (10) | 24 (610) | 1/2 (13) | 16 (406) | 13/32 (10) | 16 (406) | 15/32 (12) |
| 18.5 (5.639) | 24 (610) | 23/64 (9) | 24 (610) | 31/64 (12) | 16 (406) | 25/64 (10) | 16 (406) | 15/32 (12) |
| 19 (5.791) | 24 (610) | 23/64 (9) | 24 (610) | 15/32 (12) | 16 (406) | 3/8 (10) | 16 (406) | 29/64 (12) |

2.20 – RADIUS WALLS CONTINUED

| Outside Radius, ft. (m) | Form Cavity Width | | | | | | | |
|----------------------------|-------------------|---------------|---------------|---------------|---------------|---------------|-------------|---------------|
| | 4" (102mm) | | 6.25" (159mm) | | 8" (203mm) | | 10" (254mm) | |
| | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) |
| 19.5 (5.944) | 24 (610) | 11/32 (9) | 24 (610) | 15/32 (12) | 16 (406) | 3/8 (10) | 16 (406) | 7/16 (11) |
| 20 (6.096) | 24 (610) | 11/32 (9) | 24 (610) | 29/64 (12) | 16 (406) | 23/64 (9) | 16 (406) | 27/64 (11) |
| 20.5 (6.248) | 24 (610) | 21/64 (8) | 24 (610) | 7/16 (11) | 16 (406) | 11/32 (9) | 16 (406) | 27/64 (11) |
| 21 (6.401) | 24 (610) | 21/64 (8) | 24 (610) | 7/16 (11) | 16 (406) | 11/32 (9) | 16 (406) | 13/32 (10) |
| 21.5 (6.553) | 24 (610) | 5/16 (8) | 24 (610) | 27/64 (11) | 16 (406) | 21/64 (8) | 16 (406) | 25/64 (10) |
| 22 (6.706) | 24 (610) | 5/16 (8) | 24 (610) | 13/32 (10) | 16 (406) | 21/64 (8) | 16 (406) | 25/64 (10) |
| 22.5 (6.858) | 24 (610) | 19/64 (8) | 24 (610) | 13/32 (10) | 16 (406) | 5/16 (8) | 16 (406) | 3/8 (10) |
| 23 (7.010) | 24 (610) | 19/64 (8) | 24 (610) | 25/64 (10) | 16 (406) | 5/16 (8) | 16 (406) | 3/8 (10) |
| 23.5 (7.163) | 24 (610) | 9/32 (7) | 24 (610) | 25/64 (10) | 24 (610) | 29/64 (12) | 16 (406) | 23/64 (9) |
| 24 (7.315) | 24 (610) | 9/32 (7) | 24 (610) | 3/8 (10) | 24 (610) | 29/64 (12) | 16 (406) | 23/64 (9) |
| 24.5 (7.468) | 24 (610) | 9/32 (7) | 48 (1,219) | 47/64 (19) | 24 (610) | 7/16 (11) | 16 (406) | 11/32 (9) |
| 25 (7.620) | 24 (610) | 17/64 (7) | 48 (1,219) | 23/32 (18) | 24 (610) | 7/16 (11) | 16 (406) | 11/32 (9) |
| 25.5 (7.772) | 24 (610) | 17/64 (7) | 48 (1,219) | 45/64 (18) | 24 (610) | 27/64 (11) | 16 (406) | 21/64 (8) |
| 26 (7.925) | 48 (1,219) | 33/64 (13) | 48 (1,219) | 45/64 (18) | 24 (610) | 13/32 (10) | 16 (406) | 21/64 (8) |
| 26.5 (8.077) | 48 (1,219) | 33/64 (13) | 48 (1,219) | 11/16 (17) | 24 (610) | 13/32 (10) | 16 (406) | 5/16 (8) |
| 27 (8.230) | 48 (1,219) | 1/2 (13) | 48 (1,219) | 43/64 (17) | 24 (610) | 25/64 (10) | 16 (406) | 5/16 (8) |
| 27.5 (8.382) | 48 (1,219) | 1/2 (13) | 48 (1,219) | 21/32 (17) | 24 (610) | 25/64 (10) | 16 (406) | 5/16 (8) |
| 28 (8.534) | 48 (1,219) | 31/64 (12) | 48 (1,219) | 41/64 (16) | 24 (610) | 25/64 (10) | 16 (406) | 19/64 (8) |
| 28.5 (8.687) | 48 (1,219) | 15/32 (12) | 48 (1,219) | 41/64 (16) | 24 (610) | 3/8 (10) | 24 (610) | 29/64 (12) |
| 29 (8.839) | 48 (1,219) | 15/32 (12) | 48 (1,219) | 5/8 (16) | 24 (610) | 3/8 (10) | 24 (610) | 7/16 (11) |
| 29.5 (8.992) | 48 (1,219) | 29/64 (12) | 48 (1,219) | 39/64 (15) | 24 (610) | 23/64 (9) | 24 (610) | 7/16 (11) |
| 30 (9.144) | 48 (1,219) | 29/64 (12) | 48 (1,219) | 39/64 (15) | 24 (610) | 23/64 (9) | 24 (610) | 27/64 (11) |
| 30.5 (9.296) | 48 (1,219) | 7/16 (11) | 48 (1,219) | 19/32 (15) | 48 (1,219) | 45/64 (18) | 24 (610) | 27/64 (11) |
| 31 (9.449) | 48 (1,219) | 7/16 (11) | 48 (1,219) | 37/64 (15) | 48 (1,219) | 45/64 (18) | 24 (610) | 13/32 (10) |

INSTALLATION GUIDE

2.20 – RADIUS WALLS CONTINUED

| Outside Radius, ft. (m) | Form Cavity Width | | | | | | | |
|----------------------------|-------------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| | 4" (102mm) | | 6.25" (159mm) | | 8" (203mm) | | 10" (254mm) | |
| | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) |
| 31.5 (9.601) | 48 (1,219) | 27/64 (11) | 48 (1,219) | 37/64 (15) | 48 (1,219) | 11/16 (17) | 24 (610) | 13/32 (10) |
| 32 (9.754) | 48 (1,219) | 27/64 (11) | 48 (1,219) | 9/16 (14) | 48 (1,219) | 43/64 (17) | 24 (610) | 25/64 (10) |
| 32.5 (9.906) | 48 (1,219) | 27/64 (11) | 48 (1,219) | 9/16 (14) | 48 (1,219) | 21/32 (17) | 24 (610) | 25/64 (10) |
| 33 (10.058) | 48 (1,219) | 13/32 (10) | 48 (1,219) | 35/64 (14) | 48 (1,219) | 21/32 (17) | 24 (610) | 25/64 (10) |
| 33.5 (10.211) | 48 (1,219) | 13/32 (10) | 48 (1,219) | 17/32 (13) | 48 (1,219) | 41/64 (16) | 24 (610) | 3/8 (10) |
| 34 (10.363) | 48 (1,219) | 25/64 (10) | 48 (1,219) | 17/32 (13) | 48 (1,219) | 41/64 (16) | 24 (610) | 3/8 (10) |
| 34.5 (10.516) | 48 (1,219) | 25/64 (10) | 48 (1,219) | 33/64 (13) | 48 (1,219) | 5/8 (16) | 24 (610) | 3/8 (10) |
| 35 (10.668) | 48 (1,219) | 25/64 (10) | 48 (1,219) | 33/64 (13) | 48 (1,219) | 39/64 (15) | 24 (610) | 23/64 (9) |
| 35.5 (10.820) | 48 (1,219) | 3/8 (10) | 48 (1,219) | 1/2 (13) | 48 (1,219) | 39/64 (15) | 24 (610) | 23/64 (9) |
| 36 (10.973) | 48 (1,219) | 3/8 (10) | 48 (1,219) | 1/2 (13) | 48 (1,219) | 19/32 (15) | 24 (610) | 23/64 (9) |
| 36.5 (11.125) | 48 (1,219) | 3/8 (10) | 48 (1,219) | 1/2 (13) | 48 (1,219) | 19/32 (15) | 24 (610) | 11/32 (9) |
| 37 (11.278) | 48 (1,219) | 23/64 (9) | 48 (1,219) | 31/64 (12) | 48 (1,219) | 37/64 (15) | 24 (610) | 11/32 (9) |
| 37.5 (11.430) | 48 (1,219) | 23/64 (9) | 48 (1,219) | 31/64 (12) | 48 (1,219) | 37/64 (15) | 24 (610) | 11/32 (9) |
| 38 (11.582) | 48 (1,219) | 23/64 (9) | 48 (1,219) | 15/32 (12) | 48 (1,219) | 9/16 (14) | 24 (610) | 21/64 (8) |
| 38.5 (11.735) | 48 (1,219) | 11/32 (9) | 48 (1,219) | 15/32 (12) | 48 (1,219) | 9/16 (14) | 24 (610) | 21/64 (8) |
| 39 (11.887) | 48 (1,219) | 11/32 (9) | 48 (1,219) | 15/32 (12) | 48 (1,219) | 35/64 (14) | 24 (610) | 21/64 (8) |
| 39.5 (12.040) | 48 (1,219) | 11/32 (9) | 48 (1,219) | 29/64 (12) | 48 (1,219) | 35/64 (14) | 24 (610) | 21/64 (8) |
| 40 (12.192) | 48 (1,219) | 11/32 (9) | 48 (1,219) | 29/64 (12) | 48 (1,219) | 17/32 (13) | 24 (610) | 5/16 (8) |
| 40.5 (12.344) | 48 (1,219) | 21/64 (8) | 48 (1,219) | 7/16 (11) | 48 (1,219) | 17/32 (13) | 48 (1,219) | 5/8 (16) |
| 41 (12.497) | 48 (1,219) | 21/64 (8) | 48 (1,219) | 7/16 (11) | 48 (1,219) | 17/32 (13) | 48 (1,219) | 5/8 (16) |
| 41.5 (12.649) | 48 (1,219) | 21/64 (8) | 48 (1,219) | 7/16 (11) | 48 (1,219) | 33/64 (13) | 48 (1,219) | 39/64 (15) |
| 42 (12.802) | 48 (1,219) | 5/16 (8) | 48 (1,219) | 27/64 (11) | 48 (1,219) | 33/64 (13) | 48 (1,219) | 39/64 (15) |
| 42.5 (12.954) | 48 (1,219) | 5/16 (8) | 48 (1,219) | 27/64 (11) | 48 (1,219) | 1/2 (13) | 48 (1,219) | 19/32 (15) |
| 43 (13.106) | 48 (1,219) | 5/16 (8) | 48 (1,219) | 27/64 (11) | 48 (1,219) | 1/2 (13) | 48 (1,219) | 19/32 (15) |

2.20 – RADIUS WALLS CONTINUED

| Outside Radius, ft. (m) | Form Cavity Width | | | | | | | |
|----------------------------|-------------------|--------------|---------------|---------------|---------------|---------------|---------------|---------------|
| | 4" (102mm) | | 6.25" (159mm) | | 8" (203mm) | | 10" (254mm) | |
| | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) |
| 43.5 (13.259) | 48 (1,219) | 5/16 (8) | 48 (1,219) | 13/32 (10) | 48 (1,219) | 1/2 (13) | 48 (1,219) | 19/32 (15) |
| 44 (13.411) | 48 (1,219) | 5/16 (8) | 48 (1,219) | 13/32 (10) | 48 (1,219) | 31/64 (12) | 48 (1,219) | 37/64 (15) |
| 44.5 (13.564) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 13/32 (10) | 48 (1,219) | 31/64 (12) | 48 (1,219) | 37/64 (15) |
| 45 (13.716) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 13/32 (10) | 48 (1,219) | 31/64 (12) | 48 (1,219) | 9/16 (14) |
| 45.5 (13.868) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 25/64 (10) | 48 (1,219) | 15/32 (12) | 48 (1,219) | 9/16 (14) |
| 46 (14.021) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 25/64 (10) | 48 (1,219) | 15/32 (12) | 48 (1,219) | 35/64 (14) |
| 46.5 (14.173) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 25/64 (10) | 48 (1,219) | 15/32 (12) | 48 (1,219) | 35/64 (14) |
| 47 (14.326) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 3/8 (10) | 48 (1,219) | 29/64 (12) | 48 (1,219) | 35/64 (14) |
| 47.5 (14.478) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 3/8 (10) | 48 (1,219) | 29/64 (12) | 48 (1,219) | 17/32 (13) |
| 48 (14.630) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 3/8 (10) | 48 (1,219) | 29/64 (12) | 48 (1,219) | 17/32 (13) |
| 48.5 (14.783) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 3/8 (10) | 48 (1,219) | 7/16 (11) | 48 (1,219) | 17/32 (13) |
| 49 (14.935) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 23/64 (9) | 48 (1,219) | 7/16 (11) | 48 (1,219) | 33/64 (13) |
| 49.5 (15.088) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 23/64 (9) | 48 (1,219) | 7/16 (11) | 48 (1,219) | 33/64 (13) |
| 50 (15.240) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 23/64 (9) | 48 (1,219) | 27/64 (11) | 48 (1,219) | 33/64 (13) |
| 50.5 (15.392) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 23/64 (9) | 48 (1,219) | 27/64 (11) | 48 (1,219) | 1/2 (13) |
| 51 (15.545) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 11/32 (9) | 48 (1,219) | 27/64 (11) | 48 (1,219) | 1/2 (13) |
| 51.5 (15.697) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 11/32 (9) | 48 (1,219) | 27/64 (11) | 48 (1,219) | 1/2 (13) |
| 52 (15.850) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 11/32 (9) | 48 (1,219) | 13/32 (10) | 48 (1,219) | 31/64 (12) |
| 52.5 (16.002) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 11/32 (9) | 48 (1,219) | 13/32 (10) | 48 (1,219) | 31/64 (12) |
| 53 (16.154) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 11/32 (9) | 48 (1,219) | 13/32 (10) | 48 (1,219) | 31/64 (12) |
| 53.5 (16.307) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 21/64 (8) | 48 (1,219) | 13/32 (10) | 48 (1,219) | 15/32 (12) |
| 54 (16.459) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 21/64 (8) | 48 (1,219) | 25/64 (10) | 48 (1,219) | 15/32 (12) |
| 54.5 (16.612) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 21/64 (8) | 48 (1,219) | 25/64 (10) | 48 (1,219) | 15/32 (12) |
| 55 (16.764) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 21/64 (8) | 48 (1,219) | 25/64 (10) | 48 (1,219) | 15/32 (12) |

2.20 – RADIUS WALLS CONTINUED

| Outside Radius, ft. (m) | Form Cavity Width | | | | | | | |
|----------------------------|-------------------|--------------|---------------|--------------|---------------|---------------|---------------|---------------|
| | 4" (102mm) | | 6.25" (159mm) | | 8" (203mm) | | 10" (254mm) | |
| | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) |
| 55.5 (16.916) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 21/64 (8) | 48 (1,219) | 25/64 (10) | 48 (1,219) | 29/64 (12) |
| 56 (17.069) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 5/16 (8) | 48 (1,219) | 3/8 (10) | 48 (1,219) | 29/64 (12) |
| 56.5 (17.221) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 5/16 (8) | 48 (1,219) | 3/8 (10) | 48 (1,219) | 29/64 (12) |
| 57 (17.374) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 5/16 (8) | 48 (1,219) | 3/8 (10) | 48 (1,219) | 29/64 (12) |
| 57.5 (17.526) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 5/16 (8) | 48 (1,219) | 3/8 (10) | 48 (1,219) | 7/16 (11) |
| 58 (17.678) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 5/16 (8) | 48 (1,219) | 3/8 (10) | 48 (1,219) | 7/16 (11) |
| 58.5 (17.831) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 5/16 (8) | 48 (1,219) | 23/64 (9) | 48 (1,219) | 7/16 (11) |
| 59 (17.983) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 23/64 (9) | 48 (1,219) | 7/16 (11) |
| 59.5 (18.136) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 23/64 (9) | 48 (1,219) | 27/64 (11) |
| 60 (18.288) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 23/64 (9) | 48 (1,219) | 27/64 (11) |
| 60.5 (18.440) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 23/64 (9) | 48 (1,219) | 27/64 (11) |
| 61 (18.593) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 11/32 (9) | 48 (1,219) | 27/64 (11) |
| 61.5 (18.745) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 11/32 (9) | 48 (1,219) | 13/32 (10) |
| 62 (18.898) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 11/32 (9) | 48 (1,219) | 13/32 (10) |
| 62.5 (19.050) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 11/32 (9) | 48 (1,219) | 13/32 (10) |
| 63 (19.202) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 11/32 (9) | 48 (1,219) | 13/32 (10) |
| 63.5 (19.355) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 11/32 (9) | 48 (1,219) | 13/32 (10) |
| 64 (19.507) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 21/64 (8) | 48 (1,219) | 25/64 (10) |
| 64.5 (19.660) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 21/64 (8) | 48 (1,219) | 25/64 (10) |
| 65 (19.812) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 21/64 (8) | 48 (1,219) | 25/64 (10) |
| 65.5 (19.964) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 21/64 (8) | 48 (1,219) | 25/64 (10) |
| 66 (20.117) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 21/64 (8) | 48 (1,219) | 25/64 (10) |
| 66.5 (20.269) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 21/64 (8) | 48 (1,219) | 3/8 (10) |
| 67 (20.422) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 5/16 (8) | 48 (1,219) | 3/8 (10) |

2.20 – RADIUS WALLS CONTINUED

| Outside Radius, ft. (m) | Form Cavity Width | | | | | | | |
|----------------------------|-------------------|--------------|---------------|--------------|---------------|--------------|---------------|--------------|
| | 4" (102mm) | | 6.25" (159mm) | | 8" (203mm) | | 10" (254mm) | |
| | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) |
| 67.5 (20.574) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 5/16 (8) | 48 (1,219) | 3/8 (10) |
| 68 (20.726) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 5/16 (8) | 48 (1,219) | 3/8 (10) |
| 68.5 (20.879) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 5/16 (8) | 48 (1,219) | 3/8 (10) |
| 69 (21.031) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 5/16 (8) | 48 (1,219) | 23/64 (9) |
| 69.5 (21.184) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 5/16 (8) | 48 (1,219) | 23/64 (9) |
| 70 (21.336) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 23/64 (9) |
| 70.5 (21.488) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 23/64 (9) |
| 71 (21.641) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 23/64 (9) |
| 71.5 (21.793) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 23/64 (9) |
| 72 (21.946) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 11/32 (9) |
| 72.5 (22.098) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 11/32 (9) |
| 73 (22.250) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 11/32 (9) |
| 73.5 (22.403) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 19/64 (8) | 48 (1,219) | 11/32 (9) |
| 74 (22.555) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 11/32 (9) |
| 74.5 (22.708) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 11/32 (9) |
| 75 (22.860) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 11/32 (9) |
| 75.5 (23.012) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 21/64 (8) |
| 76 (23.165) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 21/64 (8) |
| 76.5 (23.317) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 21/64 (8) |
| 77 (23.470) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 21/64 (8) |
| 77.5 (23.622) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 9/32 (7) | 48 (1,219) | 21/64 (8) |
| 78 (23.774) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 21/64 (8) |
| 78.5 (23.927) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 21/64 (8) |
| 79 (24.079) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 5/16 (8) |

2.20 – RADIUS WALLS CONTINUED

| Outside Radius, ft. (m) | Form Cavity Width | | | | | | | |
|----------------------------|-------------------|--------------|---------------|--------------|---------------|--------------|---------------|--------------|
| | 4" (102mm) | | 6.25" (159mm) | | 8" (203mm) | | 10" (254mm) | |
| | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) |
| 79.5 (24.232) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 5/16 (8) |
| 80 (24.384) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 5/16 (8) |
| 80.5 (24.536) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 5/16 (8) |
| 81 (24.689) | 48 (1,219) | 5/32 (4) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 5/16 (8) |
| 81.5 (24.841) | 48 (1,219) | 5/32 (4) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 5/16 (8) |
| 82 (24.994) | 48 (1,219) | 5/32 (4) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 17/64 (7) | 48 (1,219) | 5/16 (8) |
| 82.5 (25.146) | 48 (1,219) | 5/32 (4) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 5/16 (8) |
| 83 (25.298) | 48 (1,219) | 5/32 (4) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 19/64 (8) |
| 83.5 (25.451) | 48 (1,219) | 5/32 (4) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 19/64 (8) |
| 84 (25.603) | 48 (1,219) | 5/32 (4) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 19/64 (8) |
| 84.5 (25.756) | 48 (1,219) | 5/32 (4) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 19/64 (8) |
| 85 (25.908) | 48 (1,219) | 5/32 (4) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 19/64 (8) |
| 85.5 (26.060) | 48 (1,219) | 5/32 (4) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 19/64 (8) |
| 86 (26.213) | 48 (1,219) | 5/32 (4) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 19/64 (8) |
| 86.5 (26.365) | 48 (1,219) | 5/32 (4) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 19/64 (8) |
| 87 (26.518) | 48 (1,219) | 5/32 (4) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 19/64 (8) |
| 87.5 (26.670) | 48 (1,219) | 5/32 (4) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 1/4 (6) | 48 (1,219) | 9/32 (7) |
| 88 (26.822) | 48 (1,219) | 5/32 (4) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 9/32 (7) |
| 88.5 (26.975) | 48 (1,219) | 5/32 (4) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 9/32 (7) |
| 89 (27.127) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 9/32 (7) |
| 89.5 (27.280) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 9/32 (7) |
| 90 (27.432) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 9/32 (7) |
| 90.5 (27.584) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 13/64 (5) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 9/32 (7) |
| 91 (27.737) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 9/32 (7) |

2.20 – RADIUS WALLS CONTINUED

| Outside Radius, ft. (m) | Form Cavity Width | | | | | | | |
|----------------------------|-------------------|-------------|---------------|--------------|---------------|--------------|---------------|--------------|
| | 4" (102mm) | | 6.25" (159mm) | | 8" (203mm) | | 10" (254mm) | |
| | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) | C, in. (mm) | A, in. (mm) |
| 91.5 (27.889) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 9/32 (7) |
| 92 (28.042) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 9/32 (7) |
| 92.5 (28.194) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 17/64 (7) |
| 93 (28.346) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 17/64 (7) |
| 93.5 (28.499) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 15/64 (6) | 48 (1,219) | 17/64 (7) |
| 94 (28.651) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 17/64 (7) |
| 94.5 (28.804) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 17/64 (7) |
| 95 (28.956) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 17/64 (7) |
| 95.5 (29.108) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 17/64 (7) |
| 96 (29.261) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 17/64 (7) |
| 96.5 (29.413) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 17/64 (7) |
| 97 (29.566) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 17/64 (7) |
| 97.5 (29.718) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 17/64 (7) |
| 98 (29.870) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 3/16 (5) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 1/4 (6) |
| 98.5 (30.023) | 48 (1,219) | 9/64 (4) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 1/4 (6) |
| 99 (30.175) | 48 (1,219) | 1/8 (3) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 1/4 (6) |
| 99.5 (30.328) | 48 (1,219) | 1/8 (3) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 1/4 (6) |
| 100 (30.480) | 48 (1,219) | 1/8 (3) | 48 (1,219) | 11/64 (4) | 48 (1,219) | 7/32 (6) | 48 (1,219) | 1/4 (6) |

INSTALLATION GUIDE

Good. Solid. Green.™

www.logixicf.com

2 – 107

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

2.21 – TALL WALLS



LOGIX walls can be constructed to any height provided proper engineering and construction methods are used.

LOGIX tall walls should be designed in accordance with ACI 318 or CAN/CSA A23.3.



Constructing tall walls follows the same basic steps described throughout Section 2. In addition, building taller walls is done in much the same way as concrete pours using traditional formwork. Generally, LOGIX blocks are stacked and braced, normally 10 to 12 feet high. The concrete is then placed. After the concrete sets LOGIX blocks are then stacked another 10 to 12 feet, and bracing is raised or extended higher to support the wall, as well as keeping the wall plumb. This process is continued until the specified wall height is reached.

To ensure a smooth build, the following items should be considered:

- Load tables in **Section 6** can be used as a design aid for both the builder and designer. However, tall wall designs should be reviewed and approved by a local licensed professional engineer.
- In higher wind areas taller walls may require guy wires for additional support.
- Proper consolidation of concrete can be achieved by adequate vibrating. However, depending on the drop height, and the steel congestion, external vibration should be considered. External vibration should be applied to at least the corners, around openings, and congested areas of rebar. (External



2.21 – TALL WALLS CONTINUED

vibrators made specifically for ICFs are available. See **Section 2.23, Supporting Products**).

- Since tall walls are typically poured using a pump truck, using a reducing hose can provide better control of the concrete pour.
- Roughen the surface of all cold joints to ensure a good bond between the surface of the old pour and the subsequent pour. In addition, ensure adequate rebar embedments are provided.
- For the final stage of the pour, use LOGIX Taper Top blocks for the top course of the wall. This provides a larger opening for concrete to flow into the wall and also provides a larger bearing area for supporting elements.
- Several tall wall bracing and alignment systems are available. For more information see **Section 3.2, Tall Wall Bracing Systems**.

NOTE: Both ACI 318 and CAN/CSA A23.3 permit cold joints when concrete is poured in stages.

2.22 – TILT-UP WALL CONSTRUCTION

The LOGIX KD panels can provide insulation to the exterior, interior or both sides of tilt-up wall panels.

The use of LOGIX KD to insulate tilt-up walls avoids the need to finish the concrete surface and apply curing and finishing compounds.

Casting of tilt-up walls in cold weather is also possible with LOGIX KD since the walls are thermally protected within the panels.

In addition, the structural design and connections of supporting elements are not affected by the use of LOGIX KD.

CAST AGAINST LOGIX KD

Provided LOGIX KD panels are laid upon a firm level surface, tilt-up wall panels can be cast against LOGIX KD without the need for a casting bed or slab. Release agents are also not required since the walls are poured on top of the LOGIX KD panels.

STEP 1: After the formwork for the tilt-up walls have been placed, lay down the LOGIX KD panels within the formwork area before placing the rebar and concrete.

The formwork should be built high enough to accommodate the thickness of the KD panels and the tilt-up wall. Cover as much of the area within the formwork as required (for full insulation cover

2.22 – TILT-UP WALL CONSTRUCTION

CONTINUED

lay down the KD panels to cover the entire area within the formwork).

The LOGIX KD panels should be placed in a stack bond pattern with the holding points facing up. This will ensure the holding points will be properly anchored into the concrete during the pour.

Create cutouts in the LOGIX KD panels where inserts will be placed for bracing.

STEP 2: Place the rebar and inserts for lifting or bracing. Pour the concrete, finish and cure the walls as required.

STEP 3: Once the all the tilt-up panels have been erected and braces removed, replace all cutout sections of LOGIX KD panels with similar foam insulation (or insulation with equal or greater R-value).

Apply spray foam between LOGIX KD panel joints if necessary.

STEP 4: Apply interior or exterior finish to the LOGIX KD panels as required.

I
N
S
T
A
L
L
A
T
I
O
N
G
U
I
D
E

2.22 – TILT-UP WALL CONSTRUCTION

CONTINUED

WET SETTING LOGIX

Wet setting LOGIX eliminates the need to trowel finish, and apply finishing and curing compounds.

STEP 1: To prepare the LOGIX KD panels for wet setting, lay the panels on a flat surface with the holding points facing down. Keep the LOGIX KD panels slightly elevated from the ground to avoid damaging the holding points. Lay the LOGIX KD panels in a stack bond pattern and connect the panels together with a metal strongback or 2x4s. Connect the strongback or 2x4s along the embedded furring tabs with wood screws.

STEP 2: Once the concrete for the tilt-up wall panels have been placed and properly screed, the LOGIX KD panels can be wet set into place.

The LOGIX KD panels can be wet set by holding onto the strongbacks or 2x4s. Once the LOGIX KD panels are in place press down firmly to ensure the holding points are properly embedded into the concrete.

Smaller cut pieces of LOGIX KD panels can be wet set by hand to fill in any remaining areas of the formed wall.

The number of LOGIX KD panels should be determined ahead of time, assembled and ready for placement.

2.22 – TILT-UP WALL CONSTRUCTION

CONTINUED

STEP 3: Use a vibrator to along the strongbacks or 2x4s to properly consolidate the concrete.

STEP 4: Remove the strongbacks or 2x4s after the concrete has set.

STEP 5: After the walls are lifted and placed foam spray the joints between the LOGIX KD panels.

STEP 6: Apply interior or exterior finish to the LOGIX KD panels as required.

LOGIX KD PANELS ON BOTH SIDES OF WALL

To apply LOGIX KD panels to both sides of tilt-up walls simply follow the instructions for casting walls against LOGIX KD panels and wet setting LOGIX KD panels on tilt-up walls.

I
N
S
T
A
L
L
A
T
I
O
N
G
U
I
D
E

2.23 – SUPPORTING PRODUCTS

A list of supporting ICF products are shown below. Consult with the listed manufacturer prior to using with LOGIX Insulated Concrete Forms. Please note: the products listed below does not prohibit the use of LOGIX ICFs with other supporting products not listed.

FOOTINGS

| Product Name | Manufacturer | Contact | Website |
|--------------|---------------------|----------------|-----------------|
| Fastfoot | Fab-form Industries | 1-888-303-3278 | fab-form.com |
| Form-A-Drain | CertainTeed Corp. | 708-301-4449 | certainteed.com |
| Footing Tube | Footing Tube | 1-888-929-2011 | foottube.com |

EXTERIOR FINISHES

| Product Name | Manufacturer | Contact | Website |
|----------------------------------|-----------------------------|----------------|--------------------|
| Durock | Alfacing International Ltd. | 1-888-238-6345 | durock.com |
| Senerflex | Degussa Wall Systems, Inc. | 1-800-221-9255 | senergy.cc |
| Sto EIFS System | Sto Corp. | 1-800-221-2397 | stocorp.com |
| GrailCoat | GrailCoat | 1-877-472-4528 | grailcoat.com |
| TAFS (Textured Acrylic Finishes) | dryvit | 1-800-263-3308 | dryvit.com |
| SoftCoat PB System | Total Wall, Inc. | 1-888-702-9915 | totalwall.com |
| Akroflex | Omega Products Corp. | 602-721-5027 | omega-products.com |
| Impact System | parex | 1-800-537-2739 | parex.com |
| PermaCrete | Quality Systems | 1-800-607-3762 | permacrete.com |
| Crack Guard | Poly-Wall | 1-800-846-3020 | poly-wall.com |
| Protecto Bond | Protecto Wrap | 1-800-759-9727 | protecwrap.com |
| WeatherWall Systems | Eco Specialty Products Ltd. | 1-888-481-5507 | ecocoatings.ca |

WATERPROOFING

| Product Name | Manufacturer | Contact | Website |
|------------------------------|-------------------------------|----------------|-----------------------|
| System III | Epro | 1-800-882-1896 | eproserv.com |
| Blueskin WP2000 | Bakor, Inc | 1-800-387-9598 | bakor.com |
| Colphene 3000 | Soprema, Inc | 1-800 567-1492 | soprema.com |
| Delta-MS Clear | Cosella-Dorken Products, Inc. | 1-888-4DELTA4 | cosella-dorken.com |
| Platon | Armtec Ltd. | 1-800-265-7622 | systemplaton.com |
| Tamko TW60 | Tamko, Inc. | 1-800-641-4691 | tamko.com |
| Grace waterproofing products | Grace Construction Products | See website | graceconstruction.com |
| Aqua-Wrap/Green Sheild | Aqua Seal Inc. | 1-888-282-3861 | aquasealusa.com |

CONNECTION SYSTEMS

| Product Name | Manufacturer | Contact | Website |
|-----------------------------|------------------------------|----------------|----------------------|
| ICF Ledger Connector System | Simpson Strong-Tie Co., Inc. | 1-800-999-5099 | simpsonstrongtie.com |
| McMillan Joist Hanger | New Tech Concrete Solutions | 1-888-835-6655 | - |
| ICF-Connect | ICF-Connect Ltd. | 1-866-497-1576 | icfconnect.com |

Good. Solid. Green.™

www.logixicf.com

2 – 1 1 4



2.23 – SUPPORTING PRODUCTS CONTINUED

BUCK SYSTEMS

| Product Name | Manufacturer | Contact | Website |
|--------------|--------------------------|----------------|-----------|
| VBuck | Vinyl Technologies, Inc. | 1-888-578-2825 | vbuck.com |

ADHESIVE & SEALANTS

| Product Name | Manufacturer | Contact | Website |
|------------------------------------|----------------------|----------------|--------------------------|
| Enerfoam Sealant/Enerbond Adhesive | Dow Chemical Company | 1-800-800-FOAM | dow.com/buildingproducts |

WALL BRACING & ALIGNMENT SYSTEMS

| Product Name | Manufacturer | Contact | Website |
|-----------------|-----------------|----------------|-----------------------------|
| Giraffe Bracing | Giraffe Bracing | 1-888-778-2285 | www.giraffebracing.com |
| Plumwall | Plumwall Ltd. | 1-905-786-7586 | www.plumwall.com |
| Mono-Brace | Tapco | 814-336-6549 | www.mono-brace.com |
| Amazing Brace | Lakeland Group | 905-372-7413 | www.lakeland-multitrade.com |

EXTERNAL VIBRATORS

| Product Name | Manufacturer | Contact | Website |
|-------------------|--------------------------|----------------|------------------------|
| Brecon | Brecon Inc. | 815-463-8073 | http://icfvibrator.com |
| Arkie Wall Banger | Available from Wind-lock | 1-800-872-5625 | - |

SUPPLIERS OF SUPPORTING ICF PRODUCTS

| Company | Contact | Website |
|-----------------------------|----------------|-----------------------|
| Wind-lock | 1-800-872-5625 | wind-lock.com |
| Grace Construction Products | See website | graceconstruction.com |


3.0 – ALIGNMENT & SCAFFOLDING SYSTEMS

TABLE OF CONTENTS

| | |
|--|--------|
| 3.1 – WALL BRACING & ALIGNMENT SYSTEMS..... | P. 3-2 |
| 3.2 – TALL WALL BRACING SYSTEMS..... | P. 3-4 |
| 3.3 – TALL WALL BRACING SYSTEMS USING SCAFFOLDING | P. 3-5 |

A
L
I
G
N
M
E
N
T
&
S
C
A
F
F
O
L
D
I
N
G
S
Y
S
T
E
M
S

3.1 – WALL BRACING & ALIGNMENT SYSTEMS



A bracing system provides support for the wall and acts as an alignment system to keep the walls straight and plumb during concrete placement. Typically, the wall alignment system is installed on the inner side of the LOGIX wall.

There are a number of proprietary systems available. However, each bracing unit typically consists of a vertical upright steel channel with slots for attaching screws to the LOGIX webs, a turnbuckle arm, and a scaffold bracket.



Normally, wall bracing systems are installed after placing 2 to 4 courses of LOGIX forms (depending on wind and other conditions). Attach the bracing system to the webs using #10 screws with a hex head. Screws should be snug, but not tight.

Place bracing units no more than 2ft (0.610m) from each corner or wall end, and every 7ft (2.134m) or less thereafter in accordance with OSHA/OHSA requirements. In addition, every door and window opening should be flanked on either side by bracing units, typically installed on the inner side of the LOGIX wall.



STEP 1: Attach the upright steel channel to the LOGIX webs with a #10 screw in each course. The screws should be snug but not tight. Always place screws near the top of the slots to accommodate settling at the interlock during concrete placement.

3.1 – WALL BRACING & ALIGNMENT SYSTEMS CONTINUED



STEP 2: Attach a turnbuckle arm to the upright with a bolt and then secure to the floor or ground. In light or sandy soils, additional care must be taken to secure diagonal turnbuckle. Ensure wall is close to plumb and threads on the turnbuckle is secured.



STEP 3: The scaffold bracket is then inserted behind the top of the turnbuckle and secured at the bottom with an additional bolt.

STEP 4: Place the appropriate scaffolding planks and rails according to safety regulations. For requirements on toeboard and handrail configuration, consult OSHA/OHSA.

STEP 5: Prior to concrete placement, make certain walls are leaning slightly inward. The wall must not lean out at all.



STEP 6: A stringline must be used to achieve straight walls.

STEP 7: Before, during and after concrete placement, the diagonal turnbuckle arm is used to adjust wall straightness to stringline.

3.2 – TALL WALL BRACING SYSTEMS



Tall walls are constructed in much the same way as concrete pours using traditional formwork. In general, the LOGIX blocks are stacked and braced, normally 10 to 12 feet high. The concrete is then placed. After the concrete sets the LOGIX blocks are then stacked another 10 to 12 feet, and bracing is raised or extended higher to support the wall, as well as keeping the wall plumb. This process is continued until the specified wall height is reached.



In higher wind areas taller walls may require guy wires for additional support.

LOGIX can be built to any height using either proprietary bracing systems or traditional scaffolding.







There are a number of proprietary tall wall bracing and alignment systems available. Many of the systems are designed to accommodate walls heights from 30 to 50 feet. For a list of some of these systems see **Section 2.23, Supporting Products**.

NOTE: When using wall bracing systems always follow the manufacturers recommended installation and instructions, including all required federal and local safety guidelines. Users of LOGIX and bracing systems should always follow OSHA/OHSA guidelines.

With minor modifications traditional scaffold (masonry scaffold) systems can also be used as the bracing and alignment system for tall walls (see **Section 3.2**). In addition, more experienced builders may have their own custom bracing systems designed to meet their preferred method of construction.

3.3 – TALL WALL BRACING SYSTEMS USING SCAFFOLDING



The following installation instructions demonstrates the use of scaffolding as a tall wall bracing and alignment system. The scaffolding system described is available from Form Systems, Inc. For more information contact your local LOGIX representative.

INSTALLATION STEPS


STEP 1: Complete two courses making sure they are straight, level and well anchored (**Figure A**).

STEP 2: The first scaffolding items needed are the base frames and screw jacks. The left end of the base frame as seen in **Figures B and C** is the end that will sit against the forms to allow the screw jacks to be adjusted.

STEP 3: Insert the screw jacks into the base frames as seen in **Figure C**. Create a base frame by attaching two 7ft (2.134m) ledgers (the horizontal pipes) to two base frames. Each ledger end has a wedge to anchor the system together (**Figure D**). To remove, hit from below. Once base frame is in place, level in all directions.


STEP 4: There are two kinds of vertical poles. Poles with the 2/3 rosettes go against the wall. Those with the full rosettes go into the center cup of the base frame (**Figure C**).

3.3 – TALL WALL BRACING SYSTEMS USING SCAFFOLDING CONTINUED



STEP 5: Install the two-foot ledgers that will hold the decks in place on every third rosette from the bottom. Note that the only 7ft (2.134m) ledger required against the wall is on the base frame. The rest of the scaffolding will require 7ft (2.134m) ledgers only on one side (**Figure F**).

STEP 6: Place one wire clip per course at each vertical 2/3 rosette pole (**Figure E**).



STEP 7: Insert 7ft (2.134m) ledgers for railings in the two rosettes above the planks (**Figure G**).

STEP 8: There are two adjustable diagonals. One is 4ft (1.220m) long and is intended to go to the inside of the vertical poles. It's designed to align the wall during the second or third build. For the first build, use the 10ft (3.048m) external adjustable diagonal (**Figure G**).



4.0 – ESTIMATING

TABLE OF CONTENTS

| | |
|--|---------|
| 4.1 – ESTIMATING..... | P. 4-3 |
| 4.2 – MATERIAL TAKE-OFF LIST | P. 4-4 |
| 4.3 – FORM UNITS | P. 4-5 |
| ESTIMATING STANDARD FORMS AND CORNERS.... | P. 4-5 |
| ESTIMATING BRICK LEDGE FORMS | P. 4-7 |
| ESTIMATING TRANSITION, DOUBLE TAPER TOP & TAPER TOP FORMS | P. 4-7 |
| ESTIMATING HEIGHT ADJUSTERS | P. 4-8 |
| ESTIMATING END CAPS | P. 4-8 |
| 4.4 – CONCRETE..... | P. 4-9 |
| 4" WALLS | P. 4-9 |
| 6.25" WALLS | P. 4-9 |
| 8" WALLS | P. 4-10 |
| 10" WALLS | P. 4-11 |
| 12" WALLS | P. 4-11 |
| ADD EXTRA CONCRETE FOR BRICK LEDGES | P. 4-12 |
| ADD EXTRA CONCRETE FOR TRANSITION FORMS..... | P. 4-13 |
| ADD EXTRA CONCRETE FOR TAPER TOPS..... | P. 4-13 |
| ADD EXTRA CONCRETE FOR DOUBLE TAPER TOPS..... | P. 4-13 |
| ALTERNATE METHOD FOR CALCULATING CONCRETE | P. 4-14 |
| 4.5 – REBAR..... | P. 4-15 |
| 4.6 – WATERPROOFING | P. 4-16 |
| 4.7 – PARGING | P. 4-17 |
| 4.8 – COURSE HEIGHT TABLE..... | P. 4-18 |
| 4.9 – LAYOUT TABLE..... | P. 4-19 |
| 4" PREFERRED WALL DIMENSIONS..... | P. 4-19 |
| 6.25" PREFERRED WALL DIMENSIONS..... | P. 4-20 |
| 8" PREFERRED WALL DIMENSIONS..... | P. 4-21 |
| 10" PREFERRED WALL DIMENSIONS..... | P. 4-22 |
| 12" PREFERRED WALL DIMENSIONS..... | P. 4-23 |
| 4.10 – ESTIMATING FORM..... | P. 4-24 |

4.1 – ESTIMATING

Calculating the number of forms needed is a simple task with LOGIX.

Drawing a wall section on graph paper before estimating a project saves time and effort and is a very helpful thing to do.

An important thing to remember in estimating is that walls with different heights should be calculated separately. As the wall heights change, so do the quantities required.

NOTE: The LOGIX Estimator program is now available for download www.logixicf.com.

4.2 – MATERIAL TAKE-OFF LIST

The material take off is the first step in any estimate.

- _____ Linear feet of exterior and interior LOGIX walls
- _____ Height of walls
- _____ Number of courses in wall
- _____ Thickness of wall (4", 6.25", 8", 10" or 12")
- _____ Number of 90° corners (both inside and outside)
- _____ Number of 45° corner (both inside and outside)
- _____ Linear feet of Brick Ledge
- _____ Linear feet of Transition forms
- _____ Linear feet of Taper Top
- _____ Linear feet of Double Taper Top
- _____ Square feet of parge coating "stucco" (height x length) between grade and siding
- _____ Square feet of water proofing (height x length) from grade to lap over footing
- _____ Square feet of door and window openings
- _____ Linear feet of buck material
- _____ Number of beam pockets (End Caps)
- _____ Linear feet of end walls (End Caps)
- _____ Linear feet of Height Adjusters (both sides of wall)

SQUARE FOOTAGE OF DIFFERENT FORM TYPES

| | |
|-------------------------|--|
| Standard (straight): | 5.33sf |
| Brick Ledge: | 5.33sf |
| Transition: | 5.33sf |
| Taper Top: | 5.33sf |
| Double Taper Top: | 5.33sf |
| 90° Corner: | 5.33sf (5.89sf for 10" and 12" corner forms) |
| 45° Corner: | 3.90sf |
| Pilaster: | 3.49sf max. |
| 4" Height Adjuster: | 0.66sf |
| Half Height Standard: | 2.67sf |
| Half Height 90° Corner: | 2.67sf |
| Half Height 45° Corner: | 1.95sf |

4.3 – FORM UNITS

ESTIMATING STANDARD FORMS AND CORNERS

STEP 1: Determine the total lineal feet of walls (both interior and exterior walls that will be built using LOGIX). Add an extra 2ft for every 45° or 90° inside corner to the total lineal feet of walls. With this new lineal footage, multiply by the height of the walls to determine the property's total square footage. When figuring the total square footage of walls with different heights it's easiest to figure each wall separately and then add totals together.

Subtract the total square footage of all window and door openings.

STEP 2: Determine number of 45° forms (**A**) by multiplying number of 45° turns by the number of courses (i.e. 6 courses x 4 turns). Then multiply the number of 45° forms by 3.9 sf/form. Then subtract this from your gross square footage of wall determined in **Step 1**.

If no 45° turns continue with **Step 3**.

STEP 3: Determine number of 90° corner forms (**B**) by multiplying number of 90° turns by the number of courses (i.e. 6 courses x 4 turns). Then multiply the number of 90° forms by 5.33 sf/form (or 5.89sf for 10" or 12" corner forms). Then subtract this from your square footage of wall determined in **Step 2** (if no 45° turns used, then subtract from gross square footage determined in **Step 1**).

ESTIMATING

4.3 – FORM UNITS CONTINUED

STEP 4: Divide square footage of wall determined in **Step 3** by 5.33 to determine gross number of Standard forms required. (C)

NOTE: Standard forms are all 16" (406mm) tall and 48" (1220mm) long with a wall area of 5.33sf each. All 90° Corners are 16" tall. The 4", 6.25" and 8" Ninety degree corner forms have one leg that is 16" long, the other 32" long for a total of 48", and a wall area of 5.33sf. The 10" and 12" Ninety degree corner forms have one leg that is 18.5" long, the other 34.5" long for a total of 53", and a wall area of 5.89sf.

- A. Number of **45°** forms required: _____
- B. Number of **90°** forms required: _____
- C. Number of **Standard** forms required: _____
- D. Total number of forms required: _____

4.3 – FORM UNITS CONTINUED

ESTIMATING BRICK LEDGE FORMS

NOTE: Brick Ledge forms are available in straight units only. Corner applications require miter cutting Brick Ledge forms on site.

Brick Ledge forms only come in 6.25", 8", 10" and 12" cavity sizes.

STEP 1: Measure the total linear feet of Brick Ledge needed and divide by 4 (the length in feet of each block) to determine the total number of Brick Ledge forms needed. When miter cutting Brick Ledge corners, add one Brick Ledge form for waste at each corner to the total Brick Ledge count.

STEP 2: Subtract the number of Brick Ledge forms from the total number of Standard forms determined earlier to avoid ordering too many Standard forms.

ESTIMATING TRANSITION, DOUBLE TAPER TOP & TAPER TOP FORMS

NOTE: The above forms are available in straight units only. Corner applications require miter cutting the forms on site.

Transition, Taper Top and Double Taper Top forms come in 6.25", 8", 10" or 12" cavity sizes.

4.3 – FORM UNITS CONTINUED

Follow **Steps 1 & 2** in “**Estimating Brick Ledge Forms**” to estimate the number of Transition, Taper Top or Double Taper Top forms required.

ESTIMATING HEIGHT ADJUSTERS

A 2ft Height Adjuster = 0.66sf. The number of 2ft long Height Adjusters needed is equal to the total linear footage.

NOTES: Height Adjusters come in one size, 4” x 24” x 2.75” thick. Remember to count both sides of the wall. Height Adjusters can be used in window openings to adjust height without cutting standards.

ESTIMATING END CAPS

NOTES: End Caps are 16” tall and 2-1/4” thick . End Caps come in all wall cavity sizes - 4”, 6.25”, 8”, 10” and 12”. Use End Caps at end wall applications. Use two End Caps for each beam pocket. Use End Caps for step foundations if necessary. End Caps can be used to form side bucks on door and window openings.

4.4 – CONCRETE

4" WALLS

STEP 1: Take the square footage of all wall area and subtract the square footage of all window and door openings.

STEP 2: Multiply by 0.333ft (the width of the cavity) to get the cubic feet of concrete required.

STEP 3: Divide by 27cf to determine the total number of yards of concrete required (or divide by 35.32 to determine meters of concrete required).

Example: 1845sf of wall area minus 322sf of window and door area equals 1523sf of net wall area. 1523sf times 0.333ft equals 507cf divided by 27cf per yard equals 18.8 yards of concrete required. Or divide 507cf by 35.32 for meters required. In this case, 14.4 meters.

E
S
T
I
M
A
T
I
N
G

6.25" WALLS

STEP 1: Take the square footage of all wall area and subtract the square footage of all window and door openings.

STEP 2: Multiply by 0.521ft (the width of the cavity) to get the cubic feet of concrete required.

4.4 – CONCRETE CONTINUED

STEP 3: Divide by 27cf to determine the yards of concrete required (or divide by 35.32 to determine meters required).

Example: 1845sf of wall area minus 322sf of window and door are equals 1523sf of net wall area. 1523sf times 0.521ft equals 793cf divided by 27cf per yard equals 29.4 yards of concrete. Or divide 793cf by 35.32 for meters required. In this case, 22.5.

8" WALLS

STEP 1: Take the square footage of all wall area and subtract the square footage of all window and door openings.

STEP 2: Multiply by 0.667ft (the width of the cavity) to get the cubic feet of concrete required.

STEP 3: Divide by 27 to determine the yards of concrete required (or by 35.32 to determine meters required).

Example: 1845sf of wall area minus 322sf of window and door area equals 1523sf of net wall area. 1523sf times 0.667ft equals 1016cf divided by 27cf per yard equals 37.6 yards of concrete. Or divide 1016cf by 35.32 for meters required. In this case, 28.8.

4.4 – CONCRETE CONTINUED

10" WALLS

STEP 1: Take the square footage of all wall area and subtract the square footage of all window and door openings.

STEP 2: Multiply by 0.833ft (the width of the cavity) to get the cubic feet of concrete required.

STEP 3: Divide by 27cf to determine the total number of yards of concrete required (or by 35.32 to determine meters of concrete required).

Example: 1845sf of wall area minus 322sf of window and door area equals 1523sf of net wall area. 1523sf times 0.833ft equals 1269cf divided by 27cf per yard equals 47.0 yards of concrete required. Or divide 1269cf by 35.32 for meters required. In this case, 35.9 meters.

ESTIMATING

12" WALLS

STEP 1: Take the square footage of all wall area and subtract the square footage of all window and door openings.

STEP 2: Multiply by 1ft (the width of the cavity) to get the cubic feet of concrete required.

4.4 – CONCRETE CONTINUED

STEP 3: Divide by 27cf to determine the total number of yards of concrete required (or by 35.32 to determine meters of concrete required).

Example: 1845sf of wall area minus 322sf of window and door area equals 1523sf of net wall area. 1523sf times 1ft equals 1523cf divided by 27cf per yard equals 56.4 yards of concrete required. Or divide 1523cf by 35.32 for meters required. In this case, 43.1 meters.

ADD EXTRA CONCRETE FOR BRICK LEDGES

Multiply linear feet of Brick Ledge by 0.007 cubic yards or 0.005 meters to determine the additional yards or meters of concrete needed.

Example: 200lf of Brick Ledge would require 1.4 extra yards of concrete (200 linear feet x 0.007 = 1.4 yards).

4.4 – CONCRETE CONTINUED

ADD EXTRA CONCRETE FOR TRANSITION FORMS

Multiply linear feet of Transition forms by 0.004 cubic yards or 0.003 meters to determine the additional yards or meters of concrete needed.

Example: 200lf of Transition forms would require 0.8 extra yards of concrete (200 linear feet x 0.004 = 0.8 yards).

ADD EXTRA CONCRETE FOR TAPER TOPS

Multiply linear feet of Taper Top by 0.003 cubic yards or cubic meters 0.002 to determine the additional yards or meter of concrete needed.

Example: 200lf of Taper Top forms would require an additional 0.6 yards of extra concrete (200lf x 0.003 = 0.6 yards).

ADD EXTRA CONCRETE FOR DOUBLE TAPER TOPS

Multiply linear feet of Double Taper Tops by 0.006 cubic yards or cubic meters 0.005 to determine the additional yards or meter of concrete needed.

Example: 200lf of Taper Top forms would require an additional 1.2 yards of extra concrete (200lf x 0.006 = 1.2 yards).

4.4 – CONCRETE CONTINUED

ALTERNATE METHOD FOR CALCULATING CONCRETE

An alternate method to calculate concrete is to use the chart below. Simply multiply the total number of forms by the appropriate multiplier to determine the cubic yards or cubic meters of concrete required.

| Form Size | Cubic Yards per Form Unit | Cubic Meters per Form Unit |
|-----------|------------------------------|-------------------------------|
| 4" | 0.066 | 0.050 |
| 6.25" | 0.103 | 0.079 |
| 8" | 0.132 | 0.100 |
| 10" | 0.165 | 0.126 |
| 12" | 0.198 | 0.151 |

4.5 – REBAR

Rebar estimating varies from wall to wall depending on factors such as height, vertical loading, horizontal loading, backfill heights, etc.

NOTE: Each Brick Ledge and Transition form will require six stirrups to tie the horizontal rebar in the corbel to the horizontal rebar in the interior of the form.

4.6 – WATERPROOFING

Multiply linear footage of walls by the height of backfill. When calculating backfill height, make sure to add enough height to allow the waterproofing materials to extend over the edge of the footing.

Divide this number by the square footage per roll of membrane material to determine the total number of rolls required.

If using a rigid waterproofing board, do not include a footing overlap in you calculations.

4.7 – PARGING

Parging typically covers from the top of the waterproofing membrane to a height 2" above the bottom edge of the siding.

Multiply the linear footage of wall by height of parging to determine total square footage of parging required.

Divide this number by the square footage per bag of parging material to determine the total number of bags required.

4.8 – COURSE HEIGHT TABLE

This table shows wall heights that are readily achieved using Standard LOGIX forms used in combination with 4" (102mm) Height Adjusters and/or 8" (203mm) Half Height forms.

| Number of Courses | Height of Wall | Add One Height Adj. | Add One Half-height | Add One Height Adj. & One Half-height |
|-------------------|--------------------|---------------------|---------------------|---------------------------------------|
| 1 | 1' - 4" (406mm) | 1' - 8" (508mm) | 2' - 0" (610mm) | 2' - 4" (711mm) |
| 2 | 2' - 8" (813mm) | 3' - 0" (914mm) | 3' - 4" (1016mm) | 3' - 8" (1118mm) |
| 3 | 4' - 0" (1219mm) | 4' - 4" (1321mm) | 4' - 8" (1422mm) | 5' - 0" (1524mm) |
| 4 | 5' - 4" (1626mm) | 5' - 8" (1727mm) | 6' - 0" (1829mm) | 6' - 4" (1930mm) |
| 5 | 6' - 8" (2032mm) | 7' - 0" (2134mm) | 7' - 4" (2235mm) | 7' - 8" (2337mm) |
| 6 | 8' - 0" (2438mm) | 8' - 4" (2540mm) | 8' - 8" (2642mm) | 9' - 0" (2743mm) |
| 7 | 9' - 4" (2845mm) | 9' - 8" (2946mm) | 10' - 0" (3048mm) | 10' - 4" (3150mm) |
| 8 | 10' - 8" (3251mm) | 11' - 0" (3353mm) | 11' - 4" (3454mm) | 11' - 8" (3556mm) |
| 9 | 12' - 0" (3658mm) | 12' - 4" (3759mm) | 12' - 8" (3861mm) | 13' - 0" (3962mm) |
| 10 | 13' - 4" (4064mm) | 13' - 8" (4166mm) | 14' - 0" (4267mm) | 14' - 4" (4369mm) |
| 11 | 14' - 8" (4470mm) | 15' - 0" (4572mm) | 15' - 4" (4674mm) | 15' - 8" (4775mm) |
| 12 | 16' - 0" (4877mm) | 16' - 4" (4978mm) | 16' - 8" (5080mm) | 17' - 0" (5182mm) |
| 13 | 17' - 4" (5283mm) | 17' - 8" (5385mm) | 18' - 0" (5486mm) | 18' - 4" (5588mm) |
| 14 | 18' - 8" (5690mm) | 19' - 0" (5791mm) | 19' - 4" (5893mm) | 19' - 8" (5994mm) |
| 15 | 20' - 0" (6096mm) | 20' - 4" (6198mm) | 20' - 8" (6299mm) | 21' - 0" (6401mm) |
| 16 | 21' - 4" (6502mm) | 21' - 8" (6604mm) | 22' - 0" (6706mm) | 22' - 4" (6807mm) |
| 17 | 22' - 8" (6909mm) | 23' - 0" (7010mm) | 23' - 4" (7112mm) | 23' - 8" (7214mm) |
| 18 | 24' - 0" (7315mm) | 24' - 4" (7417mm) | 24' - 8" (7518mm) | 25' - 0" (7620mm) |
| 19 | 25' - 4" (7722mm) | 25' - 8" (7823mm) | 26' - 0" (7925mm) | 26' - 4" (8026mm) |
| 20 | 26' - 8" (8128mm) | 27' - 0" (8230mm) | 27' - 4" (8331mm) | 27' - 8" (8433mm) |
| 21 | 28' - 0" (8534mm) | 28' - 4" (8636mm) | 28' - 8" (8738mm) | 29' - 0" (8839mm) |
| 22 | 29' - 4" (8941mm) | 29' - 8" (9042mm) | 30' - 0" (9144mm) | 30' - 4" (9246mm) |
| 23 | 30' - 8" (9347mm) | 31' - 0" (9449mm) | 31' - 4" (9550mm) | 31' - 8" (9652mm) |
| 24 | 32' - 0" (9754mm) | 32' - 4" (9855mm) | 32' - 8" (9957mm) | 33' - 0" (10058mm) |
| 25 | 33' - 4" (10160mm) | 33' - 8" (10262mm) | 34' - 0" (10363mm) | 34' - 4" (10465mm) |

ESTIMATING

Good. Solid. Green.™

www.logixcf.com

4 – 18




REPRINTED 2013

Rev. May 27/10

4.9 – LAYOUT TABLE

4" PREFERRED WALL DIMENSIONS



| Outside-Outside Corner | Inside-Inside Corner | Inside-Outside Corner |
|------------------------|----------------------|-----------------------|
| 3' 4" | 1' 9" | 2' 6.5" |
| 4' 0" | 2' 5" | 3' 2.5" |
| 4' 8" | 3' 1" | 3' 10.5" |
| 5' 4" | 3' 9" | 4' 6.5" |
| 6' 0" | 4' 5" | 5' 2.5" |
| 6' 8" | 5' 1" | 5' 10.5" |
| 7' 4" | 5' 9" | 6' 6.5" |
| 8' 0" | 6' 5" | 7' 2.5" |
| 8' 8" | 7' 1" | 7' 10.5" |
| 9' 4" | 7' 9" | 8' 6.5" |
| 10' 0" | 8' 5" | 9' 2.5" |
| 10' 8" | 9' 1" | 9' 10.5" |
| 11' 4" | 9' 9" | 10' 6.5" |
| 12' 0" | 10' 5" | 11' 2.5" |
| 12' 8" | 11' 1" | 11' 10.5" |
| 13' 4" | 11' 9" | 12' 6.5" |
| 14' 0" | 12' 5" | 13' 2.5" |
| 14' 8" | 13' 1" | 13' 10.5" |
| 15' 4" | 13' 9" | 14' 6.5" |
| 16' 0" | 14' 5" | 15' 2.5" |
| 16' 8" | 15' 1" | 15' 10.5" |
| 17' 4" | 15' 9" | 16' 6.5" |
| 18' 0" | 16' 5" | 17' 2.5" |
| 19' 4" | 17' 9" | 18' 6.5" |
| 20' 0" | 18' 5" | 19' 2.5" |
| 20' 8" | 19' 1" | 19' 10.5" |
| 21' 4" | 19' 9" | 20' 6.5" |
| 22' 0" | 20' 5" | 21' 2.5" |
| 22' 8" | 21' 1" | 21' 10.5" |


| Outside-Outside Corner | Inside-Inside Corner | Inside-Outside Corner |
|------------------------|----------------------|-----------------------|
| 23' 4" | 21' 9" | 22' 6.5" |
| 24' 0" | 22' 5" | 23' 2.5" |
| 24' 4" | 22' 9" | 23' 6.5" |
| 24' 8" | 23' 1" | 23' 10.5" |
| 26' 0" | 24' 5" | 25' 2.5" |
| 26' 8" | 25' 1" | 25' 10.5" |
| 27' 4" | 25' 9" | 26' 6.5" |
| 28' 0" | 26' 5" | 27' 2.5" |
| 28' 8" | 27' 1" | 27' 10.5" |
| 29' 4" | 27' 9" | 28' 6.5" |
| 30' 0" | 28' 5" | 29' 2.5" |
| 30' 8" | 29' 1" | 29' 10.5" |
| 31' 4" | 29' 9" | 30' 6.5" |
| 32' 0" | 30' 5" | 31' 2.5" |
| 32' 8" | 31' 1" | 31' 10.5" |
| 33' 4" | 31' 9" | 32' 6.5" |
| 34' 0" | 32' 5" | 33' 2.5" |
| 34' 8" | 33' 1" | 33' 10.5" |
| 35' 4" | 33' 9" | 34' 6.5" |
| 36' 0" | 34' 5" | 35' 2.5" |
| 36' 8" | 35' 1" | 35' 10.5" |
| 37' 4" | 35' 9" | 36' 6.5" |
| 38' 0" | 36' 5" | 37' 2.5" |
| 39' 4" | 37' 9" | 38' 6.5" |
| 40' 0" | 38' 5" | 39' 2.5" |
| 40' 8" | 39' 1" | 39' 10.5" |
| 41' 4" | 39' 9" | 40' 6.5" |
| 42' 0" | 40' 5" | 41' 2.5" |
| 42' 8" | 41' 1" | 41' 10.5" |

NOTES:

1. Preferred wall length dimensions that allow the use of full size LOGIX blocks (no cutting required) are indicated in shaded dimensions.
2. This table shows increments of 8" to allow block webs to be aligned between successive courses for attachment of interior/exterior finishes.
3. Window and door openings can fall anywhere in the wall envelope, window/door openings do not need to fall on cut line.

4.9 – LAYOUT TABLE

6.25" PREFERRED WALL DIMENSIONS



ESTIMATING

| Outside-Outside Corner | Inside-Inside Corner | Inside-Outside Corner |
|---------------------------|-------------------------|--------------------------|
| 3' 4" | 1' 4.5" | 2' 4.25" |
| 4' 0" | 2' 0.5" | 3' 0.25" |
| 4' 8" | 2' 8.5" | 3' 8.25" |
| 5' 4" | 3' 4.5" | 4' 4.25" |
| 6' 0" | 4' 0.5" | 5' 0.25" |
| 6' 8" | 4' 8.5" | 5' 8.25" |
| 7' 4" | 5' 4.5" | 6' 4.25" |
| 8' 0" | 6' 0.5" | 7' 0.25" |
| 8' 8" | 6' 8.5" | 7' 8.25" |
| 9' 4" | 7' 4.5" | 8' 4.25" |
| 10' 0" | 8' 0.5" | 9' 0.25" |
| 10' 8" | 8' 8.5" | 9' 8.25" |
| 11' 4" | 9' 4.5" | 10' 4.25" |
| 12' 0" | 10' 0.5" | 11' 0.25" |
| 12' 8" | 10' 8.5" | 11' 8.25" |
| 13' 4" | 11' 4.5" | 12' 4.25" |
| 14' 0" | 12' 0.5" | 13' 0.25" |
| 14' 8" | 12' 8.5" | 13' 8.25" |
| 15' 4" | 13' 4.5" | 14' 4.25" |
| 16' 0" | 14' 0.5" | 15' 0.25" |
| 16' 8" | 14' 8.5" | 15' 8.25" |
| 17' 4" | 15' 4.5" | 16' 4.25" |
| 18' 0" | 16' 0.5" | 17' 0.25" |
| 19' 4" | 17' 4.5" | 18' 4.25" |
| 20' 0" | 18' 0.5" | 19' 0.25" |
| 20' 8" | 18' 8.5" | 19' 8.25" |
| 21' 4" | 19' 4.5" | 20' 4.25" |
| 22' 0" | 20' 0.5" | 21' 0.25" |
| 22' 8" | 20' 8.5" | 21' 8.25" |

| Outside-Outside Corner | Inside-Inside Corner | Inside-Outside Corner |
|---------------------------|-------------------------|--------------------------|
| 23' 4" | 21' 4.5" | 22' 4.25" |
| 24' 0" | 22' 0.5" | 23' 0.25" |
| 24' 4" | 22' 4.5" | 23' 4.25" |
| 24' 8" | 22' 8.5" | 23' 8.25" |
| 26' 0" | 24' 0.5" | 25' 0.25" |
| 26' 8" | 24' 8.5" | 25' 8.25" |
| 27' 4" | 25' 4.5" | 26' 4.25" |
| 28' 0" | 26' 0.5" | 27' 0.25" |
| 28' 8" | 26' 8.5" | 27' 8.25" |
| 29' 4" | 27' 4.5" | 28' 4.25" |
| 30' 0" | 28' 0.5" | 29' 0.25" |
| 30' 8" | 28' 8.5" | 29' 8.25" |
| 31' 4" | 29' 4.5" | 30' 4.25" |
| 32' 0" | 30' 0.5" | 31' 0.25" |
| 32' 8" | 30' 8.5" | 31' 8.25" |
| 33' 4" | 31' 4.5" | 32' 4.25" |
| 34' 0" | 32' 0.5" | 33' 0.25" |
| 34' 8" | 32' 8.5" | 33' 8.25" |
| 35' 4" | 33' 4.5" | 34' 4.25" |
| 36' 0" | 34' 0.5" | 35' 0.25" |
| 36' 8" | 34' 8.5" | 35' 8.25" |
| 37' 4" | 35' 4.5" | 36' 4.25" |
| 38' 0" | 36' 0.5" | 37' 0.25" |
| 39' 4" | 37' 4.5" | 38' 4.25" |
| 40' 0" | 38' 0.5" | 39' 0.25" |
| 40' 8" | 38' 8.5" | 39' 8.25" |
| 41' 4" | 39' 4.5" | 40' 4.25" |
| 42' 0" | 40' 0.5" | 41' 0.25" |
| 42' 8" | 40' 8.5" | 41' 8.25" |

NOTES:

1. Preferred wall length dimensions that allow the use of full size LOGIX blocks (no cutting required) are indicated in shaded dimensions.
2. This table shows increments of 8" to allow block webs to be aligned between successive courses for attachment of interior/exterior finishes.
3. Window and door openings can fall anywhere in the wall envelope, window/door openings do not need to fall on cut line.

Good. Solid. Green.™

www.logixcf.com

4 – 20


LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. May 27/10

4.9 – LAYOUT TABLE

8" PREFERRED WALL DIMENSIONS



| Outside-Outside Corner | Inside-Inside Corner | Inside-Outside Corner |
|------------------------|----------------------|-----------------------|
| 3' 4" | 1' 1" | 2' 2.5" |
| 4' 0" | 1' 9" | 2' 10.5" |
| 4' 8" | 2' 5" | 3' 6.5" |
| 5' 4" | 3' 1" | 4' 2.5" |
| 6' 0" | 3' 9" | 4' 10.5" |
| 6' 8" | 4' 5" | 5' 6.5" |
| 7' 4" | 5' 1" | 6' 2.5" |
| 8' 0" | 5' 9" | 6' 10.5" |
| 8' 8" | 6' 5" | 7' 6.5" |
| 9' 4" | 7' 1" | 8' 2.5" |
| 10' 0" | 7' 9" | 8' 10.5" |
| 10' 8" | 8' 5" | 9' 6.5" |
| 11' 4" | 9' 1" | 10' 2.5" |
| 12' 0" | 9' 9" | 10' 10.5" |
| 12' 8" | 10' 5" | 11' 6.5" |
| 13' 4" | 11' 1" | 12' 2.5" |
| 14' 0" | 11' 9" | 12' 10.5" |
| 14' 8" | 12' 5" | 13' 6.5" |
| 15' 4" | 13' 1" | 14' 2.5" |
| 16' 0" | 13' 9" | 14' 10.5" |
| 16' 8" | 14' 5" | 15' 6.5" |
| 17' 4" | 15' 1" | 16' 2.5" |
| 18' 0" | 15' 9" | 16' 10.5" |
| 19' 4" | 17' 1" | 18' 2.5" |
| 20' 0" | 17' 9" | 18' 10.5" |
| 20' 8" | 18' 5" | 19' 6.5" |
| 21' 4" | 19' 1" | 20' 2.5" |
| 22' 0" | 19' 9" | 20' 10.5" |
| 22' 8" | 20' 5" | 21' 6.5" |


| Outside-Outside Corner | Inside-Inside Corner | Inside-Outside Corner |
|------------------------|----------------------|-----------------------|
| 23' 4" | 21' 1" | 22' 2.5" |
| 24' 0" | 21' 9" | 22' 10.5" |
| 24' 4" | 22' 1" | 23' 2.5" |
| 24' 8" | 22' 5" | 23' 6.5" |
| 26' 0" | 23' 9" | 24' 10.5" |
| 26' 8" | 24' 5" | 25' 6.5" |
| 27' 4" | 25' 1" | 26' 2.5" |
| 28' 0" | 25' 9" | 26' 10.5" |
| 28' 8" | 26' 5" | 27' 6.5" |
| 29' 4" | 27' 1" | 28' 2.5" |
| 30' 0" | 27' 9" | 28' 10.5" |
| 30' 8" | 28' 5" | 29' 6.5" |
| 31' 4" | 29' 1" | 30' 2.5" |
| 32' 0" | 29' 9" | 30' 10.5" |
| 32' 8" | 30' 5" | 31' 6.5" |
| 33' 4" | 31' 1" | 32' 2.5" |
| 34' 0" | 31' 9" | 32' 10.5" |
| 34' 8" | 32' 5" | 33' 6.5" |
| 35' 4" | 33' 1" | 34' 2.5" |
| 36' 0" | 33' 9" | 34' 10.5" |
| 36' 8" | 34' 5" | 35' 6.5" |
| 37' 4" | 35' 1" | 36' 2.5" |
| 38' 0" | 35' 9" | 36' 10.5" |
| 39' 4" | 37' 1" | 38' 2.5" |
| 40' 0" | 37' 9" | 38' 10.5" |
| 40' 8" | 38' 5" | 39' 6.5" |
| 41' 4" | 39' 1" | 40' 2.5" |
| 42' 0" | 39' 9" | 40' 10.5" |
| 42' 8" | 40' 5" | 41' 6.5" |

NOTES:

1. Preferred wall length dimensions that allow the use of full size LOGIX blocks (no cutting required) are indicated in shaded dimensions.
2. This table shows increments of 8" to allow block webs to be aligned between successive courses for attachment of interior/exterior finishes.
3. Window and door openings can fall anywhere in the wall envelope, window/door openings do not need to fall on cut line.

4.9 – LAYOUT TABLE

10" PREFERRED WALL DIMENSIONS



| Outside-Outside Corner | Inside-Inside Corner | Inside-Outside Corner | Outside-Outside Corner | Inside-Inside Corner | Inside-Outside Corner |
|------------------------|----------------------|-----------------------|------------------------|----------------------|-----------------------|
| 3' 4" | 0' 9" | 2' 0.5" | 23' 4" | 20' 9" | 22' 0.5" |
| 4' 0" | 1' 5" | 2' 8.5" | 24' 0" | 21' 5" | 22' 8.5" |
| 4' 5" | 1' 10" | 3' 1.5" | 24' 4" | 21' 9" | 23' 0.5" |
| 4' 8" | 2' 1" | 3' 4.5" | 24' 5" | 21' 10" | 23' 1.5" |
| 5' 4" | 2' 9" | 4' 0.5" | 24' 8" | 22' 1" | 23' 4.5" |
| 6' 0" | 3' 5" | 4' 8.5" | 26' 0" | 23' 5" | 24' 8.5" |
| 6' 8" | 4' 1" | 5' 4.5" | 26' 8" | 24' 1" | 25' 4.5" |
| 7' 4" | 4' 9" | 6' 0.5" | 27' 4" | 24' 9" | 26' 0.5" |
| 8' 0" | 5' 5" | 6' 8.5" | 28' 0" | 25' 5" | 26' 8.5" |
| 8' 5" | 5' 10" | 7' 1.5" | 28' 5" | 25' 10" | 27' 1.5" |
| 8' 8" | 6' 1" | 7' 4.5" | 28' 8" | 26' 1" | 27' 4.5" |
| 9' 4" | 6' 9" | 8' 0.5" | 29' 4" | 26' 9" | 28' 0.5" |
| 10' 0" | 7' 5" | 8' 8.5" | 30' 0" | 27' 5" | 28' 8.5" |
| 10' 8" | 8' 1" | 9' 4.5" | 30' 8" | 28' 1" | 29' 4.5" |
| 11' 4" | 8' 9" | 10' 0.5" | 31' 4" | 28' 9" | 30' 0.5" |
| 12' 0" | 9' 5" | 10' 8.5" | 32' 0" | 29' 5" | 30' 8.5" |
| 12' 5" | 9' 10" | 11' 1.5" | 32' 5" | 29' 10" | 31' 1.5" |
| 12' 8" | 10' 1" | 11' 4.5" | 32' 8" | 30' 1" | 31' 4.5" |
| 13' 4" | 10' 9" | 12' 0.5" | 33' 4" | 30' 9" | 32' 0.5" |
| 14' 0" | 11' 5" | 12' 8.5" | 34' 0" | 31' 5" | 32' 8.5" |
| 14' 8" | 12' 1" | 13' 4.5" | 34' 8" | 32' 1" | 33' 4.5" |
| 15' 4" | 12' 9" | 14' 0.5" | 35' 4" | 32' 9" | 34' 0.5" |
| 16' 0" | 13' 5" | 14' 8.5" | 36' 0" | 33' 5" | 34' 8.5" |
| 16' 5" | 13' 10" | 15' 1.5" | 36' 5" | 33' 10" | 35' 1.5" |
| 16' 8" | 14' 1" | 15' 4.5" | 36' 8" | 34' 1" | 35' 4.5" |
| 17' 4" | 14' 9" | 16' 0.5" | 37' 4" | 34' 9" | 36' 0.5" |
| 18' 0" | 15' 5" | 16' 8.5" | 38' 0" | 35' 5" | 36' 8.5" |
| 19' 4" | 16' 9" | 18' 0.5" | 39' 4" | 36' 9" | 38' 0.5" |
| 20' 0" | 17' 5" | 18' 8.5" | 40' 0" | 37' 5" | 38' 8.5" |
| 20' 5" | 17' 10" | 19' 1.5" | 40' 5" | 37' 10" | 39' 1.5" |
| 20' 8" | 18' 1" | 19' 4.5" | 40' 8" | 38' 1" | 39' 4.5" |
| 21' 4" | 18' 9" | 20' 0.5" | 41' 4" | 38' 9" | 40' 0.5" |
| 22' 0" | 19' 5" | 20' 8.5" | 42' 0" | 39' 5" | 40' 8.5" |
| 22' 8" | 20' 1" | 21' 4.5" | 42' 8" | 40' 1" | 41' 4.5" |

NOTES:

1. Preferred wall length dimensions that allow the use of full size LOGIX blocks (no cutting required) are indicated in shaded dimensions.
2. This table shows increments of 8" to allow block webs to be aligned between successive courses for attachment of interior/exterior finishes.
3. Window and door openings can fall anywhere in the wall envelope, window/door openings do not need to fall on cut line.

www.logixcf.com


Good. Solid. Green.™

4 – 22

LOGIX®
INSULATED CONCRETE FORMS

4.9 – LAYOUT TABLE

12" PREFERRED WALL DIMENSIONS



| Outside-Outside Corner | Inside-Inside Corner | Inside-Outside Corner |
|---------------------------|-------------------------|--------------------------|
| 3' 4" | 0' 5" | 1' 10.5" |
| 4' 0" | 1' 1" | 2' 6.5" |
| 4' 5" | 1' 6" | 2' 11.5" |
| 4' 8" | 1' 9" | 3' 2.5" |
| 5' 4" | 2' 5" | 3' 10.5" |
| 6' 0" | 3' 1" | 4' 6.5" |
| 6' 8" | 3' 9" | 5' 2.5" |
| 7' 4" | 4' 5" | 5' 10.5" |
| 8' 0" | 5' 1" | 6' 6.5" |
| 8' 5" | 5' 6" | 6' 11.5" |
| 8' 8" | 5' 9" | 7' 2.5" |
| 9' 4" | 6' 5" | 7' 10.5" |
| 10' 0" | 7' 1" | 8' 6.5" |
| 10' 8" | 7' 9" | 9' 2.5" |
| 11' 4" | 8' 5" | 9' 10.5" |
| 12' 0" | 9' 1" | 10' 6.5" |
| 12' 5" | 9' 6" | 10' 11.5" |
| 12' 8" | 9' 9" | 11' 2.5" |
| 13' 4" | 10' 5" | 11' 10.5" |
| 14' 0" | 11' 1" | 12' 6.5" |
| 14' 8" | 11' 9" | 13' 2.5" |
| 15' 4" | 12' 5" | 13' 10.5" |
| 16' 0" | 13' 1" | 14' 6.5" |
| 16' 5" | 13' 6" | 14' 11.5" |
| 16' 8" | 13' 9" | 15' 2.5" |
| 17' 4" | 14' 5" | 15' 10.5" |
| 18' 0" | 15' 1" | 16' 6.5" |
| 19' 4" | 16' 5" | 17' 10.5" |
| 20' 0" | 17' 1" | 18' 6.5" |
| 20' 5" | 17' 6" | 18' 11.5" |
| 20' 8" | 17' 9" | 19' 2.5" |
| 21' 4" | 18' 5" | 19' 10.5" |
| 22' 0" | 19' 1" | 20' 6.5" |
| 22' 8" | 19' 9" | 21' 2.5" |

| Outside-Outside Corner | Inside-Inside Corner | Inside-Outside Corner |
|---------------------------|-------------------------|--------------------------|
| 23' 4" | 20' 5" | 21' 10.5" |
| 24' 0" | 21' 1" | 22' 6.5" |
| 24' 4" | 21' 5" | 22' 10.5" |
| 24' 5" | 21' 6" | 22' 11.5" |
| 24' 8" | 21' 9" | 23' 2.5" |
| 26' 0" | 23' 1" | 24' 6.5" |
| 26' 8" | 23' 9" | 25' 2.5" |
| 27' 4" | 24' 5" | 25' 10.5" |
| 28' 0" | 25' 1" | 26' 6.5" |
| 28' 5" | 25' 6" | 26' 11.5" |
| 28' 8" | 25' 9" | 27' 2.5" |
| 29' 4" | 26' 5" | 27' 10.5" |
| 30' 0" | 27' 1" | 28' 6.5" |
| 30' 8" | 27' 9" | 29' 2.5" |
| 31' 4" | 28' 5" | 29' 10.5" |
| 32' 0" | 29' 1" | 30' 6.5" |
| 32' 5" | 29' 6" | 30' 11.5" |
| 32' 8" | 29' 9" | 31' 2.5" |
| 33' 4" | 30' 5" | 31' 10.5" |
| 34' 0" | 31' 1" | 32' 6.5" |
| 34' 8" | 31' 9" | 33' 2.5" |
| 35' 4" | 32' 5" | 33' 10.5" |
| 36' 0" | 33' 1" | 34' 6.5" |
| 36' 5" | 33' 6" | 34' 11.5" |
| 36' 8" | 33' 9" | 35' 2.5" |
| 37' 4" | 34' 5" | 35' 10.5" |
| 38' 0" | 35' 1" | 36' 6.5" |
| 39' 4" | 36' 5" | 37' 10.5" |
| 40' 0" | 37' 1" | 38' 6.5" |
| 40' 5" | 37' 6" | 38' 11.5" |
| 40' 8" | 37' 9" | 39' 2.5" |
| 41' 4" | 38' 5" | 39' 10.5" |
| 42' 0" | 39' 1" | 40' 6.5" |
| 42' 8" | 39' 9" | 41' 2.5" |

NOTES:

1. Preferred wall length dimensions that allow the use of full size LOGIX blocks (no cutting required) are indicated in shaded dimensions.
2. This table shows increments of 8" to allow block webs to be aligned between successive courses for attachment of interior/exterior finishes.
3. Window and door openings can fall anywhere in the wall envelope, window/door openings do not need to fall on cut line.

4.10 – ESTIMATING FORM

Customer Name: _____ Date: _____

Project Name: _____

Wall Type (Circle): Frost Wall Basement Main Floor Second Floor Other

Form Size (Circle): 4" 6.25" 8" 10" 12"

Estimating Data

| | | | |
|--|--------------------------------|--|---------------------------------|
| | Lineal Feet (LF) of Wall | | LF Height Adjusters |
| | Wall Height | | LF Extended Brick Ledge |
| | Number of 90° Turns | | LF Taper Top Form |
| | Number of 45° Turns | | Height of Backfill |
| | Number of Logix Courses | | Square Footage (SF) of Openings |
| | Number of Courses of Standards | | Gross SF of Wall (GSF) |
| | LF Form Lock | | Net SF of Wall (NSF) |

ESTIMATING

| Quantity | Description | Notes |
|----------|--------------------------------------|-------|
| | Total Number of Forms | |
| | Standard Forms | |
| | ½ Height Standards | |
| | 90° Corner Forms | |
| | ½ Height 90° Corner Forms | |
| | Brick Ledge | |
| | Transition Forms | |
| | Taper Top Forms | |
| | Double Taper Top Forms | |
| | Number of Height Adjusters (2' each) | |
| | Number of Form Lock (12.5' each) | |
| | Filament Tape (1 roll/50 blocks) | |
| | Zip Ties (1 bag/200 blocks) | |
| | Waterproofing Membrane (200sf/roll) | |
| | Rolls of Fiber Mesh (475sf/roll) | |
| | Bags of Prepcoat (85sf/bag) | |
| | LF/Type Rebar | |
| | Cubic Yards of Concrete | |
| | LF Window/Door Buck | |
| | Number of Alignment System Sets | |
| | Man Hours/sf | |

www.logixcf.com

Good. Solid. Green.™

4 – 2 4



5.0 – CAD DRAWINGS

TABLE OF CONTENTS

5.1 – LOGIX ICF FORMS

| | |
|---|---------|
| 5.1.1 – STANDARD FORM | P. 5-8 |
| 5.1.2 – BRICK LEDGE FORM | P. 5-9 |
| 5.1.3 – TRANSITION FORM | P. 5-10 |
| 5.1.4 – TAPER TOP FORM | P. 5-11 |
| 5.1.5 – DOUBLE TAPER TOP FORM | P. 5-12 |
| 5.1.6 – LEFT HAND CORNER FORM | P. 5-13 |
| 5.1.7 – RIGHT HAND CORNER FORM | P. 5-14 |
| 5.1.8 – LEFT HAND 45° FORM | P. 5-15 |
| 5.1.9 – RIGHT HAND 45° FORM | P. 5-16 |
| 5.1.10 – PILASTER FORM | P. 5-17 |
| 5.1.11 – HALF HEIGHT STANDARD FORM | P. 5-18 |
| 5.1.12 – HALF HEIGHT LEFT HAND CORNER FORM | P. 5-19 |
| 5.1.13 – HALF HEIGHT RIGHT HAND CORNER FORM | P. 5-20 |
| 5.1.14 – HALF HEIGHT LEFT HAND 45° FORM | P. 5-21 |
| 5.1.15 – HALF HEIGHT RIGHT HAND 45° FORM | P. 5-22 |
| 5.1.16 – END CAP & 4" HEIGHT ADJUSTER | P. 5-23 |
| 5.1.17 – REBAR SLOT LOCATIONS - LOGIX PRO FORMS (1 of 4) | P. 5-24 |
| 5.1.18 – LOGIX KD FORMS | |
| 5.1.18.1 – LOGIX KD RIGHT- HAND CORNER FORMS | P. 5-28 |
| 5.1.18.2 – LOGIX KD LEFT HAND CORNER FORMS | P. 5-30 |
| 5.1.18.3 – LOGIX KD FORMS | P. 5-32 |
| 5.1.19 – XRV PANELS | P. 5-33 |
| 5.1.20 – LOGIX HORIZONTAL & VERTICAL STEEL HOOKS | P. 5-34 |
| 5.1.21 – LOGIX FLEX BARS | P. 5-36 |
| 5.1.22 – LOGIX XTENDER | P. 5-37 |
| 5.1.23 – LOGIX T-WALL | P. 5-38 |

5.2 – FROST WALLS

- 5.2.1 – 4' FROST WALL (CRAWL SPACE).....P. 5-40
- 5.2.2 – 4'-8" FROST WALL (CRAWL SPACE)P. 5-41
- 5.2.3 – 6' FROST WALL (CRAWL SPACE).....P. 5-42
- 5.2.4 – 4' FROST WALL (INTEGRAL SLAB)P. 5-43
- 5.2.5 – 4' FROST WALL WITH DOUBLE
TAPER TOP SUPPORTING WOOD
FRAME AND BALANCED BACKFILL.....P. 5-44

5.3 – FOUNDATION WALLS

- 5.3.1 – 8' FOUNDATIONP. 5-45
- 5.3.2 – 8'-4" FOUNDATION.....P. 5-46
- 5.3.3 – 8'-8" FOUNDATION.....P. 5-47
- 5.3.4 – 9'-4" FOUNDATION.....P. 5-48
- 5.3.5 – 10'-4" FOUNDATION.....P. 5-49
- 5.3.6 – LOGIX BRICK LEDGE SUPPORTING
WOOD FRAME ABOVE GRADEP. 5-50
- 5.3.7 – 4' KNEE WALL WITH
6.25" LOGIX FORMSP. 5-51
- 5.3.8 – WATERPROOF DETAIL AROUND
BRICK LEDGE (optional)P. 5-52
- 5.3.9 – BELOW GRADE BRICK VENEERP. 5-53
- 5.3.10 – ALASKAN SLAB WITH LOGIX
XTENDERP. 5-54
- 5.3.11 – LOGIX FOOTING WITH XTENDER.....P. 5-55
- 5.3.12 – 8" TO 4" TRANSITION.....P. 5-56
- 5.3.13 – 8" TO 8" TRANSITION.....P. 5-57
- 5.3.14 – 8" TO 6.25" TRANSITION.....P. 5-58
- 5.3.15 – 8' FOUNDATION WALL WITH
BRICK LEDGEP. 5-59
- 5.3.16 – BRICK LEDGE FLASHING DETAILS.....P. 5-60
- 5.3.17 – WATERPROOF
MEMBRANE PROTECTIONP. 5-61

5.4 – SLAB CONSTRUCTION

| | |
|---|---------|
| 5.4.1 – 8' SLAB ON GRADE | P. 5-62 |
| 5.4.2 – 9'-4" SLAB ON GRADE | P. 5-63 |
| 5.4.3 – 8' SHALLOW FROST WALL..... | P. 5-64 |
| 5.4.4 – 9' SHALLOW FROST WALL..... | P. 5-65 |
| 5.4.5 – 8' WALL SLAB ON GRADE WITH DOUBLE TAPER TOP..... | P. 5-66 |
| 5.4.6 – SLAB ON GRADE WITH RADIANT HEATING | P. 5-67 |
| 5.4.7 – SLAB ON GRADE WITH BRICK LEDGE & MODIFIED TAPER TOP..... | P. 5-68 |

5.5 – ONE STOREY CONSTRUCTION

| | |
|--|---------|
| 5.5.1 – 8' FOUNDATION WALL/8' MAIN FLOOR | P. 5-69 |
| 5.5.2 – 8' FOUNDATION WALL/9' MAIN FLOOR | P. 5-70 |
| 5.5.3 - 8'-8" FOUNDATION WALL/ 10' MAIN FLOOR..... | P. 5-71 |
| 5.5.4 - 8" TO 4" TRANSITION WALL SECTION | P. 5-72 |
| 5.5.5 - ONE STOREY WALL SECTION WITH LOGIX XRV..... | P. 5-73 |
| 5.5.6 - LOGIX 6.25" BELOW- & ABOVE-GRADE WALL WITH BRICKLEDGE.. | P. 5-74 |

5.6 – TWO STOREY CONSTRUCTION

| | |
|--|---------|
| 5.6.1 – 8' FOUNDATION WALL/8' MAIN FLOOR/8' SECOND LEVEL..... | P. 5-75 |
| 5.6.2 – 8' FOUNDATION WALL/9' MAIN FLOOR/8' SECOND LEVEL..... | P. 5-76 |
| 5.6.3 – TWO STOREY WITH BRICK LEDGE & TRANSITION FORM -1 of 2..... | P. 5-77 |
| 5.6.4 – TWO STOREY WITH BRICK LEDGE & TRANSITION FORM - 2 of 2..... | P. 5-78 |
| 5.6.5 - TWO STOREY WALL SECTION WITH LOGIX XRV | P. 5-79 |

5.7 – FLOOR CONNECTIONS

| | |
|---|---------|
| 5.7.1 – 2x6 TOP PLATE RECESSED WITH DOUBLE TAPER TOP | P. 5-80 |
| 5.7.2 – 2x8 TOP PLATE OVERHUNG WITH DOUBLE TAPER TOP | P. 5-80 |
| 5.7.3 – 2x8 TOP PLATE OVERHUNG WITH TAPER TOP | P. 5-81 |
| 5.7.4 – MASONRY VENEER WITH TAPER TOP .. | P. 5-81 |
| 5.7.5 – TAPER TOP WITH LOG HOME | P. 5-82 |
| 5.7.6 – TAPER TOP WITH LOG HOME 2x12 SILL PLATE | P. 5-83 |
| 5.7.7 – TRANSITION - 8" TAPER TOP TO 4" STANDARD | P. 5-84 |
| 5.7.8 – SIMPSON ICF HANGER | P. 5-85 |
| 5.7.9 – SIMPSON STRONG TIE - ICF LEDGER CONNECTION SYSTEM..... | P. 5-86 |
| 5.7.10 – 8" TO 6" TRANSITION WITH | P. 5-87 |
| SIMPSON ICF HANGERS | P. 5-87 |
| 5.7.11 – ANCHOR TUNNEL - FLOOR LEDGER CONNECTION | P. 5-88 |
| 5.7.12 – McMILLAN JOIST HANGER | P. 5-89 |
| 5.7.13 – SIMPSON STRONG TIE- STUD FRAME CONNECTIONS | P. 5-90 |
| 5.7.14 – FRAME STRAP ALTERNATIVE..... | P. 5-91 |
| 5.7.15 – 6.25" TRANSITION FORM SUPPORTING WOOD FLOOR JOIST | P. 5-92 |
| 5.7.16 – WOOD FLOOR JOIST PARALLEL TO WALL (1 OF 2)..... | P. 5-93 |
| 5.7.17 – BELOW GRADE BRICK VENEER (1 OF 4) | P. 5-95 |
| 5.7.18 – McMILLAN JOIST HANGER WOOD JOIST CONNECTION | P. 5-99 |

5.8 – ROOF CONNECTIONS

| | |
|---|----------|
| 5.8.1 – ROOF - 2x6 RECESSED TOP PLATE | P. 5-100 |
| 5.8.2 – ROOF - 2x8 OVERHUNG TOP PLATE..... | P. 5-100 |
| 5.8.3 – ROOF - 2x6 WITH TAPER TOP FORM..... | P. 5-101 |
| 5.8.4 – ROOF - HURRICANE TIE DOWN STRAP | P. 5-102 |
| 5.8.5 – VAULTED CEILINGS - 1 of 2..... | P. 5-103 |
| 5.8.6 – LOGIX WALL WITH SIP ROOF | P. 5-105 |
| 5.8.7 – ROOF DETAIL WITH SIMPSON STRONG-TIE H1/H2.5 STRAP | P. 5-106 |
| 5.8.8 – GABLE WALL END WOOD FRAMED CONNECTION..... | P. 5-107 |

5.9 – WINDOW & DOOR DETAILS

| | |
|---|----------|
| 5.9.1 – DOOR JAMB, HEAD & SILL | P. 5-108 |
| 5.9.2 – SLOPED CONCRETE SILL..... | P. 5-109 |
| 5.9.3 – WINDOW HEAD / SILL DETAIL..... | P. 5-110 |
| 5.9.4 – WINDOW BUCK DETAILS..... | P. 5-111 |
| 5.9.5 – STEEL LINTEL WITH BRICK VENEER..... | P. 5-113 |
| 5.9.6 - WINDOW HEAD/SILL DETAIL WITH LOGIX XRV | P. 5-114 |
| 5.9.7 – WINDOW FLASHING DETAIL | P. 5-115 |

5.10 – SPECIAL DETAILS

| | |
|--|----------|
| 5.10.1 – REINFORCING - CORNER WALL | P. 5-116 |
| 5.10.2 – REINFORCING - CORNER WITH BRICK LEDGE FORMS | P. 5-117 |
| 5.10.3 – REINFORCING - CORNER WITH 6.25" TRANSITION FORMS | P. 5-118 |
| 5.10.4 – REINFORCING - T-WALL | P. 5-119 |
| 5.10.5 – TYPICAL REINFORCEMENT AROUND OPENINGS | P. 5-120 |
| 5.10.6 / 5.10.7 – BRICK LEDGE STANDARD REINFORCEMENT / BRICK LEDGE HEAVY REINFORCEMENT | P. 5-121 |
| 5.10.8 – BRICK LEDGE STIRRUP DETAIL | P. 5-122 |

| | |
|---|----------|
| 5.10.9 – ATTACHING TO STUD FRAMED WALLS..... | P. 5-123 |
| 5.10.10 – LOGIX ICF WITH EXTERIOR FINISHES | P. 5-124 |
| 5.10.11 – LOGIX ICF WITH STONE VENEER..... | P. 5-125 |
| 5.10.12 – LOGIX ICF POOL APPLICATION..... | P. 5-126 |
| 5.10.13 – GRAB BAR SUPPORT | P. 5-127 |
| 5.10.14 – DECK ATTACHMENT | P. 5-128 |
| 5.10.15 – TRANSITION FROM TAPER TOP TO BRICK LEDGE | P. 5-129 |
| 5.10.16 – TERMITE STRIP | P. 5-130 |
| 5.10.17 – SIMPSON STRONG TIE WITH CABINETS..... | P. 5-131 |
| 5.10.18– LOGIX ICF WITH BILCO SIZE “C” STANDARD CLASSIC SERIES DOORS..... | P. 5-132 |
| 5.10.19 – LOGIX 6.25” ON 8” BRICK LEDGE | P. 5-133 |
| 5.10.20 – FIRE WALL ABOVE ROOF LINE | P. 5-134 |
| 5.10.21 – OVERHEAD GARAGE DOOR..... | P. 5-135 |
| 5.10.22 – RADON BARRIER UNDER SLAB | P. 5-136 |
| 5.10.23 – POOL DETAIL FORMING FOR COPING OPTION 1 (1 OF 5)..... | P. 5-137 |
| 5.10.24 – POOL DETAIL FORMING FOR COPING OPTION 2 (2 OF 5)..... | P. 5-138 |
| 5.10.25 – POOL DETAIL OF INLET / OUTLET FIXTURE (3 OF 5) | P. 5-139 |
| 5.10.26 – POOL DETAIL AT FOOTING (4 OF 5) | P. 5-140 |
| 5.10.27 – POOL SKIMMER (5 OF 5) | P. 5-141 |
| 5.10.28 – BRICK LEDGE WITH TIMBER POST | P. 5-142 |

5.1 – LOGIX ICF FORMS

All drawings are downloadable at www.logixicf.com

LOGIX ICFs are available in many variations designed to accommodate all construction type details.


LOGIX carries both assembled form units, known as LOGIX PRO, and unassembled (or knock-down) systems known as LOGIX KD. LOGIX KD is also available in thicker panel forms, known as LOGIX XRV (see Drawings 5.1.18 and 5.1.19, respectively). LOGIX XRV are panelized forms that are available in thicker foam panels ranging from 4 to 8 inches. In addition, LOGIX Xtenders allow LOGIX forms to be used for wider concrete wall thicknesses greater than 12 inches (see Drawing 5.1.22).

For a complete list of LOGIX product lines see Section 8.1.


NOTE: The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

LOGIX ICF FORMS 5.1.1 – STANDARD FORM


All drawings are downloadable at www.logixcf.com




PLAN VIEW



SIDE ELEVATION



END VIEW



| FORM SIZES | | | | | |
|------------|--------------|----------------|---------------|---------------|---------------|
| | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) | 12" (305mm) |
| A | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) | 12" (305mm) |
| B | 9.5" (241mm) | 11.75" (298mm) | 13.5" (343mm) | 15.5" (394mm) | 17.5" (445mm) |

NOTES:

- Forms are available as assembled (LOGIX PRO) or unassembled (or knock-down) form blocks (LOGIX KD. See 5.1.18).
- Concrete core thickness wider than 12" (305mm) are available using LOGIX Xtenders (See 5.1.22).
- 6 1/4" [159mm] LOGIX Standard Form shown.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

Good. Solid. Green.™

www.logixcf.com


5 – 8

LOGIX®
INSULATED CONCRETE FORMS


Rev. Nov 11/10

LOGIX ICF FORMS 5.1.2 – BRICK LEDGE FORM

All drawings are downloadable at www.logixicf.com




PLAN VIEW



SIDE ELEVATION

END VIEW



| FORM SIZES | | | | | |
|------------|-----------------|-----------------|-----------------|-----------------|-----------------|
| | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) | 12" (305mm) |
| A | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) | 12" (305mm) |
| B | 13.325" (340mm) | 15.625" (397mm) | 17.375" (441mm) | 19.375" (492mm) | 21.375" (543mm) |
| C | 9.875" (251mm) | 12.125" (308mm) | 13.875" (352mm) | 15.875" (403mm) | 17.875" (454mm) |
| D | 9.5" (241mm) | 11.75" (298mm) | 13.5" (343mm) | 15.5" (394mm) | 17.5" (445mm) |

NOTES:

- Forms are available as assembled (LOGIX PRO) or unassembled (or knock-down) form blocks (LOGIX KD. See 5.1.18).
- Concrete core thickness wider than 12" (305mm) are available using LOGIX Xtenders (See 5.1.22).
- 6 1/4" [159mm] LOGIX Brick Ledge Form shown.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

CAD DRAWINGS

www.logixicf.com

Good. Solid. Green.™

5 – 9


LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013


Rev. Nov 11/10

LOGIX ICF FORMS 5.1.3 – TRANSITION FORM

All drawings are downloadable at www.logixicf.com




PLAN VIEW



SIDE ELEVATION

END VIEW



FORM SIZES

| | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) | 12" (305mm) |
|---|--------------|----------------|----------------|----------------|----------------|
| A | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) | 12" (305mm) |
| B | 8.5" (216mm) | 10" (254mm) | 11.75" (298mm) | 13.75" (349mm) | 15.75" (400mm) |
| C | 9.5" (241mm) | 11.75" (298mm) | 13.5" (343mm) | 15.5" (394mm) | 17.5" (445mm) |

NOTES:

- Forms are available as assembled (LOGIX PRO) or unassembled (knock-down) form blocks (LOGIX KD. See 5.1.18).
- Concrete core thickness wider than 12" (305mm) are available using LOGIX Xtenders (See 5.1.22).
- Use of LOGIX Transition Forms on the exterior below-grade could subject the EPS face of the corbel ledge to frost heave forces. The LOGIX Brickledge Forms or LOGIX Taper Top Forms are recommended for use below-grade where the ledge is located on the exterior of the structure.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com


Good. Solid. Green.™

5 – 10

LOGIX®
INSULATED CONCRETE FORMS


LOGIX ICF FORMS 5.1.4 – TAPER TOP FORM

All drawings are downloadable at www.logixicf.com




PLAN VIEW


2 3/4" (70mm) panels



SIDE ELEVATION



END VIEW



| FORM SIZES | | | | | |
|------------|---------------|----------------|---------------|----------------|----------------|
| | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) | 12" (305mm) |
| A | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) | 12" (305mm) |
| B | 9.5" (241mm) | 11.75" (298mm) | 13.5" (343mm) | 15.5" (394mm) | 17.5" (445mm) |
| C | 5.75" (146mm) | 8" (203mm) | 9.75" (248mm) | 11.75" (298mm) | 13.75" (349mm) |

NOTES:

- Forms are available as assembled (LOGIX PRO) or unassembled (knock-down) form blocks (LOGIX KD. See 5.1.18).
- Concrete core thickness wider than 12" (305mm) are available using LOGIX Xenders (See 5.1.22).
- 6 1/4" [159mm] Taper Top Form shown.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

CAD DRAWINGS

www.logixicf.com

Good. Solid. Green.™

5-11


LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013


Rev. Nov 11/10

LOGIX ICF FORMS 5.1.5 – DOUBLE TAPER TOP FORM


All drawings are downloadable at www.logixicf.com




PLAN VIEW



SIDE ELEVATION



END VIEW



FORM SIZES

| | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) | 12" (305mm) |
|---|--------------|----------------|---------------|---------------|---------------|
| A | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) | 12" (305mm) |
| B | 9.5" (241mm) | 11.75" (298mm) | 13.5" (343mm) | 15.5" (394mm) | 17.5" (445mm) |
| C | 7.5" (191mm) | 9.75" (248mm) | 11.5" (292mm) | 13.5" (343mm) | 15.5" (394mm) |

NOTES:

- Forms are available as assembled (LOGIX PRO) or unassembled (knock-down) form blocks (LOGIX KD. See 5.1.18).
- Concrete core thickness wider than 12" (305mm) are available using LOGIX Xenders (See 5.1.22).
- 6 1/4" [159mm] Double Tapered Top Form shown.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™


5 – 12

LOGIX®
INSULATED CONCRETE FORMS


Rev. Nov 11/10

LOGIX ICF FORMS 5.1.6 – LEFT HAND CORNER FORM


All drawings are downloadable at www.logixicf.com



PLAN VIEW



SIDE ELEVATION



| | FORM SIZES | | | |
|---|-----------------|-----------------|-----------------|----------------|
| | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) |
| A | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) |
| B | 9.5" (241mm) | 11.75" (298mm) | 13.5" (343mm) | 15.5" (394mm) |
| C | 3.5" (90mm) | 3.375" (87mm) | 2.25" (57mm) | 2.125" (55mm) |
| D | 7.67" (195mm) | 7.67" (195mm) | 6.125" (157mm) | 5.875" (150mm) |
| E | 32.125" (816mm) | 32.125" (816mm) | 32.125" (816mm) | 34.5" (876mm) |
| F | 16.125" (410mm) | 16.125" (410mm) | 16.125" (410mm) | 18.5" (470mm) |

NOTES:

- Forms are available as assembled (LOGIX PRO) or unassembled (knock-down) form blocks (LOGIX KD. See 5.1.18).
- Concrete core thickness wider than 12" (305mm) are available using LOGIX Xenders (See 5.1.22).
- 6 1/4" [159mm] Left Hand Corner Form shown.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5 – 13


LOGIX®
INSULATED CONCRETE FORMS

Rev. Nov 11/10


CAD DRAWINGS

LOGIX ICF FORMS 5.1.7 – RIGHT HAND CORNER FORM


All drawings are downloadable at www.logixcf.com



PLAN VIEW



SIDE ELEVATION



| FORM SIZES | | | | |
|------------|-----------------|-----------------|-----------------|----------------|
| | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) |
| A | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) |
| B | 9.5" (241mm) | 11.75" (298mm) | 13.5" (343mm) | 15.5" (394mm) |
| C | 3.5" (90mm) | 3.375" (87mm) | 2.25" (57mm) | 2.125" (55mm) |
| D | 7.67" (195mm) | 7.67" (195mm) | 6.125" (157mm) | 5.875" (150mm) |
| E | 32.125" (816mm) | 32.125" (816mm) | 32.125" (816mm) | 34.5" (876mm) |
| F | 16.125" (410mm) | 16.125" (410mm) | 16.125" (410mm) | 18.5" (470mm) |

NOTES:

- Forms are available as assembled (LOGIX PRO) or unassembled (knock-down) form blocks (LOGIX KD. See 5.1.18).
- Concrete core thickness wider than 12" (305mm) are available using LOGIX Xenders (See 5.1.22).
- 6 1/4" [159mm] Right Hand Corner Form shown.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

CAD DRAWINGS

www.logixcf.com



Good. Solid. Green.™

5 – 14


LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 11/10

All drawings are downloadable at www.logixicf.com**PLAN VIEW****ELEVATION A-A**

For clarity knobs partially removed in elevation views.

**ELEVATION B-B****FORM SIZES**

| | 4" (102mm) | 6.25" (159mm) | 8" (203mm) |
|---|----------------|----------------|---------------|
| A | 4" (102mm) | 6.25" (159mm) | 8" (203mm) |
| B | 9.5" (241mm) | 11.75" (298mm) | 13.5" (343mm) |
| C | 22.75" (577mm) | 21.75" (553mm) | 21" (535mm) |
| D | 5.5" (141mm) | 4.625" (118mm) | 3.875" (99mm) |

NOTES:




- Forms are available as assembled (LOGIX PRO) or unassembled (knock-down) form blocks (LOGIX KD. See 5.1.18).
- Concrete core thickness wider than 12" (305mm) are available using LOGIX Xenders (See 5.1.22).
- 6 1/4" [159mm] Left Hand 45° Corner Form shown.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixicf.com**Good. Solid. Green.™****5 – 15**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 11/10

All drawings are downloadable at www.logixicf.com**PLAN VIEW****ELEVATION B-B****ELEVATION A-A**

For clarity knobs partially removed in elevation views.

**NOTES:**


- Forms are available as assembled (LOGIX PRO) or unassembled (knock-down) form blocks (LOGIX KD. See 5.1.18).
- Concrete core thickness wider than 12" (305mm) are available using LOGIX Xtenders (See 5.1.22).
- 6 1/4" [159mm] Right Hand 45° Corner Form shown.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


| FORM SIZES | | | |
|------------|----------------|----------------|---------------|
| | 4" (102mm) | 6.25" (159mm) | 8" (203mm) |
| A | 4" (102mm) | 6.25" (159mm) | 8" (203mm) |
| B | 9.5" (241mm) | 11.75" (298mm) | 13.5" (343mm) |
| C | 22.75" (577mm) | 21.75" (553mm) | 21" (535mm) |
| D | 5.5" (141mm) | 4.625" (118mm) | 3.875" (99mm) |

www.logixicf.com**Good. Solid. Green.™****5 – 16**
LOGIX®
 INSULATED CONCRETE FORMS


All drawings are downloadable at www.logixicf.com




TOP VIEW




FRONT ELEVATION



**RIGHT
(LEFT SIDE SIMILAR)**



REAR ELEVATION




The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

LOGIX ICF FORMS 5.1.11 – HALF HEIGHT STANDARD FORM


All drawings are downloadable at www.logixicf.com

NOTES:


1. 6 $\frac{1}{4}$ " Half Height
Standard Form shown




PLAN VIEW



SIDE ELEVATION



END VIEW



FORM SIZES

| | 4" (102mm) | 6.25" (159mm) | 8" (203mm) |
|---|--------------|----------------|---------------|
| A | 4" (102mm) | 6.25" (159mm) | 8" (203mm) |
| B | 9.5" (241mm) | 11.75" (298mm) | 13.5" (343mm) |

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5 – 18


LOGIX®
INSULATED CONCRETE FORMS

LOGIX ICF FORMS 5.1.12 – HALF HEIGHT LEFT HAND CORNER FORM


All drawings are downloadable at www.logixicf.com

NOTES:


- 1. 6½" Half Height Left Hand Corner Form shown



PLAN VIEW



SIDE ELEVATION



| FORM SIZES | | | |
|------------|---------------|----------------|----------------|
| | 4" (102mm) | 6.25" (159mm) | 8" (203mm) |
| A | 4" (102mm) | 6.25" (159mm) | 8" (203mm) |
| B | 9.5" (241mm) | 11.75" (298mm) | 13.5" (343mm) |
| C | 3.5" (90mm) | 3.375" (87mm) | 2.25" (57mm) |
| D | 7.67" (195mm) | 7.67" (195mm) | 6.125" (157mm) |


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

LOGIX ICF FORMS 5.1.13 – HALF HEIGHT RIGHT HAND CORNER FORM


All drawings are downloadable at www.logixicf.com

NOTES:


1. 6 $\frac{1}{4}$ " Half Height Right Hand Corner Form shown



PLAN VIEW



SIDE ELEVATION



FORM SIZES

| | 4" (102mm) | 6.25" (159mm) | 8" (203mm) |
|---|---------------|----------------|----------------|
| A | 4" (102mm) | 6.25" (159mm) | 8" (203mm) |
| B | 9.5" (241mm) | 11.75" (298mm) | 13.5" (343mm) |
| C | 3.5" (90mm) | 3.375" (87mm) | 2.25" (57mm) |
| D | 7.67" (195mm) | 7.67" (195mm) | 6.125" (157mm) |

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

Good. Solid. Green.™



www.logixicf.com

5 – 20



LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**

1. $6\frac{1}{4}$ " LOGIX Half Height Left Hand 45° Corner Form shown

**PLAN VIEW****ELEVATION A-A**

For clarity knobs partially removed in elevation views.




**ELEVATION B-B**

| FORM SIZES | | | |
|------------|----------------|----------------|---------------|
| | 4" (102mm) | 6.25" (159mm) | 8" (203mm) |
| A | 4" (102mm) | 6.25" (159mm) | 8" (203mm) |
| B | 9.5" (241mm) | 11.75" (298mm) | 13.5" (343mm) |
| C | 22.75" (577mm) | 21.75" (553mm) | 21" (535mm) |
| D | 5.5" (141mm) | 4.625" (118mm) | 3.875" (99mm) |


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

All drawings are downloadable at www.logixicf.com**NOTES:**

1. 6 $\frac{1}{4}$ " Half Height
Right Hand 45°
Corner Form shown



For clarity knobs partially removed in elevation views.


**FORM SIZES**

| | 4" (102mm) | 6.25" (159mm) | 8" (203mm) |
|---|----------------|----------------|---------------|
| A | 4" (102mm) | 6.25" (159mm) | 8" (203mm) |
| B | 9.5" (241mm) | 11.75" (298mm) | 13.5" (343mm) |
| C | 22.75" (577mm) | 21.75" (553mm) | 21" (535mm) |
| D | 5.5" (141mm) | 4.625" (118mm) | 3.875" (99mm) |


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

LOGIX ICF FORMS 5.1.16 – END CAP & 4" HEIGHT ADJUSTER

All drawings are downloadable at www.logixicf.com




PLAN VIEW




SIDE ELEVATION




END VIEW



| FORM SIZES | | | | | |
|------------|---------------|------------------|---------------|----------------|----------------|
| | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) | 12" (305mm) |
| A | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) | 12" (305mm) |




PLAN VIEW



SIDE ELEVATION



END VIEW



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

Good. Solid. Green.™

www.logixicf.com

5 – 23

LOGIX®
INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Nov 11/10


CAD DRAWINGS

All drawings are downloadable at www.logixicf.com

CAD DRAWINGS




4" LOGIX PRO




6 $\frac{1}{4}$ " LOGIX PRO

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

All drawings are downloadable at www.logixicf.com



8" LOGIX PRO





10" LOGIX PRO

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S




The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com


Good. Solid. Green.™

5 - 26

LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

10" [254mm] LOGIX KD CONNECTORS




12" [305mm] LOGIX KD CONNECTORS

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


5.1.18 – LOGIX KD FORMS

5.1.18.1 – LOGIX KD RIGHT-HAND CORNER FORMS


All drawings are downloadable at www.logixicf.com




PLAN VIEW



SIDE ELEVATION



**WEB COMPONENTS
(NTS)**








| | FORM SIZES | | | |
|---|------------|-----------------|-----------------|----------------|
| | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) |
| A | N/A | 6.25" (159mm) | 8" (203mm) | 10" (254mm) |
| B | N/A | 11.75" (298mm) | 13.5" (343mm) | 15.5" (394mm) |
| C | N/A | 3.375" (87mm) | 2.25" (57mm) | 2.125" (55mm) |
| D | N/A | 7.67" (195mm) | 6.125" (157mm) | 5.875" (150mm) |
| E | N/A | 32.125" (816mm) | 32.125" (816mm) | 34.5" (876mm) |
| F | N/A | 16.125" (410mm) | 16.125" (410mm) | 18.5" (470mm) |

NOTES:

1. 6 1/4" Right Hand LOGIX KD Corner Form shown.
2. Drawings showing rebar slot locations will be available upon request.
3. For 12" Right Hand LOGIX KD Corner Form see Pg 3/4 or 4/4.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

All drawings are downloadable at www.logixicf.com**PLAN VIEW****SIDE ELEVATION****REBAR SLOT
LOCATIONS**





The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 – 29****LOGIX®**
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 11/10

C A D D R A W I N G S






All drawings are downloadable at www.logixicf.com**PLAN VIEW****SIDE ELEVATION****WEB COMPONENTS (NTS)****FORM SIZES**

| | 4" (102mm) | 6.25" (159mm) | 8" (203mm) | 10" (254mm) |
|---|------------|-----------------|-----------------|----------------|
| A | N/A | 6.25" (159mm) | 8" (203mm) | 10" (254mm) |
| B | N/A | 11.75" (298mm) | 13.5" (343mm) | 15.5" (394mm) |
| C | N/A | 3.375" (87mm) | 2.25" (57mm) | 2.125" (55mm) |
| D | N/A | 7.67" (195mm) | 6.125" (157mm) | 5.875" (150mm) |
| E | N/A | 32.125" (816mm) | 32.125" (816mm) | 34.5" (876mm) |
| F | N/A | 16.125" (410mm) | 16.125" (410mm) | 18.5" (470mm) |

NOTES:

1. 6 1/4" Right Hand LOGIX KD Corner Form shown.
2. Drawings showing rebar slot locations will be available upon request.
3. For 12" Right Hand LOGIX KD Corner Form see Pg 3/4 or 4/4.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

All drawings are downloadable at www.logixicf.com**PLAN VIEW****SIDE ELEVATION****WEB COMPONENTS
(NTS)****REBAR SLOT
LOCATIONS**

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5-31****LOGIX®**
INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Nov 11/10


C A D D R A W I N G S

All drawings are downloadable at www.logixicf.com


LOGIX KD PANELS




Standard



Taper Top




Brick Ledge




Transition Block


LOGIX KD PANELS





Standard—Standard




Taper Top—Taper Top




Brick Ledge—Brick Ledge

Transition Block
—Transition Block


Standard—Taper Top




Taper Top—Brick Ledge




Brick Ledge—Transition Block



Standard—Brick Ledge



Taper Top—Transition Block



Standard—Transition Block

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

CAD DRAWINGS


www.logixicf.com

Good. Solid. Green.™


5 – 32

LOGIX®
INSULATED CONCRETE FORMS


All drawings are downloadable at www.logixicf.com





PLAN VIEW



SIDE ELEVATION



END VIEW



**WEB COMPONENTS
(NTS) (See Note 2)**

| PANEL SIZES | | | | | |
|-------------|---------|---------|---------|---------|---------|
| A | 4" | 5" | 6" | 7" | 8" |
| | (102mm) | (127mm) | (152mm) | (178mm) | (203mm) |

NOTES:

1. 2 3/4" [159mm] thick panel size is also available.
2. For rebar slot locations on KD Connectors see Knockdown Corner Form dwgs.
3. Concrete core thickness wider than 12" (305mm) are available using LOGIX Xtenders (See 5.1.22).
4. 8" [203mm] LOGIX XRV Panel shown.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™


5 – 3 3

LOGIX®
INSULATED CONCRETE FORMS


CAD DRAWINGS

All drawings are downloadable at www.logixicf.com

HORIZONTAL HOOK CONNECTING
STANDARD TO STANDARD
FORMS – PLAN VIEW
(Applicable for all LOGIX Standard Form
sizes)



HORIZONTAL HOOK CONNECTING STANDARD
TO CORNER FORMS – PLAN VIEW
(see Notes)



SECTION A-A

SECTION B-B

NOTES:


1. Applicable for connecting 4" or 6.25" LOGIX Standard Forms to 4" or 6.25" LOGIX Corner Forms.
2. Use traditional zip ties when connecting the shorter legs of the 8", 10" or 12" LOGIX Corner Forms to LOGIX Standard Forms.
3. When connecting the shorter leg of the 4" LOGIX Corner Form be sure to connect the Horizontal Hook at the web's center rebar slot.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


CAD DRAWINGS

www.logixicf.com**Good. Solid. Green.™****5 – 34**

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

VERTICAL HOOK CONNECTING COURSES – PLAN VIEW



SECTION A-A

SECTION B-B


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 – 3 5**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09


All drawings are downloadable at www.logixicf.com



Male/male Flex Bar
(Female/female Flex Bar similar)

PLAN VIEW

**Male/male
Flex Bar**




SIDE ELEVATION



END VIEW


**Female/female
Flex Bar**



SIDE ELEVATION



END VIEW



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com


Good. Solid. Green.™

5 – 3 6


LOGIX®
INSULATED CONCRETE FORMS

LOGIX ICF FORMS 5.1.22 – LOGIX XTENDER


All drawings are downloadable at www.logixicf.com




PLAN VIEW




SIDE ELEVATION



END VIEW



**SIDE ELEVATION
(without Xtenders)**



**SIDE ELEVATION
(with Xtenders)**

| CONCRETE CORE THICKNESS | | | | | |
|-------------------------|---------------|-------------------|----------------|----------------|----------------|
| | | KD Connector Size | | | |
| | | 6.25" (159mm) | 8" (203mm) | 10" (254mm) | 12" (305mm) |
| KD Connector Size | 4" (102mm) | 10.25" (260mm) | 12" (305mm) | 14" (356mm) | 16" (406mm) |
| | 6.25" (159mm) | 12.5" (318mm) | 14.25" (362mm) | 16.25" (413mm) | 18.25" (464mm) |
| | 8" (203mm) | 14.25" (362mm) | 16" (406mm) | 18" (457mm) | 20" (508mm) |
| | 10" (254mm) | 16.25" (413mm) | 18" (457mm) | 20" (508mm) | 22" (559mm) |
| | 12" (305mm)E | 18.25" (464mm) | 20" (508mm) | 22" (559mm) | 24" (610mm) |

NOTES:

1. Table lists concrete core thickness using two KD Connectors with one Xtender.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5 – 37

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013


Rev. Nov 11/10

CAD DRAWINGS


LOGIX ICF FORMS 5.1.23 – LOGIX T-WALL

All drawings are downloadable at www.logixicf.com


CAD DRAWINGS




**LONG T-WALL
PLAN VIEW**



**LONG T-WALL
SIDE ELEVATION**



**LONG T-WALL
END VIEW**



| | T-WALL SIZES | | | | | | | |
|---|----------------------------|-----------------------------|---------------------------|----------------------------|-----------------------------|------------------------------|-----------------------------|------------------------------|
| | 6½" to 4" (159mm to 102mm) | 6½" to 6½" (159mm to 159mm) | 8" to 4" (203mm to 102mm) | 8" to 6½" (203mm to 159mm) | 10" to 4" (254mm to 102mm)* | 10" to 6½" (254mm to 159mm)* | 12" to 4" (305mm to 102mm)* | 12" to 6½" (305mm to 159mm)* |
| A | 48" (1219mm) | 50.25" (1276mm) | 48" (1219mm) | 50.25" (1276mm) | 48" (1219mm) | 50.25" (1276mm) | 48" (1219mm) | 50.25" (1276mm) |
| B | 5.375" (137mm) | 6.5" (165mm) | 5.375" (137mm) | 6.5" (165mm) | 5.375" (137mm) | 6.5" (165mm) | 5.375" (137mm) | 6.5" (165mm) |
| C | 11.75" (298mm) | 11.75" (298mm) | 13.5" (343mm) | 13.5" (343mm) | 15.5" (394mm) | 15.5" (394mm) | 17.5" (445mm) | 17.5" (445mm) |
| D | 6.25" (159mm) | 6.25" (159mm) | 8" (203mm) | 8" (203mm) | 10" (254mm) | 10" (254mm) | 12" (305mm) | 12" (305mm) |
| E | 4" (102mm) | 6.25" (159mm) | 4" (102mm) | 6.25" (159mm) | 4" (102mm) | 6.25" (159mm) | 4" (102mm) | 6.25" (159mm) |
| F | 9.5" (241mm) | 11.75" (298mm) | 9.5" (241mm) | 11.75" (298mm) | 9.5" (241mm) | 11.75" (298mm) | 9.5" (241mm) | 11.75" (298mm) |

*Assembled without diagonal tie

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™


5 – 3 8

LOGIX®
INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Nov 30/12

All drawings are downloadable at www.logixicf.com





SHORT T-WALL
PLAN VIEW



LONG T-WALL

| | T-WALL SIZES | | | | | | | |
|---|---|--|------------------------------|---|--------------------------------|---|--------------------------------|---|
| | 6 $\frac{1}{4}$ " to 4" (159mm to 102mm) | 6 $\frac{1}{4}$ " to 6 $\frac{1}{4}$ " (159mm to 159mm) | 8" to 4" (203mm to 102mm) | 8" to 6 $\frac{1}{4}$ " (203mm to 159mm) | 10" to 4" (254mm to 102mm)* | 10" to 6 $\frac{1}{4}$ " (254mm to 159mm)* | 12" to 4" (305mm to 102mm)* | 12" to 6 $\frac{1}{4}$ " (305mm to 159mm)* |
| A | 16" (406mm) | 18.25" (464mm) | 16" (406mm) | 18.25" (464mm) | 16" (406mm) | 18.25" (464mm) | 16" (406mm) | 18.25" (464mm) |
| B | 5.375" (137mm) | 6.5" (165mm) | 5.375" (137mm) | 6.5" (165mm) | 5.375" (137mm) | 6.5" (165mm) | 5.375" (137mm) | 6.5" (165mm) |
| C | 11.75" (298mm) | 11.75" (298mm) | 13.5" (343mm) | 13.5" (343mm) | 15.5" (394mm) | 15.5" (394mm) | 17.5" (445mm) | 17.5" (445mm) |
| D | 6.25" (159mm) | 6.25" (159mm) | 8" (203mm) | 8" (203mm) | 10" (254mm) | 10" (254mm) | 12" (305mm) | 12" (305mm) |
| E | 4" (102mm) | 6.25" (159mm) | 4" (102mm) | 6.25" (159mm) | 4" (102mm) | 6.25" (159mm) | 4" (102mm) | 6.25" (159mm) |
| F | 9.5" (241mm) | 11.75" (298mm) | 9.5" (241mm) | 11.75" (298mm) | 9.5" (241mm) | 11.75" (298mm) | 9.5" (241mm) | 11.75" (298mm) |

*Assembled without diagonal tie




LONG T-WALL

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

All drawings are downloadable at www.logixcf.com**NOTES:**


See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

CAD DRAWINGS



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 - 40**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S

www.logixcf.com


Good. Solid. Green.™

5-41

LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

All drawings are downloadable at www.logixcf.com


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5-42

LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com**NOTES:**

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for wall reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 43**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 11/10


C A D D R A W I N G S

5.2.5 – 4' FROST WALL WITH DOUBLE TAPER TOP SUPPORTING WOOD FRAME AND BALANCED BACKFILL

All drawings are downloadable at www.logixcf.com

NOTE:

1. Provide proper drainage as specified.
2. See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for wall reinforcement details



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

CAD DRAWINGS

www.logixcf.com

Good. Solid. Green.™

5 - 44


LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

www.logixcf.com**Good. Solid. Green.™****5-45**


LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.



CAD DRAWINGS

www.logixcf.com

Good. Solid. Green.™

5 - 4 6


LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.



CAD DRAWINGS


www.logixcf.com**Good. Solid. Green.™****5-47**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.



CAD DRAWINGS


www.logixcf.com**Good. Solid. Green.™****5 - 48**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.



CAD DRAWINGS


www.logixcf.com**Good. Solid. Green.™****5-49**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S

NOTES:

1. See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.




The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 50****LOGIX®**
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

**NOTES:**


The above knee wall is applicable under the following conditions:

1. Min. vertical rebar, use #4@32" max. (10M@813 mm max.) on center for 60ksi steel (#4@24" for 40ksi steel). Footing dowels to match vertical rebar in wall for size and spacing.
2. Horizontal rebar: #4@16" max (10M@406 mm max.) on center.
3. Max. backfill height: 4 ft (1.2 m); Equivalent fluid density: $\leq 75\text{pcf}$ (1200 kg/m³) w/ no surcharge; Soil must be well drained (no heavy clay)
4. Min. soil bearing capacity: 2000 psf (13.8 MPa)
5. Min. 28 day concrete compressive strength: 3000 psi (20 MPa)
6. Max. knee wall length: 40 ft (12 m); Max. knee wall height: 4 ft (1.2 m)
7. Max. 2 stories above-grade of stud framed wall construction – house superstructure not to exceed 2000 lb/ft.
8. Consult a local licensed engineer for knee walls that do not meet the above notes and drawing.

5.3.8 – WATERPROOF DETAIL AROUND BRICK LEDGE (optional)

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



NOTES:

1. See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.
2. See Drawing 5.10.7 for stirrup details for Brick Ledge Forms.


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 – 52

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 – 53

LOGIX®
 INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09


C A D D R A W I N G S

5.3.10 – ALASKAN SLAB WITH LOGIX XTENDER

All drawings are downloadable at www.logixicf.com



ALASKAN SLAB DETAIL
WITH FRAMED WALL



ALASKAN SLAB DETAIL
WITH CONTINUOUS ICF

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixicf.com

Good. Solid. Green.™

5 – 54

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com



NOTES:

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.
2. For more information on LOGIX Tie Extenders, see Drawing 5.1.22.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5 – 55

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 11/10


CAD DRAWINGS

RESIDENTIAL DRAWINGS 5.3.12 – 8" TO 4" TRANSITION

All drawings are downloadable at www.logixcf.com

NOTES:

1. See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.
2. See Drawing 5.10.7 for stirrup details for Brick Ledge Form.



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 – 56


LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 11/10

RESIDENTIAL DRAWINGS 5.3.13 – 8" TO 8" TRANSITION

All drawings are downloadable at www.logixcf.com



CAD DRAWINGS

www.logixcf.com

Good. Solid. Green.™

5-57

LOGIX®
INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Nov 11/10

RESIDENTIAL DRAWINGS 5.3.14 – 8" TO 6.25" TRANSITION

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



NOTES:

1. See Section 6 – Engineering in the LOGIX Design Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com


Good. Solid. Green.™

5 – 58

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 11/10

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5-59



LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013


Rev. Nov 04/11

All drawings are downloadable at www.logixcf.com**NOTES:**

1. See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.
2. See Residential Drawing 5.10.6 to 5.10.8 or Commercial Drawing 5.9.5 to 5.9.7 for stirrup details for Brick Ledge Forms.
3. Red Zone membrane must be adhered with Resisto H2O Primer.

FLASHING DETAILS w/
LOGIX BRICK LEDGEFLASHING DETAILS w/
CONCRETE BRICK LEDGE

Resisto Red Zone
membrane strip
applied over termination
of metal flashing.
(see Notes)

DETAIL A:
TYPICAL WATERPROOFING
DETAIL


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 – 60

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

NOTES:

Protection board not required if backfill material consists only of well-drained sand. Backfill material with well-drained gravels or clays require a protection board against damp-proof membrane.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

C A D D R A W I N G S

www.logixicf.com

Good. Solid. Green.™

5 – 6 1

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013


Rev. Nov 04/11

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.



CAD DRAWINGS

www.logixcf.com**Good. Solid. Green.™****5 – 62**

LOGIX®
INSULATED CONCRETE FORMS


RESIDENTIAL DRAWINGS 5.4.2 – 9'-4" SLAB ON GRADE

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.



CAD DRAWINGS

www.logixcf.com

Good. Solid. Green.™

5 – 63

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013


Rev. Sep 23/09

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.



CAD DRAWINGS


www.logixcf.com**Good. Solid. Green.™****5 – 6 4**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

www.logixcf.com**Good. Solid. Green.™****5 – 6 5**
LOGIX®
 INSULATED CONCRETE FORMS


5.4.5 – 8' WALL SLAB ON GRADE WITH DOUBLE TAPER TOP

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.



CAD DRAWINGS

www.logixcf.com


Good. Solid. Green.™

5 – 6 6

LOGIX®
INSULATED CONCRETE FORMS

5.4.6 – SLAB ON GRADE WITH RADIANT HEATING

All drawings are downloadable at www.logixicf.com




NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for wall reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS

**NOTES:**


1. See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.
2. See Drawing 5.10.7 for stirrup details for Brick Ledge Form.
3. See Drawing 5.10.44 for waterproof detail for Brick Ledge Form.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 6 8**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.



NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

C A D D R A W I N G S

www.logixcf.com


Good. Solid. Green.™

5 – 6 9

LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

www.logixcf.com

Good. Solid. Green.™


5 – 7 0

LOGIX®
INSULATED CONCRETE FORMS

RESIDENTIAL DRAWINGS 5.5.3 - 8'-8" FOUNDATION WALL/ 10' MAIN FLOOR

All drawings are downloadable at www.logixicf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.



CAD DRAWINGS

www.logixicf.com

Good. Solid. Green.™

5-71


LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

All drawings are downloadable at www.logixcf.com**NOTES:**

1. See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.
2. See Drawing 5.10.16 for stirrup details for Transition Form.
3. See Drawing 5.10.7 for stirrup details for Brick Ledge Form.
4. See Drawing 5.10.44 for waterproof detail for Brick Ledge Form.



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

CAD DRAWINGS

www.logixcf.com


Good. Solid. Green.™

5-72

LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTE:**

1. See Section 6 – Engineering in the LOGIX Design Manual for reinforcement details.
2. See Anchor Tunnel – Floor Ledger Connection drawing for anchor tunnel details.
3. See Simpson Strong-Tie ICF Ledger Connection System drawings for details on Simpson Strong-Tie ICFVL installations.
4. For installation instructions for Simpson Strong-Tie LTA1 visit www.strongtie.com.



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5-73**
LOGIX®
 INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09

5.5.6 - LOGIX 6.25" BELOW- & ABOVE- GRADE WALL WITH BRICKLEDGE

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



NOTES:

1. See LOGIX Design Manual, Section 6 Engineering, for reinforcement requirements for varying wall heights for above- and below-grade LOGIX walls.
2. See Residential Drawings 5.7.8 & 5.7.9 in Section 5 of the LOGIX Design Manual for Simpson Strong Tie details
3. See Residential Drawings 5.10.8 in Section 5 of the LOGIX Design Manual for Brickledge stirrup detail


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™


5 - 7 4

LOGIX®
INSULATED CONCRETE FORMS



All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 – 7 6

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5-77

LOGIX®
INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09

C A D D R A W I N G S

5.6.4 – TWO STOREY WITH BRICK LEDGE & TRANSITION FORM - 2 of 2

All drawings are downloadable at www.logixcf.com



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

CAD DRAWINGS

www.logixcf.com

Good. Solid. Green.™

5 – 7 8


LOGIX®
INSULATED CONCRETE FORMS

RESIDENTIAL DRAWINGS 5.6.5 - TWO STOREY WALL SECTION WITH LOGIX XRV

All drawings are downloadable at www.logixicf.com

NOTE:

1. See Section 6 – Engineering in the LOGIX Design Manual for reinforcement details.
2. See Anchor Tunnel – Floor Ledger Connection drawing for anchor tunnel details.
3. See Simpson Strong-Tie ICF Ledger Connection System drawings for details on Simpson Strong-Tie ICFVL installations.



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

CAD DRAWINGS

www.logixicf.com

Good. Solid. Green.™

5-79



LOGIX
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

5.7.1 – 2x6 TOP PLATE RECESSED WITH DOUBLE TAPER TOP

5.7.2 – 2x8 TOP PLATE OVERHUNG WITH DOUBLE TAPER TOP

**2x6 TOP PLATE RECESSED****2x8 TOP PLATE OVERHUNG**

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


C A D D R A W I N G S

RESIDENTIAL DRAWINGS 5.7.3 – 2x8 TOP PLATE OVERHUNG


WITH TAPER TOP

5.7.4 – MASONRY VENEER WITH TAPER TOP

All drawings are downloadable at www.logixicf.com



**2x8 TOP PLATE OVERHUNG WITH
TAPERED TOP FORM**



**2x6 TOP PLATE OVERHUNG WITH
MASONRY AND TAPERED TOP FORM**

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5 – 8 1

LOGIX®
INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09

CAD DRAWINGS

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



LOG HOME ON 2x8 SILL PLATE & TAPER TOP FORM

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com


Good. Solid. Green.™

5 – 82

LOGIX®
INSULATED CONCRETE FORMS

5.7.6 – TAPER TOP WITH LOG HOME 2x12 SILL PLATE

All drawings are downloadable at www.logixicf.com



LOG HOME ON 2x12 SILL PLATE & TAPER TOP FORM

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5 – 8 3

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013


Rev. Sep 23/09

CAD DRAWINGS

5.7.7 – TRANSITION - 8" TAPER TOP TO 4" STANDARD

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



NOTES:

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixcf.com

Good. Solid. Green.™


5 – 84

LOGIX®
INSULATED CONCRETE FORMS


All drawings are downloadable at www.logixicf.com





ICFLC-W & ICFLC-CW



ICFVL



STEEL LEDGER INSTALLATION



WOOD LEDGER INSTALLATION

NOTES:

1. For more information see Section 2 of the LOGIX Product Manual or visit www.strongtie.com.
2. Use extra caution when installing Simpson ICF Ledger Connection systems on both sides of a wall. Consult your local Simpson Strongtie rep or call Simpson Strongtie at (800) 999-5099 prior to installation.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5 – 8 5

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013


Rev. Sep 23/09

CAD DRAWINGS


5.7.9 – SIMPSON STRONG TIE - ICF LEDGER CONNECTION SYSTEM

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



ICFVL-W for solid sawn
lumber or ICFVL-CW for LVL



NOTES:

1. For more information see Section 2 of the LOGIX Product Manual or visit www.strongtie.com.
2. Use extra caution when installing Simpson ICF Ledger Connection systems on both sides of a wall. Consult your local Simpson Strongtie rep or call Simpson Strongtie at (800) 999-5099 prior to installation.
3. Attachment of second ledger to be designed by others.


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 – 86

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**

1. See Section 6 – Engineering in the LOGIX Design Manual for reinforcement details.
2. For spacing of Simpson Strongtie ICF Ledger Connection Systems refer to Section 2.12.4 of the LOGIX Design Manual.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 – 87**
LOGIX®
 INSULATED CONCRETE FORMS



REPRINTED 2013

Rev. Nov 04/11 Sep 23/09

C A D D R A W I N G S

5.7.11 – ANCHOR TUNNEL - FLOOR LEDGER CONNECTION

All drawings are downloadable at www.logixcf.com



| Maximum Floor Clear Span, Feet | Maximum Anchor Bolt Spacing | | | |
|--------------------------------|------------------------------------|------------------------------------|------------------------------|------------------------------|
| | Staggered 1/2\" Diam. Anchor Bolts | Staggered 5/8\" Diam. Anchor Bolts | Two 3/2\" Diam. Anchor Bolts | Two 5/8\" Diam. Anchor Bolts |
| 8 | 18 | 20 | 36 | 40 |
| 10 | 16 | 18 | 32 | 36 |
| 12 | 14 | 18 | 28 | 36 |
| 14 | 12 | 16 | 24 | 32 |
| 16 | 10 | 14 | 20 | 28 |
| 18 | 9 | 13 | 18 | 26 |
| 20 | 8 | 11 | 16 | 22 |
| 22 | 7 | 10 | 14 | 20 |
| 24 | 7 | 9 | 14 | 18 |
| 26 | 6 | 9 | 12 | 18 |
| 28 | 6 | 8 | 12 | 16 |
| 30 | 5 | 8 | 10 | 16 |
| 32 | 5 | 7 | 10 | 14 |

NOTES:

1. Minimum ledger board nominal depth shall be 8". The thickness of the ledger board shall be a minimum of 2". Thickness of ledger board is in nominal lumber dimensions. Ledger board shall be minimum No.2 Grade.
2. Minimum edge distance shall be 2" for 1/2" \varnothing anchor bolts and 2 1/2" for 5/8" \varnothing anchor bolts.
3. Interpolation is permitted between floor spans.
4. Floor span corresponds to the clear span of the floor structure spanning between load bearing walls or beams.
5. Anchor bolts shall extend through the ledger to the center of the horizontal or vertical core thickness of the waffle-grid concrete cross section.
6. Minimum vertical distance between bolts shall be 1 1/2" for 1/2" \varnothing anchor bolts, and 2" for 5/8" \varnothing anchor bolts.
7. In order to use this table, the wall must be within the vertical reinforcement parameters. Consult an engineer beyond the parameters. This table is only valid for a service dead load of 15psf and a service live load of 40psf.
8. See Section 6 - Engineering in the LOGIX Product Manual for reinforcing details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


CAD DRAWINGS

www.logixcf.com

Good. Solid. Green.™


5 – 8 8

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S

**NOTES:**


1. For more information visit www.strongtie.com.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 90**
LOGIX®
 INSULATED CONCRETE FORMS

RESIDENTIAL DRAWINGS 5.7.14 – FRAME STRAP ALTERNATIVE

All drawings are downloadable at www.logixicf.com



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5-91

LOGIX®
INSULATED CONCRETE FORMS



REPRINTED 2013

Rev. Sep 23/09

CAD DRAWINGS

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



STIRRUP DETAIL

NOTES:


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 – 92

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

C A D D R A W I N G S

www.logixicf.com

Good. Solid. Green.™

5 – 93


LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 04/11

All drawings are downloadable at www.logixicf.com


CAD DRAWINGS

**NOTES:**

See Section 6 – Engineering in the LOGIX Design Manual for reinforcement details.


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 – 94**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

All drawings are downloadable at www.logixcf.com


CAD DRAWINGS

**NOTES:**

1. See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.
2. See Drawing 5.10.7 for stirrup details for Brick Ledge Form.
3. See Drawing 5.10.44 for waterproof detail for Brick Ledge Form.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 96**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5-97

LOGIX®
INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09

C A D D R A W I N G S

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS




The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 – 98

LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.



www.logixicf.com**Good. Solid. Green.™****5 – 99**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 04/11

5.8 – ROOF CONNECTIONS**5.8.1 – ROOF - 2x6 RECESSED TOP PLATE****5.8.2 – ROOF - 2x8 OVERHUNG TOP PLATE**All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S


**5.8.1 - 2x6 RECESSED TOP PLATE****5.8.2 - 2x8 OVERHUNG TOP PLATE****NOTES:**

See Section 6 – Engineering in the LOGIX Design Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 100****LOGIX®**
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

**NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5-101

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013


Rev. Sep 23/09

CAD DRAWINGS

5.8.4 – ROOF - HURRICANE TIE DOWN STRAP

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixcf.com

Good. Solid. Green.™


5 – 102

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com



Vaulted Ceiling - A - Frame



Vaulted Ceiling - Scissor Truss

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

CAD DRAWINGS

www.logixicf.com


Good. Solid. Green.™

5-103

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09


All drawings are downloadable at www.logixcf.com**NOTES:**

See Section 6 –
Engineering in the LOGIX
Product Manual for
reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

C A D D R A W I N G S

www.logixcf.com**Good. Solid. Green.™****5 – 1 0 4**
LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**

1. See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.
2. Helpful Hint: Wedge behind beveled block can be a good place to run electrical wires after screws are in place.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5-105**
LOGIX®
 INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09

5.8.7 – ROOF DETAIL WITH SIMPSON STRONG-TIE H1/H2.5 STRAP

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 – 1 0 6

LOGIX®
INSULATED CONCRETE FORMS



All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5-107**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 30/12

All drawings are downloadable at www.logixcf.com**DOOR HEAD & SILL USING WOOD BUCKS****DOOR JAMB USING WOOD BUCKS****NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

C A D D R A W I N G S


www.logixcf.com**Good. Solid. Green.™****5 – 1 0 8****LOGIX®**
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.



**WOOD WINDOW BUCK
SLOPED CONCRETE SILL**

**NOTE:**


Adjust 2x lumber to suit specified slope of concrete sill.

www.logixicf.com**Good. Solid. Green.™****5-109**

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

CAD DRAWINGS



NOTES:

1. For wall & lintel reinforcement, see LOGIX Product Manual Section 6, Engineering.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixicf.com

Good. Solid. Green.™




5 - 1 1 0

LOGIX®
INSULATED CONCRETE FORMS


All top & bottom plates and side bucks to be located in wall so there is no conflict with webs. No cutting of webs at anytime during installation of window or door openings.



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.



All drawings are downloadable at www.logixcf.com**TOP VIEW**Top & vertical plates for
6 1/4" [159mm] concrete cores width**SECTION A-A****PLAN WINDOW SILL**

All top & bottom plates and side bucks to be located in wall so there is no conflict with webs. No cutting of webs at anytime during installation of window or door openings.



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 - 1 1 2****LOGIX®**
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

SECTION THROUGH LINTEL


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

C A D D R A W I N G S

www.logixicf.com**Good. Solid. Green.™****5 – 1 1 3**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

All drawings are downloadable at www.logixicf.com**NOTES:**


1. See Section 6 – Engineering in the LOGIX Design Manual for wall & lintel reinforcement.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

C A D D R A W I N G S

www.logixicf.com**Good. Solid. Green.™****5 - 1 1 4**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5-115

LOGIX®
INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Nov 11/10

CAD DRAWINGS

All drawings are downloadable at www.logixcf.com



C A D D R A W I N G S

**NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 1 1 6**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com**SECTION A-A****STIRRUP DETAIL**
(See Note 2)**NOTES:**

1. See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.
2. Stirrup shown is rated for 1300lbs/ft (19kN/m). For heavier load conditions and stirrup dimensions see Brick Ledge Stirrup details drawings.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixcf.com**Good. Solid. Green.™****5-117****LOGIX®**
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

All drawings are downloadable at www.logixcf.com


CAD DRAWINGS

**NOTES:**

1. See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.
2. Stirrup shown is rated for 1300lbs/ft (19kN/m). Maximum load capacity w/o stirrups – 900lbs/ft (13kN/m).

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 1 1 8****LOGIX®**
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com**NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

C A D D R A W I N G S


www.logixcf.com**Good. Solid. Green.™****5-119**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

All drawings are downloadable at www.logixcf.com


C A D D R A W I N G S




The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 120**
LOGIX®
 INSULATED CONCRETE FORMS

5.10.6 / 5.10.7 – BRICK LEDGE STANDARD REINFORCEMENT / BRICK LEDGE HEAVY REINFORCEMENT

All drawings are downloadable at www.logixcf.com

5.10.5 - BRICK LEDGE STANDARD REINFORCEMENT



* 1 kN = 224.8lb

5.10.6 - BRICK LEDGE HEAVY REINFORCEMENT

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com



Good. Solid. Green.™

5-121

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09



All drawings are downloadable at www.logixcf.com**BRICK LEDGE STANDARD REINFORCEMENT****DETAIL A****NOTES:**

See Section 6 –
Engineering in the LOGIX
Product Manual for
reinforcement details.

* 1kN = 224.8lb

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 122**
LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com**INTERIOR LOGIX WALL TO EXTERIOR STUD FRAMED WALLS****INTERIOR LOGIX WALL TO INTERIOR STUD FRAMED WALLS**

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

C A D D R A W I N G S


www.logixcf.com**Good. Solid. Green.™****5 – 1 2 3**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

All drawings are downloadable at www.logixicf.com

C A D D R A W I N G S


**NOTES:**

1. If no base coat, fasten mesh to ICF with staples.
2. Detail above is a general drawing only. Follow manufacturer's installation instructions.
3. See LOGIX Product Manual section 2.21 for supporting exterior finish products.
4. See LOGIX Product Manual section 2.18.3 for more information on exterior siding.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 – 124**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

**NOTES:**

1. All fasteners to be attached to the embedded furring tabs.
2. Recommended min. fastener spacings:
 1. Grabber construction non-corrosive screws: No.8 min. 1.25" long, 8" o.c. horiz., 12" o.c. vert. spacing.
 - OR
 2. Staples 1.59mm 16ga. min. 1.25" long, 8" o.c. horiz., 5" o.c. vert. spacing.
3. Always follow manufacturer's instructions or recommendations.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5-125

LOGIX®
INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09

CAD DRAWINGS

All drawings are downloadable at www.logixicf.com

CAD DRAWINGS






The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5 – 1 2 6

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**WOOD BLOCKING****TAPCON CONCRETE SCREWS****ICF MESH GRAPPLER****NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixicf.com**Good. Solid. Green.™****5-127**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 11/10

C A D D R A W I N G S

All drawings are downloadable at www.logixcf.com

**NOTES:**

See Section 6 –
Engineering in the LOGIX
Product Manual for
reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

C A D D R A W I N G S

www.logixcf.com


Good. Solid. Green.™

5 – 1 2 8

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.



**10" TAPERED TOP TO 8" BRICK LEDGE
TRANSITION**

C A D D R A W I N G S


www.logixcf.com**Good. Solid. Green.™****5 – 1 2 9**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.



NOTES:

1. See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.
2. Treating the soil ahead of time is another method of avoiding termite related problems.
3. The use of 4" Height Adjusters will ensure there is an 8" gap exposing any termite presence in the wall.
4. Please refer to local building codes for more information on termite control.


CAD DRAWINGS

www.logixcf.com

Good. Solid. Green.™

5 – 130

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**CABINET INSTALLATION****NOTES:**

1. For more information visit www.strongtie.com.
2. Use extra caution when installing Simpson ICF Ledger Connection systems on both sides of a wall. Consult your local Simpson Strongtie rep or call Simpson Strongtie at (800) 999-5099 prior to installation.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5-131**
LOGIX®
 INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09

5.10.18– LOGIX ICF WITH BILCO SIZE "C" STANDARD CLASSIC SERIES DOORS

All drawings are downloadable at www.logixicf.com

CAD DRAWINGS



LOGIX Material List for Bilco Size "C" Doors:

90° Corner Forms (per course) – 2
Standards (per course) – 3 (Field cut to size)

NOTES:

1. Foundation wall height typically one course higher than chamber.
2. Caulk all around the exterior of the frame where it meets the concrete with exterior grade silicone caulking.
3. Install Bilco door as per recommended manufacturer's installation instructions.
4. For more information on Bilco products please visit www.bilco.com


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5 – 132

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com**NOTES:**

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.

www.logixcf.com**Good. Solid. Green.™****5-133****LOGIX®**
INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Nov 11/10

C A D D R A W I N G S

All drawings are downloadable at www.logixcf.com



C A D D R A W I N G S

**NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 134**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com**AGAINST CAST-IN-PLACE CONCRETE****AGAINST LOGIX****NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


C A D D R A W I N G S

www.logixcf.com**Good. Solid. Green.™****5-135**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 30/12

All drawings are downloadable at www.logixcf.com



NOTES:

- Apply caulking to seal vertical joints between ICF forms up to radon/vapor termination.
- Consult local officials for additional required radon mitigation measures.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


CAD DRAWINGS

www.logixcf.com

Good. Solid. Green.™

5 – 136

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5-137**
LOGIX®
 INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Nov 30/12

C A D D R A W I N G S

All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com


Good. Solid. Green.™

5 - 138

LOGIX®
 INSULATED CONCRETE FORMS

RESIDENTIAL DRAWINGS 5.10.25 – POOL DETAIL OF INLET / OUTLET FIXTURE (3 OF 5)

All drawings are downloadable at www.logixcf.com



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

CAD DRAWINGS

www.logixcf.com

Good. Solid. Green.™

5-139


LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 30/12

All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S




The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 1 4 0**
LOGIX®
 INSULATED CONCRETE FORMS

RESIDENTIAL DRAWINGS 5.10.27 – POOL SKIMMER
(5 OF 5)

All drawings are downloadable at www.logixcf.com



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

CAD DRAWINGS

www.logixcf.com

Good. Solid. Green.™

5-141


LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 30/12

All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S

**NOTES:**

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.
2. Install vertical rebar 6" beyond corbel width for full height of wall each face.
3. Reinforcement details should be reviewed by a local licensed professional engineer.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 - 142**
LOGIX®
 INSULATED CONCRETE FORMS

TABLE OF CONTENTS

5.2 – FOUNDATION DETAILS

| | |
|---|---------|
| 5.2.1 – LOGIX WALL WITH CMU BRICK | |
| LEDGE | P. 5-10 |
| 5.2.2 – HOLLOW CORE SLAB ON GRADE..... | P. 5-11 |
| 5.2.3 – EXTERIOR WALL ON PILE | |
| SUPPORTED GRADE BEAM | P. 5-12 |
| 5.2.4 – INTERIOR WALL ON PILE SUPPORTED | |
| GRADE BEAM | P. 5-13 |
| 5.2.5 – LOGIX ICF GRADE BEAM | P. 5-14 |
| 5.2.6 – PILE SUPPORTED GRADE BEAMS | P. 5-15 |
| 5.2.7 – ICF BASE AT INTERIOR WALL..... | P. 5-16 |
| 5.2.8 – BRICK VENEER ON CONCRETE FILL | P. 5-17 |
| 5.2.9 – DEEP GRADE BEAM ON PILE CAP | P. 5-18 |
| 5.2.10 – LOGIX FOOTING WITH | |
| XTENDER | P. 5-19 |
| 5.2.11 – BRICK LEDGE FLASHING DETAILS..... | P. 5-20 |
| 5.2.12 – FOUNDATION WITH TIE | |
| XTENDERS SUPPORTING STONE VENEER..... | P. 5-21 |

5.3 – FLOOR CONNECTIONS

| | |
|--|---------|
| 5.3.1 – BEARING LENGTHS - 4" LOGIX | |
| STANDARD FORM ON TOP | P. 5-22 |
| 5.3.2 – 2x LUMBER LEDGER..... | P. 5-26 |
| 5.3.3 – LVL LUMBER LEDGER..... | P. 5-26 |
| 5.3.4 – ANGLE IRON LEDGER..... | P. 5-27 |
| 5.3.5 – BRICK LEDGE WITH TOP CHORD | |
| BEARING | P. 5-28 |
| 5.3.6 – BOTTOM CHORD BEARING TRUSS..... | P. 5-29 |
| 5.3.7 – 6.25" TRANSITION FORM SUPPORTING | |
| OPEN WEB FLOOR JOIST | P. 5-30 |
| 5.3.8 – SIMPSON STRONG TIE - ICF LEDGER | |
| CONNECTION SYSTEM..... | P. 5-31 |

5.3.9 – SIMPSON STRONG

TIE - JOIST HANGERP. 5-32

5.3.10 – STEEL COMPOSITE DECKP. 5-33

5.3.11 – 6.25" TO 4" TRANSITION WALL

WITH PRECAST CONCRETE WALLP. 5-34

5.3.12 – HAMBRO FLOOR.....P. 5-35

5.3.13 – HAMBRO JOISTS BUTTED UP ON

LOGIX ICF WALL (1 OF 2).....P. 5-36

5.3.14 – HAMBRO JOISTS BUTTED UP ON

LOGIX ICF WALL (2 OF 2).....P. 5-37

5.3.15 – HOLLOW CORE SLAB WITH LOGIXP. 5-38

5.3.16 – HOLLOW CORE SLAB WITH

FRAMED WALL.....P. 5-39

5.3.17 – SUSPENDED SLAB (CAST-IN-PLACE)P. 5-40

5.3.18 – STEEL DECK ON OPEN WEB STEEL

JOIST (BEARING END)P. 5-41

5.3.19 – STEEL DECK ON OPEN WEB STEEL

JOIST (NONBEARING END)P. 5-42

5.3.20 – COMPOSITE STEEL BEAM ON BRICK

LEDGEP. 5-43

5.3.21 – STEEL ANGLE TO FLOOR JOIST.....P. 5-44

5.3.22 – 8" CORE SLAB ON

DOUBLE TAPER TOPP. 5-45

5.4 – ROOF DETAILS

5.4.1 – INTERIOR WALL SUPPORTING OPEN

WEB STEEL JOIST.....P. 5-46

5.4.2 – METAL LINER ROOF PANELS.....P. 5-47

5.4.3 – OPEN WEB STEEL FLAT ROOF.....P. 5-48

5.4.4 – PRECAST CONCRETE FLAT ROOF.....P. 5-48

5.4.5 – ICF PARAPET: FLAT ROOF ON OPEN

WEB JOISTP. 5-49

5.4.6 – ICF PARAPET: FLAT ROOF ON OPEN

WEB JOIST WITH INSULATION.....P. 5-50

| | |
|---|---------|
| 5.4.7 – ICF PARAPET: FLAT ROOF WITH DECK SUPPORT | P. 5-51 |
| 5.4.8 – ICF PARAPET: FLAT ROOF WITH PRECAST CONCRETE PANEL | P. 5-52 |
| 5.4.9 – ICF PARAPET: FLAT ROOF ON WOOD JOISTS WITH METAL CAP..... | P. 5-53 |
| 5.4.10 – ICF PARAPET: FLAT ROOF ON WOOD JOISTS WITH EPS COPING | P. 5-54 |
| 5.4.11 – WOOD PARAPET ON WOOD JOISTS | P. 5-55 |
| 5.4.12 – WOOD PARAPET ON WOOD JOISTS WITH METAL CAP | P. 5-56 |
| 5.4.13 – WOOD PARAPET WITH OPEN WEB STEEL JOIST | P. 5-57 |
| 5.4.14 – WOOD PARAPET WITH PRECAST CONCRETE PANEL ROOF..... | P. 5-58 |
| 5.4.15 – PARAPET - METAL COPING W/ BRICK VENEER..... | P. 5-59 |
| 5.4.16 – STEEL DECK ON LOGIX | P. 5-60 |
| 5.4.17 – STEEL DECK ON LOGIX W/ FIRE SEALANT..... | P. 5-61 |
| 5.4.18 – ROOF DECK ON STEEL JOIST W/ LOGIX TAPER TOP | P. 5-62 |
| 5.4.19 – SCUPPER DETAIL | P. 5-63 |
| 5.4.20 – SEPARATION WALL | P. 5-64 |

5.5 – BEAM CONNECTIONS

| | |
|--|---------|
| 5.5.1 – STEEL DECK ON STRUCTURAL BEAM..... | P. 5-65 |
| 5.5.2 – WOOD BEAM WITH FIRE CUT | P. 5-66 |
| 5.5.3 – WOOD BEAM WITH CLIP ANGLES | P. 5-67 |
| 5.5.4 – BOND BEAM..... | P. 5-68 |
| 5.5.5 – STRUCTURAL STEEL CHANNEL BEAM | P. 5-69 |
| 5.5.6 – STEEL BEAM BRACKET SUPPORTING WOOD BEAM | P. 5-71 |

5.5.7 – STEEL BEAM BRACKET SUPPORTING

STEEL BEAMP. 5-72

5.5.8 – STEEL BEAM POCKETP. 5-73

5.5.9 – STEEL BEAM POCKET FLUSH WITH

SILL.....P. 5-74

5.5.10 – JOIST BEARING ON STEEL BEAM.....P. 5-75

5.6 – WINDOW & DOOR DETAILS

5.6.1 – DOOR JAMB, HEAD & SILLP. 5-76

5.6.2 – SLOPED CONCRETE SILL.....P. 5-77

5.6.3 – WINDOW HEAD / SILL DETAIL.....P. 5-78

5.6.4 – WINDOW HEAD / SILL STEEL FRAMEP. 5-79

5.6.5 – ALUMINUM WINDOW HEAD / SILL.....P. 5-80

5.6.6 – STEEL LINTEL WITH BRICK VENEER.....P. 5-81

5.6.7 – WINDOW SCREENP. 5-82

5.6.8 – EXTERIOR WINDOW SCREENP. 5-83

5.6.9 – CANOPY & ROLL-UP DOORP. 5-84

5.6.10 – WINDOW HEAD/SILL DETAIL WITH

LOGIX XRV.....P. 5-85

5.6.11 – WELDED PRESS STEEL DOOR

FRAME - CENTER MOUNTEDP. 5-86

5.6.12 – WELDED PRESSED STEEL DOOR

FRAME - FLUSH MOUNTEDP. 5-87

5.6.13 – BRICK VENEER OVER DOOR

OPENINGP. 5-88

5.6.14 – ALUMINUM WINDOW FRAMEP. 5-89

5.6.15 – ALUMINUM WINDOW HEAD/SILL

W/ TIMBERSTRAND LSLP. 5-90

5.6.16 – WINDOW OPENING - TEMPORARY

FORM SUPPORT FOR EXPOSED

CONCRETE W/ 4" TRIM.....P. 5-91

5.6.17 – WINDOW FLASHING DETAILP. 5-93

5.7 – PILASTER DETAILS

5.7.1 – REINFORCING - LOGIX PILASTER.....P. 5-94

| | |
|---|----------|
| 5.7.2 – LOGIX PILASTER AT TEE-WALL..... | P. 5-95 |
| 5.7.3 – LOGIX PILASTER AT CORNER WITH STRUCTURAL STEEL COLUMN | P. 5-96 |
| 5.7.4 – STRUCTURAL BEAM WITH BASE PLATE | P. 5-97 |
| 5.7.5 – STRUCTURAL BEAM WITH STUDS | P. 5-98 |
| 5.7.6 – STEEL DECK ON OPEN WEB JOIST | P. 5-99 |
| 5.7.7 – INTEGRAL SLAB | P. 5-100 |
| 5.7.8 – LOGIX PILASTER ON CONCRETE PIER | P. 5-101 |
| 5.7.9 – LOGIX PILASTER SUPPORTING STEEL BEAM & COLUMN | P. 5-102 |
| 5.7.10 – WOOD BEAM ON LOGIX PILASTER..... | P. 5-103 |
| 5.7.11 – WOOD COLUMN ON LOGIX PILASTER..... | P. 5-104 |
| 5.7.12 – BRACING - LOGIX PILASTER | P. 5-105 |
| 5.8 – SOUND TRANSMISSION CLASSIFICATION (STC) | |
| 5.8.1 – 4" LOGIX WALL LAYOUT (STC 50) | P. 5-106 |
| 5.8.2 – 6.25" LOGIX WALL LAYOUT (STC 56) | P. 5-107 |
| 5.9 – SPECIAL DETAILS | |
| 5.9.1 – REINFORCING - CORNER WALL | P. 5-108 |
| 5.9.2 – REINFORCING - CORNER WITH BRICK LEDGE FORMS | P. 5-109 |
| 5.9.3 – REINFORCING - CORNER WITH 6.25" TRANSITION FORMS | P. 5-110 |
| 5.9.4 – REINFORCING - TEE-WALL | P. 5-111 |
| 5.9.5 / 5.9.6 – BRICK LEDGE STANDARD REINFORCEMENT / BRICK LEDGE HEAVY REINFORCEMENT | P. 5-112 |
| 5.9.7 – BRICK LEDGE STIRRUP DETAIL | P. 5-113 |
| 5.9.8 – CORBEL SUPPORTING TIMBER POST | P. 5-114 |
| 5.9.9 / 5.9.10 – ATTACHING TO EXISTING CONCRETE WALL/ATTACHING TO EXISTING CONCRETE MASONRY WALL..... | P. 5-115 |

| | |
|---|----------|
| 5.9.11 – ATTACHING TO STUD FRAMED WALLS..... | P. 5-116 |
| 5.9.12 – 12" WALL JOGS..... | P. 5-117 |
| 5.9.13 – HORIZONTAL TRANSITION - 6.25" TO 8" CORNER WALL..... | P. 5-118 |
| 5.9.14 – HORIZONTAL TRANSITION - 6.25" TO 8" TEE WALL WITH END CAP..... | P. 5-120 |
| 5.9.15 – WEEP SCREED & FLASHING AT CONCRETE DECK..... | P. 5-122 |
| 5.9.16 – EXTERIOR FINISHES..... | P. 5-123 |
| 5.9.17 – LOGIX ICF WITH STONE VENEER..... | P. 5-124 |
| 5.9.18 – LOGIX ICF POOL APPLICATION..... | P. 5-125 |
| 5.9.19 – GANTRY SYSTEM ON LOGIX PILASTER..... | P. 5-126 |
| 5.9.20 – PRECAST PANEL WALL..... | P. 5-127 |
| 5.9.21 – ANGLE IRON SUPPORTING BRICK VENEER..... | P. 5-128 |
| 5.9.22 – HSS COLUMN ON LOGIX | P. 5-129 |
| 5.9.23 – METAL HANDRAIL | P. 5-130 |
| 5.9.24 – WALL BASE WEEP SCREED | P. 5-131 |
| 5.9.25 – BRICKLEDGE FORMED WITH 12" KD FORMS | P. 5-132 |
| 5.9.26 – STEEL ANGLE SUPPORTING BRICK VENEER..... | P. 5-133 |
| 5.9.27 – LOGIX ICF COLUMN | P. 5-134 |
| 5.9.28 – STUD WALL CLOSURE ATTACHMENT..... | P. 5-135 |
| 5.9.29 – HAND RAIL | P. 5-136 |
| 5.9.30 – LOGIX WITH PANELBOARD (1 of 2) | P. 5-137 |

5.9.31 – ANGLE SEAT DETAILS.....P. 5-139

5.9.32 – EMBEDDED VERTICAL PIPE.....P. 5-140

5.9.33 – 1 HR FIRE RATED WALL DETAIL
 AT PARTITION/ICF WALL JOINT .P. 5-141

5.9.34 – CORBEL REINFORCING DETIALS P. 5-142

5.9.35 – COLUMN W/ LOGIX PILASTER ...P. 5-143

5.9.36 – ZERO LOT LINE
 CONSTRUCTION DETAILP. 5-144

5.9.37 – CORBEL SUPPORTING DECK
 AND STONE VENEERP. 5-145

5.9.38 – ANGLED STUD FRAMED
 WALL ATTACHMENTP. 5-146

5.9.39 – 18” JOGS WITH LEFT &P. 5-147
 RIGHT HAND 10” LOGIX PRO ..P. 5-147
 CORNER FORMSP. 5-147

5.9.40 – FIRE WALL ABOVE ROOF LINE ..P. 5-148

5.9.41 – FIRE BREAK AT CEILING/FLOOR.P. 5-149

5.9.42 – CONCRETE ENCASED
 STEEL COLUMNP. 5-150

5.9.43 – BRICK LEDGE SHELF ANGLEP. 5-151

All drawings are downloadable at www.logixicf.com

LOGIX ICFs are available in many variations designed to accommodate all construction type details.

LOGIX carries both assembled form units, known as LOGIX PRO, and unassembled (or knock-down) systems known as LOGIX KD. LOGIX KD is also available in thicker panel forms, known as LOGIX XRV (see Drawings 5.1.18 and 5.1.19, respectively). LOGIX XRV are panelized forms that are available in thicker foam panels ranging from 4 to 8 inches. In addition, LOGIX Xtenders allow LOGIX forms to be used for wider concrete wall thicknesses greater than 12 inches (see Drawing 5.1.22).

For a complete list of LOGIX product lines see Section 8.1.

NOTE: The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com


Good. Solid. Green.™

5 – 9



5.2.1 – LOGIX WALL WITH CMU BRICK
LEDGEAll drawings are downloadable at www.logixcf.com

C A D D R A W I N G S

**NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.



www.logixcf.com**Good. Solid. Green.™****5 – 10**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

www.logixcf.com**Good. Solid. Green.™****5-11**

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

LOGIX Standard Form
(6 $\frac{1}{4}$ " [159mm] shown)

Rigid foam insulation

Concrete grade beam

Rigid insulation under slab.

Void form u/s concrete grade
beam between piles

Concrete pile

NOTES:

See Section 6 – Engineering in the
LOGIX Design Manual or the LOGIX
Field Manual for reinforcement details.


C A D D R A W I N G S

www.logixcf.com**Good. Solid. Green.™****5 – 12**

LOGIX®
INSULATED CONCRETE FORMS



All drawings are downloadable at www.logixicf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.



All drawings are downloadable at www.logixicf.com

CAD DRAWINGS




The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5 – 14

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

NOTES:

1. Refer to Section 6 of Logix Product Manual for additional information on vertical reinforcement for above- and below-grade walls.
2. Size and reinforcement for grade-beam to be designed as site specific.
3. Size, spacing and reinforcing for piles to be designed as site specific.
4. Reinforcing in wall to be designed as site specific.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5-15

LOGIX®
 INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09

C A D D R A W I N G S

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



NOTES:

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 – 16

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 - 17**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 11/10


C A D D R A W I N G S

All drawings are downloadable at www.logixicf.com**NOTES:**

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 – 18**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.
2. For more information on LOGIX Tie Extenders, see Drawing 5.1.22..

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 – 19**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013


Rev. Nov 11/10

C A D D R A W I N G S

All drawings are downloadable at www.logixcf.com


NOTES:

1. See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.
2. See Residential Drawing 5.10.6 to 5.10.8 or Commercial Drawing 5.9.5 to 5.9.7 for stirrup details for Brick Ledge Forms.
3. Red Zone membrane must be adhered with Resisto H2O Primer.




FLASHING DETAILS w/
LOGIX BRICK LEDGE

Resisto Red Zone
membrane strip
applied over termination
of metal flashing.
(see Notes)



DETAIL A:
TYPICAL WATERPROOFING
DETAIL



FLASHING DETAILS w/
CONCRETE BRICK LEDGE


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 – 20

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5-21**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 30/12


C A D D R A W I N G S

STANDARD


BRICK LEDGE

PILASTER


TRANSITION
BLOCK




4" Standard on
6" Standard




4" Standard on
6" Brick Ledge




4" Standard on
4" Standard with
Pilaster




4" Standard on
12" Knockdown**
with Pilaster




4" Standard on
Transition Block



4" Standard on
8" Standard




4" Standard on
8" Brick Ledge




4" Standard on
6" Standard with
Pilaster


TAPER TOP




4" Standard on
6" Taper Top




4" Standard on
10" Standard



4" Standard on
10" Brick Ledge




4" Standard on
8" Standard with
Pilaster




4" Standard on
8" Taper Top



4" Standard on
12" Knockdown**



4" Standard on
10" Standard with
Pilaster



4" Standard on
10" Taper Top

* Remove foam to achieve bearing length ** LOGIX 12" Knockdown Form available in 2008.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

All drawings are downloadable at www.logixcf.com

| STANDARD | BRICK LEDGE | PILASTER | TAPER TOP |
|---|---|--|--|
| 6 1/4" Standard on 8" Standard | 6 1/4" Standard on 6" Brick Ledge | 6 1/4" Standard on 6 1/4" Standard with Pilaster | 6 1/4" Standard on 6" Taper Top |
| 6 1/4" Standard on 10" Standard | 6 1/4" Standard on 8" Brick Ledge | 6 1/4" Standard on 8" Standard with Pilaster | 6 1/4" Standard on 8" Taper Top |
| 6 1/4" Standard on 12" Knockdown** | 6 1/4" Standard on 10" Brick Ledge | 6 1/4" Standard on 10" Standard with Pilaster | 6 1/4" Standard on 10" Taper Top |
| | | 6 1/4" Standard on 12" Knockdown with Pilaster** | <p>TRANSITION BLOCK</p> 6 1/4" Standard on 6" Transition Block |


* Remove foam to achieve bearing length ** LOGIX 12" Knockdown Form available in 2008.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


All drawings are downloadable at www.logixcf.com

CAD DRAWINGS

STANDARD




8" Standard on
10" Standard




8" Standard on
12" Knockdown**

BRICK LEDGE




8" Standard on
8" Brick Ledge




8" Standard on
10" Brick Ledge


PILASTER



8" Standard on
8" Standard with
Pilaster




8" Standard on
10" Standard with
Pilaster




8" Standard on
12" Knockdown**
with Pilaster

TAPER TOP



8" Standard on
8" Taper Top



8" Standard on
10" Taper Top

* Remove foam to achieve bearing length ** LOGIX 12" Knockdown Form available in 2008.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™


5 - 24

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com


10" LOGIX STANDARD FORM ON TOP

STANDARD




10" Standard on
12" Knockdown**

BRICK LEDGE




10" Standard on
10" Brick Ledge

PILASTER



10" Standard on
10" Standard with
Pilaster


TAPER TOP



10" Standard or
10" Taper Top

12" LOGIX KNOCKDOWN** FORM ON TOP

PILASTER



12" Knockdown** on
12" Knockdown** with Pilaster

* Remove foam to achieve bearing length ** LOGIX 12" Knockdown Form available in 2008.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

CAD DRAWINGS

www.logixicf.com


Good. Solid. Green.™

5-25


LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



LUMBER LEDGER




LVL LEDGER

NOTES:


See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

All drawings are downloadable at www.logixcf.com



BOLTED ANGLE SEAT DETAIL



WELDED ANGLE SEAT DETAIL

NOTES:


See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

5.3.5 – BRICK LEDGE WITH TOP CHORD BEARING

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixcf.com

Good. Solid. Green.™

5 – 28

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5-29

LOGIX®
INSULATED CONCRETE FORMS



REPRINTED 2013

Rev. Sep 23/09

CAD DRAWINGS

All drawings are downloadable at www.logixcf.com



C A D D R A W I N G S

**STIRRUP DETAIL****NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 30**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**


1. For more information see Section 2 of the LOGIX Product Manual or visit www.strongtie.com.
2. Use extra caution when installing Simpson ICF Ledger Connection systems on both sides of a wall. Consult your local Simpson Strongtie rep or call Simpson Strongtie at (800) 999-5099 prior to installation.
3. Attachment of second ledger to be designed by others.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5-31**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

HUC410 hanger



JOIST HANGER
(Installed on face of concrete in ICF)


NOTES:

1. For more information see Section 2 of the LOGIX Product Manual or visit www.strongtie.com.
2. Use extra caution when installing Simpson ICF Ledger Connection systems on both sides of a wall. Consult your local Simpson Strongtie rep or call Simpson Strongtie at (800) 999-5099 prior to installation.


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 3 2**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com



STEEL COMPOSITE DECK (BEARING END)



STEEL COMPOSITE DECK (NON-BEARING END)

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™


5 – 3 3

LOGIX®
INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09

CAD DRAWINGS

All drawings are downloadable at www.logixcf.com**PRECAST CONCRETE SITTING ON TOP OF 6.25" TRANSITION FORM****NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

**PRECAST CONCRETE SITTING ON TOP OF 6.25" STANDARD FORM****NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

C A D D R A W I N G S


www.logixcf.com**Good. Solid. Green.™****5 – 3 4****LOGIX®**
INSULATED CONCRETE FORMS

COMMERCIAL DRAWINGS 5.3.12 – HAMBRO FLOOR

All drawings are downloadable at www.logixcf.com



HAMBRO FLOOR SYSTEM (BEARING END)



HAMBRO FLOOR SYSTEM (NON-BEARING END)

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 – 3 5

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09



CAD DRAWINGS

5.3.13 – HAMBRO JOISTS BUTTED UP ON LOGIX ICF WALL (1 OF 2)

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

Joist bears directly on concrete.
Embed or baseplate not required.
(see Note 2)



NOTES:

1. See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.
2. No fasteners required in open holes when joist bears on concrete. Unless noted otherwise (typ.).
3. When calculating bearing elevation – add $\frac{1}{4}$ " to the thickness of the slab to allow for the joist bearing shoe.

CAD DRAWINGS

www.logixcf.com



Good. Solid. Green.™

5 – 3 6

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.





(Slab not shown for clarity)

NOTES:

1. See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.
2. On bearing surfaces less than 8" (nom.), joists must be staggered by a min. of 6".
3. No fasteners required in open holes when joist bears on concrete. Unless noted otherwise (typ.).
4. When calculating bearing elevation – add $\frac{1}{4}$ " to the thickness of the slab to allow for the joist bearing shoe.

C A D D R A W I N G S

www.logixicf.com**Good. Solid. Green.™****5 – 3 7**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com**HOLLOW CORE PRECAST CONCRET SLAB (BEARING END)****HOLLOW CORE PRECAST CONCRET SLAB
(NON-BEARING END)**

NOTES:
See Section 6 –
Engineering in the LOGIX
Product Manual for
reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 3 8**



LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.



All drawings are downloadable at www.logixcf.com


C A D D R A W I N G S

**NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 40**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com**NOTES:**

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

C A D D R A W I N G S

www.logixcf.com**Good. Solid. Green.™****5-41**
LOGIX®
 INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09

All drawings are downloadable at www.logixcf.com**NOTES:**


See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.

C A D D R A W I N G S



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixcf.com**Good. Solid. Green.™****5 – 42**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com**NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixcf.com**Good. Solid. Green.™****5 – 43**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com**NOTES:**

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 - 4 4**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**See Section 6 – Engineering in the LOGIX
Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixicf.com**Good. Solid. Green.™****5 – 4 5**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 04/11

5.4.1 – INTERIOR WALL SUPPORTING OPEN
WEB STEEL JOISTAll drawings are downloadable at www.logixcf.com**NOTES:**

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.




The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 4 6**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

NOTES:

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5-47

LOGIX®
INSULATED CONCRETE FORMS



REPRINTED 2013

Rev. Sep 23/09

CAD DRAWINGS

All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S


**5.8.5 - STEEL DECK ROOF ON OPEN WEB JOIST****5.8.6 - PRECAST CONCRETE FLAT ROOF****NOTES:**

See Section 6 –
Engineering in the LOGIX
Product Manual for
reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 4 8**

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 – 49**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013


Rev. Sep 23/09

C A D D R A W I N G S

All drawings are downloadable at www.logixcf.com**NOTES:**


See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.

C A D D R A W I N G S



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 50**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 – 51**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013


Rev. Sep 23/09

C A D D R A W I N G S

5.4.8 – ICF PARAPET: FLAT ROOF WITH PRECAST CONCRETE PANEL

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 – 52

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 – 53**
LOGIX®
 INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09

C A D D R A W I N G S

All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S

**NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 54**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09


All drawings are downloadable at www.logixicf.com



CAD DRAWINGS

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™


5 – 56

LOGIX®
INSULATED CONCRETE FORMS

COMMERCIAL DRAWINGS

5.4.13 – WOOD PARAPET WITH OPEN WEB STEEL JOIST


All drawings are downloadable at www.logixicf.com



CAD DRAWINGS

All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S


**NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 58**

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 – 59**
LOGIX®
 INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Nov 11/10

C A D D R A W I N G S

All drawings are downloadable at www.logixicf.com


C A D D R A W I N G S

**NOTES:**

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 - 6 0**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**


1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 – 6 1**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

C A D D R A W I N G S

**NOTES:**


1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 - 6 2**
LOGIX®
 INSULATED CONCRETE FORMS

COMMERCIAL DRAWINGS 5.4.19 – SCUPPER DETAIL

All drawings are downloadable at www.logixicf.com



NOTES:

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5 – 6 3

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013


Rev. Nov 11/10

CAD DRAWINGS

COMMERCIAL DRAWINGS 5.4.20 – SEPARATION WALL

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

NOTES:

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.

www.logixcf.com

Good. Solid. Green.™

5 – 64


LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2012

Rev. Nov 11/10

All drawings are downloadable at www.logixcf.com**NOTES:**

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.




The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


C A D D R A W I N G S

www.logixcf.com**Good. Solid. Green.™****5 – 6 5**
LOGIX®
 INSULATED CONCRETE FORMS


All drawings are downloadable at www.logixcf.com




PLAN VIEW - Section at beam
(Reinforcement not shown for clarity)



FRONT ELEVATION



SIDE VIEW - Section at beam side



Restrain lateral rotation
by wedge blocking

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixcf.com

Good. Solid. Green.™


5 - 6 6

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com




PLAN VIEW - Section at beam
(Reinforcement not shown for clarity)



FRONT VIEW

SIDE VIEW



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


COMMERCIAL DRAWINGS 5.5.4 – BOND BEAM

All drawings are downloadable at www.logixcf.com

NOTES:

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.

CAD DRAWINGS



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™


5 – 6 8

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

All drawings are downloadable at www.logixcf.com




CAD DRAWINGS

COMMERCIAL DRAWINGS 5.5.5 – STRUCTURAL STEEL CHANNEL BEAM CONTINUED

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



www.logixcf.com


Good. Solid. Green.™

5 – 7 0

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2012

Rev. Sep 23/09

All drawings are downloadable at www.logixcf.com**NOTES:**

For reinforcement details in walls, see Section 6 – Engineering in the LOGIX Product Manual.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixcf.com**Good. Solid. Green.™****5-71****LOGIX®**
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

All drawings are downloadable at www.logixcf.com

CAD DRAWINGS



NOTES:

For reinforcement details in walls, see Section 6 – Engineering in the LOGIX Product Manual.



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 – 72

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


Section through Wall at Beam Pocketwww.logixicf.com**Good. Solid. Green.™****5 – 73**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2012


Rev. Sep 23/09

All drawings are downloadable at www.logixicf.com

CAD DRAWINGS



LOGIX ICF
8" [203mm] shown



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

Section through Wall at Beam Pocket


www.logixicf.com

Good. Solid. Green.™

5 - 7 4

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com



NOTES:

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.

www.logixicf.com

Good. Solid. Green.™

5 – 7 5


LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2012


Rev. Nov 11/10

CAD DRAWINGS

All drawings are downloadable at www.logixcf.com



DOOR HEAD & SILL USING WOOD BUCKS



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

DOOR JAMB USING WOOD BUCKS

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

CAD DRAWINGS

www.logixcf.com


Good. Solid. Green.™

5 – 7 6


LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.



**WOOD WINDOW BUCK
SLOPED CONCRETE SILL**

**NOTE:**


Adjust 2x lumber to suit specified slope of concrete sill.

www.logixicf.com**Good. Solid. Green.™****5-77**

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

C A D D R A W I N G S

**NOTES:**


1. For wall & lintel reinforcement, see LOGIX Product Manual Section 6, Engineering.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 - 7 8**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com**NOTES:**

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.




The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 79**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

C A D D R A W I N G S



All drawings are downloadable at www.logixcf.com**NOTES:**

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 80**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com




**SECTION THROUGH
LINTEL**

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

CAD DRAWINGS

All drawings are downloadable at www.logixcf.com

**NOTES:**

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 – 82

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**


See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 – 83**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com


C A D D R A W I N G S

**NOTES:**

1. See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 84**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**

1. See Section 6 – Engineering in the LOGIX Design Manual for wall & lintel reinforcement.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixicf.com**Good. Solid. Green.™****5 – 8 5**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013


Rev. Sep 23/09

5.6.11 – WELDED PRESS STEEL DOOR FRAME - CENTER MOUNTED

All drawings are downloadable at www.logixicf.com



INTERIOR DOOR FRAME - HEAD CENTER MOUNTED DOOR



INTERIOR DOOR FRAME - JAMB CENTER MOUNTED DOOR

NOTES:

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5 – 8 6

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**INTERIOR DOOR FRAME - HEAD
FLUSH MOUNTED DOOR****INTERIOR DOOR FRAME - JAMB
FLUSH MOUNTED DOOR****NOTES:**


1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 – 87**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S


**NOTES:**

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 8 8**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com



ALUMINUM WINDOW JAMB



ALUMINUM WINDOW HEAD

NOTES:

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5 – 8 9

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com**NOTES:**

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

C A D D R A W I N G S


www.logixcf.com**Good. Solid. Green.™****5 – 90**
LOGIX®
 INSULATED CONCRETE FORMS

5.6.16 – WINDOW OPENING - TEMPORARY FORM SUPPORT FOR EXPOSED CONCRETE W/ 4" TRIM


All drawings are downloadable at www.logixcf.com




FORM SUPPORT - EXTERIOR SIDE



FORM SUPPORT - INTERIOR SIDE



ELEVATION - EXTERIOR SIDE



ELEVATION - INTERIOR SIDE

NOTE:

1. For 4" exposed concrete trim around opening on the interior face apply same form support and detail as shown for exterior face details.
2. Unless otherwise shown, temporary form work material includes 2x4 and plysheets.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

CAD DRAWINGS

www.logixcf.com


Good. Solid. Green.™

5-91


LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com


C A D D R A W I N G S




A - A
FORM SUPPORT ALONG
LINTEL



B - B
FORM SUPPORT ALONG
SILL



C - C
FORM SUPPORT AT
LINTEL AND SILL END



D - D
FORM SUPPORT AT SIDES
OF OPENING


NOTE:

1. For 4" exposed concrete trim around opening on the interior face apply same form support and detail as shown for exterior face details.
2. Unless otherwise shown, temporary form work material includes 2x4 and plysheets.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 - 92**
LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5-93

LOGIX®
INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Nov 11/10

CAD DRAWINGS

All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S

**NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixcf.com

Good. Solid. Green.™

5 – 94

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

**NOTES:**

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5 – 9 5

LOGIX®
INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09

CAD DRAWINGS


All drawings are downloadable at www.logixcf.com**NOTES:**

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 96**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S

www.logixcf.com

Good. Solid. Green.™

5-97


LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2012

Rev. Sep 23/09

All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixcf.com

Good. Solid. Green.™

5 – 98


LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com



All drawings are downloadable at www.logixcf.com**NOTES:**

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.




The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

C A D D R A W I N G S

www.logixcf.com**Good. Solid. Green.™****5 – 100**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.



C A D D R A W I N G S

www.logixcf.com



Good. Solid. Green.™

5-101

LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2012

Rev. Sep 23/09


All drawings are downloadable at www.logixcf.com**Logix Pilaster Supporting Steel Column****Logix Pilaster Supporting Steel Beam****NOTES:**

For reinforcement details in walls, see Section 6 – Engineering in the LOGIX Product Manual.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 102**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com



CAD DRAWINGS

www.logixcf.com

Good. Solid. Green.™

5-103


LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2012

Rev. Sep 23/09


5.7.11 – WOOD COLUMN ON LOGIX PILASTER

All drawings are downloadable at www.logixcf.com




PLAN VIEW

(Reinforcement not shown for clarity)




SIDE VIEW

(Reinforcement not shown for clarity)



FRONT VIEW



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


CAD DRAWINGS

www.logixcf.com

Good. Solid. Green.™

5-104

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5-105**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013


Rev. Nov 04/11

C A D D R A W I N G S

5.8 – SOUND TRANSMISSION CLASSIFICATION (STC)

5.8.1 – 4" LOGIX WALL LAYOUT (STC 50)

All drawings are downloadable at www.logixcf.com



STC50 - 4" [102mm] LOGIX WALL


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 - 1 0 6

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**STC56 - 6.25" [159mm] LOGIX WALL**

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5-107**
LOGIX®
 INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09

C A D D R A W I N G S

All drawings are downloadable at www.logixcf.com



C A D D R A W I N G S

**NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 108**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com**SECTION A-A****STIRRUP DETAIL**
(See Note 2)**NOTES:**


1. See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.
2. Stirrup shown is rated for 1300lbs/ft (19kN/m). For heavier load conditions and stirrup dimensions see Brick Ledge Stirrup details drawings.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5-109****LOGIX®**
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com


CAD DRAWINGS

**NOTES:**

1. See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.
2. Stirrup shown is rated for 1300lbs/ft (19kN/m). Maximum load capacity w/o stirrups – 900lbs/ft (13kN/m).

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 1 1 0**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com**NOTES:**


See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixcf.com**Good. Solid. Green.™****5-111**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09



5.10.5 - BRICK LEDGE STANDARD REINFORCEMENT





5.10.6 - BRICK LEDGE HEAVY REINFORCEMENT

* 1kN = 224.8lb

NOTES:

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

All drawings are downloadable at www.logixcf.com**BRICK LEDGE STANDARD REINFORCEMENT****DETAIL A****NOTES:**

See Section 6 –
Engineering in the LOGIX
Product Manual for
reinforcement details.

* 1kN = 224.8lb


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5-113**

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013



Rev. Nov 30/12

All drawings are downloadable at www.logixcf.com**NOTES**

1. Install vertical rebar 6" (150) beyond corbel width for full height of wall each face.
2. Reinforcement details should be reviewed by a local licensed professional engineer.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.



www.logixcf.com**Good. Solid. Green.™****5 - 1 1 4**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com**5.9.1 - LOGIX WALL ATTACHMENT TO EXISTING CONCRETE WALL****5.9.2 - LOGIX WALL ATTACHMENT TO EXISTING CONCRETE MASONRY WALL****NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.




www.logixcf.com**Good. Solid. Green.™****5-115**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com**INTERIOR LOGIX WALL TO EXTERIOR STUD FRAMED WALLS****INTERIOR LOGIX WALL TO INTERIOR STUD FRAMED WALLS**

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

CAD DRAWINGS


www.logixcf.com**Good. Solid. Green.™****5 – 1 1 6**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com**PLAN VIEW****DETAIL A****DETAIL B****NOTES:**

1. To maintain form integrity apply wooden straps at joints.
2. Creating a 12" (305mm) jog might create misaligned interlocks – cut interlocks where misalignment occurs.
3. To create jog in other direction cut opposite forms.
4. Interlocks not shown for clarity.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixcf.com**Good. Solid. Green.™****5-117**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**Notes:**

1. These drawings illustrate an example of wall bracing for horizontal wall transitions at corners. The contractor shall practice sound judgement (based on wall structure, pouring sequence and other site-conditions) to determine if additional form support and bracing is required.
2. Avoid placing concrete directly into the corners.
3. Follow all required national and local wall brace safety regulations.
4. See page 2 for perspective views.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 – 1 1 8**
LOGIX®
 INSULATED CONCRETE FORMS


**Notes:**

1. These drawings illustrate an example of wall bracing for horizontal wall transitions at corners. The contractor shall practice sound judgement (based on wall structure, pouring sequence and other site-conditions) to determine if additional form support and bracing is required.
2. Avoid placing concrete directly into the corners.
3. Follow all required national and local wall brace safety regulations.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

5.9.14 – HORIZONTAL TRANSITION - 6.25" TO 8" TEE WALL WITH END CAP

All drawings are downloadable at www.logixicf.com



Notes:

1. These drawings illustrate an example of wall bracing for horizontal wall transitions at corners. The contractor shall practice sound judgement (based on wall structure, pouring sequence and other site-conditions) to determine if additional form support and bracing is required.
2. Avoid placing concrete directly into the corners.
3. Follow all required national and local wall brace safety regulations.
4. See page 2 for perspective views.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.





CAD DRAWINGS

www.logixicf.com

Good. Solid. Green.™


5 - 120

LOGIX®
INSULATED CONCRETE FORMS

**Notes:**

1. These drawings illustrate an example of wall bracing for horizontal wall transitions at corners. The contractor shall practice sound judgement (based on wall structure, pouring sequence and other site-conditions) to determine if additional form support and bracing is required.
2. Avoid placing concrete directly into the corners.
3. Follow all required national and local wall brace safety regulations.
4. See page 2 for perspective views.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

All drawings are downloadable at www.logixicf.com


The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5 – 122

LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5-123

LOGIX®
 INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09

C A D D R A W I N G S

All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S


**NOTES:**

1. All fasteners to be attached to the embedded furring tabs.
2. Recommended min. fastener spacings:
 1. Grabber construction non-corrosive screws: No.8 min. 1.25" long, 8" o.c. horiz., 12" o.c. vert. spacing.
 - OR
 2. Staples 1.59mm 16ga. min. 1.25" long, 8" o.c. horiz., 5" o.c. vert. spacing.
3. Always follow manufacturer's instructions or recommendations.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 124**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com




CAD DRAWINGS

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

All drawings are downloadable at www.logixcf.com


C A D D R A W I N G S

**NOTES:**

All embedded plates & and anchors as per specs.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 1 2 6**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5-127**
LOGIX®
 INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09

C A D D R A W I N G S

All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

NOTES:


See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

www.logixcf.com**Good. Solid. Green.™****5 – 1 2 8**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com

NOTES:

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5-129

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09


CAD DRAWINGS

COMMERCIAL DRAWINGS 5.9.23 – METAL HANDRAIL

All drawings are downloadable at www.logixcf.com

NOTES:

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 – 130

LOGIX®
INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09

All drawings are downloadable at www.logixicf.com

NOTES:

See Section 6 – Engineering in the LOGIX Design Manual or the LOGIX Field Manual for reinforcement details.



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5-131

LOGIX®
INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Sep 23/09

CAD DRAWINGS


All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 132**
LOGIX®
 INSULATED CONCRETE FORMS


All drawings are downloadable at www.logixicf.com**NOTES:**

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

All drawings are downloadable at www.logixicf.com

CAD DRAWINGS




The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™

5 – 134

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 – 135**
LOGIX®
 INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Nov 11/10

C A D D R A W I N G S

All drawings are downloadable at www.logixicf.com

CAD DRAWINGS



NOTES:

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™




5 – 136

LOGIX®
INSULATED CONCRETE FORMS

(applicable for LOGIX 6.25" & larger)

All drawings are downloadable at www.logixicf.com**NOTES:**

1. 6 $\frac{1}{4}$ " [159mm] LOGIX Standard Form shown.
2. See Section 6 – Engineering in the LOGIX Design Manual for wall reinforcement details.



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5-137**
LOGIX®
 INSULATED CONCRETE FORMS




REPRINTED 2013

Rev. Nov 11/10

CONTINUED

All drawings are downloadable at www.logixcf.com**NOTES:**


1. 4" [102mm] LOGIX Standard Form shown.
2. For more horizontal and vertical rebar reinforcement details, see Section 6 – Engineering in the LOGIX Design Manual.
3. For more lintel reinforcement details, see Section 6 – Engineering in the LOGIX Design Manual.




The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 138**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com



SECTION AT BOLTED ANGLE SEAT DETAIL



NOTES:

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

CAD DRAWINGS

www.logixcf.com

Good. Solid. Green.™

5-139


LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2012


Rev. Nov 11/10

All drawings are downloadable at www.logixcf.com


PVC pipe cut in half.
Attach to inside foam panel.
Support with metal plumbers tape.
Block top of PVC pipe
prior to concrete pour.



Metal plumbers tape
@ 16" o/c vertically.
Wrap around pipe and
Screw to embedded
furring tabs.



Embedded vertical pipe –
Foam panel partially
removed for clarity



Metal plumbers
tape.
Inside foam panel view –
Foam panel and webs
partially removed for
clarity.



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com

Good. Solid. Green.™

5 – 140

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5-141****LOGIX®**
INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Nov 11/10

C A D D R A W I N G S

All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S


**NOTES:**

1. Corbel steel details to be verified and approved by a locally licensed engineer.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 1 4 2**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com

Good. Solid. Green.™



5-143

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 11/10

CAD DRAWINGS

All drawings are downloadable at www.logixicf.com

NOTES:

1. Fire rated stucco w/ mesh finish shall be factory applied to LOGIX exterior form panels. (LOGIX Knockdown forms shall be used for the wall construction).
2. All exposed edges of LOGIX exterior form panels, including top of wall (top edge of top course), shall be fully covered with fire rated mesh and stucco finish..
3. All joints/seams between form panels shall be sealed with minimum $\frac{3}{8}$ " fire stop caulking.
4. Stucco finish shall be tested to, and meet requirements, of CAN4-S114 "Standard Method of Test for Determination of Non-combustibility in Building Materials".
5. 2 hour minimum fire rating of Logix ICF, as per CAN/ULC S101-M "Standard Method of Fire Endurance Tests of Building Construction & Materials" (ASTM E119 "Standard Test Methods for Fire Tests of Building Construction & Materials").
6. Refer to Section 6 Engineering in the LOGIX Design Manual for wall reinforcement.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


C A D D R A W I N G S

www.logixicf.com

Good. Solid. Green.™

5 - 1 4 4

LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com**NOTES:**

1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixicf.com**Good. Solid. Green.™****5 – 145**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 11/10

All drawings are downloadable at www.logixicf.com

C A D D R A W I N G S

**NOTES:**


1. See Section 6 - Engineering in the LOGIX Design Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.


www.logixicf.com**Good. Solid. Green.™****5 – 1 4 6**
LOGIX®
 INSULATED CONCRETE FORMS

5.9.39 – 18" JOGS WITH LEFT & RIGHT HAND 10" LOGIX PRO CORNER FORMS


All drawings are downloadable at www.logixicf.com



PLAN VIEW



DETAIL A



DETAIL B

NOTES:

1. To maintain form integrity apply wooden straps at joints.
2. Creating a jog might create misaligned interlocks – cut interlocks where misalignment occurs.
3. To create jog in other direction cut opposite forms.
4. Interlocks not shown for clarity.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com


Good. Solid. Green.™

5-147

LOGIX®
INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixcf.com


C A D D R A W I N G S

**NOTES:**

See Section 6 – Engineering in the LOGIX Product Manual for reinforcement details.

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 1 4 8**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5 – 149**
LOGIX®
 INSULATED CONCRETE FORMS


REPRINTED 2013

Rev. Nov 04/11

C A D D R A W I N G S


All drawings are downloadable at www.logixcf.com

C A D D R A W I N G S



The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixcf.com**Good. Solid. Green.™****5 – 1 5 0**
LOGIX®
 INSULATED CONCRETE FORMS

All drawings are downloadable at www.logixicf.com

The tables and drawings represented herein are believed to be accurate and conforming to current design and construction practices. However, the tables and drawings should be used as a reference guide only. The user shall check to ensure the drawing meets local building codes, design and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the tables and drawings without notice and assumes no liability in connection with the use of the tables and drawings including modification, copying or distribution.

www.logixicf.com**Good. Solid. Green.™****5-151**
LOGIX®
 INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 30/12

C A D D R A W I N G S

6.0 – ENGINEERING

TABLE OF CONTENTS

| | |
|---|----------------|
| 6.1 – U.S. ENGINEERING ANALYSIS REPORT | P. 6-3 |
| BELOW-GRADE WALL REINFORCEMENT TABLES.... | P. 6-6 |
| ABOVE-GRADE WALL REINFORCEMENT TABLES.. | P. 6-15 |
| LINTEL REINFORCEMENT TABLES..... | P. 6-20 |
| SHEAR WALLS | P. 6-36 |
| 6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: | |
| IMPERIAL UNITS..... | P. 6-39 |
| BELOW-GRADE WALL TABLES | P. 6-43 |
| ABOVE-GRADE WALL TABLE..... | P. 6-48 |
| LINTEL TABLES | P. 6-51 |
| 6.3 – SOIL CLASSIFICATION TABLES..... | P. 6-67 |
| 6.4 – FOOTING WIDTH TABLES | P. 6-68 |

APPENDIX

LOGIX below-grade tables with seismic loading considered are available for download at www.logixicf.com by clicking “Technical Library”, “Design Manual”, “Engineering”.

The tables are grouped into the following provinces:

- AB, SK, MB, NF, PEI, NS
- ON, NB
- BC, QB

APPENDIX A - BELOW-GRADE REINFORCEMENT TABLES
FOR AB, SK, MB, NF, PEI, NS

APPENDIX B - BELOW-GRADE REINFORCEMENT TABLES
FOR ON, NB

APPENDIX C - BELOW-GRADE REINFORCEMENT TABLES
FOR BC, QB

DISCLAIMER

By using the LOGIX Design Manual, in part or in whole, the user accepts the following terms and conditions.


The LOGIX Design Manual shall be used for the sole purpose of estimating, design or construction of LOGIX Insulated Concrete Forms used in residential, commercial or industrial structures.

The information represented herein is to be used as a reference guide only. The user shall check to ensure the information provided in this manual, including updates and amendments, meets local building codes and construction practices by consulting local building officials, construction and design professionals, including any additional requirements.

Logix reserves the right to make changes to the information provided herein without notice and assumes no liability in connection with the use of this manual including modification, copying or distribution.

The user shall check to ensure that any construction projects utilizing the LOGIX Design Manual includes the latest updates/amendments (related to the version of the LOGIX Design Manual being used at the time of the construction project). Updates/amendments to the LOGIX Design Manual are available for download in the "Technical Library" under "Addenda" at www.logixicf.com.

6.1 – U.S. ENGINEERING ANALYSIS REPORT



Engineering LTD

6913 Young Court • Woodridge, Illinois 60517 • (630) 963-7817

November 1, 2010

RSJR No. 10-151MY

AMC Foam Technologies
LOGIX Insulated Concrete Forms
151 Paramount Road
Winnipeg, MB R2X2W6


Re: LOGIX ICF (Insulated Concrete Form) Engineering Approval – Illinois

To Whom It May Concern:

As per your request, we have completed a review of the U.S. Engineering Analysis Report included in Chapter 6 of the LOGIX ICF Product Manual. We approve the use of Tables 1, 2A, 2B, 2C, 2D, 3, 4A, 4B, 4C, 4D, 4E, 5A, 5B, 5C, 5D, and 5E dated Sep 23/09 for use in the State of Illinois. The tables meet or exceed the requirements of the 2006 International Building Code and are in compliance with American Concrete Institute Building Code Requirements for Structural Concrete (ACI 318).

Respectfully submitted for:
RSJR Engineering LTD
By:

Roman Szczesniak, S.E.
RSJR Engineering LTD



ENGINEERING

Good. Solid. Green.™

www.logixicf.com

6 – 3



THIS PAGE HAS BEEN INTENTIONALLY LEFT BLANK

6.1 – U.S. ENGINEERING ANALYSIS REPORT

INTRODUCTION

LOGIX walls are intended to be used both above and below grade, and can carry large vertical as well as lateral loads. They are particularly effective for residential, commercial and industrial buildings; providing excellent insulation as well as thermal mass and structural strength. They can be easily adapted to accommodate concrete floors and other “non-standard” building systems.

Construction must be in conformance with the LOGIX Design Manual, including assembly of formwork, bracing, accurate rebar positioning, concrete mix design & placement, and details for interconnection with the other building components.

STRUCTURAL DESIGN AND PERFORMANCE

The LOGIX Building System can be used for an infinite variety of building situations with proper engineering. This report, with its load tables and diagrams, is intended to assist with the structural design of buildings using the LOGIX system for the basement only, or continuing to two stories above-grade and/or roof. Where unusual conditions are encountered, it is recommended that the user consult a designer who can evaluate the loadings to the various components and who can appreciate the limitations of “prescriptive” design under unusual conditions. Connection details have generally been excluded from this report because of the great variety of floor and roof systems that can be used with the Logix wall system. The designer should refer to the Logix Design Manual and the literature for the various proprietary products that are available for connections, which are an important part of the total design.

REINFORCEMENT TABLES

Above- and below-grade walls and lintel reinforcement tables are provided in this report. The tables were developed using the applicable sections of Chapter 16 of the International Building Code 2012, Sections 404 and 611 of the International Residential Code 2012, and ACI 318 Building Code Requirements for Structural Concrete.

Table 1 makes use of plain concrete foundation walls adapted from the IRC 2012, Table 404.1.2(8), for LOGIX used below-grade. For walls that fall outside the scope of Table 1, Tables 2A, 2B, 2C and 2D are provided, which cover wall reinforcement for larger walls and larger loading conditions.

Tables 3A and 3B provides reinforcement tables for LOGIX walls used above-grade.

Building limitations used to develop Tables 2A to 2D, and Tables 3A and 3B include:

Building perimeter = 80 ft max x 40 ft max
Roof clear span = 40 ft max
Floor clear span = 32 ft max
Number of stories above grade = 2 max
Number of stories below grade = 1

Tables 4A to 4E and Tables 5A to 5E provide lintel tables for factored uniform and concentrated loading conditions, respectively.

More specific design assumptions and limitations are located with the corresponding reinforcement tables.

6.1 – U.S. ENGINEERING ANALYSIS REPORT

BELOW-GRADE WALL REINFORCEMENT TABLES

NOTES FOR TABLE 1 - BELOW-GRADE TABLE ADAPTED FROM IRC 2012

Table 1 was developed adapting Table 404.1.2(8), Minimum Vertical Reinforcement For 6-, 8-, 10-Inch And 12-Inch Nominal Flat Basement Walls, of IRC 2012. Table 1 allows the use of foundation walls without reinforcement (in lieu of Tables 2A to 2D) provided the walls meet the following criteria:

1. Minimum 28day compressive strength of concrete = 2500 psi
2. Concrete foundation walls with corbels (ie, brick ledge), brackets or other projections built into the wall for support of masonry veneer or other purposes are not within the scope of the tables in this section
3. Where vertical rebar is not required (NR), provide minimum horizontal rebar as follows (Table 404.1.2(1)):
 - Maximum unsupported height of basement wall is LESS than or equal to 8 ft - One No. 4 bar within 12 inches of the top of the wall story and one No. 4 bar near mid-height of the wall story
 - Maximum unsupported height of basement wall is GREATER than 8 ft - One No. 4 bar within 12 inches of the top of the wall story and one No. 4 bar near third points in the wall story
4. Walls are not subject to hydrostatic pressure from ground water
5. Walls must be laterally supported at top and bottom of wall before backfilling
6. Interpolation is not permitted
7. Maximum 60 feet in plan dimensions, floors not more than 32 feet or roofs not more than 40 feet in clear span. Buildings shall not exceed 2 stories above-grade with each story not more than 10 feet high. Maximum ground snow load of 70 psf, and located in Seismic Design Categories A, B or C. For Seismic Design Categories D0, D1, or D2 see Items 7 to 9.
8. In Seismic Design Category D0, D1, and D2, concrete foundation walls supporting above grade concrete or LOGIX walls shall comply with above and below-grade tables in this manual, ACI 318, ACI 332 or PCA 100
9. In Seismic Design Category D0, D1, and D2, where Table 1 permits plain concrete, and supporting light-frame walls shall comply with the following:
 - Wall height shall not exceed 8 feet
 - Unbalanced backfill height shall not exceed 4 feet
 - Minimum thickness for plain concrete foundation walls shall be 7.5 inches except that 6 inches is permitted where the maximum wall height is 4 feet, 6 inches
 - Minimum reinforcement shall consist of one #4 horizontal bar within the top 12 inches of the wall
10. Backfill shall not be placed against the wall until the wall has sufficient strength and has been anchored to the floor above, or has been sufficiently braced to prevent damage by the back fill.
11. For walls that fall outside the scope Table 1 see "Notes for Tables 2A to 2D - LOGIX Below-grade Tables."

E
N
G
I
N
E
E
R
I
N
G

6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 1 - LOGIX BELOW-GRADE WALLS MINIMUM VERTICAL REINFORCEMENT - IRC2012

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| Height of Basement Wall, ft | Max. Unbalanced Backfill Height, ft | 6.25" LOGIX | | | 8" LOGIX | | | 10" LOGIX | | | 12" LOGIX | | |
|-----------------------------|-------------------------------------|--|----|----|--|----|----|--|----|----|--|----|----|
| | | Design Lateral Soil Load (psf per foot of depth) | | | Design Lateral Soil Load (psf per foot of depth) | | | Design Lateral Soil Load (psf per foot of depth) | | | Design Lateral Soil Load (psf per foot of depth) | | |
| | | 30 | 45 | 60 | 30 | 45 | 60 | 30 | 45 | 60 | 30 | 45 | 60 |
| 5 | 5 | RR | RR | RR | NR | NR | NR | NR | NR | NR | NR | NR | NR |
| 6 | 4 | RR | RR | RR | NR | NR | NR | NR | NR | NR | NR | NR | NR |
| | 5 | RR | RR | RR | NR | NR | NR | NR | NR | NR | NR | NR | NR |
| | 6 | RR | RR | RR | NR | NR | NR | NR | NR | NR | NR | NR | NR |
| 7 | 4 | RR | RR | RR | NR | NR | NR | NR | NR | NR | NR | NR | NR |
| | 5 | RR | RR | RR | NR | NR | NR | NR | NR | NR | NR | NR | NR |
| | 6 | RR | RR | RR | NR | NR | RR | NR | NR | NR | NR | NR | NR |
| | 7 | RR | RR | RR | NR | RR | RR | NR | NR | NR | NR | NR | NR |
| 8 | 4 | RR | RR | RR | NR | NR | NR | NR | NR | NR | NR | NR | NR |
| | 5 | RR | RR | RR | NR | NR | NR | NR | NR | NR | NR | NR | NR |
| | 6 | RR | RR | RR | NR | NR | RR | NR | NR | NR | NR | NR | NR |
| | 7 | RR | RR | RR | NR | RR | RR | NR | NR | NR | NR | NR | NR |
| | 8 | RR | RR | RR | RR | RR | RR | NR | NR | RR | NR | NR | NR |
| 9 | 4 | RR | RR | RR | NR | NR | NR | NR | NR | NR | NR | NR | NR |
| | 5 | RR | RR | RR | NR | NR | NR | NR | NR | NR | NR | NR | NR |
| | 6 | RR | RR | RR | NR | NR | RR | NR | NR | NR | NR | NR | NR |
| | 7 | RR | RR | RR | NR | RR | RR | NR | NR | RR | NR | NR | NR |
| | 8 | RR | RR | RR | RR | RR | RR | NR | RR | RR | NR | NR | RR |
| 10 | 9 | RR | RR | RR | RR | RR | RR | NR | RR | RR | NR | NR | RR |
| | 4 | RR | RR | RR | NR | NR | NR | NR | NR | NR | NR | NR | NR |
| | 5 | RR | RR | RR | NR | NR | NR | NR | NR | NR | NR | NR | NR |
| | 6 | RR | RR | RR | NR | NR | RR | NR | NR | NR | NR | NR | NR |
| | 7 | RR | RR | RR | NR | RR | RR | NR | NR | RR | NR | NR | NR |
| | 8 | RR | RR | RR | RR | RR | RR | NR | RR | RR | NR | NR | RR |
| | 9 | RR | RR | RR | RR | RR | RR | RR | RR | RR | NR | RR | RR |
| | 10 | RR | RR | RR | RR | RR | RR | RR | RR | RR | NR | RR | RR |

NOTES:

1. "NR" denotes plain concrete or no reinforcement required, except 6.25" LOGIX will requires #4@32" on center.
2. "RR" denotes reinforcement required. Refer to Tables 2A to 2D for LOGIX Below-grade tables.
3. Table 1 shall be read in conjunction with "Notes for Table 1 - Below-grade Table Adapted from IRC 2012".

ENGINEERING

6.1 – U.S. ENGINEERING ANALYSIS REPORT

NOTES FOR TABLES 2A to 2D - LOGIX BELOW-GRADE TABLES

Tables 2A to 2D are recommended for use when larger walls and/or loading conditions fall outside the scope of Table 1.

LOGIX below-grade Tables 2A to 2D shall be used in conjunction with corresponding Figures 2A to 2D, the notes listed below, and the building limitations noted in the "Reinforcement Tables" section, which form the basis of these tables.

1. Vertical rebar spacing shown in the tables provide simple placement between ICF ties.
2. Steel yield strength = 40 ksi, 28 day concrete compressive strength = 3 ksi
3. Rebar spacing is based on 40 ksi reinforcing steel. For spacing based on 60 ksi reinforcing steel multiply spacings by 1.5.
4. Deflection criteria = $L/240$
5. Snow load = 70 psf
6. Assumed eccentricity = 3" (to account for loads on LOGIX Brick Ledge).
7. The basement walls must be supported at the top and bottom of the wall.
8. For light vehicles parked or travelling near the wall use reinforcement corresponding to 1 feet higher backfill.
9. Where spaces have been left blank, the corresponding bar size is presumed to be less economical and/or practical than that shown. Consult a local licensed engineer to determine proper design.
10. For walls with over 50% of height exposed to wind, also check rebar requirements for above-grade walls.
11. Except as noted for seismic design, horizontal rebar shall be #4 at 32 inches on center. At least one rebar shall be placed at the bottom course and top course.
12. In Seismic Design Categories D0, D1, and D2, the reinforcing steel shall meet the requirements of ASTM A 706 for low-alloy steel with a minimum yield strength of 60 ksi.
13. For townhouses in Seismic Category C, the minimum vertical reinforcement shall be one #5 at 24 inches on center or one #4 bar at 16 inches on center, and the minimum horizontal reinforcement shall be one #4 bar at 16 inches on center.
14. For all buildings in Seismic Design Categories D0, D1 and D2, the minimum vertical reinforcement shall be one #5 at 18 inches on center or one #4 bar at 12 inches on center, and the minimum horizontal reinforcement shall be one #5 bar at 16 inches on center.
15. Horizontal reinforcement shall be continuous around building corners using corner bars or by bending the bars. The minimum lap splice shall be 24 inches. For townhouses in Seismic Design Categories D0, D1, and D2, each end of all horizontal reinforcement shall terminate with a standard hook or lap splice.
16. Carefully consider floor/wall connection details for lateral loads, especially with higher backfills, walkout basements, and active seismic areas.
17. Soil density is often referred to as "equivalent fluid density" or design fluid pressure.

6.1 – U.S. ENGINEERING ANALYSIS REPORT

NOTES FOR TABLES 2A to 2D - LOGIX BELOW-GRADE TABLES Cont'd




Fig 2A
Assumed typical flooring, wall & roof for **Table 2A**. Height & thickness of above-grade walls, floor & roof spans, including materials (i.e., wood frame, concrete, and cladding) can vary provided the total factored load on basement wall does not exceed 6.7 kips/ft.




Fig 2B
Assumed typical flooring, wall & roof for **Table 2B**. Height & thickness of above-grade walls, floor & roof spans, including materials (i.e., wood frame, concrete, and cladding) can vary provided the total factored load on basement wall does not exceed 8 kips/ft.




Fig 2C
Assumed typical flooring, wall & roof for **Table 2C**. Height & thickness of above-grade walls, floor & roof spans, including materials (i.e., wood frame, concrete, and cladding) can vary provided the total factored load on basement wall does not exceed 8 kips/ft.




Fig 2D
Assumed typical flooring, wall & roof for **Table 2D**. Height & thickness of above-grade walls, floor & roof spans, including materials (i.e., wood frame, concrete, and cladding) can vary provided the total factored load on basement wall does not exceed 9 kips/ft.

ENGINEERING

6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 2A - LOGIX 6.25" BELOW-GRADE WALL MINIMUM VERTICAL REINFORCEMENT

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| Maximum Height of Basement Wall, ft | Maximum Unbalanced Backfill Height, ft | Bar Spacing, in. | | | | | | | | | | | | | | | | | | | |
|-------------------------------------|--|----------------------------------|----|----|----|----|----------------------------------|----|----|----|----|----------------------------------|----|----|----|----|----------------------------------|----|----|----|----|
| | | Maximum Equivalent Density 30pcf | | | | | Maximum Equivalent Density 45pcf | | | | | Maximum Equivalent Density 60pcf | | | | | Maximum Equivalent Density 75pcf | | | | |
| 8 | 4-5 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| | 6 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 24 | 40 | 48 | 48 | 48 | 16 | 24 | 40 | 48 | 48 |
| | 7 | 48 | 48 | 48 | 48 | 48 | 24 | 40 | 48 | 48 | 48 | 16 | 24 | 32 | 40 | 48 | 8 | 16 | 24 | 32 | 40 |
| | 8 | 32 | 48 | 48 | 48 | 48 | 16 | 24 | 32 | 48 | 48 | 8 | 16 | 16 | 24 | 40 | 8 | 12 | 16 | 16 | 24 |
| 9 | 4 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| | 5 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 48 |
| | 6 | 48 | 48 | 48 | 48 | 48 | 40 | 48 | 48 | 48 | 48 | 16 | 32 | 48 | 48 | 48 | 12 | 24 | 32 | 40 | 48 |
| | 7 | 48 | 48 | 48 | 48 | 48 | 16 | 32 | 40 | 48 | 48 | 12 | 16 | 24 | 32 | 48 | 8 | 12 | 16 | 24 | 32 |
| | 8 | 24 | 40 | 48 | 48 | 48 | 12 | 16 | 24 | 32 | 48 | 8 | 12 | 16 | 24 | 24 | 6 | 8 | 12 | 16 | 16 |
| | 9 | 16 | 24 | 32 | 40 | 48 | 8 | 12 | 16 | 24 | 32 | 6 | 8 | 12 | 16 | 16 | - | 6 | 8 | 12 | 16 |
| 10 | 4 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| | 5 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 40 | 48 | 48 | 48 | 48 | 24 | 40 | 48 | 48 | 48 |
| | 6 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 48 | 16 | 24 | 32 | 48 | 48 | 12 | 16 | 24 | 32 | 48 |
| | 7 | 32 | 48 | 48 | 48 | 48 | 16 | 24 | 32 | 40 | 48 | 8 | 12 | 16 | 24 | 32 | 6 | 12 | 16 | 16 | 24 |
| | 8 | 16 | 24 | 40 | 48 | 48 | 8 | 12 | 16 | 24 | 32 | 6 | 8 | 12 | 16 | 24 | - | 8 | 8 | 12 | 16 |
| | 9 | 12 | 16 | 24 | 32 | 48 | 6 | 8 | 16 | 16 | 24 | - | 6 | 8 | 12 | 16 | - | - | 8 | 6 | 12 |
| | 10 | 8 | 12 | 16 | 24 | 32 | - | 8 | 12 | 16 | 16 | - | 6 | 8 | 6 | 12 | - | - | 6 | 6 | 6 |
| 11 | 4 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| | 5 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 48 | 16 | 32 | 40 | 48 | 48 |
| | 6 | 48 | 48 | 48 | 48 | 48 | 24 | 32 | 48 | 48 | 48 | 12 | 16 | 32 | 40 | 48 | 8 | 16 | 16 | 24 | 40 |
| | 7 | 24 | 32 | 48 | 48 | 48 | 12 | 16 | 24 | 32 | 48 | 8 | 12 | 16 | 24 | 32 | 6 | 8 | 12 | 16 | 24 |
| | 8 | 12 | 16 | 32 | 40 | 48 | 8 | 12 | 16 | 24 | 32 | - | 8 | 12 | 16 | 16 | - | 6 | 8 | 12 | 16 |
| | 9 | 8 | 16 | 16 | 24 | 32 | 6 | 8 | 12 | 16 | 16 | - | 6 | 8 | 12 | 6 | - | - | 6 | 6 | 6 |
| | 10 | 6 | 8 | 16 | 16 | 24 | - | 6 | 8 | 12 | 16 | - | - | 6 | 6 | 6 | - | - | - | 6 | 6 |
| | 11 | 6 | 8 | 12 | 16 | 16 | - | - | 6 | 6 | 6 | - | - | - | 6 | 6 | - | - | - | - | 6 |
| 12 | 4 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| | 5 | 48 | 48 | 48 | 48 | 48 | 40 | 48 | 48 | 48 | 48 | 24 | 32 | 48 | 48 | 48 | 16 | 24 | 32 | 48 | 48 |
| | 6 | 40 | 48 | 48 | 48 | 48 | 16 | 24 | 40 | 48 | 48 | 12 | 16 | 24 | 32 | 40 | 8 | 12 | 16 | 24 | 32 |
| | 7 | 16 | 24 | 40 | 48 | 48 | 8 | 16 | 16 | 24 | 40 | 6 | 8 | 12 | 16 | 24 | - | 8 | 12 | 16 | 16 |
| | 8 | 12 | 16 | 24 | 32 | 40 | 6 | 8 | 12 | 16 | 24 | - | 6 | 8 | 12 | 16 | - | - | 8 | 6 | 6 |
| | 9 | 8 | 12 | 16 | 24 | 24 | - | 6 | 8 | 12 | 16 | - | - | 6 | 6 | 6 | - | - | - | 6 | 6 |
| | 10 | 6 | 8 | 12 | 16 | 16 | - | - | 8 | 6 | 6 | - | - | - | 6 | 6 | - | - | - | - | 6 |
| | 11 | - | 6 | 8 | 12 | 16 | - | - | 6 | 6 | 6 | - | - | - | - | 6 | - | - | - | - | - |
| | 12 | - | 6 | 8 | 6 | 6 | - | - | - | 6 | 6 | - | - | - | - | - | - | - | - | - | - |
| | | #4 | #5 | #6 | #7 | #8 | #4 | #5 | #6 | #7 | #8 | #4 | #5 | #6 | #7 | #8 | #4 | #5 | #6 | #7 | #8 |

NOTES:

1. Reinforcement to be placed on interior face of concrete wall. Effective depth of vertical rebar (exterior face of concrete to center of vertical rebar) = 4.375"
2. Table 2A shall be read in conjunction with Fig 2A, and section "Notes for Tables 2A to 2D - LOGIX Below-grade Tables."
3. Steel yield strength = 40 ksi, 28 day concrete compressive strength = 3 ksi.

Good. Solid. Green.™

www.logixcf.com

6 – 10

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 2B - LOGIX 8" BELOW-GRADE WALL MINIMUM VERTICAL REINFORCEMENT

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| Maximum Height of Basement Wall, ft | Maximum Unbalanced Backfill Height, ft | Bar Spacing, in. | | | | | | | | | | | | | | | | | | | |
|-------------------------------------|--|----------------------------------|----|----|----|----|----------------------------------|----|----|----|----|----------------------------------|----|----|----|----|----------------------------------|----|----|----|----|
| | | Maximum Equivalent Density 30pcf | | | | | Maximum Equivalent Density 45pcf | | | | | Maximum Equivalent Density 60pcf | | | | | Maximum Equivalent Density 75pcf | | | | |
| 8 | 4-6 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| | 7 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 48 |
| | 8 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 24 | 40 | 48 | 48 | 48 | 16 | 24 | 40 | 48 | 48 |
| 9 | 4-6 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| | 7 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 40 | 48 | 48 | 48 | 48 | 24 | 32 | 48 | 48 | 48 |
| | 8 | 48 | 48 | 48 | 48 | 48 | 40 | 48 | 48 | 48 | 48 | 16 | 32 | 40 | 48 | 48 | 12 | 16 | 24 | 40 | 48 |
| | 9 | 48 | 48 | 48 | 48 | 48 | 24 | 32 | 48 | 48 | 48 | 12 | 16 | 24 | 40 | 48 | 8 | 12 | 16 | 24 | 32 |
| | 4-6 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| | 7 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 48 | 16 | 24 | 40 | 48 | 48 |
| | 8 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 48 | 16 | 24 | 32 | 48 | 48 | 8 | 16 | 24 | 32 | 40 |
| | 9 | 48 | 48 | 48 | 48 | 48 | 16 | 24 | 40 | 48 | 48 | 8 | 16 | 24 | 32 | 40 | 8 | 12 | 16 | 16 | 24 |
| | 10 | 24 | 40 | 48 | 48 | 48 | 12 | 16 | 24 | 32 | 48 | 8 | 12 | 16 | 16 | 24 | 6 | 8 | 12 | 16 | 16 |
| 11 | 4-5 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| | 6 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 48 |
| | 7 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 24 | 40 | 48 | 48 | 48 | 16 | 24 | 32 | 48 | 48 |
| | 8 | 48 | 48 | 48 | 48 | 48 | 24 | 32 | 48 | 48 | 48 | 12 | 16 | 24 | 40 | 48 | 8 | 12 | 16 | 24 | 32 |
| | 9 | 32 | 48 | 48 | 48 | 48 | 12 | 16 | 32 | 40 | 48 | 8 | 12 | 16 | 24 | 32 | 6 | 8 | 12 | 16 | 24 |
| | 10 | 16 | 32 | 40 | 48 | 48 | 8 | 16 | 16 | 24 | 32 | 6 | 8 | 12 | 16 | 24 | - | 6 | 8 | 12 | 16 |
| | 11 | 12 | 16 | 32 | 40 | 48 | 6 | 12 | 16 | 16 | 24 | - | 8 | 8 | 12 | 16 | - | 6 | 8 | 8 | 12 |
| 12 | 4-5 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| | 6 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 48 |
| | 7 | 48 | 48 | 48 | 48 | 48 | 40 | 48 | 48 | 48 | 48 | 16 | 32 | 40 | 48 | 48 | 12 | 16 | 24 | 40 | 48 |
| | 8 | 48 | 48 | 48 | 48 | 48 | 16 | 32 | 40 | 48 | 48 | 12 | 16 | 24 | 32 | 40 | 8 | 12 | 16 | 24 | 32 |
| | 9 | 24 | 40 | 48 | 48 | 48 | 12 | 16 | 24 | 32 | 40 | 8 | 12 | 16 | 24 | 24 | 6 | 8 | 12 | 16 | 16 |
| | 10 | 16 | 24 | 32 | 48 | 48 | 8 | 12 | 16 | 24 | 32 | - | 8 | 12 | 16 | 24 | - | 6 | 8 | 12 | 16 |
| | 11 | 12 | 16 | 24 | 32 | 40 | 6 | 8 | 12 | 16 | 24 | - | 6 | 8 | 12 | 16 | - | - | 6 | 8 | 12 |
| | 12 | 8 | 12 | 16 | 24 | 32 | - | 8 | 8 | 12 | 16 | - | - | 6 | 8 | 12 | - | - | - | 8 | 6 |
| 14 | 4-5 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| | 6 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 40 | 48 | 48 | 48 | 48 | 16 | 32 | 48 | 48 | 48 |
| | 7 | 48 | 48 | 48 | 48 | 48 | 24 | 40 | 48 | 48 | 48 | 16 | 24 | 32 | 48 | 48 | 8 | 16 | 24 | 32 | 40 |
| | 8 | 32 | 48 | 48 | 48 | 48 | 12 | 16 | 32 | 40 | 48 | 8 | 12 | 16 | 24 | 32 | 6 | 8 | 12 | 16 | 24 |
| | 9 | 16 | 24 | 40 | 48 | 48 | 8 | 12 | 16 | 24 | 32 | 6 | 8 | 12 | 16 | 24 | - | 6 | 8 | 12 | 16 |
| | 10 | 12 | 16 | 24 | 32 | 40 | 6 | 8 | 12 | 16 | 24 | - | 6 | 8 | 12 | 16 | - | - | 6 | 8 | 12 |
| | 11 | 8 | 12 | 16 | 24 | 32 | - | 6 | 8 | 12 | 16 | - | - | 6 | 8 | 12 | - | - | - | 6 | 6 |
| | 12 | 6 | 8 | 12 | 16 | 24 | - | 6 | 8 | 8 | 12 | - | - | - | 8 | 6 | - | - | - | 6 | 6 |
| | 13 | - | 8 | 8 | 12 | 16 | - | - | 6 | 8 | 12 | - | - | - | 6 | 6 | - | - | - | - | 6 |
| | 14 | - | 6 | 8 | 12 | 16 | - | - | - | 6 | 6 | - | - | - | - | 6 | - | - | - | - | - |
| 16 | 4-5 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| | 6 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 24 | 40 | 48 | 48 | 48 | 16 | 24 | 32 | 48 | 48 |
| | 7 | 48 | 48 | 48 | 48 | 48 | 16 | 24 | 40 | 48 | 48 | 12 | 16 | 24 | 32 | 40 | 8 | 12 | 16 | 24 | 32 |
| | 8 | 24 | 32 | 48 | 48 | 48 | 8 | 16 | 24 | 32 | 40 | 6 | 8 | 16 | 16 | 24 | - | 8 | 12 | 16 | 16 |
| | 9 | 12 | 16 | 24 | 32 | 48 | 6 | 8 | 16 | 16 | 24 | - | 6 | 8 | 12 | 16 | - | - | 8 | 8 | 12 |
| | 10 | 8 | 12 | 16 | 24 | 32 | - | 8 | 8 | 12 | 16 | - | - | 6 | 8 | 12 | - | - | 6 | 8 | 6 |
| | 11 | 6 | 8 | 12 | 16 | 24 | - | 6 | 8 | 8 | 12 | - | - | 6 | 8 | 6 | - | - | - | 6 | 6 |
| | 12 | - | 6 | 8 | 12 | 16 | - | - | 6 | 8 | 6 | - | - | - | 6 | 6 | - | - | - | - | 6 |
| | 13 | - | 6 | 8 | 8 | 12 | - | - | - | 6 | 6 | - | - | - | - | 6 | - | - | - | - | - |
| | 14 | - | - | 6 | 8 | 12 | - | - | - | 6 | 6 | - | - | - | - | - | - | - | - | - | - |
| | 15 | - | - | 6 | 8 | 6 | - | - | - | - | 6 | - | - | - | - | - | - | - | - | - | - |
| | 16 | - | - | - | 6 | 6 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

- NOTES:**
- Reinforcement to be placed on interior face of concrete wall. Effective depth of vertical rebar (exterior face of concrete to center of vertical rebar) = 6"
 - Table 2B shall be read in conjunction with Fig 2B, and section "Notes for Tables 2A to 2D - LOGIX Below-grade Tables."
 - Steel yield strength = 40 ksi, 28 day concrete compressive strength = 3 ksi.

6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 2C - LOGIX 10" BELOW-GRADE WALL MINIMUM VERTICAL REINFORCEMENT

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| Maximum Height of Basement Wall, ft | Maximum Unbalanced Backfill Height, ft | Bar Spacing, in. | | | | | | | | | | | | | | | | | | | |
|-------------------------------------|--|----------------------------------|----|----|----|----|----------------------------------|----|----|----|----|----------------------------------|----|----|----|----|----------------------------------|----|----|----|--|
| | | Maximum Equivalent Density 30pcf | | | | | Maximum Equivalent Density 45pcf | | | | | Maximum Equivalent Density 60pcf | | | | | Maximum Equivalent Density 75pcf | | | | |
| 8 | 4-8 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | |
| 9 | 4-7 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | |
| | 8 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | |
| | 9 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 48 | 16 | 24 | 40 | 48 | |
| 10 | 4-7 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | |
| | 8 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 24 | 32 | 48 | 48 | |
| | 9 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 24 | 32 | 48 | 48 | 48 | 12 | 16 | 32 | 40 | 48 | |
| | 10 | 48 | 48 | 48 | 48 | 48 | 24 | 40 | 48 | 48 | 48 | 12 | 24 | 32 | 40 | 48 | 8 | 16 | 16 | 32 | |
| 11 | 4-7 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | |
| | 8 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 48 | 16 | 32 | 40 | 48 | 48 | |
| | 9 | 48 | 48 | 48 | 48 | 48 | 40 | 48 | 48 | 48 | 16 | 24 | 40 | 48 | 48 | 12 | 16 | 24 | 32 | 48 | |
| | 10 | 48 | 48 | 48 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 16 | 24 | 32 | 48 | 8 | 12 | 16 | 24 | 32 | |
| | 11 | 40 | 48 | 48 | 48 | 48 | 12 | 24 | 32 | 40 | 48 | 8 | 12 | 16 | 24 | 32 | 6 | 8 | 12 | 16 | |
| 12 | 4-6 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | |
| | 7 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 40 | 48 | 48 | 48 | 48 | |
| | 8 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 48 | 16 | 24 | 40 | 48 | 48 | |
| | 9 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 16 | 24 | 32 | 48 | 48 | 8 | 16 | 24 | 32 | 40 | |
| | 10 | 48 | 48 | 48 | 48 | 48 | 16 | 24 | 40 | 48 | 8 | 16 | 24 | 32 | 40 | 8 | 12 | 16 | 16 | 24 | |
| | 11 | 24 | 40 | 48 | 48 | 48 | 12 | 16 | 24 | 32 | 48 | 8 | 12 | 16 | 24 | 32 | 6 | 8 | 12 | 16 | |
| | 12 | 16 | 32 | 40 | 48 | 48 | 8 | 12 | 16 | 24 | 32 | 6 | 8 | 12 | 16 | 24 | - | 6 | 8 | 12 | |
| 14 | 4-6 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | |
| | 7 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 48 | |
| | 8 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 24 | 32 | 48 | 48 | 48 | 12 | 16 | 32 | 40 | 48 | |
| | 9 | 48 | 48 | 48 | 48 | 48 | 24 | 32 | 48 | 48 | 12 | 16 | 24 | 40 | 48 | 8 | 12 | 16 | 24 | 32 | |
| | 10 | 32 | 48 | 48 | 48 | 48 | 12 | 16 | 32 | 40 | 8 | 12 | 16 | 24 | 32 | 6 | 8 | 12 | 16 | 24 | |
| | 11 | 16 | 32 | 40 | 48 | 48 | 8 | 16 | 16 | 24 | 32 | 6 | 8 | 12 | 16 | 24 | - | 6 | 8 | 12 | |
| | 12 | 12 | 16 | 32 | 40 | 48 | 6 | 12 | 16 | 16 | 24 | - | 8 | 8 | 12 | 16 | - | - | 8 | 8 | |
| | 13 | 8 | 16 | 24 | 32 | 40 | 6 | 8 | 12 | 16 | 16 | - | 6 | 8 | 12 | 16 | - | - | 6 | 8 | |
| | 14 | 8 | 12 | 16 | 24 | 32 | - | 6 | 8 | 12 | 16 | - | - | 6 | 8 | 12 | - | - | - | 6 | |
| 16 | 4-6 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | |
| | 7 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 24 | 40 | 48 | 48 | 48 | |
| | 8 | 48 | 48 | 48 | 48 | 48 | 40 | 48 | 48 | 48 | 16 | 24 | 40 | 48 | 48 | 12 | 16 | 24 | 32 | 48 | |
| | 9 | 48 | 48 | 48 | 48 | 48 | 16 | 24 | 40 | 48 | 8 | 16 | 24 | 32 | 40 | 8 | 12 | 16 | 24 | 24 | |
| | 10 | 24 | 40 | 48 | 48 | 48 | 12 | 16 | 24 | 32 | 6 | 12 | 16 | 16 | 24 | - | 8 | 12 | 16 | 16 | |
| | 11 | 16 | 24 | 32 | 48 | 48 | 8 | 12 | 16 | 24 | 32 | - | 8 | 12 | 16 | 16 | - | 6 | 8 | 12 | |
| | 12 | 12 | 16 | 24 | 32 | 40 | 6 | 8 | 12 | 16 | 24 | - | 6 | 8 | 12 | 16 | - | - | 6 | 8 | |
| | 13 | 8 | 12 | 16 | 24 | 32 | - | 6 | 8 | 12 | 16 | - | - | 6 | 8 | 12 | - | - | - | 6 | |
| | 14 | 6 | 8 | 12 | 16 | 24 | - | 6 | 8 | 12 | 12 | - | - | 6 | 8 | 8 | - | - | - | 6 | |
| | 15 | - | 8 | 12 | 16 | 16 | - | - | 6 | 8 | 12 | - | - | - | 6 | 8 | - | - | - | 6 | |
| | 16 | - | 6 | 8 | 12 | 16 | - | - | 6 | 8 | 8 | - | - | - | - | 6 | - | - | - | - | |

NOTES:
See next page.

6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 2C - LOGIX 10" BELOW-GRADE WALL MINIMUM VERTICAL REINFORCEMENT Cont'd

| Maximum Height of Basement Wall, ft | Maximum Unbalanced Backfill Height, ft | Bar Spacing, in. | | | | | | | | | | | | | | | | | | | |
|-------------------------------------|--|----------------------------------|----|----|----|----|----------------------------------|----|----|----|----|----------------------------------|----|----|----|----|----------------------------------|----|----|----|----|
| | | Maximum Equivalent Density 30pcf | | | | | Maximum Equivalent Density 45pcf | | | | | Maximum Equivalent Density 60pcf | | | | | Maximum Equivalent Density 75pcf | | | | |
| 18 | 4-6 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| | 7 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 40 | 48 | 48 | 48 | 48 | 16 | 32 | 48 | 48 | 48 |
| | 8 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 48 | 16 | 24 | 32 | 48 | 48 | 8 | 16 | 24 | 32 | 40 |
| | 9 | 40 | 48 | 48 | 48 | 48 | 16 | 24 | 32 | 48 | 48 | 8 | 12 | 16 | 24 | 32 | 6 | 8 | 12 | 16 | 24 |
| | 10 | 16 | 32 | 48 | 48 | 48 | 8 | 16 | 16 | 24 | 40 | 6 | 8 | 12 | 16 | 24 | - | 6 | 8 | 12 | 16 |
| | 11 | 12 | 16 | 24 | 40 | 48 | 6 | 8 | 16 | 16 | 24 | - | 6 | 8 | 12 | 16 | - | - | 8 | 8 | 12 |
| | 12 | 8 | 12 | 16 | 24 | 32 | - | 8 | 12 | 16 | 16 | - | - | 8 | 8 | 12 | - | - | 6 | 8 | 8 |
| | 13 | 6 | 8 | 16 | 16 | 24 | - | 6 | 8 | 12 | 16 | - | - | 6 | 8 | 8 | - | - | - | 6 | 8 |
| | 14 | - | 8 | 12 | 16 | 16 | - | - | 6 | 8 | 12 | - | - | - | 6 | 8 | - | - | - | - | 6 |
| | 15 | - | 6 | 8 | 12 | 16 | - | - | 6 | 8 | 8 | - | - | - | - | 6 | - | - | - | - | - |
| | 16 | - | 6 | 8 | 8 | 12 | - | - | - | 6 | 8 | - | - | - | - | 6 | - | - | - | - | - |
| | 17 | - | - | 6 | 8 | 12 | - | - | - | 6 | 6 | - | - | - | - | - | - | - | - | - | - |
| 18 | - | - | 6 | 8 | 8 | - | - | - | - | 6 | - | - | - | - | - | - | - | - | - | - | |
| 20 | 4-6 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| | 7 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 48 | 16 | 24 | 40 | 48 | 48 |
| | 8 | 48 | 48 | 48 | 48 | 48 | 24 | 40 | 48 | 48 | 48 | 12 | 16 | 32 | 40 | 48 | 8 | 12 | 16 | 24 | 32 |
| | 9 | 32 | 48 | 48 | 48 | 48 | 12 | 16 | 24 | 40 | 48 | 8 | 12 | 16 | 24 | 32 | 6 | 8 | 12 | 16 | 24 |
| | 10 | 16 | 24 | 40 | 48 | 48 | 8 | 12 | 16 | 24 | 32 | 6 | 8 | 12 | 16 | 16 | - | 6 | 8 | 12 | 16 |
| | 11 | 12 | 16 | 24 | 32 | 40 | 6 | 8 | 12 | 16 | 24 | - | 6 | 8 | 12 | 16 | - | - | 6 | 8 | 12 |
| | 12 | 8 | 12 | 16 | 24 | 32 | - | 6 | 8 | 12 | 16 | - | - | 6 | 8 | 12 | - | - | - | 6 | 8 |
| | 13 | 6 | 8 | 12 | 16 | 24 | - | - | 8 | 8 | 12 | - | - | - | 6 | 8 | - | - | - | - | 6 |
| | 14 | - | 6 | 8 | 12 | 16 | - | - | 6 | 8 | 8 | - | - | - | 6 | 6 | - | - | - | - | 6 |
| | 15 | - | 6 | 8 | 12 | 12 | - | - | - | 6 | 8 | - | - | - | - | 6 | - | - | - | - | - |
| | 16 | - | - | 6 | 8 | 12 | - | - | - | 6 | 6 | - | - | - | - | - | - | - | - | - | - |
| | 17 | - | - | 6 | 8 | 8 | - | - | - | - | 6 | - | - | - | - | - | - | - | - | - | - |
| | 18 | - | - | - | 6 | 8 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| | 19 | - | - | - | 6 | 6 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| | 20 | - | - | - | - | 6 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| | | #4 | #5 | #6 | #7 | #8 | #4 | #5 | #6 | #7 | #8 | #4 | #5 | #6 | #7 | #8 | #4 | #5 | #6 | #7 | #8 |

NOTES:

1. Reinforcement to be placed on interior face of concrete wall. Effective depth of vertical rebar (exterior face of concrete to center of vertical rebar = 8"
2. Table 2C shall be read in conjunction with Fig 2C, and section "Notes for Tables 2A to 2D - LOGIX Below-grade Tables."
3. Steel yield strength = 40 ksi, 28 day concrete compressive strength = 3 ksi.

ENGINEERING

ENGINEERING

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

NOTES:

- Rev. Sep 23/09

ABOVE-GRADE WALL REINFORCEMENT TABLES

NOTES FOR ABOVE-GRADE WALL TABLES - Tables 3A & 3B

Table 3A covers reinforcement for LOGIX above-grade walls with wind speeds up to 150mph. For larger wind speeds see Table 3B, which covers wind speeds up to 300mph.

LOGIX above-grade tables cover three different construction types:

- One storey LOGIX supporting wood roof frame (Fig. 3A)
- One storey LOGIX supporting 2nd storey wood frame plus wood roof frame (Fig. 3B)
- Two storey LOGIX supporting wood roof frame (Fig. 3C)

For two story buildings, the height of the second story wall is equal to the height of the first story provided the height of the first storey wall is not more than 12 feet high.

For first story walls greater than 12 feet high, the second story wall height is a maximum of 12 feet.

With the exception of 4" LOGIX, the second story concrete wall thickness is one size less than the concrete core thickness used for the first storey wall.




Fig 3A
Assumed typical flooring, wall & roof section for Tables 3A and 3B, LOGIX Supporting Roof Only.




Fig 3B
Assumed typical flooring, wall & roof section for Tables 3A and 3B, LOGIX Supporting 2nd Story Wood Frame & Roof Structure.




Fig 3C
Assumed typical flooring, wall & roof section for Tables 3A and 3B, LOGIX Supporting 2nd Story LOGIX & Roof Structure.

6.1 – U.S. ENGINEERING ANALYSIS REPORT

NOTES FOR ABOVE-GRADE WALL TABLES Cont'd

The above-grade tables shall be used in conjunction with the notes listed below, the building limitations noted in the "Reinforcement Tables" section, and Figures 3A to 3B, which form the basis of this table.

1. Vertical rebar spacing shown in the tables provide simple placement between ICF ties.
2. Steel yield strength = 40 ksi and 60 ksi for Table 3A and 3B, respectively. 28 day concrete compressive strength = 3 ksi
3. For rebar spacing is based on 40 ksi reinforcing steel multiply bar spacing by 1.5 if using 60 ksi steel.
4. Deflection criteria = $L/240$
5. Snow load = 70 psf
6. Assumed eccentricity = 1".
7. The walls must be supported at the top and bottom of the wall.
8. Where spaces have been left blank, the corresponding bar size is presumed to be less economical and/or practical than that shown. Consult a local licensed engineer to determine proper design.
9. Except as noted for seismic considerations, vertical rebar shall be placed in middle of wall, and minimum horizontal rebar shall be:
 - 4" & 6.25" LOGIX = #4 @ 32" on center
 - 8" & 10" LOGIX = #4 @ 16" on center

Provide additional mat of rebar for 12" LOGIX

- Horizontal rebar = #4 @ 32" on center (double mat)

- Vertical rebar = to match vertical bar spacing in **Table 3A or 3B**, whichever applies.

Provide at least one #4 bar (two for 12" LOGIX) to be placed at the bottom course and top course.

10. In Seismic Design Categories D0, D1, and D2, the reinforcing steel shall meet the requirements of ASTM A 706 for low-alloy steel with a minimum yield strength of 60 ksi.
11. For townhouses in Seismic Category C, the minimum vertical reinforcement shall be one #5 at 24 inches on center or one #4 bar at 16 inches on center, and the minimum horizontal reinforcement shall be one #4 bar at 16 inches on center.
12. For all buildings in Seismic Design Categories D0, D1 and D2, the minimum vertical reinforcement shall be one #5 at 18 inches on center or one #4 bar at 12 inches on center, and the minimum horizontal reinforcement shall be one #5 bar at 16 inches on center.
13. Horizontal reinforcement shall be continuous around building corners using corner bars or by bending the bars. The minimum lap splice shall be 24 inches. For townhouses in Seismic Design Categories D0, D1, and D2, each end of all horizontal reinforcement shall terminate with a standard hook or lap splice.
14. For openings provide one #4 horizontal bar within 12 inches from the bottom of the opening to extend minimum 24 inches beyond opening. In locations with wind speeds greater than or equal to 110mph or in Seismic Design Categories A and B, provide one #4 bar for the full height of the wall story within 12 inches each side of the opening. In locations with wind speeds greater than 110 mph, townhouses in Seismic Design Categories D0, D1, and D2, provide two #4 bars or one #5 bar for full height of the wall story within 12 inches of each side of the opening.
15. Where design wind pressure exceeds 40 psf or for townhouses in Seismic Design Category C, and all buildings in Seismic Design Categories D0, D1 and D2, the vertical wall reinforcement in the top-most ICF story shall terminate with a 90-degree standard hook in accordance with IRC 2006, Section R611.7.1.5. The free end of the hook shall be within 4 inches of the top of the wall and shall be oriented parallel to the horizontal steel in the top of the wall.

E
N
G
I
N
E
E
R
I
N
G

6.1 – U.S. ENGINEERING ANALYSIS REPORT

16. Carefully consider floor/wall connection details for lateral loads, especially with higher backfills, walkout basements, and active seismic areas.
17. Tables R301.2.1.3 and R611.3(1) are taken from the 2006 International Residential Code. These tables can be used to convert wind speeds to wind loads used in Table 3A, Logix Above-Grade Wall Minimum Vertical Reinforcement.
18. For larger wind speeds greater than 150mph see Table 3B.

**TABLE R301.2.1.3
EQUIVALENT BASIC WIND SPEEDS^a**

| | | | | | | | | | | | | | |
|-------------------------|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 3-second gust, V_{3s} | 85 | 90 | 100 | 105 | 110 | 120 | 125 | 130 | 140 | 145 | 150 | 160 | 170 |
| Fastest mile, V_{fm} | 71 | 76 | 85 | 90 | 95 | 104 | 109 | 114 | 123 | 128 | 133 | 142 | 152 |

For SI: 1 mile per hour = 0.447 m/s.

a. Linear interpolation is permitted.

**TABLE R611.3(1)
DESIGN WIND PRESSURE FOR USE WITH TABLES R611.3(2), R611.4(1), AND R611.5 FOR ABOVE GRADE WALLS^a**

| WIND SPEED (mph) ^e | DESIGN WIND PRESSURE (psf) | | | | | |
|----------------------------------|----------------------------|----|-----------------|---------------------------------|-----------------|------------------|
| | Enclosed ^b | | | Partially Enclosed ^b | | |
| | Exposure ^c | | | Exposure ^c | | |
| | B | C | D | B | C | D |
| 85 | 18 | 24 | 29 | 23 | 31 | 37 |
| 90 | 20 | 27 | 32 | 25 | 35 | 41 |
| 100 | 24 | 34 | 39 | 31 | 43 | 51 |
| 110 | 29 | 41 | 48 | 38 | 52 | 61 |
| 120 | 35 | 48 | 57 | 45 | 62 | 73 |
| 130 | 41 | 56 | 66 | 53 | 73 | 85 ^d |
| 140 | 47 | 65 | 77 | 61 | 84 ^d | 99 ^d |
| 150 | 54 | 75 | 88 ^d | 70 | 96 ^d | 114 ^d |

For SI: 1 pound per square foot = 0.0479 kPa; 1 mile per hour = 0.447 m/s; 1 foot = 304.8 mm; 1 square foot = 0.0929 m².

a. This table is based on ASCE 7-98 components and cladding wind pressures using a mean roof height of 35 ft and a tributary area of 10 ft².

b. Buildings in wind-borne debris regions as defined in Section R202 shall be considered as "Partially Enclosed" unless glazed openings are protected in accordance with Section R301.2.1.2, in which case the building shall be considered as "Enclosed." All other buildings shall be classified as "Enclosed."

c. Exposure Categories shall be determined in accordance with Section R301.2.1.4.

d. For wind pressures greater than 80 psf, design is required in accordance with ACI 318 and approved manufacturer guidelines.

e. Interpolation is permitted between wind speeds.

ENGINEERING

6.1 – U.S. ENGINEERING ANALYSIS REPORT

**TABLE 3A - LOGIX ABOVE-GRADE WALL MINIMUM VERTICAL REINFORCEMENT
(WIND SPEEDS UP TO 150 MPH)**

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

LOGIX ABOVE-GRADE WALLS - VERTICAL REINFORCEMENT SPACING, in.

| Ground Floor LOGIX Supporting Roof Only | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---------------------------|----|----|----|----|-----|----------------------------|----|----|----|----|-----|---------------------------|----|----|----|----|-----|---------------------------|----|----|----|----|-----|---------------------------|----|----|----|----|-----|----|----|----|----|----|-----|----|----|----|----|
| Wall Height, ft | 4" LOGIX Wall Thickness | | | | | | 6.25" LOGIX Wall Thickness | | | | | | 8" LOGIX Wall Thickness | | | | | | 10" LOGIX Wall Thickness | | | | | | 12" LOGIX Wall Thickness | | | | | | | | | | | | | | | |
| | Unfactored Wind Load, psf | | | | | | Unfactored Wind Load, psf | | | | | | Unfactored Wind Load, psf | | | | | | Unfactored Wind Load, psf | | | | | | Unfactored Wind Load, psf | | | | | | | | | | | | | | | |
| | 20 | 40 | 60 | 80 | 90 | 114 | 20 | 40 | 60 | 80 | 90 | 114 | 20 | 40 | 60 | 80 | 90 | 114 | 20 | 40 | 60 | 80 | 90 | 114 | 20 | 40 | 60 | 80 | 90 | 114 | 20 | 40 | 60 | 80 | 90 | 114 | | | | |
| 8 | 48 | 48 | 32 | 16 | 12 | 8 | 48 | 48 | 48 | 48 | 40 | 24 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | | |
| 9 | 48 | 40 | 16 | 12 | 8 | 6 | 48 | 48 | 48 | 32 | 24 | 16 | 48 | 48 | 48 | 48 | 48 | 24 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | |
| 10 | 48 | 24 | 12 | 8 | 6 | - | 48 | 48 | 40 | 24 | 16 | 12 | 48 | 48 | 48 | 40 | 32 | 16 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | |
| 12 | 32 | 12 | 6 | - | - | - | 48 | 48 | 16 | 12 | 8 | 6 | 48 | 48 | 40 | 16 | 16 | 8 | 48 | 48 | 48 | 32 | 24 | 16 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | |
| 14 | 12 | 6 | - | - | - | - | 40 | 24 | 12 | 6 | 6 | - | 48 | 48 | 16 | 12 | 8 | 6 | 48 | 48 | 32 | 16 | 16 | 8 | 48 | 48 | 48 | 32 | 16 | 16 | 8 | 48 | 48 | 48 | 32 | 32 | 24 | 24 | 24 | 24 |
| 16 | 6 | - | - | - | - | - | 16 | 12 | 8 | - | - | - | 24 | 24 | 12 | 8 | 6 | - | 40 | 40 | 16 | 12 | 8 | 6 | 48 | 48 | 32 | 16 | 12 | 8 | 6 | 48 | 48 | 32 | 16 | 16 | 12 | 12 | 12 | |
| 18 | - | - | - | - | - | - | 12 | 8 | - | - | - | - | 12 | 12 | 8 | 6 | - | - | 16 | 16 | 12 | 8 | 6 | - | 24 | 24 | 16 | 12 | 8 | 6 | - | 24 | 24 | 16 | 12 | 12 | 8 | 8 | 8 | |
| 20 | - | - | - | - | - | - | 6 | 6 | - | - | - | - | 8 | 8 | 6 | - | - | - | 12 | 12 | 8 | 6 | - | - | 12 | 12 | 12 | 8 | 6 | - | - | 12 | 12 | 12 | 8 | 8 | 6 | 6 | 6 | |

| Ground Floor LOGIX Supporting 2nd Storey Wood Frame & Roof Structure | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---------------------------|----|----|----|----|-----|----------------------------|----|----|----|----|-----|---------------------------|----|----|----|----|-----|---------------------------|----|----|----|----|-----|---------------------------|----|----|----|----|-----|----|----|----|----|----|----|----|----|----|
| Wall Height, ft | 4" LOGIX Wall Thickness | | | | | | 6.25" LOGIX Wall Thickness | | | | | | 8" LOGIX Wall Thickness | | | | | | 10" LOGIX Wall Thickness | | | | | | 12" LOGIX Wall Thickness | | | | | | | | | | | | | | |
| | Unfactored Wind Load, psf | | | | | | Unfactored Wind Load, psf | | | | | | Unfactored Wind Load, psf | | | | | | Unfactored Wind Load, psf | | | | | | Unfactored Wind Load, psf | | | | | | | | | | | | | | |
| | 20 | 40 | 60 | 80 | 90 | 114 | 20 | 40 | 60 | 80 | 90 | 114 | 20 | 40 | 60 | 80 | 90 | 114 | 20 | 40 | 60 | 80 | 90 | 114 | 20 | 40 | 60 | 80 | 90 | 114 | | | | | | | | | |
| 8 | 48 | 48 | 32 | 16 | 12 | 8 | 48 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | | | |
| 9 | 48 | 48 | 16 | 12 | 8 | 6 | 48 | 48 | 48 | 48 | 32 | 16 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | | |
| 10 | 32 | 24 | 12 | 8 | 6 | - | 48 | 48 | 48 | 24 | 16 | 12 | 48 | 48 | 48 | 48 | 48 | 24 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | |
| 12 | 12 | 8 | 6 | - | - | - | 48 | 48 | 24 | 12 | 8 | 8 | 48 | 48 | 48 | 24 | 16 | 12 | 48 | 48 | 48 | 48 | 40 | 24 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| 14 | 6 | - | - | - | - | - | 24 | 24 | 12 | 8 | 6 | - | 48 | 48 | 24 | 12 | 12 | 8 | 48 | 48 | 48 | 24 | 16 | 12 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| 16 | - | - | - | - | - | - | 12 | 12 | 8 | - | - | - | 16 | 16 | 12 | 8 | 6 | - | 32 | 32 | 24 | 12 | 12 | 8 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| 18 | - | - | - | - | - | - | 8 | 8 | - | - | - | - | 12 | 12 | 8 | 6 | - | - | 16 | 16 | 16 | 8 | 8 | - | 16 | 16 | 16 | 16 | 12 | 12 | 8 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| 20 | - | - | - | - | - | - | - | - | - | - | - | - | 6 | 6 | 6 | - | - | - | 8 | 8 | 8 | 6 | 6 | - | 12 | 12 | 12 | 12 | 8 | 8 | 6 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |

| Ground Floor LOGIX Supporting 2nd Storey LOGIX & Roof Structure | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---------------------------|----|----|----|----|-----|----------------------------|----|----|----|----|-----|---------------------------|----|----|----|----|-----|---------------------------|----|----|----|----|-----|---------------------------|----|----|----|----|-----|----|----|----|----|----|----|----|
| Wall Height, ft | 4" LOGIX Wall Thickness | | | | | | 6.25" LOGIX Wall Thickness | | | | | | 8" LOGIX Wall Thickness | | | | | | 10" LOGIX Wall Thickness | | | | | | 12" LOGIX Wall Thickness | | | | | | | | | | | | |
| | Unfactored Wind Load, psf | | | | | | Unfactored Wind Load, psf | | | | | | Unfactored Wind Load, psf | | | | | | Unfactored Wind Load, psf | | | | | | Unfactored Wind Load, psf | | | | | | | | | | | | |
| | 20 | 40 | 60 | 80 | 90 | 114 | 20 | 40 | 60 | 80 | 90 | 114 | 20 | 40 | 60 | 80 | 90 | 114 | 20 | 40 | 60 | 80 | 90 | 114 | 20 | 40 | 60 | 80 | 90 | 114 | | | | | | | |
| 8 | 48 | 48 | 32 | 16 | 12 | 8 | 48 | 48 | 48 | 48 | 48 | 40 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | | |
| 9 | 48 | 48 | 16 | 12 | 8 | 6 | 48 | 48 | 48 | 48 | 48 | 24 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | |
| 10 | 24 | 24 | 12 | 6 | 6 | - | 48 | 48 | 48 | 32 | 24 | 16 | 48 | 48 | 48 | 48 | 48 | 40 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| 12 | 8 | 8 | - | - | - | - | 40 | 40 | 32 | 16 | 12 | 8 | 48 | 48 | 48 | 40 | 24 | 12 | 48 | 48 | 48 | 48 | 48 | 40 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| 14 | - | - | - | - | - | - | 16 | 16 | 12 | 8 | 6 | - | 32 | 32 | 32 | 16 | 12 | 8 | 48 | 48 | 48 | 48 | 32 | 16 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 32 | 48 |
| 16 | - | - | - | - | - | - | 8 | 8 | 8 | - | - | - | 12 | 12 | 12 | 8 | 8 | - | 16 | 16 | 16 | 16 | 12 | 8 | 32 | 32 | 32 | 32 | 32 | 24 | 12 | 48 | 48 | 48 | 48 | 48 | 48 |
| 18 | - | - | - | - | - | - | - | - | - | - | - | - | 8 | 8 | 8 | 6 | - | - | 8 | 8 | 8 | 8 | 8 | 6 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 8 | 48 | |
| 20 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | 6 | 6 | 6 | 6 | 6 | - | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 6 | 48 | | |

6.1 – U.S. ENGINEERING ANALYSIS REPORT

**TABLE 3B - LOGIX ABOVE-GRADE WALL MINIMUM VERTICAL REINFORCEMENT
(WIND SPEEDS GREATER THAN 150 MPH)**

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

LOGIX ABOVE-GRADE WALLS - VERTICAL REINFORCEMENT SPACING, in.

| Ground Floor LOGIX Supporting Roof Only | | | | | | | | | | | | | | | | | | | | |
|---|-------------------------|-----|-----|-----|----------------------------|-----|-----|-----|-------------------------|-----|-----|-----|--------------------------|-----|-----|-----|--------------------------|-----|-----|-----|
| Wall Height, ft | 4" LOGIX Wall Thickness | | | | 6.25" LOGIX Wall Thickness | | | | 8" LOGIX Wall Thickness | | | | 10" LOGIX Wall Thickness | | | | 12" LOGIX Wall Thickness | | | |
| | Wind Speed, mph | | | | Wind Speed, mph | | | | Wind Speed, mph | | | | Wind Speed, mph | | | | Wind Speed, mph | | | |
| | 200 | 250 | 275 | 300 | 200 | 250 | 275 | 300 | 200 | 250 | 275 | 300 | 200 | 250 | 275 | 300 | 200 | 250 | 275 | 300 |
| 8 | 12 | 6 | - | - | 24 | 12 | 8 | 8 | 32 | 16 | 12 | 12 | 48 | 24 | 16 | 16 | 48 | 32 | 24 | 16 |
| 9 | 8 | - | - | - | 16 | 8 | 8 | 6 | 24 | 12 | 8 | 8 | 32 | 16 | 12 | 12 | 48 | 24 | 16 | 12 |
| 10 | 6 | - | - | - | 12 | 6 | 6 | - | 16 | 8 | 8 | 6 | 24 | 12 | 8 | 8 | 32 | 16 | 12 | 12 |
| 12 | - | - | - | - | 8 | - | - | - | 8 | 6 | - | - | 16 | 8 | 6 | - | 16 | 8 | 8 | 6 |
| 14 | - | - | - | - | - | - | - | - | 6 | - | - | - | 8 | 6 | - | - | 12 | 6 | 6 | - |
| 16 | - | - | - | - | - | - | - | - | - | - | - | - | 6 | - | - | - | 8 | - | - | - |
| 18 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | 6 | - | - | - |
| 20 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

| Ground Floor LOGIX Supporting 2nd Storey LOGIX (or 2nd Storey Wood Frame) & Roof Structure | | | | | | | | | | | | | | | | | | | | |
|--|-------------------------|-----|-----|-----|----------------------------|-----|-----|-----|-------------------------|-----|-----|-----|--------------------------|-----|-----|-----|--------------------------|-----|-----|-----|
| Wall Height, ft | 4" LOGIX Wall Thickness | | | | 6.25" LOGIX Wall Thickness | | | | 8" LOGIX Wall Thickness | | | | 10" LOGIX Wall Thickness | | | | 12" LOGIX Wall Thickness | | | |
| | Wind Speed, mph | | | | Wind Speed, mph | | | | Wind Speed, mph | | | | Wind Speed, mph | | | | Wind Speed, mph | | | |
| | 200 | 250 | 275 | 300 | 200 | 250 | 275 | 300 | 200 | 250 | 275 | 300 | 200 | 250 | 275 | 300 | 200 | 250 | 275 | 300 |
| 8 | 6 | - | - | - | 24 | 12 | 8 | 8 | 48 | 16 | 12 | 12 | 48 | 32 | 24 | 16 | 48 | 32 | 24 | 16 |
| 9 | 6 | - | - | - | 16 | 8 | 6 | - | 24 | 12 | 8 | 8 | 48 | 16 | 16 | 12 | 48 | 24 | 16 | 12 |
| 10 | - | - | - | - | 12 | 6 | - | - | 16 | 8 | 8 | 6 | 32 | 16 | 12 | 8 | 48 | 16 | 12 | 12 |
| 12 | - | - | - | - | 6 | - | - | - | 8 | 6 | - | - | 16 | 8 | 6 | - | 24 | 8 | 8 | 6 |
| 14 | - | - | - | - | - | - | - | - | 6 | - | - | - | 8 | - | - | - | 16 | 8 | 6 | - |
| 16 | - | - | - | - | - | - | - | - | - | - | - | - | 6 | - | - | - | 8 | - | - | - |
| 18 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | 6 | - | - | - |
| 20 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

NOTES:

1. Table 3B must be used in conjunction with the notes listed under "Notes For Above-Grade Wall Tables".
2. Vertical bar spacing is for #4 rebar. #5 rebar can be substituted provided the spacing is multiplied by 1.5. Spacing shall be no more than 48 inches on center.
3. Closer spacing of vertical and horizontal rebar (at least 12" on center, each way) provides better resistance from impact due to wind borne debris.
4. Steel yield strength = 60 ksi, 28 day concrete compressive strength = 3 ksi.

ENGINEERING

6.1 – U.S. ENGINEERING ANALYSIS REPORT

LINTEL REINFORCEMENT TABLES




Fig 4
Lintel reinforcement

The lintel tables cover a wide range of uniform and concentrated load conditions, and span lengths. The depth of the lintels range from 8 inch to 30 inches. Uniform and concentrated loading are considered to be concentric and centered on the lintel. Uniform loads act along the entire lintel span, such as from roof trusses at 2 ft spacing. Concentrated load lintel tables consider only a single concentrated load acting anywhere along the lintel span. In addition, the lintel tables do not consider uniform and concentrated loads to act simultaneously on the lintel.

The following notes are common to both uniform and concentrated load lintel tables:

1. 28 day concrete compressive strength = 3 ksi. Steel yield strength = 40 ksi.
2. Stirrups are D9.5 wire or #3 bars, bent as shown, and conforming to ACI 318.
3. Shaded areas of the lintel tables require reinforcement, except for length Z.
4. Dimension D is to the concrete surface, not counting bucks or top plate.
5. Bottom steel must extend a min. 2 ft beyond opening, and no splices are permitted.
6. Deflection is limited to $L/360$, not considering long term effects. Long term deflection could be twice the short term depending on the nature of the load.
7. Seismic and wind loads are not considered.
8. Shear planes are not interrupted by embedded joists.
9. Top of lintel is assumed to be laterally restrained.

These tables should only be used if the above conditions are met. For other conditions, consult a structural engineer.

6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 4A - LOGIX 4" LINTEL REINFORCEMENT WITH UNIFORM LOAD

Based on 40 ksi reinforcing steel. Lintels tables for 60 ksi reinforcing steel are available for download at www.logixcf.com.

Where not shown otherwise, bottom steel is 1-#5

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | 1 - #6 |
| 5 | | | | 1 - #6 | - | - |
| 6 | | | 1 - #6 | - | - | - |
| 7 | | 1 - #6 | - | - | - | - |
| 8 | | - | - | - | - | - |
| 9 | 1 - #6 | - | - | - | - | - |
| 10 | - | - | - | - | - | - |
| 12 | - | - | - | - | - | - |
| 14 | - | - | - | - | - | - |
| 16 | - | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | 49 | 25 | 17 | 13 | 10 | 8 |

| s=4", D=10" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | 1 - #6 |
| 6 | | | | 1 - #6 | - | - |
| 7 | | | 1 - #6 | - | - | - |
| 8 | | 1 - #6 | - | - | - | - |
| 9 | | 1 - #6 | - | - | - | - |
| 10 | | - | - | - | - | - |
| 12 | - | - | - | - | - | - |
| 14 | - | - | - | - | - | - |
| 16 | - | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | 34 | 23 | 17 | 14 | 12 |

| s=5", D=12" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | 1 - #6 | 1 - #6 |
| 7 | | | | 1 - #6 | - | - |
| 8 | | | 1 - #6 | - | - | - |
| 9 | | 1 - #6 | - | - | - | - |
| 10 | | 1 - #6 | - | - | - | - |
| 12 | | - | - | - | - | - |
| 14 | 1 - #6 | - | - | - | - | - |
| 16 | - | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | 81 | 43 | 29 | 22 | 18 | 15 |

| s=7", D=16" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | 1 - #6 | 1 - #6 |
| 8 | | | | 1 - #6 | 1 - #6 | - |
| 9 | | | 1 - #6 | - | - | - |
| 10 | | | 1 - #6 | - | - | - |
| 12 | | 1 - #6 | - | - | - | - |
| 14 | | - | - | - | - | - |
| 16 | 1 - #6 | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | 60 | 41 | 31 | 25 | 21 |

| s=9", D=20" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | 1 - #6 | 1 - #6 |
| 9 | | | | 1 - #6 | 1 - #6 | - |
| 10 | | | 1 - #6 | 1 - #6 | - | - |
| 12 | | 1 - #6 | - | - | - | - |
| 14 | | - | - | - | - | - |
| 16 | 1 - #6 | - | - | - | - | - |
| 18 | 1 - #6 | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | | 52 | 40 | 32 | 27 |

| s=11", D=24" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | 1 - #6 |
| 9 | | | | | 1 - #6 | 1 - #6 |
| 10 | | | | 1 - #6 | 1 - #6 | - |
| 12 | | | 1 - #6 | - | - | - |
| 14 | | 1 - #6 | - | - | - | - |
| 16 | | - | - | - | - | - |
| 18 | 1 - #6 | - | - | - | - | - |
| 20 | 1 - #6 | - | - | - | - | - |
| No stirrup distance, Z (in.) | | | 63 | 49 | 39 | 33 |

| s=14", D=30" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | 1 - #6 |
| 10 | | | | | 1 - #6 | 1 - #6 |
| 12 | | | | 1 - #6 | - | - |
| 14 | | | 1 - #6 | - | - | - |
| 16 | | 1 - #6 | - | - | - | - |
| 18 | | - | - | - | - | - |
| 20 | 1 - #6 | - | - | - | - | - |
| No stirrup distance, Z (in.) | | | 79 | 61 | 50 | 42 |

Notes:

- Where not shown otherwise, bottom steel is 1-#5
- Table is to be read in conjunction w/ Figure 4.
- Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
- Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to Figure 4.
- Factored Uniform Load includes 1.2, and 1.6 for dead and live load, respectively. For example, (1.2*dead load)+(1.6*live load)

6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 4B - LOGIX 6.25" LINTEL REINFORCEMENT WITH UNIFORM LOAD

Based on 40 ksi reinforcing steel. Lintels tables for 60 ksi reinforcing steel are available for download at www.logixicf.com.

Where not shown otherwise, bottom steel is 1-#5

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | 1 - #6 |
| 5 | | | | 1 - #6 | 1 - #6 | 2 - #5 |
| 6 | | | 1 - #6 | 2 - #5 | - | - |
| 7 | | 1 - #6 | 2 - #5 | - | - | - |
| 8 | | 2 - #5 | - | - | - | - |
| 9 | | - | - | - | - | - |
| 10 | 2 - #5 | - | - | - | - | - |
| 12 | - | - | - | - | - | - |
| 14 | - | - | - | - | - | - |
| 16 | - | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | 39 | 26 | 20 | 16 | 13 |

| s=4", D=10" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | 1 - #6 |
| 6 | | | | 1 - #6 | 2 - #5 | 2 - #5 |
| 7 | | | 1 - #6 | 2 - #5 | 2 - #6 | 2 - #6 |
| 8 | | 1 - #6 | 2 - #5 | 2 - #6 | 2 - #6 | - |
| 9 | | 1 - #6 | 2 - #6 | - | - | - |
| 10 | | 2 - #5 | 2 - #6 | - | - | - |
| 12 | 1 - #6 | - | - | - | - | - |
| 14 | 2 - #6 | - | - | - | - | - |
| 16 | - | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | 52 | 36 | 27 | 22 | 18 |

| s=5", D=12" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | 1 - #6 | 1 - #6 |
| 7 | | | | 1 - #6 | 2 - #5 | 2 - #5 |
| 8 | | | 1 - #6 | 2 - #5 | 2 - #6 | 2 - #6 |
| 9 | | 1 - #6 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #7 |
| 10 | | 1 - #6 | 2 - #5 | 2 - #6 | 2 - #7 | - |
| 12 | 1 - #6 | 2 - #5 | 2 - #7 | - | - | - |
| 14 | 2 - #5 | 2 - #7 | - | - | - | - |
| 16 | 2 - #6 | - | - | - | - | - |
| 18 | 2 - #7 | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | 65 | 45 | 34 | 27 | 23 |

| s=7", D=16" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | 1 - #6 | 1 - #6 |
| 8 | | | | 1 - #6 | 1 - #6 | 2 - #5 |
| 9 | | | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #6 |
| 10 | | | 1 - #6 | 2 - #5 | 2 - #6 | 2 - #6 |
| 12 | | 1 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #8 |
| 14 | 1 - #6 | 2 - #5 | 2 - #6 | 2 - #7 | 2 - #8 | - |
| 16 | 1 - #6 | 2 - #6 | 2 - #7 | - | - | - |
| 18 | 2 - #5 | 2 - #7 | 2 - #8 | - | - | - |
| 20 | 2 - #6 | 2 - #8 | - | - | - | - |
| No stirrup distance, Z (in.) | | 89 | 62 | 48 | 39 | 32 |

| s=9", D=20" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | 1 - #6 | 1 - #6 |
| 9 | | | | 1 - #6 | 1 - #6 | 2 - #5 |
| 10 | | | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #6 |
| 12 | | 1 - #6 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #7 |
| 14 | | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #8 |
| 16 | 1 - #6 | 2 - #5 | 2 - #7 | 2 - #7 | 2 - #8 | - |
| 18 | 2 - #5 | 2 - #6 | 2 - #7 | 2 - #8 | - | - |
| 20 | 2 - #5 | 2 - #7 | 2 - #8 | - | - | - |
| No stirrup distance, Z (in.) | | 112 | 79 | 61 | 49 | 42 |

| s=11", D=24" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | 1 - #6 |
| 9 | | | | | 1 - #6 | 1 - #6 |
| 10 | | | | 1 - #6 | 1 - #6 | 2 - #5 |
| 12 | | | 1 - #6 | 2 - #5 | 2 - #6 | 2 - #6 |
| 14 | | 1 - #6 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #7 |
| 16 | | 2 - #5 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 |
| 18 | 1 - #6 | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 | - |
| 20 | 2 - #5 | 2 - #6 | 2 - #7 | 2 - #8 | - | - |
| No stirrup distance, Z (in.) | | | 94 | 73 | 60 | 51 |

Notes:

- Where not shown otherwise, bottom steel is 1-#5
- Table is to be read in conjunction w/ Figure 4.
- Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
- Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to Figure 4.
- Factored Uniform Load includes 1.2, and 1.6 for dead and live load, respectively. For example, (1.2*dead load)+(1.6*live load)

ENGINEERING

| s=14", D=30" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | 1 - #6 |
| 10 | | | | | 1 - #6 | 1 - #6 |
| 12 | | | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 |
| 14 | | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #6 | 2 - #6 |
| 16 | | 1 - #6 | 2 - #5 | 2 - #6 | 2 - #7 | 2 - #7 |
| 18 | 1 - #6 | 2 - #5 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 |
| 20 | 1 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 | - |
| No stirrup distance, Z (in.) | | | 117 | 91 | 75 | 64 |

www.logixicf.com

Good. Solid. Green.™

6 - 22



6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 4C - LOGIX 8" LINTEL REINFORCEMENT WITH UNIFORM LOAD

Based on 40 ksi reinforcing steel. Lintels tables for 60 ksi reinforcing steel are available for download at www.logixcf.com.

Where not shown otherwise, bottom steel is 2-#5

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | 2 - #6 | 2 - #6 |
| 7 | | | | 2 - #6 | - | - |
| 8 | | | 2 - #6 | - | - | - |
| 9 | | 2 - #6 | - | - | - | - |
| 10 | | - | - | - | - | - |
| 12 | - | - | - | - | - | - |
| 14 | - | - | - | - | - | - |
| 16 | - | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | 49 | 33 | 25 | 20 | 17 |

| s=4", D=10" | | | | | | |
|---------------------------------|------------------------------|-----|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | 2 - #6 | 2 - #6 |
| 8 | | | | 2 - #6 | 2 - #6 | - |
| 9 | | | 2 - #6 | 2 - #6 | - | - |
| 10 | | | 2 - #6 | - | - | - |
| 12 | | - | - | - | - | - |
| 14 | 2 - #6 | - | - | - | - | - |
| 16 | - | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | | 45 | 34 | 28 | 23 |

| s=5", D=12" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | 2 - #6 | 2 - #6 |
| 9 | | | | 2 - #6 | 2 - #6 | - |
| 10 | | | 2 - #6 | 2 - #6 | - | - |
| 12 | | 2 - #6 | - | - | - | - |
| 14 | | 2 - #6 | - | - | - | - |
| 16 | 2 - #6 | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | 81 | 56 | 43 | 35 | 29 |

| s=7", D=16" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | 2 - #6 |
| 10 | | | | | 2 - #6 | 2 - #6 |
| 12 | | | 2 - #6 | 2 - #6 | - | - |
| 14 | | | - | - | - | - |
| 16 | | 2 - #6 | - | - | - | - |
| 18 | | - | - | - | - | - |
| 20 | 2 - #6 | - | - | - | - | - |
| No stirrup distance, Z (in.) | | | | 60 | 49 | 41 |

| s=9", D=20" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | 2 - #6 |
| 12 | | | | 2 - #6 | 2 - #6 | - |
| 14 | | | 2 - #6 | - | - | - |
| 16 | | 2 - #6 | - | - | - | - |
| 18 | | 2 - #6 | - | - | - | - |
| 20 | | - | - | - | - | - |
| No stirrup distance, Z (in.) | | | | | 62 | 52 |

| s=11", D=24" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|------|------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | 2 - #6 | - | - |
| 16 | | | 2 - #6 | - | - | - |
| 18 | | 2 - #6 | - | - | - | - |
| 20 | | 2 - #6 | - | - | - | - |
| No stirrup distance, Z (in.) | | | | | | 63 |

| s=14", D=30" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | | 2 - #6 | 2 - #6 |
| 16 | | | | 2 - #6 | - | - |
| 18 | | | 2 - #6 | - | - | - |
| 20 | | 2 - #6 | - | - | - | - |
| No stirrup distance, Z (in.) | | | | | | 79 |

Notes:

- Where not shown otherwise, bottom steel is 2-#5
- Table is to be read in conjunction w/ **Figure 4**.
- Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
- Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to **Figure 4**.
- Factored Uniform Load includes 1.2, and 1.6 for dead and live load, respectively. For example, (1.2*dead load)+(1.6*live load)

www.logixcf.com

Good. Solid. Green.™

6 – 23

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

ENGINEERING

6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 4D - LOGIX 10" LINTEL REINFORCEMENT WITH UNIFORM LOAD

Based on 40 ksi reinforcing steel. Lintels tables for 60 ksi reinforcing steel are available for download at www.logixicf.com.

Where not shown otherwise, bottom steel is 2-#5

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | |
|---------------------------------|------------------------------|-----|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | 2 - #6 | 2 - #6 |
| 7 | | | | 2 - #6 | - | - |
| 8 | | | 2 - #6 | - | - | - |
| 9 | | | - | - | - | - |
| 10 | | - | - | - | - | - |
| 12 | - | - | - | - | - | - |
| 14 | - | - | - | - | - | - |
| 16 | - | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | | 41 | 31 | 25 | 21 |

| s=4", D=10" | | | | | | |
|---------------------------------|------------------------------|-----|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | 2 - #6 |
| 8 | | | | 2 - #6 | 2 - #6 | 2 - #7 |
| 9 | | | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #8 |
| 10 | | | 2 - #6 | 2 - #7 | 2 - #8 | - |
| 12 | | | 2 - #7 | 2 - #8 | - | - |
| 14 | 2 - #6 | | 2 - #8 | - | - | - |
| 16 | 2 - #8 | | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | 79 | 55 | 42 | 34 | 29 |

| s=5", D=12" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | 2 - #6 | 2 - #6 |
| 9 | | | | 2 - #6 | 2 - #6 | 2 - #7 |
| 10 | | | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #8 |
| 12 | | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 | - |
| 14 | | 2 - #7 | 2 - #8 | - | - | - |
| 16 | 2 - #6 | - | - | - | - | - |
| 18 | 2 - #7 | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | | 69 | 53 | 43 | 36 |

| s=7", D=16" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | 2 - #6 |
| 10 | | | | | 2 - #6 | 2 - #6 |
| 12 | | | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #8 |
| 14 | | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 | - |
| 16 | | 2 - #6 | 2 - #7 | 2 - #8 | - | - |
| 18 | 2 - #6 | 2 - #7 | 2 - #8 | - | - | - |
| 20 | 2 - #6 | 2 - #8 | - | - | - | - |
| No stirrup distance, Z (in.) | | | 94 | 73 | 60 | 51 |

| s=9", D=20" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | 2 - #6 |
| 12 | | | | 2 - #6 | 2 - #6 | 2 - #7 |
| 14 | | | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 |
| 16 | | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 | - |
| 18 | | 2 - #6 | 2 - #7 | 2 - #8 | - | - |
| 20 | 2 - #6 | 2 - #7 | 2 - #8 | - | - | - |
| No stirrup distance, Z (in.) | | | 118 | 92 | 76 | 64 |

| s=11", D=24" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | 2 - #6 | 2 - #6 |
| 14 | | | | 2 - #6 | 2 - #7 | 2 - #7 |
| 16 | | | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 |
| 18 | | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 | - |
| 20 | | 2 - #7 | 2 - #8 | 2 - #8 | - | - |
| No stirrup distance, Z (in.) | | | | 110 | 91 | 78 |

| s=14", D=30" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | | 2 - #6 | 2 - #6 |
| 16 | | | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 |
| 18 | | | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 |
| 20 | | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 | - |
| No stirrup distance, Z (in.) | | | | | 113 | 97 |

Notes:

- Where not shown otherwise, bottom steel is 2-#5
- Table is to be read in conjunction w/ Figure 4.
- Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
- Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to Figure 4.
- Factored Uniform Load includes 1.2, and 1.6 for dead and live load, respectively. For example, (1.2*dead load)+(1.6*live load)

www.logixicf.com

Good. Solid. Green.™

6 - 24



6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 4E - LOGIX 12" LINTEL REINFORCEMENT WITH UNIFORM LOAD

Based on 40 ksi reinforcing steel. Lintels tables for 60 ksi reinforcing steel are available for download at www.logixcf.com.

Where not shown otherwise, bottom steel is 2-#5

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | 2 - #6 | 2 - #6 |
| 7 | | | | 2 - #6 | 2 - #6 | 2 - #7 |
| 8 | | | 2 - #6 | 2 - #7 | 2 - #7 | - |
| 9 | | | 2 - #7 | - | - | - |
| 10 | | 2 - #7 | - | - | - | - |
| 12 | 2 - #6 | - | - | - | - | - |
| 14 | - | - | - | - | - | - |
| 16 | - | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | | 49 | 37 | 30 | 25 |

| s=4", D=10" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | 2 - #6 |
| 8 | | | | 2 - #6 | 2 - #6 | 2 - #7 |
| 9 | | | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #8 |
| 10 | | | 2 - #6 | 2 - #7 | 2 - #8 | - |
| 12 | | 2 - #6 | 2 - #8 | - | - | - |
| 14 | 2 - #6 | 2 - #8 | - | - | - | - |
| 16 | 2 - #8 | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | | 65 | 50 | 41 | 34 |

| s=5", D=12" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | 2 - #6 | 2 - #6 |
| 9 | | | | 2 - #6 | 2 - #6 | 2 - #7 |
| 10 | | | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #8 |
| 12 | | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 | - |
| 14 | | 2 - #7 | 2 - #8 | - | - | - |
| 16 | 2 - #6 | - | - | - | - | - |
| 18 | 2 - #7 | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | | 81 | 62 | 51 | 43 |

| s=7", D=16" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | 2 - #6 |
| 10 | | | | | 2 - #6 | 2 - #6 |
| 12 | | | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #8 |
| 14 | | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 | - |
| 16 | | 2 - #6 | 2 - #8 | - | - | - |
| 18 | 2 - #6 | 2 - #7 | 2 - #8 | - | - | - |
| 20 | 2 - #6 | 2 - #8 | - | - | - | - |
| No stirrup distance, Z (in.) | | | | | 70 | 60 |

| s=9", D=20" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | 2 - #6 |
| 12 | | | | 2 - #6 | 2 - #6 | 2 - #7 |
| 14 | | | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 |
| 16 | | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 | - |
| 18 | | 2 - #7 | 2 - #8 | 2 - #8 | - | - |
| 20 | 2 - #6 | 2 - #7 | 2 - #8 | - | - | - |
| No stirrup distance, Z (in.) | | | | | 89 | 76 |

| s=11", D=24" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | 2 - #6 | 2 - #7 | 2 - #7 |
| 16 | | | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 |
| 18 | | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 | - |
| 20 | | 2 - #7 | 2 - #8 | - | - | - |
| No stirrup distance, Z (in.) | | | | | 107 | 91 |

| D=30" | | | | | | |
|---------------------------------|------------------------------|--------|--------|--------|--------|--------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | 2 - #6 |
| 14 | | | | 2 - #6 | 2 - #6 | 2 - #6 |
| 16 | | | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 |
| 18 | | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 | 2 - #8 |
| 20 | | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 | - |
| No stirrup distance, Z (in.) | | | | | | |

Notes:

- Where not shown otherwise, bottom steel is 2-#5
- Table is to be read in conjunction w/ **Figure 4**.
- Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
- Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to **Figure 4**.
- Factored Uniform Load includes 1.2, and 1.6 for dead and live load, respectively. For example, (1.2*dead load)+(1.6*live load)

www.logixcf.com

Good. Solid. Green.™

6 – 25



6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 5A - LOGIX 4" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD

Based on 40 ksi reinforcing steel. Lintels tables for 60 ksi reinforcing steel are available for download at www.logixicf.com.

Where not shown otherwise, bottom steel is 1-#5

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|-------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3 | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | - |
| 5 | | | | | | | | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - |
| 6 | | | | | | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - | - | - |
| 7 | | | | | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - | - | - | - |
| 8 | | | | | 1 - #6 | - | - | - | - | - | - | - | - | - | - | - |
| 9 | | | | 1 - #6 | - | - | - | - | - | - | - | - | - | - | - | - |
| 10 | | | 1 - #6 | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 12 | | 1 - #6 | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 14 | | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 16 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 18 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

| s=4", D=10" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3 | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 |
| 5 | | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | - | - |
| 6 | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - | - |
| 7 | | | | | | | | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - |
| 8 | | | | | | | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - | - |
| 9 | | | | | | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - | - | - |
| 10 | | | | | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - | - | - | - |
| 12 | | | | 1 - #6 | - | - | - | - | - | - | - | - | - | - | - | - |
| 14 | | | 1 - #6 | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 16 | | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 18 | | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 20 | 1 - #6 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

| s=5", D=12" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3 | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 |
| 6 | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | - | - |
| 7 | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - | - |
| 8 | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - | - | - | - |
| 9 | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - |
| 10 | | | | | | | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - | - |
| 12 | | | | | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - | - | - | - |
| 14 | | | | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - | - | - | - | - |
| 16 | | | 1 - #6 | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 18 | | | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 20 | | 1 - #6 | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

| s=7", D=16" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3 | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | 1 - #6 |
| 6 | | | | | | | | | | | | | | | 1 - #6 | 1 - #6 |
| 7 | | | | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 |
| 8 | | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | - |
| 9 | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | - | - |
| 10 | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - |
| 12 | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - | - | - | - |
| 14 | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - | - |
| 16 | | | | | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - | - | - |
| 18 | | | | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - | - | - | - | - |
| 20 | | | | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - | - | - | - | - |

ENGINEERING

www.logixicf.com

Good. Solid. Green.™

6 – 26



6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 5A - LOGIX 4" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD Cont'd
Based on 40 ksi reinforcing steel. Lintels tables for 60 ksi reinforcing steel are available for download at www.logixicf.com.

| s=9", D=20" | | | | | | | | | | | | | | | | | |
|---------------|-----|------|------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | 1 - #6 | 1 - #6 |
| 8 | | | | | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 |
| 9 | | | | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | - |
| 10 | | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | - | - |
| 12 | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - | - |
| 14 | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - | - | - | - |
| 16 | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - | - |
| 18 | | | | | | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - | - | - | - |
| 20 | | | | | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - | - | - | - | - |

| s=11", D=24" | | | | | | | | | | | | | | | | | |
|---------------|-----|------|------|------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | | 1 - #6 |
| 9 | | | | | | | | | | | | | | | | 1 - #6 | 1 - #6 |
| 10 | | | | | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 |
| 12 | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - |
| 14 | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - | - |
| 16 | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - | - | - | - |
| 18 | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - | - |
| 20 | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - | - | - |

| s=14", D=30" | | | | | | | | | | | | | | | | | |
|---------------|-----|------|------|------|------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | | | 1 - #6 |
| 12 | | | | | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 |
| 14 | | | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | - | - |
| 16 | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - |
| 18 | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - | - | - |
| 20 | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | - | - | - | - | - | - | - |

Notes:

1. Where not shown otherwise, bottom steel is 1-#5
2. Table is to be read in conjunction w/ **Figure 4**.
3. Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
4. Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to **Figure 4**.
5. Factored Point Load includes 1.2, and 1.6 for dead and live load, respectively. For example, (1.2*dead load)+(1.6*live load)

ENGINEERING

6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 5B - LOGIX 6.25" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD

Based on 40 ksi reinforcing steel. Lintels tables for 60 ksi reinforcing steel are available for download at www.logixicf.com.

Where not shown otherwise, bottom steel is 1-#5

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 |
| 4 | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | - | - |
| 5 | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | - | - | - | - |
| 6 | | | | | | | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | - | - | - | - | - | - |
| 7 | | | | | | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | - | - | - | - | - | - | - | - |
| 8 | | | | | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | - | - | - | - | - | - | - | - | - |
| 9 | | | | 1 - #6 | 1 - #6 | 2 - #5 | - | - | - | - | - | - | - | - | - | - | - |
| 10 | | | | 2 - #5 | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 12 | | | 2 - #5 | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 14 | | 2 - #5 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 16 | 1 - #6 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 18 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

| s=4", D=10" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 |
| 4 | | | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 |
| 5 | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #6 |
| 6 | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #6 |
| 7 | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #6 | - |
| 8 | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | - | - |
| 9 | | | | | | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | - | - |
| 10 | | | | | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #6 | - | - | - | - | - |
| 12 | | | | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #6 | - | - | - | - | - | - | - | - |
| 14 | | | 1 - #6 | 2 - #5 | 2 - #6 | 2 - #6 | - | - | - | - | - | - | - | - | - | - | - |
| 16 | | | 2 - #6 | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 18 | | 2 - #5 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 20 | 1 - #6 | 2 - #6 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

| s=5", D=12" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | 1 - #6 | 1 - #6 |
| 4 | | | | | | | | | | | | | | | | 1 - #6 | 1 - #6 |
| 5 | | | | | | | | | | | | | | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 |
| 6 | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 |
| 7 | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #6 | 2 - #6 |
| 8 | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #6 |
| 9 | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #6 | - |
| 10 | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #6 | - | - |
| 12 | | | | | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | - | - | - | - |
| 14 | | | | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | - | - | - | - | - | - |
| 16 | | | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #6 | - | - | - | - | - | - | - | - | - | - | - |
| 18 | | | 1 - #6 | 2 - #6 | 2 - #6 | - | - | - | - | - | - | - | - | - | - | - | - |
| 20 | | 1 - #6 | 2 - #6 | 2 - #6 | - | - | - | - | - | - | - | - | - | - | - | - | - |

| s=7", D=16" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | 1 - #6 |
| 6 | | | | | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 |
| 7 | | | | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 |
| 8 | | | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 |
| 9 | | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #6 |
| 10 | | | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #6 | 2 - #6 |
| 12 | | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #6 |
| 14 | | | | | | 1 - #6 | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | - | - |
| 16 | | | | | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | - | - | - |
| 18 | | | | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | - | - | - | - | - |
| 20 | | | 1 - #6 | 1 - #6 | 2 - #5 | 2 - #5 | 2 - #6 | 2 - #6 | 2 - #6 | - | - | - | - | - | - | - | - |

ENGINEERING

www.logixicf.com

Good. Solid. Green.™

6 - 28



6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 5B - LOGIX 6.25" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD Cont'd
Based on 40 ksi reinforcing steel. Lintels tables for 60 ksi reinforcing steel are available for download at www.logixicf.com.

| s=9", D=20" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3 | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | 1 - #6 | 1 - #6 |
| 9 | | | | | | | | | | | | | | | 1 - #6 | 1 - #6 |
| 10 | | | | | | | | | | | | | | | 1 - #6 | 1 - #6 |
| 12 | | | | | | | | | | | | | | | 1 - #6 | 1 - #6 |
| 14 | | | | | | | | | | | | | | | 1 - #6 | 1 - #6 |
| 16 | | | | | | | | | | | | | | | 1 - #6 | 1 - #6 |
| 18 | | | | | | | | | | | | | | | 1 - #6 | 1 - #6 |
| 20 | | | | | | | | | | | | | | | 1 - #6 | 1 - #6 |

| s=11", D=24" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3-7 | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | |
| 16 | | | | | | | | | | | | | | | | |
| 18 | | | | | | | | | | | | | | | | |
| 20 | | | | | | | | | | | | | | | | |

| D=30" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3-9 | | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | |
| 16 | | | | | | | | | | | | | | | | |
| 18 | | | | | | | | | | | | | | | | |
| 20 | | | | | | | | | | | | | | | | |

Notes:

- Where not shown otherwise, bottom steel is 1-#5
- Table is to be read in conjunction w/ **Figure 4**.
- Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
- Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to **Figure 4**.
- Factored Point Load includes 1.2, and 1.6 for dead and live load, respectively. For example, (1.2*dead load)+(1.6*live load)

ENGINEERING

6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 5C - LOGIX 8" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD

Based on 40 ksi reinforcing steel. Lintels tables for 60 ksi reinforcing steel are available for download at www.logixicf.com.

Where not shown otherwise, bottom steel is 2-#5

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|--------|--------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 |
| 5 | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | - |
| 6 | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | - | - | - |
| 7 | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | - | - | - | - |
| 8 | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | - | - | - | - | - | - |
| 9 | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | - | - | - | - | - | - | - | - |
| 10 | | | | | | 2 - #6 | - | - | - | - | - | - | - | - | - | - | - |
| 12 | | | | 2 - #6 | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 14 | | | 2 - #6 | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 16 | | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 18 | 2 - #6 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

| s=4", D=10" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 |
| 7 | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 |
| 8 | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 |
| 9 | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | - |
| 10 | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | - | - |
| 12 | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | - | - | - | - | - |
| 14 | | | | | | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | - | - | - | - | - | - | - | - |
| 16 | | | | 2 - #7 | 2 - #7 | - | - | - | - | - | - | - | - | - | - | - | - |
| 18 | | | 2 - #7 | 2 - #7 | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 20 | | 2 - #6 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

| s=5", D=12" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | 2 - #6 |
| 8 | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 |
| 9 | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 |
| 10 | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 |
| 12 | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #8 |
| 14 | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #8 | 2 - #8 | - |
| 16 | | | | | | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 | 2 - #8 | - | - | - | - | - | - |
| 18 | | | | | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 | 2 - #8 | 2 - #8 | - | - | - | - | - | - | - |
| 20 | | | | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 | - | - | - | - | - | - | - | - | - | - |

| s=7", D=16" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | | 2 - #6 |
| 10 | | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 |
| 12 | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 |
| 14 | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 |
| 16 | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 |
| 18 | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #8 | 2 - #8 |
| 20 | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #8 | 2 - #8 | - | - |

ENGINEERING

www.logixicf.com

Good. Solid. Green.™

6 – 30



6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 5C - LOGIX 8" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD Cont'd
Based on 40 ksi reinforcing steel. Lintels tables for 60 ksi reinforcing steel are available for download at www.logixicf.com.

| s=9", D=20" | | | | | | | | | | | | | | | | | |
|---------------|-----|------|------|------|------|------|------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-11 | | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | | 2 - #6 |
| 14 | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 |
| 16 | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 |
| 18 | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 |
| 20 | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #8 |

| D=24" | | | | | | | | | | | | | | | | | |
|---------------|-----|------|------|------|------|------|------|------|------|------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-13 | | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | | 2 - #6 |
| 16 | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 |
| 18 | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 |
| 20 | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 |

| D=30" | | | | | | | | | | | | | | | | | |
|---------------|-----|------|------|------|------|------|------|------|------|------|------|------|------|--------|--------|--------|--------|
| Opening ft | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-17 | | | | | | | | | | | | | | | | | |
| 18 | | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 |
| 20 | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 |

Notes:

- Where not shown otherwise, bottom steel is 2-#5
- Table is to be read in conjunction w/ **Figure 4**.
- Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
- Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to **Figure 4**.
- Factored Point Load includes 1.2, and 1.6 for dead and live load, respectively. For example, $(1.2 \times \text{dead load}) + (1.6 \times \text{live load})$

ENGINEERING

6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 5D - LOGIX 10" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD

Based on 40 ksi reinforcing steel. Lintels tables for 60 ksi reinforcing steel are available for download at www.logixicf.com.

Where not shown otherwise, bottom steel is 2-#5

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|--------|--------|------|--------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3 | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | 2 - #6 |
| 5 | | | | | | | | | | | | | | | 2 - #6 | - |
| 6 | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | - |
| 7 | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | - | - | - |
| 8 | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | - | - | - | - | - |
| 9 | | | | | | | | 2 - #6 | 2 - #6 | - | - | - | - | - | - | - |
| 10 | | | | | | 2 - #6 | - | - | - | - | - | - | - | - | - | - |
| 12 | | | | 2 - #6 | - | - | - | - | - | - | - | - | - | - | - | - |
| 14 | | | 2 - #6 | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 16 | | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 18 | 2 - #6 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

| s=4", D=10" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3 | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 |
| 8 | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 |
| 9 | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 |
| 10 | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 |
| 12 | | | | | | | | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #8 | 2 - #8 | 2 - #8 | - |
| 14 | | | | | | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 | 2 - #8 | 2 - #8 | - | - | - | - | - |
| 16 | | | | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 | - | - | - | - | - | - | - | - | - |
| 18 | | | 2 - #6 | 2 - #8 | 2 - #8 | - | - | - | - | - | - | - | - | - | - | - |
| 20 | | 2 - #6 | 2 - #8 | 2 - #8 | - | - | - | - | - | - | - | - | - | - | - | - |

| s=5", D=12" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3 | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | 2 - #6 |
| 8 | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 |
| 9 | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #7 |
| 10 | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 |
| 12 | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 |
| 14 | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #8 | - |
| 16 | | | | | | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 | 2 - #8 | - | - | - | - | - |
| 18 | | | | | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 | 2 - #8 | - | - | - | - | - | - | - |
| 20 | | | | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 | - | - | - | - | - | - | - | - | - |

| s=7", D=16" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3-8 | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | 2 - #6 |
| 10 | | | | | | | | | | | | | | | | 2 - #6 |
| 12 | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 |
| 14 | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 |
| 16 | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 |
| 18 | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #8 |
| 20 | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #8 | 2 - #8 | - |

ENGINEERING

www.logixicf.com

Good. Solid. Green.™

6 - 3 2



6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 5D - LOGIX 10" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD Cont'd
Based on 40 ksi reinforcing steel. Lintels tables for 60 ksi reinforcing steel are available for download at www.logixicf.com.

| D=20" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-11 | | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 |
| 14 | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 |
| 16 | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 |
| 18 | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 |
| 20 | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #8 |

| D=24" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-13 | | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 |
| 16 | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 |
| 18 | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 |
| 20 | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 |

| D=30" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|------|------|------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-15 | | | | | | | | | | | | | | | | | |
| 16 | | | | | | | | | | | | | | | | | 2 - #6 |
| 18 | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 |
| 20 | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 |

Notes:

1. Where not shown otherwise, bottom steel is 2-#5
2. Table is to be read in conjunction w/ **Figure 4**.
3. Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
4. Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to **Figure 4**.
5. Factored Point Load includes 1.2, and 1.6 for dead and live load, respectively. For example, (1.2*dead load)+(1.6*live load)

ENGINEERING

6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 5E - LOGIX 12" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD

Based on 40 ksi reinforcing steel. Lintels tables for 60 ksi reinforcing steel are available for download at www.logixicf.com.
Where not shown otherwise, bottom steel is 2-#5

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|--------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | 2 - #6 |
| 5 | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 |
| 6 | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 |
| 7 | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | - |
| 8 | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | - | - | - |
| 9 | | | | | | | | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | - | - | - | - | - | - |
| 10 | | | | | | | 2 - #6 | 2 - #7 | 2 - #7 | - | - | - | - | - | - | - | - |
| 12 | | | | | 2 - #6 | 2 - #7 | - | - | - | - | - | - | - | - | - | - | - |
| 14 | | | | 2 - #7 | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 16 | | 2 - #7 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 18 | 2 - #6 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

| s=4", D=10" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 |
| 7 | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #7 |
| 8 | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 |
| 9 | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 |
| 10 | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 | 2 - #8 |
| 12 | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 | 2 - #8 | 2 - #8 | - | - |
| 14 | | | | | | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #8 | 2 - #8 | - | - | - | - | - | - |
| 16 | | | | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 | - | - | - | - | - | - | - | - | - | - |
| 18 | | | 2 - #6 | 2 - #8 | 2 - #8 | - | - | - | - | - | - | - | - | - | - | - | - |
| 20 | | 2 - #6 | 2 - #8 | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

| s=5", D=12" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | 2 - #6 |
| 8 | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 |
| 9 | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 |
| 10 | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 |
| 12 | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #8 |
| 14 | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #8 | 2 - #8 | - |
| 16 | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 | - | - | - | - | - | - |
| 18 | | | | | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 | - | - | - | - | - | - | - | - |
| 20 | | | | 2 - #6 | 2 - #7 | 2 - #8 | 2 - #8 | - | - | - | - | - | - | - | - | - | - |

| D=16" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-8 | | | | | | | | | | | | | | | | | 2 - #6 |
| 9 | | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 |
| 10 | | | | | | | | | | | | | | | | 2 - #6 | 2 - #7 |
| 12 | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 |
| 14 | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 |
| 16 | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #8 |
| 18 | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #8 | 2 - #8 |
| 20 | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #8 | - | - |

ENGINEERING

www.logixicf.com

Good. Solid. Green.™

6 - 3 4



6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 5E - LOGIX 12" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD Cont'd
Based on 40 ksi reinforcing steel. Lintels tables for 60 ksi reinforcing steel are available for download at www.logixcf.com.

| D=20" | | | | | | | | | | | | | | | | | |
|---------------|-----|------|------|------|------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-11 | | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 |
| 14 | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 |
| 16 | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 |
| 18 | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 |
| 20 | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #7 | 2 - #8 | 2 - #8 |

| D=24" | | | | | | | | | | | | | | | | | |
|---------------|-----|------|------|------|------|------|------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-13 | | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 |
| 16 | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 |
| 18 | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 |
| 20 | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 | 2 - #7 | 2 - #7 |

| D=30" | | | | | | | | | | | | | | | | | |
|---------------|-----|------|------|------|------|------|------|------|------|------|--------|--------|--------|--------|--------|--------|--------|
| Opening ft | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-15 | | | | | | | | | | | | | | | | | |
| 16 | | | | | | | | | | | | | | | | 2 - #6 | 2 - #6 |
| 18 | | | | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 |
| 20 | | | | | | | | | | | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #6 | 2 - #7 |

Notes:

1. Where not shown otherwise, bottom steel is 2-#5
2. Table is to be read in conjunction w/ **Figure 4**.
3. Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
4. Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to **Figure 4**.
5. Factored Point Load includes 1.2, and 1.6 for dead and live load, respectively. For example, $(1.2 \times \text{dead load}) + (1.6 \times \text{live load})$

ENGINEERING

6.1 – U.S. ENGINEERING ANALYSIS REPORT

SHEAR WALLS




FIGURE 2: PLAN VIEW

LOGIX SHEAR WALL - SINGLE BAR FLEXURAL REINF.

(Applies to 4, 6.25, 8 & 10" LOGIX)




FIGURE 3: PLAN VIEW

LOGIX SHEAR WALL - DOUBLE MAT FLEXURAL REINF.

(Applies to 4, 6.25, 8 & 10" LOGIX)




FIGURE 4: PLAN VIEW

LOGIX SHEAR WALL - DOUBLE MAT FLEXURAL & SHEAR REINF.

(Applies to 12" LOGIX)

NOTES:

1. Shear wall Figures 1 to 4 to be used in conjunction with Tables 6A and 6B.
2. Provide double mat of reinforcement for 12" LOGIX wall. See Figure 4.
3. Fully develop flexural reinforcement into the footing.
4. Min. 28 day concrete compressive strength = 3 ksi. Steel yield strength = 60 ksi.
5. Clear spacing between flexural reinforcement bars = 3in

These tables should only be used if the above conditions are met. For other conditions, consult a structural engineer.




FIGURE 1: ELEVATION

ENGINEERING

6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 6A - SHEAR WALL: HORIZONTAL & VERTICAL SHEAR REINFORCEMENT

4" LOGIX SHEAR WALL REINFORCEMENT SPACING, in

| | | SHEAR FORCE, Vu, kpf | | | | | | | | | | | | | | | |
|---------------|--------------|----------------------|-------|--------|-------|--------|-------|--------|-------|--------|-------|--------|-------|--------|-------|--------|-------|
| | | 0.5 | | 1 | | 1.5 | | 2 | | 2.5 | | 3 | | 3.5 | | 4 | |
| Bar Size | Wall Length, | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. |
| #4, #5, or #6 | 2 | 12 | 12 | 12 | 12 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| | 4 | 12 | 12 | 12 | 12 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 |
| | >4 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 |

6.25" LOGIX SHEAR WALL REINFORCEMENT SPACING, in

| | | SHEAR FORCE, Vu, kpf | | | | | | | | | | | | | | | |
|---------------|--------------|----------------------|-------|--------|-------|------------|-------|------------|-------|------------|-------|------------|-------|------------|-------|------------|-------|
| | | 1 | | 2 | | 3 | | 4 | | 5 | | 6 | | 7 | | 8 | |
| Bar Size | Wall Length, | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. |
| #4, #5, or #6 | 2 | 16 | 16 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| | 4 | 16 | 16 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 |
| | 6 | 16 | 16 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 |
| | >6 | 16 | 16 | 16 | 16 | 12, 16, 16 | 16 | 12, 16, 16 | 16 | 12, 16, 16 | 16 | 12, 16, 16 | 16 | 12, 16, 16 | 16 | 12, 16, 16 | 16 |

8" LOGIX SHEAR WALL REINFORCEMENT SPACING, in

| | | SHEAR FORCE, Vu, kpf | | | | | | | | | | | | | | | |
|---------------|--------------|----------------------|------------|------------|-------|-----------|-------|-----------|-------|-----------|-------|-----------|-------|-----------|-------|-----------|-------|
| | | 1.5 | | 2.5 | | 5 | | 6 | | 7 | | 8 | | 9 | | 10 | |
| Bar Size | Wall Length, | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. |
| #4, #5, or #6 | 2 | 12, 12, 16 | 4, 16, 16 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| | 4 | 12, 12, 16 | 8, 16, 16 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 |
| | 6 | 12, 12, 16 | 12, 16, 16 | 8, 12, 12 | 12 | 8, 12, 12 | 12 | 8, 12, 12 | 12 | 8, 12, 12 | 12 | 8, 12, 12 | 12 | 8, 12, 12 | 12 | 8, 12, 12 | 12 |
| | >6 | 12, 12, 16 | 16 | 12, 12, 16 | 16 | 8, 12, 16 | 16 | 8, 12, 16 | 16 | 8, 12, 16 | 16 | 8, 12, 16 | 16 | 8, 12, 16 | 16 | 8, 12, 16 | 16 |

10" LOGIX SHEAR WALL REINFORCEMENT SPACING, in

| | | SHEAR FORCE, Vu, kpf | | | | | | | | | | | | | | | |
|---------------|--------------|----------------------|-------|-----------|------------|-----------|-------|-----------|-------|-----------|-------|-----------|-------|-----------|-------|-----------|-------|
| | | 1.5 | | 2.5 | | 5 | | 6 | | 7 | | 8 | | 9 | | 10 | |
| Bar Size | Wall Length, | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. |
| #4, #5, or #6 | 2 | 8, 12, 16 | 16 | 8, 12, 4 | 16, 16, 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| | 4 | 8, 12, 16 | 16 | 8, 12, 8 | 16, 16, 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 |
| | 6 | 8, 12, 16 | 16 | 8, 12, 12 | 16, 16, 12 | 8, 12, 12 | 12 | 8, 12, 12 | 12 | 8, 12, 12 | 12 | 8, 12, 12 | 12 | 8, 12, 12 | 12 | 8, 12, 12 | 12 |
| | >6 | 8, 12, 16 | 16 | 8, 12, 16 | 16 | 8, 12, 16 | 16 | 8, 12, 16 | 16 | 8, 12, 16 | 16 | 8, 12, 16 | 16 | 8, 12, 16 | 16 | 8, 12, 16 | 16 |

12" LOGIX SHEAR WALL REINFORCEMENT SPACING, in

| | | SHEAR FORCE, Vu, kpf | | | | | | | | | | | | | | | |
|---------------|--------------|----------------------|------------|--------|------------|--------|-------|------------|-------|------------|-------|------------|-------|------------|-------|------------|-------|
| | | 1.5 | | 2.5 | | 5 | | 6 | | 7 | | 8 | | 9 | | 10 | |
| Bar Size | Wall Length, | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. | Horiz. | Vert. |
| #4, #5, or #6 | 2 | 16 | 4, 16, 16 | 16 | 4, 16, 16 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| | 4 | 16 | 8, 16, 16 | 16 | 8, 16, 16 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 |
| | 6 | 16 | 12, 16, 16 | 16 | 12, 16, 16 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 |
| | >6 | 16 | 16 | 16 | 16 | 16 | 16 | 12, 16, 16 | 16 | 12, 16, 16 | 16 | 12, 16, 16 | 16 | 12, 16, 16 | 16 | 12, 16, 16 | 16 |

NOTES:

- Table 6A to be read in conjunction with Shear Wall Figures 1 to 4.

6.1 – U.S. ENGINEERING ANALYSIS REPORT

TABLE 6B - SHEAR WALL: FLEXURAL REINFORCEMENT

| 4" LOGIX - FLEXURAL REINFORCEMENT | | | | | | | | |
|-----------------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|------------------|------------------|------------------|
| Wall Length, lw, ft | SHEAR FORCE, Vu, kpf | | | | | | | |
| | 0.5 | 1 | 1.5 | 2 | 2.5 | 3 | 3.5 | 4 |
| 2 | 1 - #4, 1 - #5 or 1 - #6 | 2 - #4, 1 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 2 - #6 | 2 - #6 | - | - | - |
| 4 | 1 - #4, 1 - #5 or 1 - #6 | 2 - #4, 1 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 2 - #6 | 4 - #5 or 2 - #6 | 4 - #5 or 2 - #6 | 4 - #5 or 4 - #6 | 4 - #6 |
| 6 | 1 - #4, 1 - #5 or 1 - #6 | 2 - #4, 1 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 2 - #6 | 4 - #4, 4 - #5 or 2 - #6 | 4 - #5 or 2 - #6 | 4 - #5 or 4 - #6 | 4 - #6 |
| 8 | 1 - #4, 1 - #5 or 1 - #6 | 2 - #4, 1 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 2 - #6 | 4 - #4, 4 - #5 or 2 - #6 | 4 - #5 or 2 - #6 | 4 - #5 or 4 - #6 | 4 - #6 |
| 10 | 1 - #4, 1 - #5 or 1 - #6 | 2 - #4, 1 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 2 - #6 | 4 - #4, 4 - #5 or 2 - #6 | 4 - #5 or 2 - #6 | 4 - #5 or 4 - #6 | 4 - #6 |
| 15 | 1 - #4, 1 - #5 or 1 - #6 | 2 - #4, 1 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 2 - #6 | 4 - #4, 4 - #5 or 2 - #6 | 4 - #5 or 2 - #6 | 4 - #5 or 4 - #6 | 4 - #5 or 4 - #6 |
| 20 | 1 - #4, 1 - #5 or 1 - #6 | 2 - #4, 1 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 2 - #6 | 4 - #4, 4 - #5 or 2 - #6 | 4 - #5 or 2 - #6 | 4 - #5 or 4 - #6 | 4 - #5 or 4 - #6 |

| 6.25" LOGIX - FLEXURAL REINFORCEMENT | | | | | | | | |
|--------------------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|------------------------------|------------------------------|------------------------------|-------------------------------|
| Wall Length, lw, ft | SHEAR FORCE, Vu, kpf | | | | | | | |
| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
| 2 | 2 - #4, 1 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 2 - #6 | 4 - #5 or 4 - #6 | 4 - #6 | - | - | - | - |
| 4 | 2 - #4, 1 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 2 - #6 | 6 - #4, 4 - #5 or 4 - #6 | 6 - #5 or 4 - #6 | 6 - #5 or 4 - #6 | 8 - #5 or 6 - #6 | 6 - #6 | 8 - #6 |
| 6 | 2 - #4, 1 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 2 - #6 | 6 - #4, 4 - #5 or 4 - #6 | 6 - #4, 6 - #5 or 4 - #6 | 10 - #4, 6 - #5 or 4 - #6 | 12 - #4, 8 - #5 or 6 - #6 | 10 - #5 or 6 - #6 | 10 - #5 or 8 - #6 |
| 8 | 2 - #4, 1 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 2 - #6 | 6 - #4, 4 - #5 or 4 - #6 | 6 - #4, 6 - #5 or 4 - #6 | 10 - #4, 6 - #5 or 4 - #6 | 12 - #4, 8 - #5 or 6 - #6 | 14 - #4, 8 - #5 or 6 - #6 | 10 - #5 or 8 - #6 |
| 10 | 2 - #4, 1 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 2 - #6 | 6 - #4, 4 - #5 or 4 - #6 | 6 - #4, 6 - #5 or 4 - #6 | 10 - #4, 6 - #5 or 4 - #6 | 12 - #4, 8 - #5 or 6 - #6 | 14 - #4, 8 - #5 or 6 - #6 | 10 - #5 or 6 - #6 |
| 15 | 2 - #4, 1 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 2 - #6 | 6 - #4, 4 - #5 or 2 - #6 | 6 - #4, 4 - #5 or 4 - #6 | 10 - #4, 6 - #5 or 4 - #6 | 10 - #4, 8 - #5 or 6 - #6 | 12 - #4, 8 - #5 or 6 - #6 | 16 - #4, 10 - #5 or 6 - #6 |
| 20 | 2 - #4, 1 - #5 or 1 - #6 | 4 - #4, 2 - #5 or 2 - #6 | 6 - #4, 4 - #5 or 2 - #6 | 6 - #4, 4 - #5 or 4 - #6 | 10 - #4, 6 - #5 or 4 - #6 | 10 - #4, 8 - #5 or 6 - #6 | 12 - #4, 8 - #5 or 6 - #6 | 16 - #4, 10 - #5 or 6 - #6 |

| 8" to 12" LOGIX - FLEXURAL REINFORCEMENT | | | | | | | | |
|--|-----------------------------|-----------------------------|------------------------------|------------------------------|------------------------------|-------------------------------|-------------------------------|-------------------------------|
| Wall Length, lw, ft | SHEAR FORCE, Vu, kpf | | | | | | | |
| | 1.5 | 2.5 | 5 | 6 | 7 | 8 | 9 | 10 |
| 2 | 4 - #4, 2 - #5 or 1 - #6 | 4 - #5 or 2 - #6 | 4 - #7 | 4 - #7 | - | - | - | - |
| 4 | 4 - #4, 2 - #5 or 1 - #6 | 6 - #4, 4 - #5 or 2 - #6 | 6 - #5 or 4 - #6 | 6 - #6 | 6 - #6 | 4 - #8 | 6 - #7 | 6 - #8 |
| 6 | 4 - #4, 2 - #5 or 1 - #6 | 4 - #4, 4 - #5 or 2 - #6 | 10 - #4, 6 - #5 or 4 - #6 | 12 - #4, 8 - #5 or 6 - #6 | 14 - #4, 8 - #5 or 6 - #6 | 10 - #5 or 6 - #7 | 6 - #7 | 6 - #7 |
| 8 | 4 - #4, 2 - #5 or 1 - #6 | 4 - #4, 4 - #5 or 2 - #6 | 10 - #4, 6 - #5 or 4 - #6 | 12 - #4, 8 - #5 or 6 - #6 | 14 - #4, 8 - #5 or 6 - #6 | 16 - #4, 10 - #5 or 6 - #6 | 18 - #4, 12 - #5 or 6 - #7 | 12 - #5 or 6 - #7 |
| 10 | 4 - #4, 2 - #5 or 1 - #6 | 4 - #4, 4 - #5 or 2 - #6 | 10 - #4, 6 - #5 or 4 - #6 | 12 - #4, 8 - #5 or 6 - #6 | 12 - #4, 8 - #5 or 6 - #6 | 16 - #4, 10 - #5 or 6 - #6 | 18 - #4, 10 - #5 or 6 - #7 | 20 - #4, 12 - #5 or 6 - #7 |
| 15 | 4 - #4, 2 - #5 or 1 - #6 | 4 - #4, 4 - #5 or 2 - #6 | 10 - #4, 6 - #5 or 4 - #6 | 10 - #4, 8 - #5 or 6 - #6 | 12 - #4, 8 - #5 or 6 - #6 | 14 - #4, 10 - #5 or 6 - #6 | 16 - #4, 10 - #5 or 6 - #7 | 18 - #4, 12 - #5 or 6 - #7 |
| 20 | 4 - #4, 2 - #5 or 1 - #6 | 4 - #4, 4 - #5 or 2 - #6 | 8 - #4, 6 - #5 or 4 - #6 | 10 - #4, 8 - #5 or 6 - #6 | 12 - #4, 8 - #5 or 6 - #6 | 14 - #4, 10 - #5 or 6 - #6 | 16 - #4, 10 - #5 or 6 - #7 | 18 - #4, 12 - #5 or 6 - #7 |

- NOTES:
- Table 6B to be used in conjunction with Shear Wall Figures 1 to 4.
 - Where spaces contain "-" consult with a local licensed engineer.
 - Where more than one bar is shown use double mat for flexural reinforcement. See Figure 3 (or Figure 4 for 12" LOGIX).

www.logixicf.com

Good. Solid. Green.™

6 – 38

LOGIX®
INSULATED CONCRETE FORMS

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

LOGIX CANADIAN ENGINEERING REPORT

CONTENTS

- Introduction
- Structural Design & Performance
- Reinforcement Tables
- Figure 1 Crawl Space Reinforcement Requirements
- Below Grade Wall Tables
- Figures 2A, 2B, 2C and 2D, Below-grade wall sections
- Tables 1A, 1B, 1C and 1D, Below-grade Wall Minimum Vertical Reinforcement for LOGIX 6.25, 8, 10 and 12 inch, respectively
- Above Grade Wall Table
- Figures 3A, 3B and 3C, Above-grade wall sections
- Table 2, LOGIX Above-Grade Wall Minimum Reinforcement
- Lintel Tables
- Figure 4, Lintel Reinforcement
- Tables 3A, 3B, 3C, 3D and 3E, Lintel Reinforcement with Uniform Load for LOGIX 4, 6.25, 8, 10 and 12 inch, respectively.
- Tables 4A, 4B, 4C, 4D and 4E, Lintel Reinforcement with Concentrated Load for LOGIX 4, 6.25, 8, 10 and 12 inch, respectively.

Reviewed for projects constructed in the following provinces:

British Columbia, Alberta, Saskatchewan, Manitoba and Ontario

by:

Colinares Consulting....



ENGINEERING

THIS PAGE HAS BEEN INTENTIONALLY LEFT BLANK

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

INTRODUCTION

LOGIX walls are intended to be used both above and below grade, and can carry large vertical as well as lateral loads. They are particularly effective for residential, commercial and industrial buildings; providing excellent insulation as well as thermal mass and structural strength. They can be easily adapted to accommodate concrete floors and other “non-standard” building systems.

Construction must be in conformance with the LOGIX Design Manual, including assembly of formwork, bracing, accurate rebar positioning, concrete mix design and placement, and details for interconnection with the other building components.

STRUCTURAL DESIGN AND PERFORMANCE

The LOGIX Building System can be used for an infinite variety of building situations with proper engineering. This report, with its load tables and diagrams, is intended to assist with the structural design of buildings using the LOGIX system for the basement only, or continuing to a second floor and/or roof. Where unusual conditions are encountered, it is recommended that the user consult a designer who can evaluate the loadings to the various components and who can appreciate the limitations of “prescriptive” design under unusual conditions. Connection details have generally been excluded from this report because of the great variety of floor and roof systems that can be used with the Logix wall system. The designer should refer to the Logix Product Manual and the literature for the various proprietary products that are available for connections, which are an important part of the total design.

REINFORCEMENT TABLES

Above- and below-grade walls and lintels were developed using the design criteria of Part 4 of the National Building Code of Canada 2005, and CSA A23.3-04, Design of Concrete Structures.

The reinforcement tables allow for bar spacings common in residential construction. In addition, the above-grade wall reinforcement tables have been properly developed to include LOGIX with a 4 inch concrete core. This is provided to reflect the construction industry's common practice of using 4 inch concrete walls above-grade with both traditional concrete and ICF walls. This is further reflected by the fact that building codes in the United States (International Residential Code 2012) allows for larger bar spacings, and the use of ICF walls above-grade with concrete core thicknesses of 3.5 inches.

Building limitations used to develop Tables 1A to 1D, and Table 2 include:

Building perimeter = 24.384 m (80 ft) max x 12.192 m (40 ft) max
Roof clear span = 12.192 m (40 ft) max
Floor clear span = 6.096 m (20 ft) max
Number of stories above grade = 2 max
Number of stories below grade = 1


Tables 3A to 3E and Tables 4A to 4E provide lintel tables for factored uniform and concentrated loading conditions, respectively.

In addition, crawl space reinforcement requirements were developed and can be found in Figure 1.

More specific design assumptions and limitations are located with the corresponding reinforcement tables.

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

FIGURE 1 - CRAWL SPACE REINFORCEMENT REQUIREMENT



NOTES:

1. 4" LOGIX wall: $d = 2.5"$
6.25" LOGIX wall: $d = 4.375"$
8" LOGIX wall: $d = 6"$
10" LOGIX wall: $d = 8"$
12" LOGIX wall: $d = 10"$
2. Min. vertical rebar: use 10M @ max. 48" on center spacing for the following conditions (applicable to all LOGIX wall sizes):
Wall height: $\leq 4' - 10"$
Equivalent fluid density: $\leq 75 \text{ pcf } (12 \text{ kN/m}^3)$ w/ no surcharge.
3. Horizontal rebar (applicable to all LOGIX wall sizes):
10M @ 32" on center max spacing. Provide at least one 10M horizontal bar in bottom and top course.
4. For 12" LOGIX wall provide additional mat of 10M rebar near exterior side of wall. Vertical and horizontal rebar spacing to match spacing of interior rebar.

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

BELOW-GRADE WALL TABLES

NOTE FOR BELOW-GRADE WALL TABLES

LOGIX below-grade Tables 1A to 1D shall be used in conjunction with corresponding Figures 2A to 2D, the notes listed below, and the building limitations noted in the "Reinforcement Tables" section, which form the basis of these tables.

1. Tables do not consider seismic loads. For seismic load considerations refer to the Appendix in the Table of Contents. Factored snow load = 3.54 kPa
2. Horizontal rebar shall be 10M @ 32" o/c. Provide at least one 10M bar to be placed at the bottom course and top course.
3. Steel yield strength = 400MPa, 28 day concrete compressive strength = 20MPa
4. Deflection criteria = $L/240$
5. Assumed eccentricity = 3" (to account for loads on LOGIX Brick Ledge).
6. The basement walls must be supported at the top and bottom of the wall.
7. For light vehicles parked or travelling near the wall use reinforcement corresponding to 1 ft higher backfill.
8. Where spaces have been left blank, the corresponding bar size is presumed to be less economical and/or practical than that shown. Consult a local licensed engineer to determine proper design.
9. Provide two 15M bars (One 15M bar for 4" concrete core thickness) should be placed around all openings (along the vertical sides and bottom of opening), and extend a minimum of 2 ft beyond openings.
10. For walls with over 50% of height exposed to wind, also check rebar requirements for above-grade walls.
11. Carefully consider floor/wall connection details for lateral loads, especially with higher backfills, walkout basements, and active seismic areas.
12. Soil density is often referred to as "equivalent fluid density", and is the density of a liquid which would exert an equivalent horizontal load on a wall. The actual soil density is generally greater – ranging between 90 & 120pcf.
13. Consult a local licensed engineer for design of walls that fall outside the scope of the tables.




Fig 2A
Assumed typical flooring, wall & roof for Table 1A. Height & thickness of above-grade walls, floor & roof spans, including materials (i.e., wood frame, concrete, and cladding) can vary provided the total factored load on basement wall does not exceed 6 kips/ft.




Fig 2B
Assumed typical flooring, wall & roof for Table 1B. Height & thickness of above-grade walls, floor & roof spans, including materials (i.e., wood frame, concrete, and cladding) can vary provided the total factored load on basement wall does not exceed 7.5 kips/ft.




Fig 2C
Assumed typical flooring, wall & roof for Table 1C. Height & thickness of above-grade walls, floor & roof spans, including materials (i.e., wood frame, concrete, and cladding) can vary provided the total factored load on basement wall does not exceed 7.5 kips/ft.




Fig 2D
Assumed typical flooring, wall & roof for Table 1D. Height & thickness of above-grade walls, floor & roof spans, including materials (i.e., wood frame, concrete, and cladding) can vary provided the total factored load on basement wall does not exceed 8.3 kips/ft.

ENGINEERING

www.logixicf.com

Good. Solid. Green.™

6-43

LOGIX®
INSULATED CONCRETE FORMS

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 1A - LOGIX 6.25" BELOW-GRADE WALL MINIMUM VERTICAL REINFORCEMENT

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| Max. Height of Basement Wall, ft | Max. Unbalanced Backfill Height, ft | Vertical Bar Spacing, in. | | | | | | | | | | | | | | | |
|---|--|--|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|
| | | Maximum Equivalent Density 30pcf | | | | Maximum Equivalent Density 45pcf | | | | Maximum Equivalent Density 60pcf | | | | Maximum Equivalent Density 75pcf | | | |
| 8 | 4 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 |
| | 5 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 |
| | 6 | 16 | 40 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 | 8 | 16 | 32 | 48 |
| | 7 | 16 | 32 | 48 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 48 | 8 | 16 | 24 | 40 |
| | 8 | 12 | 24 | 40 | 48 | 8 | 16 | 24 | 48 | 8 | 16 | 24 | 32 | 6 | 12 | 16 | 24 |
| 9 | 4 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 |
| | 5 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 |
| | 6 | 16 | 40 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 48 |
| | 7 | 16 | 32 | 48 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 |
| | 8 | 12 | 24 | 40 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 | - | 8 | 16 | 24 |
| | 9 | 8 | 16 | 32 | 48 | 6 | 12 | 16 | 32 | - | 8 | 16 | 24 | - | 8 | 12 | 16 |
| 10 | 4 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 |
| | 5 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 |
| | 6 | 16 | 40 | 48 | 48 | 12 | 24 | 40 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 40 |
| | 7 | 16 | 24 | 40 | 48 | 8 | 16 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 |
| | 8 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 24 | - | 8 | 12 | 24 |
| | 9 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 | - | 8 | 12 | 16 | - | 6 | 8 | 16 |
| | 10 | 8 | 16 | 24 | 32 | - | 8 | 16 | 24 | - | 8 | 8 | 16 | - | 6 | 8 | 12 |
| 11 | 4 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 |
| | 5 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 |
| | 6 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 | 8 | 16 | 32 | 48 | 8 | 16 | 24 | 40 |
| | 7 | 12 | 24 | 40 | 48 | 8 | 16 | 24 | 48 | 8 | 16 | 16 | 32 | 6 | 12 | 16 | 24 |
| | 8 | 8 | 16 | 32 | 48 | 8 | 12 | 16 | 32 | 6 | 8 | 16 | 24 | - | 8 | 12 | 16 |
| | 9 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 24 | - | 8 | 12 | 16 | - | 6 | 8 | 16 |
| | 10 | 6 | 12 | 16 | 32 | - | 8 | 12 | 16 | - | 6 | 8 | 16 | - | - | 6 | 12 |
| | 11 | 6 | 12 | 16 | 24 | - | 6 | 8 | 16 | - | - | 8 | 12 | - | - | - | 8 |
| 12 | 4 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 |
| | 5 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 24 | 40 | 48 | 12 | 24 | 32 | 48 |
| | 6 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 | 8 | 16 | 24 | 48 | 8 | 16 | 24 | 40 |
| | 7 | 12 | 24 | 40 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 | 6 | 12 | 16 | 24 |
| | 8 | 8 | 16 | 24 | 48 | 6 | 12 | 16 | 32 | - | 8 | 16 | 24 | - | 8 | 12 | 16 |
| | 9 | 8 | 16 | 24 | 32 | - | 8 | 16 | 24 | - | 8 | 8 | 16 | - | 6 | 8 | 12 |
| | 10 | 6 | 12 | 16 | 24 | - | 8 | 12 | 16 | - | 6 | 8 | 12 | - | - | 6 | 8 |
| | 11 | - | 8 | 12 | 24 | - | 6 | 8 | 16 | - | - | 6 | 8 | - | - | - | - |
| | 12 | - | 8 | 12 | 16 | - | - | 8 | 12 | - | - | - | 6 | - | - | - | - |
| | | 10M | 15M | 20M | 25M | 10M | 15M | 20M | 25M | 10M | 15M | 20M | 25M | 10M | 15M | 20M | 25M |

Bar size

NOTES:

- Tables do not consider seismic loads. For seismic load considerations refer to the Appendix in the Table of Contents.
- Reinforcement to be placed on interior face of concrete wall. Effective depth of vertical rebar (exterior face of concrete to center of vertical rebar) = 4.375"
- Table 1A shall be read in conjunction with Fig 2A, and section "Notes for Below-grade Wall Tables."
- 1 ft = 0.3048 m, 1 in = 25.4 mm, 1 pcf = 16.02 kg/m³ = 0.157 kN/m³

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 1B - LOGIX 8" BELOW-GRADE WALL MINIMUM VERTICAL REINFORCEMENT

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| Max. Height of Basement Wall, ft | Max. Unbalanced Backfill Height, ft | Vertical Bar Spacing, in. | | | | | | | | | | | | | | | |
|---|--|--|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|
| | | Maximum Equivalent Density 30pcf | | | | Maximum Equivalent Density 45pcf | | | | Maximum Equivalent Density 60pcf | | | | Maximum Equivalent Density 75pcf | | | |
| 8 | 4-5 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 |
| | 6 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 32 | 48 | 48 |
| | 7 | 16 | 40 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 | 12 | 24 | 32 | 48 |
| | 8 | 16 | 40 | 48 | 48 | 12 | 24 | 40 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 48 |
| 9 | 4-5 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 |
| | 6 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 |
| | 7 | 16 | 40 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 | 8 | 16 | 32 | 48 |
| | 8 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 | 8 | 16 | 32 | 48 | 8 | 16 | 24 | 40 |
| 10 | 9 | 16 | 32 | 40 | 48 | 8 | 16 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 |
| | 4-5 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 |
| | 6 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 |
| | 7 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 48 |
| 11 | 8 | 16 | 32 | 48 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 40 | 8 | 16 | 16 | 32 |
| | 9 | 12 | 24 | 40 | 48 | 8 | 16 | 24 | 48 | 6 | 12 | 16 | 32 | 6 | 12 | 16 | 24 |
| | 10 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 24 | - | 8 | 12 | 24 |
| | 4-5 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 |
| 12 | 6 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 |
| | 7 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 40 |
| | 8 | 16 | 32 | 48 | 48 | 12 | 16 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 |
| | 9 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 | - | 8 | 16 | 24 |
| 14 | 10 | 8 | 16 | 32 | 48 | 6 | 12 | 16 | 32 | - | 8 | 16 | 24 | - | 8 | 12 | 16 |
| | 11 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 24 | - | 8 | 12 | 16 | - | 6 | 8 | 16 |
| | 4-5 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 |
| | 6 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 | 12 | 24 | 32 | 48 |
| 16 | 7 | 16 | 32 | 48 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 |
| | 8 | 12 | 24 | 40 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 | 6 | 12 | 16 | 24 |
| | 9 | 8 | 16 | 32 | 48 | 6 | 12 | 16 | 32 | - | 8 | 16 | 24 | - | 8 | 12 | 16 |
| | 10 | 8 | 16 | 24 | 40 | 6 | 8 | 16 | 24 | - | 8 | 12 | 16 | - | 6 | 8 | 16 |
| 18 | 11 | 6 | 12 | 16 | 32 | - | 8 | 12 | 16 | - | 6 | 8 | 16 | - | - | 8 | 12 |
| | 12 | 6 | 8 | 16 | 24 | - | 6 | 8 | 16 | - | - | 8 | 12 | - | - | 6 | 8 |
| | 13 | - | 8 | 12 | 24 | - | 6 | 8 | 12 | - | - | 6 | 8 | - | - | - | 8 |
| | 14 | - | 8 | 12 | 16 | - | - | 8 | 12 | - | - | - | 8 | - | - | - | 6 |
| 20 | 4-5 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 |
| | 6 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 | 8 | 16 | 32 | 48 |
| | 7 | 16 | 32 | 48 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 |
| | 8 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 | - | 8 | 16 | 24 |
| 22 | 9 | 8 | 16 | 24 | 48 | 6 | 12 | 16 | 32 | - | 8 | 12 | 24 | - | 8 | 8 | 16 |
| | 10 | 6 | 12 | 16 | 32 | - | 8 | 12 | 24 | - | 6 | 8 | 16 | - | 6 | 8 | 12 |
| | 11 | 6 | 12 | 16 | 24 | - | 8 | 12 | 16 | - | 6 | 8 | 12 | - | - | 6 | 8 |
| | 12 | - | 8 | 12 | 24 | - | 6 | 8 | 16 | - | - | 6 | 8 | - | - | - | 8 |
| 24 | 13 | - | 8 | 12 | 16 | - | - | 8 | 12 | - | - | - | 8 | - | - | - | 6 |
| | 14 | - | 6 | 8 | 16 | - | - | 6 | 8 | - | - | - | 6 | - | - | - | - |
| | 15 | - | 6 | 8 | 12 | - | - | - | 8 | - | - | - | - | - | - | - | - |
| | 16 | - | - | 6 | 12 | - | - | - | 6 | - | - | - | - | - | - | - | - |
| | | 10M | 15M | 20M | 25M | 10M | 15M | 20M | 25M | 10M | 15M | 20M | 25M | 10M | 15M | 20M | 25M |
| | | Bar size | | | | | | | | | | | | | | | |

- NOTES:**
- Tables do not consider seismic loads. For seismic load considerations refer to the Appendix in the Table of Contents.
 - Reinforcement to be placed on interior face of concrete wall. Effective depth of vertical rebar (exterior face of concrete to center of vertical rebar) = 6"
 - Table 1B shall be read in conjunction with Fig 2B, and section "Notes for Below-grade Wall Tables."
 - 1 ft = 0.3048 m, 1 in = 25.4 mm, 1 pcf = 16.02 kg/m³ = 0.157 kN/m³

ENGINEERING

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 1C - LOGIX 10" BELOW-GRADE WALL MINIMUM VERTICAL REINFORCEMENT

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| Max. Height of Basement Wall, ft | Max. Unbalanced Backfill Height, ft | Vertical Bar Spacing, in. | | | | | | | | | | | | | | | |
|---|--|--|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|
| | | Maximum Equivalent Density 30pcf | | | | Maximum Equivalent Density 45pcf | | | | Maximum Equivalent Density 60pcf | | | | Maximum Equivalent Density 75pcf | | | |
| | | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 |
| 14 | 4-5 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 |
| | 6 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 32 | 48 | 48 |
| | 7 | 16 | 40 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 | 12 | 24 | 32 | 48 |
| | 8 | 16 | 40 | 48 | 48 | 12 | 24 | 40 | 48 | 8 | 16 | 32 | 48 | 8 | 16 | 24 | 40 |
| | 9 | 16 | 32 | 40 | 48 | 8 | 16 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 |
| | 10 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 | - | 8 | 12 | 24 |
| | 11 | 8 | 16 | 24 | 48 | 6 | 12 | 16 | 32 | - | 8 | 12 | 24 | - | 8 | 12 | 16 |
| | 12 | 8 | 16 | 24 | 40 | 6 | 8 | 16 | 24 | - | 8 | 12 | 16 | - | 6 | 8 | 16 |
| | 13 | 6 | 12 | 16 | 32 | - | 8 | 12 | 24 | - | 6 | 8 | 16 | - | - | 8 | 12 |
| | 14 | 6 | 12 | 16 | 24 | - | 8 | 12 | 16 | - | 6 | 8 | 12 | - | - | 6 | 12 |
| 16 | 4-5 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 |
| | 6 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 |
| | 7 | 16 | 40 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 | 8 | 16 | 32 | 48 |
| | 8 | 16 | 32 | 48 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 48 | 8 | 16 | 24 | 40 |
| | 9 | 12 | 24 | 40 | 48 | 8 | 16 | 24 | 48 | 6 | 12 | 16 | 32 | 6 | 12 | 16 | 24 |
| | 10 | 8 | 16 | 32 | 48 | 8 | 12 | 16 | 32 | 6 | 12 | 16 | 24 | - | 8 | 12 | 16 |
| | 11 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 24 | - | 8 | 12 | 16 | - | 6 | 8 | 16 |
| | 12 | 6 | 12 | 16 | 32 | - | 8 | 12 | 24 | - | 6 | 8 | 16 | - | 6 | 8 | 12 |
| | 13 | 6 | 12 | 16 | 32 | - | 8 | 12 | 16 | - | 6 | 8 | 12 | - | - | 6 | 12 |
| | 14 | - | 8 | 16 | 24 | - | 6 | 8 | 16 | - | - | 8 | 12 | - | - | 6 | 8 |
| 18 | 4-5 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 |
| | 6 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 |
| | 7 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 48 |
| | 8 | 16 | 32 | 48 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 |
| | 9 | 12 | 24 | 40 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 | - | 8 | 16 | 24 |
| | 10 | 8 | 16 | 24 | 48 | 6 | 12 | 16 | 32 | - | 8 | 16 | 24 | - | 8 | 12 | 16 |
| | 11 | 8 | 16 | 24 | 40 | - | 8 | 16 | 24 | - | 8 | 12 | 16 | - | 6 | 8 | 16 |
| | 12 | 6 | 12 | 16 | 32 | - | 8 | 12 | 16 | - | 6 | 8 | 16 | - | - | 8 | 12 |
| | 13 | - | 8 | 16 | 24 | - | 6 | 8 | 16 | - | - | 8 | 12 | - | - | 6 | 8 |
| | 14 | - | 8 | 12 | 24 | - | 6 | 8 | 12 | - | - | 6 | 8 | - | - | - | 8 |
| 20 | 4-5 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 |
| | 6 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 |
| | 7 | 16 | 32 | 48 | 48 | 16 | 32 | 40 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 48 |
| | 8 | 16 | 32 | 48 | 48 | 8 | 16 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 |
| | 9 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 | - | 8 | 12 | 24 |
| | 10 | 8 | 16 | 24 | 48 | 6 | 12 | 16 | 32 | - | 8 | 12 | 24 | - | 8 | 8 | 16 |
| | 11 | 8 | 12 | 16 | 32 | - | 8 | 12 | 24 | - | 6 | 8 | 16 | - | 6 | 8 | 12 |
| | 12 | 6 | 12 | 16 | 24 | - | 8 | 12 | 16 | - | 6 | 8 | 12 | - | - | 6 | 8 |
| | 13 | - | 8 | 12 | 24 | - | 6 | 8 | 16 | - | - | 6 | 12 | - | - | - | 8 |
| | 14 | - | 8 | 12 | 16 | - | - | 8 | 12 | - | - | 6 | 8 | - | - | - | 6 |
| | 15 | - | 6 | 8 | 16 | - | - | 6 | 8 | - | - | - | 8 | - | - | - | 6 |
| | 16 | - | 6 | 8 | 12 | - | - | 6 | 8 | - | - | - | 6 | - | - | - | - |
| | 17 | - | - | 8 | 12 | - | - | - | 8 | - | - | - | - | - | - | - | - |
| | 18 | - | - | 6 | 8 | - | - | - | 6 | - | - | - | - | - | - | - | - |
| | 19 | - | - | 6 | 8 | - | - | - | 6 | - | - | - | - | - | - | - | - |
| | 20 | - | - | - | 8 | - | - | - | - | - | - | - | - | - | - | - | - |
| | | 10M | 15M | 20M | 25M | 10M | 15M | 20M | 25M | 10M | 15M | 20M | 25M | 10M | 15M | 20M | 25M |
| | | Bar size | | | | | | | | | | | | | | | |

NOTES:

- Tables do not consider seismic loads. For seismic load considerations refer to the Appendix in the Table of Contents.
- Reinforcement to be placed on interior face of concrete wall. Effective depth of vertical rebar (exterior face of concrete to center of vertical rebar = 8"
- Table 1C shall be read in conjunction with Fig 2C, and section "Notes for Below-grade Wall Tables."
- 1 ft = 0.3048 m, 1 in = 25.4 mm, 1 pcf = 16.02 kg/m³ = 0.157 kN/m³

www.logixcf.com

Good. Solid. Green.™

6 – 4 6



6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 1D - LOGIX 12" BELOW-GRADE WALL MINIMUM VERTICAL REINFORCEMENT

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| Max. Height of Basement Wall, ft | Max. Unbalanced Backfill Height, ft | Vertical Bar Spacing, in. | | | | | | | | | | | | | | | |
|---|--|--|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|
| | | Maximum Equivalent Density 30pcf | | | | Maximum Equivalent Density 45pcf | | | | Maximum Equivalent Density 60pcf | | | | Maximum Equivalent Density 75pcf | | | |
| 14 | 4-6 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 |
| | 7 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 |
| | 8 | 16 | 40 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 | 8 | 16 | 32 | 48 |
| | 9 | 16 | 40 | 48 | 48 | 12 | 24 | 40 | 48 | 8 | 16 | 32 | 48 | 8 | 16 | 24 | 40 |
| | 10 | 16 | 32 | 48 | 48 | 8 | 16 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 |
| | 11 | 12 | 24 | 40 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 | - | 8 | 16 | 24 |
| | 12 | 8 | 16 | 32 | 48 | 6 | 12 | 16 | 32 | - | 8 | 16 | 24 | - | 8 | 12 | 16 |
| | 13 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 | - | 8 | 12 | 16 | - | 6 | 8 | 16 |
| 16 | 14 | 8 | 16 | 24 | 40 | - | 8 | 16 | 24 | - | 8 | 12 | 16 | - | 6 | 8 | 16 |
| | 4-6 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 |
| | 7 | 16 | 40 | 48 | 48 | 16 | 40 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 |
| | 8 | 16 | 40 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 48 |
| | 9 | 16 | 32 | 48 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 48 | 8 | 16 | 16 | 32 |
| | 10 | 12 | 24 | 40 | 48 | 8 | 16 | 24 | 48 | 6 | 12 | 16 | 32 | 6 | 12 | 16 | 24 |
| | 11 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 24 | - | 8 | 12 | 24 |
| | 12 | 8 | 16 | 24 | 48 | 6 | 12 | 16 | 32 | - | 8 | 12 | 24 | - | 8 | 12 | 16 |
| | 13 | 8 | 16 | 24 | 40 | - | 8 | 16 | 24 | - | 8 | 12 | 16 | - | 6 | 8 | 16 |
| | 14 | 6 | 12 | 16 | 32 | - | 8 | 12 | 16 | - | 6 | 8 | 16 | - | - | 8 | 12 |
| 18 | 15 | 6 | 12 | 16 | 24 | - | 8 | 12 | 16 | - | 6 | 8 | 12 | - | - | 6 | 8 |
| | 16 | - | 8 | 16 | 24 | - | 6 | 8 | 16 | - | - | 8 | 12 | - | - | 6 | 8 |
| | 4-6 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 |
| | 7 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 |
| | 8 | 16 | 32 | 48 | 48 | 16 | 32 | 40 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 48 |
| | 9 | 16 | 32 | 48 | 48 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 |
| | 10 | 12 | 24 | 40 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 | - | 8 | 16 | 24 |
| | 11 | 8 | 16 | 32 | 48 | 6 | 12 | 16 | 32 | - | 8 | 16 | 24 | - | 8 | 12 | 16 |
| | 12 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 24 | - | 8 | 12 | 16 | - | 6 | 8 | 16 |
| | 13 | 6 | 12 | 16 | 32 | - | 8 | 12 | 24 | - | 6 | 8 | 16 | - | 6 | 8 | 12 |
| 20 | 14 | 6 | 12 | 16 | 32 | - | 8 | 12 | 16 | - | 6 | 8 | 12 | - | - | 6 | 12 |
| | 15 | - | 8 | 16 | 24 | - | 6 | 8 | 16 | - | - | 8 | 12 | - | - | 6 | 8 |
| | 16 | - | 8 | 12 | 24 | - | 6 | 8 | 12 | - | - | 6 | 8 | - | - | - | 8 |
| | 17 | - | 8 | 12 | 16 | - | - | 8 | 12 | - | - | 6 | 8 | - | - | - | 6 |
| | 18 | - | 6 | 8 | 16 | - | - | 6 | 12 | - | - | - | 8 | - | - | - | 6 |
| | 4-6 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 |
| | 7 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 16 | 32 | 48 | 48 | 12 | 24 | 32 | 48 |
| | 8 | 16 | 32 | 48 | 48 | 12 | 24 | 40 | 48 | 8 | 16 | 32 | 48 | 8 | 16 | 24 | 40 |
| | 9 | 16 | 32 | 48 | 48 | 8 | 16 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 |
| | 10 | 12 | 24 | 32 | 48 | 8 | 16 | 24 | 40 | 6 | 12 | 16 | 32 | - | 8 | 16 | 24 |
| | 11 | 8 | 16 | 24 | 48 | 6 | 12 | 16 | 32 | - | 8 | 12 | 24 | - | 8 | 12 | 16 |
| | 12 | 8 | 16 | 24 | 40 | - | 8 | 16 | 24 | - | 8 | 12 | 16 | - | 6 | 8 | 16 |
| | 13 | 6 | 12 | 16 | 32 | - | 8 | 12 | 16 | - | 6 | 8 | 16 | - | - | 8 | 12 |
| | 14 | 6 | 8 | 16 | 24 | - | 6 | 8 | 16 | - | - | 8 | 12 | - | - | 6 | 8 |
| | 15 | - | 8 | 12 | 24 | - | 6 | 8 | 16 | - | - | 6 | 8 | - | - | - | 8 |
| | 16 | - | 8 | 12 | 16 | - | - | 8 | 12 | - | - | 6 | 8 | - | - | - | 6 |
| | 17 | - | 6 | 8 | 16 | - | - | 6 | 12 | - | - | - | 8 | - | - | - | 6 |
| | 18 | - | 6 | 8 | 16 | - | - | 6 | 8 | - | - | - | 6 | - | - | - | - |
| | 19 | - | 6 | 8 | 12 | - | - | - | 8 | - | - | - | 6 | - | - | - | - |
| | 20 | - | - | 8 | 12 | - | - | - | 8 | - | - | - | - | - | - | - | - |
| | | 10M | 15M | 20M | 25M | 10M | 15M | 20M | 25M | 10M | 15M | 20M | 25M | 10M | 15M | 20M | 25M |

NOTES:

- Tables do not consider seismic loads. For seismic load considerations refer to the Appendix in the Table of Contents.
- Effective depth (out face of concrete to center of vertical rebar = 10"
- Provide additional mat of rebar near exterior face of concrete surface:
 - Horizontal = 10M @ 32" o/c.
 - Vertical = 10M to match vertical rebar spacing
- Table 1D shall be read in conjunction with Fig 2D, and section "Notes for Below-grade Wall Tables."
- 1 ft = 0.3048 m, 1 in = 25.4 mm, 1 pcf = 16.02 kg/m³ = 0.157 kN/m³

www.logixcf.com

Good. Solid. Green.™

6-47



REPRINTED 2013

Rev. Sep 23/09

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

ABOVE-GRADE WALL TABLE

LOGIX above-grade tables cover three different construction types:

- One storey LOGIX supporting wood roof frame (Fig. 3A)
- One storey LOGIX supporting 2nd storey wood frame plus wood roof frame (Fig. 3B)
- Two storey LOGIX supporting wood roof frame (Fig. 3C)

For two story buildings, the height of the second story wall is equal to the height of the first story provided the height of the first storey wall is not more than 12 feet high.

For first story walls greater than 12 feet high, the second story wall height is a maximum of 12 feet.

With the exception of 4" LOGIX, the second story concrete wall thickness is one size less than the concrete core thickness used for the first storey wall.

ENGINEERING




Fig 3A
Assumed typical flooring, wall & roof section for Table 3, LOGIX Supporting Roof Only.




Fig 3B
Assumed typical flooring, wall & roof section for Table 3, LOGIX Supporting 2nd Story Wood Frame & Roof Structure.




Fig 3C
Assumed typical flooring, wall & roof section for Table 3, LOGIX Supporting 2nd Story LOGIX & Roof Structure.

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

NOTES FOR ABOVE-GRADE WALL TABLES

The above-grade tables shall be used in conjunction with the notes listed below, the building limitations noted in the "Reinforcement Tables" section, and Figures 3A to 3B, which form the basis of this table.

1. 28 day concrete compressive strength = 20 MPa. Steel yield strength = 400 MPa.
2. Vertical rebar to be placed in middle of wall. Minimum horizontal rebar shall be:
 - 4" & 6.25" LOGIX = 10M @ 32" o/c
 - 8", 10" & 12" LOGIX = 10M @ 16" o/c.

Provide additional mat of rebar for 12" LOGIX

- Horizontal rebar = 10M @ 16" o/c

- Vertical rebar = to match vertical bar spacing in **Table 2**

3. Provide at least one 10M bar to be placed at the bottom course and top course.
4. Max roof clear span = 40 ft. Max floor clear span = 20 ft.
5. Deflection criteria = L/240
6. Assumed eccentricity = 1".
7. Provide two 15M bars (One 15M bar for 4" concrete core thickness) to be placed around all openings (along the vertical sides and bottom of opening), and extend a minimum of 2 ft beyond openings.
8. The walls must be supported at the top and bottom of the wall.
9. Where spaces have been left blank, the corresponding bar size is presumed to be less economical and/or practical than that shown. Consult a local licensed engineer to determine proper design.
10. Carefully consider floor/wall connection details for lateral loads, especially with higher backfills, walkout basements, and active seismic areas.
11. Consult a local licensed engineer for design of walls that fall outside the scope of the above table.
12. 1 psf = 0.0479 kPa.
13. Governing load case is predominantly wind loading. Factored wind loading applicable by Provinces:

British Columbia: 35psf

Alberta: 40 psf

Saskatchewan: 30psf

Manitoba: 30psf

Ontario: 25psf

Quebec: 45psf

New Brunswick: 35psf

Nova Scotia: 35psf

New Foundland: 55psf

Prince Edward Island: 35psf

ENGINEERING

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 2 - LOGIX ABOVE-GRADE WALL MINIMUM VERTICAL REINFORCEMENT

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

LOGIX ABOVE-GRADE WALLS - VERTICAL REINFORCEMENT SPACING, in.

| Ground Floor LOGIX Supporting Roof Only | | | | | | | | | | | | | | | | | | | | | | | | |
|---|-------------------------|----|----|----|----|----|----------------------------|----|----|----|----|----|-------------------------|----|----|----|----|----|--------------------------|----|----|----|----|----|
| Wall Height, ft | 4" LOGIX Wall Thickness | | | | | | 6.25" LOGIX Wall Thickness | | | | | | 8" LOGIX Wall Thickness | | | | | | 10" LOGIX Wall Thickness | | | | | |
| | Factored Wind Load, psf | | | | | | Factored Wind Load, psf | | | | | | Factored Wind Load, psf | | | | | | Factored Wind Load, psf | | | | | |
| | 25 | 30 | 35 | 40 | 45 | 55 | 25 | 30 | 35 | 40 | 45 | 55 | 25 | 30 | 35 | 40 | 45 | 55 | 25 | 30 | 35 | 40 | 45 | 55 |
| 8 | 48 | 48 | 48 | 48 | 40 | 32 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| 9 | 48 | 48 | 40 | 40 | 32 | 24 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| 10 | 48 | 40 | 32 | 32 | 24 | 16 | 48 | 48 | 48 | 48 | 48 | 40 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| 12 | 32 | 24 | 24 | 16 | 16 | 12 | 48 | 48 | 40 | 40 | 32 | 24 | 48 | 48 | 48 | 48 | 32 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| 14 | 16 | 16 | 12 | 12 | 8 | 8 | 32 | 32 | 32 | 24 | 24 | 16 | 40 | 40 | 40 | 32 | 32 | 24 | 40 | 40 | 40 | 40 | 40 | 32 |
| 16 | 12 | 12 | 8 | 6 | - | - | 24 | 24 | 24 | 16 | 16 | 12 | 24 | 24 | 24 | 24 | 24 | 16 | 24 | 24 | 24 | 24 | 24 | 24 |
| 18 | 6 | 6 | - | - | - | - | 16 | 16 | 16 | 16 | 12 | 8 | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 |
| 20 | - | - | - | - | - | - | 8 | 8 | 8 | 8 | 8 | 8 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 |

| Ground Floor LOGIX Supporting 2nd Storey Wood Frame & Roof Structure | | | | | | | | | | | | | | | | | | | | | | | | |
|--|-------------------------|----|----|----|----|----|----------------------------|----|----|----|----|----|-------------------------|----|----|----|----|----|--------------------------|----|----|----|----|----|
| Wall Height, ft | 4" LOGIX Wall Thickness | | | | | | 6.25" LOGIX Wall Thickness | | | | | | 8" LOGIX Wall Thickness | | | | | | 10" LOGIX Wall Thickness | | | | | |
| | Factored Wind Load, psf | | | | | | Factored Wind Load, psf | | | | | | Factored Wind Load, psf | | | | | | Factored Wind Load, psf | | | | | |
| | 25 | 30 | 35 | 40 | 45 | 55 | 25 | 30 | 35 | 40 | 45 | 55 | 25 | 30 | 35 | 40 | 45 | 55 | 25 | 30 | 35 | 40 | 45 | 55 |
| 8 | 40 | 40 | 40 | 40 | 40 | 32 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| 9 | 32 | 32 | 32 | 32 | 32 | 24 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| 10 | 32 | 32 | 32 | 24 | 24 | 16 | 40 | 40 | 40 | 40 | 40 | 40 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 | 48 |
| 12 | 16 | 16 | 16 | 16 | 12 | 8 | 32 | 32 | 32 | 32 | 32 | 24 | 40 | 40 | 40 | 40 | 40 | 32 | 40 | 40 | 40 | 40 | 40 | 40 |
| 14 | 8 | 8 | 8 | 8 | 6 | - | 24 | 24 | 24 | 24 | 16 | 16 | 32 | 32 | 32 | 32 | 32 | 24 | 32 | 32 | 32 | 32 | 32 | 32 |
| 16 | - | - | - | - | - | - | 16 | 16 | 16 | 16 | 16 | 12 | 16 | 16 | 16 | 16 | 16 | 16 | 24 | 24 | 24 | 24 | 24 | 24 |
| 18 | - | - | - | - | - | - | 8 | 8 | 8 | 8 | 8 | 8 | 12 | 12 | 12 | 12 | 12 | 12 | 16 | 16 | 16 | 16 | 16 | 16 |
| 20 | - | - | - | - | - | - | 6 | 6 | 6 | 6 | 6 | 6 | 8 | 8 | 8 | 8 | 8 | 8 | 12 | 12 | 12 | 12 | 12 | 12 |

| Ground Floor LOGIX Supporting 2nd Storey LOGIX & Roof Structure | | | | | | | | | | | | | | | | | | | | | | | | |
|---|-------------------------|----|----|----|----|----|----------------------------|----|----|----|----|----|-------------------------|----|----|----|----|----|--------------------------|----|----|----|----|----|
| Wall Height, ft | 4" LOGIX Wall Thickness | | | | | | 6.25" LOGIX Wall Thickness | | | | | | 8" LOGIX Wall Thickness | | | | | | 10" LOGIX Wall Thickness | | | | | |
| | Factored Wind Load, psf | | | | | | Factored Wind Load, psf | | | | | | Factored Wind Load, psf | | | | | | Factored Wind Load, psf | | | | | |
| | 25 | 30 | 35 | 40 | 45 | 55 | 25 | 30 | 35 | 40 | 45 | 55 | 25 | 30 | 35 | 40 | 45 | 55 | 25 | 30 | 35 | 40 | 45 | 55 |
| 8 | 24 | 24 | 24 | 24 | 24 | 24 | 40 | 40 | 40 | 40 | 40 | 40 | 40 | 40 | 40 | 40 | 40 | 40 | 40 | 40 | 40 | 40 | 40 | 40 |
| 9 | 24 | 24 | 24 | 24 | 24 | 16 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 |
| 10 | 24 | 24 | 24 | 16 | 16 | 16 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 32 |
| 12 | 12 | 12 | 12 | 12 | 8 | 8 | 24 | 24 | 24 | 24 | 24 | 24 | 24 | 24 | 24 | 24 | 24 | 24 | 32 | 32 | 32 | 32 | 32 | 32 |
| 14 | - | - | - | - | - | - | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 |
| 16 | - | - | - | - | - | - | 8 | 8 | 8 | 8 | 8 | 8 | 12 | 12 | 12 | 12 | 12 | 12 | 16 | 16 | 16 | 16 | 16 | 16 |
| 18 | - | - | - | - | - | - | 6 | 6 | 6 | 6 | 6 | 6 | 8 | 8 | 8 | 8 | 8 | 8 | 12 | 12 | 12 | 12 | 12 | 12 |
| 20 | - | - | - | - | - | - | - | - | - | - | - | - | 6 | 6 | 6 | 6 | 6 | 6 | 8 | 8 | 8 | 8 | 8 | 8 |

NOTES:

1. Table 2 must be used in conjunction with the notes listed under "Notes For Above-Grade Wall Table".
2. Vertical bar spacing is for 15M rebar. 10M rebar can be substituted provided the spacing is multiplied by 0.5. Spacing shall be no more than 48 inches on center.
3. See "Notes For Above-Grade Wall Table" for wind loading applicable by Provinces.
4. 1 psf = 0.0479 kPa, 1" = 25.4 mm, 1 ft = 0.3048 m

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

LINTEL TABLES




Fig 4
Lintel reinforcement

The lintel tables cover a wide range of uniform and concentrated load conditions, and span lengths. The depth of the lintels range from 8 inch to 30 inches. Uniform and concentrated loading are considered to be concentric and centered on the lintel. Uniform loads act along the entire lintel span, such as from roof trusses at 2 ft spacing. Concentrated load lintel tables consider only a single concentrated load acting anywhere along the lintel span. In addition, the lintel tables do not consider uniform and concentrated loads to act simultaneously on the lintel.

The following notes are common to both uniform and concentrated load lintel tables:

1. 28 day concrete compressive strength = 20 MPa. Steel yield strength = 400 MPa.
2. Stirrups are D9.5 wire or 10M bars, bent as shown, and conforming to CSA -A23.1.
3. Shaded areas of the lintel tables require reinforcement, except for length Z.
4. Dimension D is to the concrete surface, not counting bucks or top plate.
5. Bottom steel must extend a min. 2 ft beyond opening, and no splices are permitted.
6. Deflection is limited to $L/360$, not considering long term effects. Long term deflection could be twice the short term depending on the nature of the load.
7. Seismic and wind loads are not considered.
8. Shear planes are not interrupted by embedded joists.
9. Top of lintel is assumed to be laterally restrained.

These tables should only be used if the above conditions are met. For other conditions, consult a structural Engineer.

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 3A - LOGIX 4" LINTEL REINFORCEMENT WITH UNIFORM LOAD

Where not shown otherwise, bottom steel is 1-15M

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | |
|---------------------------------|------------------------------|-----|------|------|------|------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | | | |
| 16 | | | | | | |
| 18 | | | | | | |
| 20 | | | | | | |
| No stirrup distance, Z (in.) | 47 | 25 | 17 | 13 | 10 | 9 |

| s=4", D=10" | | | | | | |
|---------------------------------|------------------------------|-----|------|------|------|------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | | | |
| 16 | | | | | | |
| 18 | | | | | | |
| 20 | | | | | | |
| No stirrup distance, Z (in.) | 58 | 31 | 21 | 16 | 13 | 11 |

| s=5", D=12" | | | | | | |
|---------------------------------|------------------------------|-----|------|------|------|------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | | | |
| 16 | | | | | | |
| 18 | | | | | | |
| 20 | | | | | | |
| No stirrup distance, Z (in.) | 68 | 36 | 25 | 19 | 15 | 13 |

| s=7", D=16" | | | | | | |
|---------------------------------|------------------------------|-----|------|------|------|------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | | | |
| 16 | | | | | | |
| 18 | | | | | | |
| 20 | | | | | | |
| No stirrup distance, Z (in.) | 91 | 50 | 34 | 26 | 21 | 18 |

| s=9", D=20" | | | | | | |
|---------------------------------|------------------------------|-----|------|------|------|------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | | | |
| 16 | | | | | | |
| 18 | | | | | | |
| 20 | | | | | | |
| No stirrup distance, Z (in.) | 113 | 63 | 44 | 34 | 27 | 23 |

| s=11", D=24" | | | | | | |
|---------------------------------|------------------------------|-----|------|------|------|------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | | | |
| 16 | | | | | | |
| 18 | | | | | | |
| 20 | | | | | | |
| No stirrup distance, Z (in.) | | 76 | 53 | 41 | 33 | 28 |

Notes:

- Where not shown otherwise, bottom steel is 1-15M
- Table is to be read in conjunction w/ Fig 4.
- Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
- Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to Fig 4.
- Factored Uniform Load includes 1.25, and 1.5 for dead and live load, respectively. For example, (1.25*dead load)+(1.5*live load)

| s=14", D=30" | | | | | | |
|---------------------------------|------------------------------|-----|------|------|------|------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | | | |
| 16 | | | | | | |
| 18 | | | | | | |
| 20 | | | | | | |
| No stirrup distance, Z (in.) | | 94 | 66 | 51 | 42 | 35 |

www.logixcf.com

Good. Solid. Green.™

6 – 52

LOGIX®
INSULATED CONCRETE FORMS

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 3B - LOGIX 6.25" LINTEL REINFORCEMENT WITH UNIFORM LOAD

Where not shown otherwise, bottom steel is 1-15M

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | 1 - 20M | 1 - 20M |
| 6 | | | | 1 - 20M | 2 - 15M | - |
| 7 | | | 1 - 20M | - | - | - |
| 8 | | 1 - 20M | - | - | - | - |
| 9 | | - | - | - | - | - |
| 10 | 1 - 20M | - | - | - | - | - |
| 12 | - | - | - | - | - | - |
| 14 | - | - | - | - | - | - |
| 16 | - | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | 38 | 26 | 20 | 16 | 13 |

| s=4", D=10" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | 1 - 20M | 1 - 20M |
| 7 | | | | 1 - 20M | 2 - 15M | 1 - 25M |
| 8 | | | 1 - 20M | 2 - 15M | 1 - 25M | - |
| 9 | | 1 - 20M | 2 - 15M | 1 - 25M | - | - |
| 10 | | 1 - 20M | 1 - 25M | - | - | - |
| 12 | 1 - 20M | - | - | - | - | - |
| 14 | - | - | - | - | - | - |
| 16 | - | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | 46 | 32 | 24 | 20 | 17 |

| s=5", D=12" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | 1 - 20M |
| 7 | | | | | 1 - 20M | 1 - 20M |
| 8 | | | | 1 - 20M | 2 - 15M | 2 - 15M |
| 9 | | | 1 - 20M | 2 - 15M | 2 - 20M | 2 - 20M |
| 10 | | 1 - 20M | 2 - 15M | 2 - 20M | 2 - 20M | - |
| 12 | | 2 - 15M | 2 - 20M | - | - | - |
| 14 | 1 - 20M | 2 - 20M | - | - | - | - |
| 16 | 2 - 20M | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | 55 | 38 | 29 | 23 | 20 |

| s=7", D=16" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | 1 - 20M | 1 - 20M |
| 9 | | | | | 1 - 20M | 2 - 15M |
| 10 | | | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 20M |
| 12 | | 1 - 20M | 2 - 15M | 2 - 20M | 2 - 20M | - |
| 14 | | 1 - 20M | 2 - 20M | 2 - 20M | - | - |
| 16 | 1 - 20M | 2 - 15M | - | - | - | - |
| 18 | 1 - 20M | 2 - 20M | - | - | - | - |
| 20 | 2 - 15M | - | - | - | - | - |
| No stirrup distance, Z (in.) | | 74 | 52 | 40 | 32 | 27 |

| s=9", D=20" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | 1 - 20M | 1 - 20M |
| 10 | | | | 1 - 20M | 1 - 20M | 2 - 15M |
| 12 | | | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 20M |
| 14 | | 1 - 20M | 2 - 15M | 2 - 20M | 2 - 20M | - |
| 16 | | 1 - 20M | 2 - 20M | 2 - 20M | - | - |
| 18 | 1 - 20M | 2 - 15M | 2 - 20M | - | - | - |
| 20 | 1 - 20M | 2 - 20M | - | - | - | - |
| No stirrup distance, Z (in.) | | 93 | 66 | 51 | 41 | 35 |

| s=11", D=24" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | 1 - 20M | 1 - 20M |
| 12 | | | | 1 - 20M | 2 - 15M | 2 - 15M |
| 14 | | | 1 - 20M | 2 - 15M | 2 - 20M | 2 - 20M |
| 16 | | 1 - 20M | 2 - 15M | 2 - 20M | 2 - 20M | - |
| 18 | | 2 - 15M | 2 - 20M | 2 - 20M | - | - |
| 20 | 1 - 20M | 2 - 15M | 2 - 20M | - | - | - |
| No stirrup distance, Z (in.) | | 110 | 79 | 61 | 50 | 42 |

| s=14", D=30" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | 1 - 20M | 1 - 20M |
| 14 | | | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M |
| 16 | | | 1 - 20M | 2 - 15M | 2 - 20M | 2 - 20M |
| 18 | | 1 - 20M | 2 - 15M | 2 - 20M | 2 - 20M | - |
| 20 | | 2 - 15M | 2 - 20M | 2 - 20M | - | - |
| No stirrup distance, Z (in.) | | | 97 | 76 | 63 | 53 |

Notes:

- Where not shown otherwise, bottom steel is 1-15M
- Table is to be read in conjunction w/ Fig 4.
- Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
- Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to Fig 4.
- Factored Uniform Load includes 1.25, and 1.5 for dead and live load, respectively. For example, (1.25*dead load)+(1.5*live load)

www.logixicf.com

Good. Solid. Green.™

6 – 53

LOGIX®
INSULATED CONCRETE FORMS

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 3C - LOGIX 8" LINTEL REINFORCEMENT WITH UNIFORM LOAD

Where not shown otherwise, bottom steel is 2-15M

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | |
|---------------------------------|------------------------------|-----|------|------|------|------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | | | |
| 16 | | | | | | |
| 18 | | | | | | |
| 20 | | | | | | |
| No stirrup distance, Z (in.) | | 47 | 33 | 25 | 20 | 17 |

| s=4", D=10" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | 2 - 20M | 2 - 20M |
| 9 | | | | 2 - 20M | 2 - 20M | - |
| 10 | | | 2 - 20M | - | - | - |
| 12 | | 2 - 20M | - | - | - | - |
| 14 | 2 - 20M | - | - | - | - | - |
| 16 | - | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | 58 | 40 | 31 | 25 | 21 |

| s=5", D=12" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | 2 - 20M | 2 - 20M |
| 10 | | | 2 - 20M | 2 - 20M | 2 - 20M | - |
| 12 | | 2 - 20M | - | - | - | - |
| 14 | | - | - | - | - | - |
| 16 | | - | - | - | - | - |
| 18 | | - | - | - | - | - |
| 20 | | - | - | - | - | - |
| No stirrup distance, Z (in.) | | 68 | 47 | 36 | 30 | 25 |

| s=7", D=16" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | 2 - 20M |
| 12 | | | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M |
| 14 | | | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M |
| 16 | | | 2 - 20M | 2 - 25M | - | - |
| 18 | | 2 - 20M | 2 - 25M | - | - | - |
| 20 | | 2 - 25M | - | - | - | - |
| No stirrup distance, Z (in.) | | 91 | 65 | 50 | 41 | 34 |

| s=9", D=20" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | 2 - 20M |
| 14 | | | | 2 - 20M | 2 - 20M | 2 - 25M |
| 16 | | | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M |
| 18 | | | 2 - 20M | 2 - 25M | 2 - 25M | - |
| 20 | | 2 - 20M | 2 - 25M | 2 - 25M | - | - |
| No stirrup distance, Z (in.) | | 113 | 81 | 63 | 52 | 44 |

| s=11", D=24" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | | 2 - 20M | 2 - 20M |
| 16 | | | | 2 - 20M | 2 - 20M | 2 - 25M |
| 18 | | | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M |
| 20 | | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M | - |
| No stirrup distance, Z (in.) | | | 97 | 76 | 63 | 53 |

Notes:

- Where not shown otherwise, bottom steel is 2-15M
- Table is to be read in conjunction w/ Fig 4.
- Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
- Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to Fig 4.
- Factored Uniform Load includes 1.25, and 1.5 for dead and live load, respectively. For example, (1.25*dead load)+(1.5*live load)

ENGINEERING

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 3D - LOGIX 10" LINTEL REINFORCEMENT WITH UNIFORM LOAD

Where not shown otherwise, bottom steel is 2-15M

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | |
|---------------------------------|------------------------------|-----|------|------|---------|------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | 2 - 20M | - |
| 8 | | | | - | - | - |
| 9 | | | - | - | - | - |
| 10 | | - | - | - | - | - |
| 12 | 2 - 20M | - | - | - | - | - |
| 14 | - | - | - | - | - | - |
| 16 | - | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | | 40 | 31 | 25 | 21 |

| s=4", D=10" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | 2 - 20M | 2 - 20M |
| 9 | | | | 2 - 20M | 2 - 20M | - |
| 10 | | | 2 - 20M | - | - | - |
| 12 | | 2 - 20M | - | - | - | - |
| 14 | | - | - | - | - | - |
| 16 | - | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | 70 | 49 | 38 | 31 | 26 |

| s=5", D=12" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | 2 - 20M | 2 - 20M |
| 10 | | | | 2 - 20M | 2 - 20M | 2 - 25M |
| 12 | | | 2 - 20M | 2 - 25M | 2 - 25M | - |
| 14 | | 2 - 20M | 2 - 25M | - | - | - |
| 16 | | 2 - 25M | - | - | - | - |
| 18 | 2 - 25M | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | 82 | 58 | 45 | 36 | 31 |

| s=7", D=16" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | 2 - 20M |
| 12 | | | | 2 - 20M | 2 - 20M | 2 - 25M |
| 14 | | | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M |
| 16 | | 2 - 20M | 2 - 20M | 2 - 25M | - | - |
| 18 | | 2 - 20M | 2 - 25M | - | - | - |
| 20 | | 2 - 25M | - | - | - | - |
| No stirrup distance, Z (in.) | | 109 | 78 | 61 | 50 | 42 |

| s=9", D=20" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | 2 - 20M |
| 14 | | | | 2 - 20M | 2 - 20M | 2 - 25M |
| 16 | | | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M |
| 18 | | 2 - 20M | 2 - 25M | 2 - 25M | 2 - 25M | - |
| 20 | | 2 - 20M | 2 - 25M | 2 - 25M | - | - |
| No stirrup distance, Z (in.) | | | 98 | 77 | 63 | 54 |

| s=11", D=24" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | | 2 - 20M | 2 - 20M |
| 16 | | | | 2 - 20M | 2 - 20M | 2 - 25M |
| 18 | | | 2 - 20M | 2 - 25M | 2 - 25M | 2 - 25M |
| 20 | | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M | - |
| No stirrup distance, Z (in.) | | | 116 | 92 | 76 | 65 |

| s=14", D=30" | | | | | | |
|---------------------------------|------------------------------|-----|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | | | 2 - 20M |
| 16 | | | | | 2 - 20M | 2 - 20M |
| 18 | | | | 2 - 20M | 2 - 20M | 2 - 25M |
| 20 | | | 2 - 20M | 2 - 25M | 2 - 25M | 2 - 25M |
| No stirrup distance, Z (in.) | | | | 113 | 94 | 81 |

Notes:

- Where not shown otherwise, bottom steel is 2-15M
- Table is to be read in conjunction w/ Fig 4.
- Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
- Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to Fig 4.
- Factored Uniform Load includes 1.25, and 1.5 for dead and live load, respectively. For example, (1.25*dead load)+(1.5*live load)

www.logixicf.com

Good. Solid. Green.™

6 – 5 5

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

ENGINEERING

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 3E - LOGIX 12" LINTEL REINFORCEMENT WITH UNIFORM LOAD

Where not shown otherwise, bottom steel is 2-15M

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | |
|---------------------------------|------------------------------|---------|------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | 2 - 20M | 2 - 20M |
| 8 | | | | 2 - 20M | - | - |
| 9 | | | | - | - | - |
| 10 | | 2 - 20M | - | - | - | - |
| 12 | 2 - 20M | - | - | - | - | - |
| 14 | - | - | - | - | - | - |
| 16 | - | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | | 47 | 36 | 30 | 25 |

| s=4", D=10" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | 2 - 20M | 2 - 20M |
| 9 | | | | 2 - 20M | 2 - 20M | 2 - 25M |
| 10 | | | 2 - 20M | 2 - 25M | 2 - 25M | - |
| 12 | | 2 - 20M | 2 - 25M | - | - | - |
| 14 | | - | - | - | - | - |
| 16 | 2 - 25M | - | - | - | - | - |
| 18 | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | | 58 | 45 | 36 | 31 |

| s=5", D=12" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | 2 - 20M | 2 - 20M |
| 10 | | | | 2 - 20M | 2 - 20M | 2 - 25M |
| 12 | | | 2 - 20M | 2 - 25M | 2 - 25M | - |
| 14 | | 2 - 20M | 2 - 25M | - | - | - |
| 16 | | 2 - 25M | - | - | - | - |
| 18 | 2 - 25M | - | - | - | - | - |
| 20 | - | - | - | - | - | - |
| No stirrup distance, Z (in.) | | 95 | 68 | 53 | 43 | 36 |

| s=7", D=16" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | 2 - 20M |
| 12 | | | | 2 - 20M | 2 - 20M | 2 - 25M |
| 14 | | | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M |
| 16 | | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M | - |
| 18 | | 2 - 20M | 2 - 25M | - | - | - |
| 20 | 2 - 20M | 2 - 25M | - | - | - | - |
| No stirrup distance, Z (in.) | | | 91 | 72 | 59 | 50 |

| s=9", D=20" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | 2 - 20M |
| 14 | | | | 2 - 20M | 2 - 20M | 2 - 25M |
| 16 | | | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M |
| 18 | | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M | - |
| 20 | | 2 - 20M | 2 - 25M | 2 - 25M | - | - |
| No stirrup distance, Z (in.) | | | 113 | 90 | 74 | 63 |

| s=11", D=24" | | | | | | |
|---------------------------------|------------------------------|---------|---------|---------|---------|---------|
| Opening ft | Factored Uniform Load, lb/ft | | | | | |
| | 400 | 800 | 1200 | 1600 | 2000 | 2400 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | | 2 - 20M | 2 - 20M |
| 16 | | | | 2 - 20M | 2 - 20M | 2 - 25M |
| 18 | | | 2 - 20M | 2 - 25M | 2 - 25M | 2 - 25M |
| 20 | | 2 - 20M | 2 - 25M | 2 - 25M | 2 - 25M | - |
| No stirrup distance, Z (in.) | | | | 107 | 89 | 76 |

Notes:

- Where not shown otherwise, bottom steel is 2-15M
- Table is to be read in conjunction w/ Fig 4.
- Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
- Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to Fig 4.
- Factored Uniform Load includes 1.25, and 1.5 for dead and live load, respectively. For example, (1.25*dead load)+(1.5*live load)

Good. Solid. Green.™

www.logixcf.com

6 – 5 6

LOGIX®
INSULATED CONCRETE FORMS

Rev. Sep 23/09

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 4A - LOGIX 4" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD

Where not shown otherwise, bottom steel is 1-15M

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3 | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | |
| 16 | | | | | | | | | | | | | | | | |
| 18 | | | | | | | | | | | | | | | | |
| 20 | | | | | | | | | | | | | | | | |

| s=4", D=10" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3 | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | |
| 16 | | | | | | | | | | | | | | | | |
| 18 | | | | | | | | | | | | | | | | |
| 20 | | | | | | | | | | | | | | | | |

| s=5", D=12" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3 | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | |
| 16 | | | | | | | | | | | | | | | | |
| 18 | | | | | | | | | | | | | | | | |
| 20 | | | | | | | | | | | | | | | | |

| s=7", D=16" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3 | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | |
| 16 | | | | | | | | | | | | | | | | |
| 18 | | | | | | | | | | | | | | | | |
| 20 | | | | | | | | | | | | | | | | |

ENGINEERING

Good. Solid. Green.™

www.logixcf.com

6 – 57

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 4A - LOGIX 4" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD Cont'd

| s=9", D=20" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | 1 - 20M | 1 - 20M |
| 10 | | | | | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M |
| 12 | | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | - |
| 14 | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | - | - | - |
| 16 | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | - | - | - | - |
| 18 | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | - | - | - | - | - | - |
| 20 | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | - | - | - | - | - | - | - | - |

| s=11", D=24" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | | | 1 - 20M |
| 12 | | | | | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M |
| 14 | | | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | - |
| 16 | | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | - | - |
| 18 | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | - | - | - |
| 20 | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | - | - | - | - | - |

| s=14", D=30" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|------|---------|---------|---------|---------|---------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | 1 - 20M | 1 - 20M |
| 16 | | | | | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M |
| 18 | | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | - |
| 20 | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | - | - |

Notes:

- Where not shown otherwise, bottom steel is 1-15M
- Table is to be read in conjunction w/ **Figure 4**.
- Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
- Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to **Figure 4**.
- Factored Point Load includes 1.25, and 1.5 for dead and live load, respectively. For example, (1.25*dead load)+(1.5*live load)

ENGINEERING

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 4B - LOGIX 6.25" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD

Where not shown otherwise, bottom steel is 1-15M

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3 | | | | | | | | | | | | | | | 1 - 20M | 1 - 20M |
| 4 | | | | | | | | | | | | | | 1 - 20M | 1 - 20M | 2 - 15M |
| 5 | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | - |
| 6 | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | - | - | - |
| 7 | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | - | - | - | - | - |
| 8 | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | - | - | - | - | - | - | - |
| 9 | | | | | | 1 - 20M | 1 - 20M | 2 - 15M | - | - | - | - | - | - | - | - |
| 10 | | | | | 1 - 20M | 2 - 15M | - | - | - | - | - | - | - | - | - | - |
| 12 | | | | 2 - 15M | - | - | - | - | - | - | - | - | - | - | - | - |
| 14 | | | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 16 | | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 18 | 1 - 20M | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

| s=4", D=10" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3 | | | | | | | | | | | | | | | | 1 - 20M |
| 4 | | | | | | | | | | | | | | | 1 - 20M | 2 - 15M |
| 5 | | | | | | | | | | | | | | 1 - 20M | 1 - 20M | 2 - 15M |
| 6 | | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M |
| 7 | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 15M | - |
| 8 | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 15M | - | - |
| 9 | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | - | - | - | - |
| 10 | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | - | - | - | - | - |
| 12 | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | - | - | - | - | - | - | - |
| 14 | | | | 1 - 20M | 1 - 20M | 2 - 15M | - | - | - | - | - | - | - | - | - | - |
| 16 | | | | 2 - 15M | - | - | - | - | - | - | - | - | - | - | - | - |
| 18 | | | 2 - 15M | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 20 | | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

| s=5", D=12" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3 | | | | | | | | | | | | | | | | 1 - 20M |
| 4 | | | | | | | | | | | | | | | | 1 - 20M |
| 5 | | | | | | | | | | | | | | | 1 - 20M | 2 - 15M |
| 6 | | | | | | | | | | | | | | | 1 - 20M | 2 - 15M |
| 7 | | | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M |
| 8 | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 20M |
| 9 | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 20M |
| 10 | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 15M | 2 - 20M | 2 - 20M |
| 12 | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 15M | 2 - 20M | 2 - 20M | 2 - 20M | - |
| 14 | | | | | | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 15M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | - | - |
| 16 | | | | | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 20M | 2 - 20M | - | - | - | - | - | - |
| 18 | | | | 1 - 20M | 2 - 15M | 2 - 20M | 2 - 20M | - | - | - | - | - | - | - | - | - |
| 20 | | | 1 - 20M | 2 - 15M | 2 - 20M | - | - | - | - | - | - | - | - | - | - | - |

| s=7", D=16" | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 10000 |
| 3 | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | 1 - 20M |
| 8 | | | | | | | | | | | | | | | 1 - 20M | 1 - 20M |
| 9 | | | | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M |
| 10 | | | | | | | | | | | | | | 1 - 20M | 2 - 15M | 2 - 15M |
| 12 | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 20M |
| 14 | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 15M | 2 - 20M | 2 - 20M |
| 16 | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 15M | 2 - 20M | 2 - 20M | 2 - 20M | - |
| 18 | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 15M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | - |
| 20 | | | | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 15M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | - | - |

ENGINEERING

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 4B - LOGIX 6.25" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD Cont'd

| s=9", D=20" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | | 1 - 20M | 1 - 20M |
| 12 | | | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M |
| 14 | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 15M |
| 16 | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 20M | 2 - 20M |
| 18 | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 15M | 2 - 20M | 2 - 20M | 2 - 20M |
| 20 | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 15M | 2 - 15M | 2 - 20M | 2 - 20M | 2 - 20M | - |

| s=11", D=24" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | | | 1 - 20M |
| 12 | | | | | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M |
| 14 | | | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M |
| 16 | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M |
| 18 | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 15M | 2 - 20M |
| 20 | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 15M | 2 - 15M | 2 - 20M | 2 - 20M |

| s=14", D=30" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-11 | | | | | | | | | | | | | | | | | 1 - 20M |
| 12 | | | | | | | | | | | | | | | | | 1 - 20M |
| 14 | | | | | | | | | | | | | | | | 1 - 20M | 1 - 20M |
| 16 | | | | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M |
| 18 | | | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M |
| 20 | | | | | | | | | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 1 - 20M | 2 - 15M | 2 - 15M | 2 - 15M |

Notes:

- Where not shown otherwise, bottom steel is 1-15M
- Table is to be read in conjunction w/ **Figure 4**.
- Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
- Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to **Figure 4**.
- Factored Point Load includes 1.25, and 1.5 for dead and live load, respectively. For example, (1.25*dead load)+(1.5*live load)

ENGINEERING

www.logixcf.com

Good. Solid. Green.™

6 – 60



6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 4C - LOGIX 8" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD

Where not shown otherwise, bottom steel is 2-15M

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | - | - |
| 6 | | | | | | | | | | | | | | | | - | - |
| 7 | | | | | | | | | | | | | | | | - | - |
| 8 | | | | | | | | | | | - | - | - | - | - | - | - |
| 9 | | | | | | | | | | - | - | - | - | - | - | - | - |
| 10 | | | | | | | | - | - | - | - | - | - | - | - | - | - |
| 12 | | | | | | - | - | - | - | - | - | - | - | - | - | - | - |
| 14 | | | | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 16 | | | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 18 | | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

| s=4", D=10" | | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|---------|---------|---------|---------|---------|------|---------|---------|---------|---------|---------|---------|---------|---------|---|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 | |
| 3 | | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | 2 - 20M | 2 - 20M | |
| 8 | | | | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | |
| 9 | | | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | - |
| 10 | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | - | - | - |
| 12 | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | - | - | - | - | - |
| 14 | | | | | | | 2 - 20M | 2 - 20M | - | - | - | - | - | - | - | - | - | - |
| 16 | | | | | 2 - 20M | 2 - 20M | - | - | - | - | - | - | - | - | - | - | - | - |
| 18 | | | | 2 - 20M | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 20 | | | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

| s=5", D=12" | | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|--|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 | |
| 3 | | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | | | |
| 16 | | | | | | | | | | | | | | | | | | |
| 18 | | | | | | | | | | | | | | | | | | |
| 20 | | | | | | | | | | | | | | | | | | |

| s=7", D=16" | | | | | | | | | | | | | | | | | | |
|-------------|-------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|--|
| Opening | Factored Point Load, lb | | | | | | | | | | | | | | | | | |
| ft | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 | |
| 3 | | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | | | |
| 16 | | | | | | | | | | | | | | | | | | |
| 18 | | | | | | | | | | | | | | | | | | |
| 20 | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |

ENGINEERING

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 4C - LOGIX 8" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD Cont'd

| s=9", D=20" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|--|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 | |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | | |
| 16 | | | | | | | | | | | | | | | | | |
| 18 | | | | | | | | | | | | | | | | | |
| 20 | | | | | | | | | | | | | | | | | |

| s=11", D=24" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|--|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 | |
| 3-13 | | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | | |
| 16 | | | | | | | | | | | | | | | | | |
| 18 | | | | | | | | | | | | | | | | | |
| 20 | | | | | | | | | | | | | | | | | |

| D=30" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|--|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 | |
| 3-20 | | | | | | | | | | | | | | | | | |

Notes:

- Where not shown otherwise, bottom steel is 2-15M
- Table is to be read in conjunction w/ **Figure 4**.
- Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
- Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to **Figure 4**.
- Factored Point Load includes 1.25, and 1.5 for dead and live load, respectively. For example, (1.25*dead load)+(1.5*live load)

ENGINEERING

Good. Solid. Green.™

www.logixicf.com

6 – 62



ENGINEERING

Where not shown otherwise, bottom steel is 2-15M

[illegible][illegible]

| s=5", D=12" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | | 2 - 20M |
| 10 | | | | | | | | | | | | | | | | 2 - 20M | 2 - 20M |
| 12 | | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M |
| 14 | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M | 2 - 25M |
| 16 | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M | 2 - 25M | - | - |
| 18 | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M | 2 - 25M | 2 - 25M | - | - | - | - |
| 20 | | | | | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M | 2 - 25M | - | - | - | - | - | - | - | - |

| s=7", D=16" | | | | | | | | | | | | | | | | | |
|-------------|-------------------------|------|------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Opening | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | | |
| 16 | | | | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M |
| 18 | | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M |
| 20 | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M | 2 - 25M |

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 4D - LOGIX 10" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD Cont'd

| s=9", D=20" | | | | | | | | | | | | | | | | | |
|---------------|-----|------|------|------|------|------|------|------|------|------|------|---------|---------|---------|---------|---------|---------|
| Opening ft | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-15 | | | | | | | | | | | | | | | | | |
| 16 | | | | | | | | | | | | | | | | 2 - 20M | 2 - 20M |
| 18 | | | | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M |
| 20 | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M |

| D=24" | | | | | | | | | | | | | | | | | |
|---------------|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|---------|---------|---------|
| Opening ft | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-17 | | | | | | | | | | | | | | | | | |
| 18 | | | | | | | | | | | | | | | | 2 - 20M | 2 - 20M |
| 20 | | | | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M |

| D=30" | | | | | | | | | | | | | | | | | |
|---------------|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|---------|
| Opening ft | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-19 | | | | | | | | | | | | | | | | | |
| 20 | | | | | | | | | | | | | | | | | 2 - 20M |

Notes:

- Where not shown otherwise, bottom steel is 2-15M
- Table is to be read in conjunction w/ **Figure 4**.
- Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
- Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to **Figure 4**.
- Factored Point Load includes 1.25, and 1.5 for dead and live load, respectively. For example, (1.25*dead load)+(1.5*live load)

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 4E - LOGIX 12" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD

Where not shown otherwise, bottom steel is 2-15M

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being used.

| s=3", D=8" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|---------|------|------|------|---------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | 2 - 20M |
| 7 | | | | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M |
| 8 | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | - | - | - |
| 9 | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | - | - | - | - |
| 10 | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | - | - | - | - | - | - |
| 12 | | | | | | | 2 - 20M | - | - | - | - | - | - | - | - | - | - |
| 14 | | | | | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 16 | | | 2 - 20M | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 18 | | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 20 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

| s=4", D=10" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | 2 - 20M |
| 8 | | | | | | | | | | | | | | | | 2 - 20M | 2 - 20M |
| 9 | | | | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M |
| 10 | | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M |
| 12 | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M | 2 - 25M |
| 14 | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M | - | - | - | - | - |
| 16 | | | | | | | 2 - 20M | 2 - 25M | 2 - 25M | - | - | - | - | - | - | - | - |
| 18 | | | | | 2 - 20M | 2 - 25M | 2 - 25M | - | - | - | - | - | - | - | - | - | - |
| 20 | | | 2 - 20M | 2 - 25M | - | - | - | - | - | - | - | - | - | - | - | - | - |

| s=5", D=12" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3 | | | | | | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | | 2 - 20M |
| 10 | | | | | | | | | | | | | | | | 2 - 20M | 2 - 20M |
| 12 | | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M |
| 14 | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M | 2 - 25M |
| 16 | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M | 2 - 25M | 2 - 25M | - |
| 18 | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M | 2 - 25M | 2 - 25M | - | - | - | - |
| 20 | | | | | | 2 - 20M | 2 - 25M | 2 - 25M | 2 - 25M | - | - | - | - | - | - | - | - |

| s=7", D=16" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-6 | | | | | | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | | | | | | |
| 10 | | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | | 2 - 20M |
| 14 | | | | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M |
| 16 | | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M |
| 18 | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M |
| 20 | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M | 2 - 25M | 2 - 25M | 2 - 25M |

ENGINEERING

6.2 – CANADIAN ENGINEERING ANALYSIS REPORT: IMPERIAL UNITS

TABLE 4E - LOGIX 12" LINTEL REINFORCEMENT WITH CONCENTRATED LOAD Cont'd

| D=20" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|------|---------|---------|---------|---------|---------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-15 | | | | | | | | | | | | | | | | | |
| 16 | | | | | | | | | | | | | | | | 2 - 20M | 2 - 20M |
| 18 | | | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M |
| 20 | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 25M |

| D=24" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|------|------|------|------|---------|---------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-17 | | | | | | | | | | | | | | | | | |
| 18 | | | | | | | | | | | | | | | | 2 - 20M | 2 - 20M |
| 20 | | | | | | | | | | | | | | 2 - 20M | 2 - 20M | 2 - 20M | 2 - 20M |

| D=30" | | | | | | | | | | | | | | | | | |
|---------------|-------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|---------|---------|
| Opening ft | Factored Point Load, lb | | | | | | | | | | | | | | | | |
| | 500 | 1000 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | 6500 | 7000 | 8000 | 9000 | 10000 |
| 3-19 | | | | | | | | | | | | | | | | | |
| 20 | | | | | | | | | | | | | | | | 2 - 20M | 2 - 20M |

Notes:

- Where not shown otherwise, bottom steel is 2-15M
- Table is to be read in conjunction w/ **Figure 4**.
- Where spaces contain "-" the bar is presumed to be less economical and/or practical. Alternatively, consult with a local engineer to determine if a practical bar size is possible based on local load conditions.
- Blank regions require no stirrups. Shaded regions require stirrups. For stirrup information refer to **Figure 4**.
- Factored Point Load includes 1.25, and 1.5 for dead and live load, respectively. For example, (1.25*dead load)+(1.5*live load)

6.3 – SOIL CLASSIFICATION TABLES

Reprinted from: PRESCRIPTIVE METHOD FOR INSULATING CONCRETE FORMS IN RESIDENTIAL CONSTRUCTION by NAHB Research Centre, Inc.

NOTE: LOGIX recommends builders, owners and/or designers using these tables confirm that on-site building conditions are w/in the scope of the tables being

Load Bearing Soil Classifications¹

| MINIMUM LOAD BEARING VALUE ² , psf | SOIL DESCRIPTION |
|--|--|
| 2000 psf | Clay, sandy clay, silty clay, and clayey silt |
| 3000 psf | Sand, silty sand, clayey sand, silty gravel, and clayey gravel |
| 4000 psf | Sandy gravel and medium stiff clay |
| > 4000 psf | Stiff clay, gravel, sand, sedimentary rock, and crystalline bedrock. |

1. User must verify that the values in this table agree with local codes and practices.
2. Tabulated values are the presumed strength of the soil, undisturbed (the maximum design load bearing value for the basement or foundation wall footing).

Equivalent Fluid Density Soil Classification^{1,2}

| MAXIMUM EQUIVALENT FLUID DENSITY, pcf | USC ² CLASSIFICATION | SOIL DESCRIPTION |
|---------------------------------------|---------------------------------|---|
| 30 pcf | GW, GP, SW, SP | Well-drained cohesionless soils such as clean (few or no fines) sand and gravels. |
| 45 pcf | GM, GC, SM, SM-SC, ML | Well-drained cohesionless soils such as sand and gravels containing silt or clay. |
| 60 pcf | SC, MH, CL, CH, ML-CL | Well-drained inorganic silts or clays that are broken up into smaller pieces. |

1. User must verify that the values in this table agree with local codes and practices.
2. USC - Uniform soil classification

6.4 – FOOTING WIDTH TABLES

Reprinted from: PRESCRIPTIVE METHOD FOR INSULATING CONCRETE FORMS IN RESIDENTIAL CONSTRUCTION by NAHB Research Centre, Inc.

NOTE: LOGIX recommend builders, owners and/or designers using these tables confirm that on-site loading conditions are within the scope of the tables being used.

Minimum width of concrete footing for LOGIX walls

| Maximum Number of Storeys | MINIMUM LOAD BEARING VALUE OF SOIL | | | | |
|-----------------------------------|------------------------------------|----------|----------|----------|----------|
| | 2000 psf | 2500 psf | 3000 psf | 3500 psf | 4000 psf |
| 6.25" LOGIX Wall Thickness | | | | | |
| One Storey | 15" | 12" | 10" | 9" | 8" |
| Two Storey | 20" | 16" | 13" | 12" | 10" |
| 8" LOGIX Wall Thickness | | | | | |
| One Storey | 18" | 14" | 12" | 10" | 8" |
| Two Storey | 24" | 19" | 16" | 14" | 12" |
| 10" LOGIX Wall Thickness | | | | | |
| One Storey | 20" | 16" | 13" | 11" | 10" |
| Two Storey | 27" | 22" | 18" | 15" | 14" |

- Minimum 28 day concrete compressive strength = 3000 psi (20 MPa)
- Table does not consider seismic. Footing design must also consider local design loads and building practices.
- Footings shall be minimum 8" thick, and shall have a width that allows for a nominal 2 inch projection from either face of the concrete in the wall to the edge of the footing.
- Table values are based on 40 ft building width (floor and roof clear span).
- Applicable for storey heights not greater than 9'-4".
- Basement wall shall not be considered as a storey in determining footing widths.
- Applicable also for 8 inch thick or 10 inch thick LOGIX foundation wall supporting 4 inch LOGIX storeys.
- Applicable also for 10 inch thick or 10 inch thick LOGIX foundation wall supporting 6.25 inch LOGIX storeys.

www.logixcf.com

Good. Solid. Green.™

6 – 68



Rev. Sep 23/09

7.0 – EVALUATION REPORTS

TABLE OF CONTENTS

| | |
|---|---------------|
| 7.1 – U.S. CODE REPORTS | P. 7-3 |
| 7.1.1 – ICC-ES (INTERNATIONAL CODE COUNCIL EVALUATION SERVICE) | P. 7-3 |
| 7.1.2 – WISCONSIN BUILDING PRODUCTS EVALUATION | P. 7-13 |
| 7.1.3 – LOS ANGELES COUNTY APPROVAL | P. 7-20 |
| 7.1.4 – STATE OF FLORIDA CERTIFICATE OF APPROVAL | P. 7-32 |
| 7.1.5 – MIAMI-DADE COUNTY | P. 7-34 |
| 7.1.6 – CITY OF NEW YORK - MEA (MATERIALS & EQUIPMENT ACCEPTANCE)P. | 7-37 |
| 7.1.7 – QAI FIRE RESISTANCE RATING | P. 7-39 |
| 7.1.8 – NON-COMBUSTIBLE CONSTRUCTION | P. 7-40 |
| (I-Codes) | P. 7-40 |
| 7.1.9 – VAPOR BARRIER (I-Codes) | P. 7-43 |
| 7.1.10 – GREENGUARD INDOOR AIR QUALITY CERTIFIED | P. 7-46 |
| 7.1.11 – GREENGUARD CHILDREN AND SCHOOLS CERTIFIED | P. 7-47 |
| 7.1.12 – QAI LISTING REPORT | P. 7-48 |

E
V
A
L
U
A
T
I
O
N
R
E
P
O
R
T
S

7.2 – CANADIAN CODE REPORTS P. 7-52

7.2.1 – CCMC (CANADIAN
CONSTRUCTION MATERIALS CENTRE) P. 7-52

7.2.2 – QAI FIRE RESISTANCE RATING P. 7-69

7.2.3 – NON-COMBUSTIBLE CONSTRUCTION
(NATIONAL BUILDING CODE
OF CANADA) P. 7-70

7.2.4 – VAPOUR BARRIER
(NATIONAL BUILDING
CODE OF CANADA) P. 7-71

7.2.5 – GREENGUARD INDOOR AIR
QUALITY CERTIFIED P. 7-74

7.2.6 – GREENGUARD CHILDREN AND
SCHOOLS CERTIFIED P. 7-75

7.2.7 – QAI LISTING REPORT P. 7-76

7.3 – LEED EVALUATION..... P. 7-80

7.3.1 – LEED EVALUATION (U.S.) P. 7-80

7.3.2 – LEED EVALUATION (CANADA) P. 7-83

7.1 – U.S. CODE REPORTS

7.1.1 – ICC-ES (INTERNATIONAL CODE COUNCIL EVALUATION SERVICE)



Most Widely Accepted and Trusted

ICC-ES Evaluation Report

ESR-1642

Reissued October 1, 2012

This report is subject to renewal September 1, 2013.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 03 00 00—CONCRETE
Section: 03 11 19—Insulating Concrete Forming

REPORT HOLDER:

LOGIX INSULATED CONCRETE FORMS LTD.
1917 WEST 4TH AVENUE
VANCOUVER, BRITISH COLUMBIA V6J 1M7
CANADA
(866) 944-0153
www.logixicf.com
francis@logixicf.com

EVALUATION SUBJECT:

LOGIX INSULATING CONCRETE FORMS

1.0 EVALUATION SCOPE

Compliance with the following codes:

- 2009 *International Building Code*® (IBC)
- 2009 *International Residential Code*® (IRC)
- Other Codes (see Section 8.0)

Properties evaluated

- Structural
- Surface burning characteristics
- Attic and Crawl space fire evaluation
- Fire resistance
- Noncombustible construction

2.0 USES

The Logix Insulating Concrete Forms (ICFs) are used as stay-in-place formwork for structural concrete, load-bearing and nonload-bearing, below-grade and above-grade walls. The forms are used in construction of plain and reinforced concrete beams, lintels, exterior and interior walls, and foundation and retaining walls. The forms remain in place after placement and curing of concrete and must be covered with approved interior and exterior finish material. The forms may be used in Type V construction; for use in buildings of Type I, II, III and IV construction, installation must be in accordance with Section 4.4.

3.0 DESCRIPTION

3.1 General:

The Logix ICFs are classified as a flat ICF wall system in accordance with Section R611.3 of the IRC.

3.2 Materials:

3.2.1 Logix Insulating Concrete Forms: The Logix ICFs consist of two expanded polystyrene (EPS) foam plastic boards separated by injection molded polypropylene cross ties, which are partially embedded into the EPS boards. The polypropylene cross ties, which are spaced 8 inches (203 mm) on center horizontally, maintain the EPS board facings at a fixed clear distance of 4 inches (102 mm), 6¹/₄ inches (158 mm), 8 inches (203 mm), 10 inches (254 mm) or 12 inches (305 mm). For the standard forms, the EPS boards are 16 inches (406 mm) high by 48 inches (1219 mm) long. The EPS boards have a maximum thickness of 2³/₄ inches (70 mm). When stacked in a running bond pattern, the Logix ICFs create a cavity where steel reinforcement bars and concrete are placed. In addition to the standard forms, 45-degree angle forms, 90-degree angle corner forms, taper top blocks, brick ledge blocks and transition blocks are also available. See Figure 1 for illustration of the forms.

The 45-degree-angle forms and 90-degree-angle corner forms are used to construct wall intersections. The taper top block is used to construct corbels in the wall at the desired locations. The brick ledge blocks are used to construct corbels that serve as ledges, for supporting exterior brick veneers. The EPS foam boards are molded from beads specified in the approved quality control manuals. The foam plastic has a nominal density of 1.45 pcf (23.2 kg/m³), and has a flame-spread index of 25 or less and a smoke-density index of 450 or less when tested in accordance with ASTM E 84. The foam plastic insulation complies with ASTM C 578 as Type II.

3.2.2 Cross Ties: The cross ties are 8.5 inches (216 mm), 10.75 inches (273 mm), 12.5 inches (318 mm) or 14.5 inches (368 mm) in length and have a 1.25-inch-wide-by-14.25-inch-high (32 mm by 362 mm), 0.1875-inch-thick (4.8 mm) flange. The plastic flanges, embedded ¹/₂ inch (13 mm) below the outside surface of the EPS foam boards, provide supports for attaching interior and exterior wall coverings. Refer to Figure 1 for details.

3.2.3 Concrete: Concrete must be normal-weight concrete complying with the applicable code, having a maximum aggregate size of ³/₄ inch (19 mm) and a maximum slump of 6 inches (152 mm). The maximum water-cementitious materials ratio must be 0.5, unless otherwise approved by the code official. Concrete must have a 28-day minimum compressive strength of 3,000 psi (20.7 MPa). Under the IRC, concrete must comply with IRC Sections R404.1.4 and R611.5.1.

ICC-ES Evaluation Reports are not to be construed as representing aesthetics or any other attributes not specifically addressed, nor are they to be construed as an endorsement of the subject of the report or a recommendation for its use. There is no warranty by ICC Evaluation Service, LLC, express or implied, as to any finding or other matter in this report, or as to any product covered by the report.

Copyright © 2012



Page 1 of 9

www.logixicf.com

Good. Solid. Green.™

7 – 3



7.1.1 – ICC-ES (INTERNATIONAL CODE COUNCIL EVALUATION SERVICE)

CONTINUED

ESR-1642 | Most Widely Accepted and Trusted

Page 2 of 9

3.2.4 Reinforcement: Walls must be reinforced with deformed steel bars, having a minimum yield stress of 40 ksi (275 MPa). The deformed steel bars must comply with Section 3.5.3.1 of ACI 318-05. If construction is based on the IRC, reinforcement must comply with IRC Sections R404.1.2.3.7 and R611.5.2.

3.2.5 Other Components: Wood members in contact with concrete for plates of window and door framing must be treated with an approved wood preservative or be a naturally durable species, and must be attached with corrosion-resistant fasteners complying with IBC Section 2304.9.5 or IRC Section 317.3, as applicable. Materials other than wood, such as vinyl, are permitted for window and door framing if approved by the code official.

4.0 DESIGN AND INSTALLATION

4.1 Design:

4.1.1 IBC Design Method, Including Alternate IBC Wind Design in Accordance with ICC-600-2008: Concrete walls formed by Logix ICFs must be designed and constructed in accordance with IBC Chapters 16 and 19, as applicable. Footings and foundations must be designed and constructed in accordance with IBC Chapter 18.

Solid concrete walls formed by flat ICFs may be designed and constructed in accordance with the prescriptive provisions of Section 209 of the ICC Standard for Residential Construction in High Wind Regions (ICC 600-2008), subject to the limitations in Exception 1 of IBC Sections 1609.1.1 and 1609.1.1.1. Design and construction under the provisions of ICC 600-2008 are limited to resistance to wind forces.

4.1.2 IRC Design Method: Insulating concrete walls formed by the Logix ICFs, which comply with IRC Section R611.3.1 as flat insulating concrete wall forms, must be designed and constructed in accordance with IRC Sections R404.1.2 and R611, for flat wall systems. Logix ICFs not complying with the dimensional requirements found in IRC Table R611.3 [i.e., solid concrete walls thicker than 10 inches (254 mm)] must be designed and constructed in accordance with the provisions of Section 4.1.1 of this report.

The 6¹/₄-, 8- and 10-inch-thick (158.75, 203.2 and 254 mm) concrete walls are limited to above-grade construction in accordance with IRC Section R611.

Footings and foundations must be designed and constructed in accordance with IRC Chapter 4.

4.1.3 Alternate IRC Design Method: When the Logix ICFs are used to construct buildings that do not conform to the applicability limits of IRC Sections R404.1.2 and R611.2, construction must be in accordance with the prescriptive provisions of the 2007 Prescriptive Design of Exterior Concrete Walls (PCA 100), or the structural analysis and design of the concrete must be in accordance with ACI 318 and IBC Chapters 16, 18 and 19, as noted in Section 4.1.1 of this report.

4.2 Installation:

4.2.1 General: The Logix ICFs must be installed in accordance with this report, the applicable code and Logix's published installation instructions. The published installation instructions and this report must be strictly adhered to, and a copy of these instructions must be available at the jobsite at all times during installation.

The Logix ICF wall system must be supported on concrete footings complying with IBC Chapters 18 and 19, or IRC Chapter 4, as applicable. Vertical reinforcement bars embedded in the footing must extend into the base of

the wall system the minimum development length necessary for compliance with Chapter 12 of ACI 318 (IBC and IRC). Vertical and horizontal reinforcement bars must have concrete protection in accordance with, and must be placed as required by, the design and the applicable code. Additional reinforcement around doors and windows must be described in the approved plans. Concrete quality, mixing and placement must comply with IBC Section 1905 or IRC Sections R404.1.2.3 and R611.5.1, as applicable. Window and door openings must be built into the forms, with the same dimensions as the "rough stud opening" specified by the window or door manufacturer, prior to the placement of the concrete. Connections of concrete walls to footings, floors, ceilings and roofs must be in accordance with IRC Section R611.9, or be engineered in accordance with the IBC, whichever code is applicable. Anchor bolts used to connect wood ledgers and plates to the concrete must be cast in place, with the bolts sized and spaced as required by design and the applicable code. Details must be prepared to accommodate the specific job situation, in accordance with the applicable code and the requirements of this report, subject to the approval of the code official.

4.2.2 Interior Finish:

4.2.2.1 General: The installation details in this section (Section 4.2.2) address compliance with the thermal barrier and interior finish requirements of the codes. Logix ICFs exposed to the interior of the building must be finished with minimum 1/2-inch-thick (13 mm) regular gypsum wallboard complying with ASTM C 36 or C 1396, attached to the flanges of the cross ties. The wallboard must be installed vertically and attached to the flanges of the cross ties with minimum 2-inch-long (51 mm), No. 6, Type W, coarse thread, gypsum wallboard screws spaced 16 inches (406 mm) on center horizontally, and 12 inches (305 mm) vertically. Gypsum wallboard joints must be taped and filled with joint compound in accordance with GA-216 or ASTM C 840. See Section 4.2.2.2 for installation details when use is as walls of crawl spaces without a covering on the interior face.

4.2.2.2 Attic and Crawl Space Installation: When the Logix ICFs are used as walls of attics and crawl spaces and no ignition barrier is applied to the interior space side of the foam plastic, all of the following conditions must be met:

- Entry to the attic or crawl space is only to service utilities, and no storage is permitted.
- There are no interconnected attic or basement areas.
- Air in the attic or crawl space is not circulated to other parts of the building.
- Attic ventilation is provided when required by IBC Section 1203.2 or IRC Section R806, as applicable.
- Under-floor (crawl space) ventilation is provided when required by IBC Section 1203.3 or IRC Section R408.1, as applicable.
- Combustion air is provided in accordance with IMC (*International Mechanical Code*) Section 701.

4.2.3 Exterior Finish:

4.2.3.1 Above Grade: The Logix ICFs must be covered on the exterior with an approved wall covering in accordance with the applicable code. Under the IRC, the walls must be flashed in accordance with IRC Section R703.8. The approved wall covering must be attached to the flanges of the cross ties with the fasteners described in Table 1. The fasteners must be corrosion-resistant and

www.logixicf.com

Good. Solid. Green.™

7 – 4



7.1.1 – ICC-ES (INTERNATIONAL CODE COUNCIL EVALUATION SERVICE)

CONTINUED

ESR-1642 | Most Widely Accepted and Trusted

Page 3 of 9

have sufficient length to protrude through the flanges of the cross ties a minimum of $\frac{1}{4}$ inch (6.4 mm). The fasteners have the allowable withdrawal and lateral capacities shown in Table 1. The maximum fastener spacing must be designed to support the gravity loads of the wall covering and resist the negative wind pressures. Negative wind pressure capacity of the exterior finish material must be the same as that recognized in the code for generic materials, or in a current ICC-ES evaluation report for proprietary materials.

4.2.3.2 Below-grade: Materials used to dampproof basement walls must be specified by Logix Insulated Concrete Forms, and must comply with the applicable code or a current ICC-ES evaluation report, and must be compatible with foam plastic forms. Applicable dampproofing and waterproofing requirements are in IBC Section 1805 and IRC Section R406, as applicable. Compliance is required with the drainage requirements in IBC Section 1805.4 or IRC Section R405.1, as applicable. No backfill is permitted to be applied against the wall until the complete floor system is in place, unless the wall is designed as a freestanding wall that does not rely on the floor system for structural support.

4.2.4 Foundation Walls: The Logix ICFs are permitted to be used as a foundation stem wall when supporting wood-framed or concrete construction and when the structure is supported on concrete footings complying with the applicable code. Design and installation of the Logix ICF system as foundation stem walls must comply with IBC Section 1807.1.5 or IRC Sections R404 and R404.1.2, as applicable. For concrete foundation walls under the IRC, vertical reinforcement size and spacing must be in accordance with IRC Tables R404.1.2(2), R404.1.2(3), R404.1.2(4) and R404.1.2(8). For concrete foundation walls under the IBC, vertical reinforcement size and spacing must be in accordance with IBC Table 1807.1.6.2. Under the IRC, alternate design and construction may be in accordance with ACI 318, ACI 332 or PCA 100.

4.2.5 Retaining Walls: The Logix ICFs used to form concrete retaining walls are to be reinforced with reinforcement designed in accordance with accepted engineering principles and Section 4.1 of this report.

4.2.6 Protection Against Termites: Where the probability of termite infestation is defined as "very heavy" by the code official, the forms must be installed in accordance with IBC Section 2603.8 or IRC Section R318.4, as applicable. Areas of very heavy termite infestation must be determined in accordance with IBC Figure 2603.8 or IRC Figure R301.2(6), as applicable.

4.3 Fire-resistance-rated Construction:

Walls constructed with Logix ICFs have fire-resistance ratings for bearing and nonbearing wall assemblies as shown in Table 2.

4.4 Installation in Buildings Required to Be of Type I, II, III and IV Construction:

4.4.1 General: Exterior walls constructed with Logix ICFs are permitted to be used in buildings required to be of Type I, II, III and IV construction, provided the applicable conditions cited below are met. The assemblies described in this section (Section 4.4) comply with IBC Section 1406.2.1.1.

4.4.2 Interior Finish: The forms must be finished on the interior with an approved 15-minute thermal barrier such as $\frac{1}{2}$ -inch-thick (13 mm) gypsum wallboard as required by the applicable code. The gypsum wallboard must be installed and attached as described in Section 4.2.2.1.

4.4.3 EIFS Exterior Finish: The following EIFS lamina may be installed over the exterior of the forms when applied using their respective reinforcing fabric or lath, base coat and finish coat materials described in their respective evaluation reports:

- Sto Corporation STOTerm Classic EIFS as described in [ESR-1720](#).
- Sto Corporation STOTerm Classic Next® EIFS as described in [ESR-1748](#).

4.4.4 Fireblocking: For applications on buildings of any height, floor-to-wall intersections must be fireblocked in accordance with the applicable code to prevent the passage of flame, smoke and hot gases from one story to another. The foam plastic insulation on the interior side of the exterior walls and on both sides of interior walls must be discontinuous from one story to another. See Figure 3. Details of typical floor-to-wall intersections must be provided, to the code official, on approved drawings.

4.4.5 One-story Buildings: The following conditions apply:

4.4.5.1 Fire Sprinklers: The building must be equipped throughout with an automatic sprinkler system in accordance with the applicable code.

4.4.5.2 Exterior Finish: The foam plastic on the exterior face of the foam wall must be covered with aluminum of a thickness of not less than 0.019 inch (0.48 mm), or corrosion-resistant steel having a base-metal thickness of 0.0160 inch (0.41 mm). Attachment of the metal wall covering must be designed by a registered design professional.

4.4.5.3 Interior Finish: The forms must be finished on the interior with an approved 15-minute thermal barrier such as $\frac{1}{2}$ -inch-thick (13 mm) gypsum wallboard as required by the applicable code. The gypsum wallboard must be installed and attached as described in Section 4.2.2.1.

4.5 Special Inspection:

4.5.1 IBC: Special inspection is required as noted in IBC Section 1704 for placement of reinforcing steel and concrete, and for concrete cylinder testing. Special inspections in accordance with IBC Sections 1704.1 and 1704.14 are required when the EIFS wall covering system is applied. Duties of the special inspector include verifying field preparation of materials, expiration dates, installation of components, curing of components, installation of joints and sealants.

4.5.2 IRC: For walls designed and constructed in accordance with Section 4.1.2 or PCA 100 as described in Section 4.1.3, special inspection is not required. For walls designed for use under the IRC, in accordance with the IBC as described in Sections 4.1.1 and 4.1.3, special inspection in accordance with Section 4.5.1 is required.

5.0 CONDITIONS OF USE

The Logix Insulating Concrete Forms described in this report comply with, or are suitable alternatives to what is specified in, those codes listed in Section 1.0 of this report, subject to the following conditions:

- 5.1** Forms are manufactured, identified and installed in accordance with this report and Logix's published installation instructions. If there is a conflict between the manufacturer's published installation instructions and this report, this report governs.
- 5.2** The forms are separated from the building interior as described in Section 4.2.2.1, except for crawl space construction described in Section 4.2.2.2.

EVALUATION REPORTS

www.logixicf.com

Good. Solid. Green.™

7 – 5

LOGIX®
INSULATED CONCRETE FORMS

7.1.1 – ICC-ES (INTERNATIONAL CODE COUNCIL EVALUATION SERVICE)

CONTINUED

ESR-1642 | Most Widely Accepted and Trusted

Page 4 of 9

- 5.3** When used in attics and crawl space construction as described in Section 4.2.2.2, the Logix ICFs must have at least one label as described in Section 7.0 visible in every 160 square feet (14.7 m²) of exposed interior wall area.
- 5.4** When use is as part of a fire-resistance-rated assembly, construction must be as described in Section 4.3.
- 5.5** Except as described in Section 4.4, use of the Logix ICFs is limited to Type V construction as defined in IBC Chapter 6, and to construction in accordance with the IRC.
- 5.6** When use is in buildings required to be of Types I through IV (noncombustible) construction, as described in Section 4.4, the Logix ICFs must have at least one label as described in Section 7.0 visible in every 160 square feet (14.7 m²) of wall area, prior to the application of wall covering.
- 5.7** When required by the code official, calculations showing compliance with the general design requirements of IBC Chapter 16 must be submitted to the code official for approval, except that calculations are not required when the building design is based on the prescriptive methods noted in Sections 4.1.2 and 4.1.3. The calculations and details must be prepared by a registered design professional where required by the status of the jurisdiction in which the project is to be constructed.
- 5.8** In areas where the probability of termite infestation is defined as "very heavy" and when ICFs are used with wood construction, the foam plastic must be installed in accordance with Section 4.2.6.
- 5.9** Concrete quality, mixing and placement must comply with IBC Section 1905, or IRC Section R611.5.1, as applicable.
- 5.10** Special inspection must be provided in accordance with Section 4.5.
- 5.11** When required by the code official, calculations showing compliance with IRC Sections R611.5.3 and R404.1.2.3.6 must be submitted to the code official for approval. The calculations and details, establishing the the ICFs provide sufficient strength to contain concrete during placement and that the cross-ties are capable of resisting the forces created by fluid pressure of fresh concrete, must be prepared by a registered design professional where required by the statutes of the jurisdiction in which the project is to be constructed.
- 5.12** Logix Insulating Concrete Forms are manufactured for Logix by Beaver Plastics Ltd., located in Acheson, Alberta, Canada, and Chilliwack, British Columbia, Canada; AMC Foam Technologies Inc. , in Winnipeg, Manitoba, Canada; Form Solutions in Cobourg, Ontario, Canada; Form Systems Inc., in Hayesville, Kansas; Perma R Products Inc. in Johnson City, Tennessee; Pacific Allied Products Ltd. in Kapolei, Hawaii; APTCO LLC in McFarland, California; and Plymouth Foam Inc. in Becker, Minnesota. Logix Insulating Concrete Forms are produced under a quality control program with inspections conducted by QAI Laboratories, Inc. (AA-723).

6.0 EVIDENCE SUBMITTED

Data in accordance with the ICC-ES Acceptance Criteria for Stay-in-place Foam Plastic Insulating Concrete Form (ICF) Systems for Solid Concrete Walls (AC353), dated October 2010.

7.0 IDENTIFICATION

Each bundle of Logix ICFs must bear a label specifying the company name (Logix Insulated Concrete Forms Ltd.), the evaluation report number (ESR-1642), the manufacturing location, the date of production, the name and logo of the inspection agency (QAI Laboratories, Inc.); and the phrase, "Acceptable for use in attics and crawl spaces." Also, one ICF panel in each bundle is labeled on the outer side of the panel with the same information.

8.0 OTHER CODES

8.1 Evaluation Scope:

In addition to the codes referenced in Section 1.0, the products in this report were evaluated for compliance with the requirements of the 2006 *International Building Code*® (IBC), the 2006 *International Residential Code*® (IRC), the *BOCA National Building Code/1999* (BNBC), the 1999 *Standard Building Code*® (SBC) and the 1997 *Uniform Building Code*™ (UBC).

8.2 Uses:

See Section 2.0.

8.3 Description:

See Section 3.0, except for following revisions:

- Revise Section 3.2.3 to say that concrete must comply with 2006 IRC Sections R404.4 and R611.6.1, BNBC Section 1906, SBC Section 1916.6.1 or UBC Section 1905, as applicable.
- Revise Section 3.2.4 to say that steel reinforcement must comply with 2006 IRC Sections R404.4.6 and R611.6.2, Section 3.5.3.1 of ACI 318-95 (BNBC), SBC Section 1916.6.2 or UBC Section 1903.5, as applicable.
- Revise Section 3.2.5 to say that attachment of wood members in contact with concrete must comply with 2006 IRC Section R319.3, BNBC Section 2311.3.3, SBC Section 2306.3 or UBC Section 2304.3, as applicable.

8.4 Design and Installation:

8.4.1 Design:

8.4.1.1 IBC Method: Concrete walls formed by the Logix ICFs must be designed and constructed in accordance with 2006 IBC Chapters 16 and 19, as applicable. Footings and foundations must be designed and constructed in accordance with 2006 IBC Chapter 18.

8.4.1.2 IRC Method: Concrete walls formed by the Logix ICFs must be designed and constructed in accordance with 2006 IRC Sections R404.4 and R611 for flat ICF wall systems. Footings and foundations must be designed and constructed in accordance with 2006 IRC Chapter 4.

8.4.1.3 Alternate IRC Method: When buildings constructed under the 2006 IRC provisions do not conform to the applicability limits of 2006 IRC Sections R404.4.1 and R611.2, the structural analysis and design of the concrete must be in accordance with ACI 318 and 2006 IBC Chapter 19. The empirical design approach specified in ACI 318 Section 14.5 is applicable to the design of concrete walls formed by the Logix ICFs.

8.4.1.4 UBC or BNBC: Concrete walls formed by Logix ICFs must be designed and constructed in accordance with UBC or BNBC Chapters 16 and 19, as applicable. Footings and foundations must be designed and constructed in accordance with UBC or BNBC Chapter 18, as applicable.

www.logixicf.com

Good. Solid. Green.™

7 – 6



7.1.1 – ICC-ES (INTERNATIONAL CODE COUNCIL EVALUATION SERVICE)

CONTINUED

ESR-1642 | Most Widely Accepted and Trusted

Page 5 of 9

8.4.1.5 Alternate UBC Design Method: Walls limited to a maximum of two stories plus a basement, and a maximum unsupported wall span of 10 feet (3048 mm), may be designed in accordance with Publication No. EB118, Prescriptive Method for Insulating Concrete Forms in Residential Construction, dated May 1998, published by the Portland Cement Association, subject to all applicability limits in Table 1.1 of that document.

8.4.1.6 Design in accordance with SBC: Walls constructed with the Logix ICFs comply with SBC Figure 1916.3 as flat insulating concrete forms. Wall design, construction and materials must comply with SBC Sections 1804.6.2 and 1916, as applicable, for flat insulating concrete form wall systems.

8.4.1.7 Alternate SBC Design Method: When Logix ICFs are used to construct buildings that do not conform to the applicability limits of the SBC Sections 1916.2 and 1804.6.2.1, the structural analysis and design of the concrete must be in accordance with ACI 318 and SBC Chapter 19.

8.4.2 Installation:

8.4.2.1 IBC and IRC: Same as Section 4.2, except for the following revisions:

- Revise Section 4.2.1 to say that concrete quality, mixing and placement must comply with 2006 IBC Section 1905 or 2006 IRC Section R611.6.1, as applicable. Anchorage of wood ledger boards supporting bearing ends of joists or trusses to flat ICF walls must be in accordance with 2006 IRC Section R611.8.2, or must be engineered in accordance with the IBC, whichever code is applicable.
- Revise Section 4.2.2.2 to say that combustion air is provided in accordance with 2006 IMC Sections 701 and 703.
- Revise Section 4.2.3.2 to say that compliance is required with drainage requirements in 2006 IBC Section 1807.4 or 2006 IRC Section R405.1, as applicable.
- Revise Section 4.2.4 to say that design and installation of foundation stem walls must comply with 2006 IBC Section 1805.5 or 2006 IRC Sections R404 and R404.1.2, as applicable.
- Revise Section 4.2.6 to say that where the probability of termite infestation is defined as "very heavy" by the code official, the foam plastic must be installed in accordance with 2006 IBC Section 2603.8 or 2006 IRC Section R320.5, as applicable.

8.4.2.2 BNBC, SBC and UBC: Same as Section 4.2, except for the following revisions:

- Revise Section 4.2.1 to say that the Logix ICFs and resulting concrete walls must be supported on concrete footings complying with BNBC or SBC Chapter 18 or UBC Chapters 18 and 19, as applicable. Vertical reinforcement bars embedded in the footing must extend into the base of the wall system the minimum development length necessary for compliance with Chapter 12 of ACI 318-98 (BNBC and SBC) or UBC Section 1912, as applicable. Concrete quality, mixing and placement must comply with Chapter 5 of ACI 318-95 (BNBC), SBC Section 1916.6.1 or UBC Section 1905, as applicable. Anchor bolts used to connect the wood ledgers or plates to the concrete must be cast-in-place, with the bolts sized and spaced as required by the design and the applicable code.

- Revise Section 4.2.2.2 to say under-floor ventilation is provided that complies with BNBC Section 1210.2, SBC Section 1804.6.3.1 or UBC Section 2306.7, as applicable.
- Revise Section 4.2.3.2 to say applicable dampproofing and waterproofing requirements are in BNBC Section 1813.0, SBC Section 1814 or UBC Appendix Chapter 18, as applicable. Compliance is required with drainage requirements in BNBC Section 1813.5, SBC Section 1814 or UBC Section 1804.7, as applicable.
- Revise Section 4.2.4 to say that design and installation of foundation stem walls must comply with BNBC Section 1812.0, SBC Section 1804.6.2 or UBC Table 18-I-C, as applicable.
- Revise Section 4.2.6 to say that, under the SBC, where the probability of termite infestation is defined as "very heavy" by the code official, the foam plastic must be installed in accordance with SBC Sections 1916.7 and 2603.3. Areas of very heavy termite infestation must be determined in accordance with SBC Figure 2304.1.4.

8.4.3 Special Inspection:

8.4.3.1 IBC: Special inspection is required as noted in 2006 IBC Section 1704 for placement of reinforcing steel and concrete, and for concrete cylinder testing. Special inspection, in accordance with 2006 IBC Sections 1704.1 and 1704.12, is required when an EIFS wall covering is applied. Duties of the special inspector include verifying field preparation of materials, expiration dates, installation of components, curing of components, and installation of joints and sealants.

8.4.3.2 IRC: For walls designed and constructed in accordance with Section 8.4.1.2, special inspection is not required. For walls designed for use under the IRC, in accordance with Section 8.4.1.3 of this report, special inspection in accordance with Section 8.4.5.1 is required.

8.4.3.3 BNBC: Special inspection is required as noted in BNBC Section 1704.5, and is to include, but not be limited to, concrete, reinforcing steel and formwork materials, installation of reinforcing steel, formwork installation, bracing and concreting operations.

8.4.3.4 SBC: Special inspection is required as noted in SBC Section 1707.1, and is to include, but not be limited to, concrete, reinforcing steel and formwork materials, installation of reinforcing steel, formwork installation, bracing and concreting operations.

8.4.3.5 UBC: Special inspection is required as noted in UBC Section 1701 for placement of reinforcing steel and concrete, and for concrete cylinder testing. When approved by the code official, special inspection may be waived when all of the following conditions are met:

1. Wall systems are a maximum of 8 feet high (2.4 m) and are limited to use in single-story construction of Group R, Division 3, or Group U Occupancies.
2. Maximum height of a concrete lift is 48 inches (1219 mm). Succeeding lifts must be placed in accordance with UBC Section 1905.10.5.
3. Installation is by properly trained installers approved by Logix Insulated Concrete Forms Ltd.
4. The installation instructions indicate methods used to verify proper placement of concrete.
5. Half the allowable stresses or loads permitted by the UBC are used for the design of the walls.

www.logixicf.com

Good. Solid. Green.™

7-7

LOGIX®
INSULATED CONCRETE FORMS

7.1.1 – ICC-ES (INTERNATIONAL CODE COUNCIL EVALUATION SERVICE)

CONTINUED

ESR-1642 | Most Widely Accepted and Trusted

Page 6 of 9

8.5 Conditions of Use:

8.5.1 IBC and IRC: Same as Section 5.0, except for the following revisions:

- Revise Section 5.7 to say that when required by the code official, calculations showing compliance with the general design requirements of Chapter 16 of the BNBC or UBC, as applicable, must be submitted to the code official for approval, except that calculations are not required when the building design is based on the prescriptive method noted in Section 8.4.1.5 or 8.4.1.6. The calculations and details must be prepared by a registered design professional where required by the statutes of the jurisdiction in which the project is to be constructed.
- Revise Section 5.8 to say that in areas where the probability of termite infestation is defined as “very heavy” and when ICFs are used with wood construction, the foam plastic must be installed in accordance with Section 8.4.2.1
- Revise Section 5.9 to say that concrete quality, mixing and placement must comply with 2006 IBC Section 1905 or 2006 IRC Section R611.6.1, as applicable.
- Revise Section 5.10 to say that special inspection must be in accordance with Section 8.4.5.1 or 8.4.5.2, as applicable.
- Section 5.11 is not applicable.

8.5.2 BNBC, SBC and UBC: Same as Section 5.0, except for the following revisions:

- Revise Section 5.5 to say that, except as described in Section 8.4.4, the concrete walls formed by the Logix ICFs are limited to combustible construction as defined in Chapter 6 of the BNBC, SBC or UBC, as applicable.

- Revise Section 5.7 to say that when required by the code official, calculations showing compliance with the design requirements of Section 8.4.1.1 must be submitted to the code official for approval, except calculations are not required when the building design is based on the prescriptive method noted in Section 8.4.1.5 (UBC) or Section 8.4.1.6 (SBC) as applicable. The calculations and details must be prepared by a registered design professional where required by the statutes of the jurisdiction in which the project is to be constructed.
- Revise Section 5.8 to say that in areas where the probability of termite infestation is defined as “very heavy” and when ICFs are used with wood construction, the foam plastic must be installed in accordance with Section 8.4.2.2, as applicable.
- Revise Section 5.9 to say that concrete quality, mixing and placement must comply with Chapter 5 of ACI 318-95 (BNBC), SBC Section 1916.6.1 or UBC Section 1905, as applicable.
- Revise Section 5.10 to say that special inspection must be in accordance with Sections 8.4.5.3 (BNBC), 8.4.5.4 (SBC) or 8.4.5.5 (UBC), as applicable.
- Section 5.11 is not applicable.

8.6 Evidence Submitted:

Data in accordance with the ICC-ES Acceptance Criteria for Stay-in-place Foam Plastic Insulating Concrete Form (ICF) Systems for Solid Concrete Walls (AC353), dated October 2007 (editorially revised April 2008).

8.7 Identification:

See Section 7.0.

TABLE 1—ALLOWABLE WITHDRAWAL AND LATERAL CAPACITIES OF SCREWS¹

| SCREW TYPE | ALLOWABLE CAPACITY (pounds) | |
|--|-----------------------------|------------------|
| | Withdrawal Capacity | Lateral Capacity |
| No. 6, Type W, coarse-thread, corrosion-resistant gypsum wallboard screw | 31 | 68 |

For SI: 1 pound = 4.45 N.

¹Screws must be corrosion-resistant and have sufficient length to penetrate the flanges of the cross ties at least 1/4 inches (6 mm).

TABLE 2—LOGIX INSULATING CONCRETE FORMS IN FIRE-RESISTANCE-RATED ASSEMBLIES^{1,2}

| TYPE-RATING | CAVITY THICKNESS (inches) | INTERIOR WALL FINISH | EXTERIOR WALL FINISH | STEEL REINFORCEMENT |
|--|---------------------------|---|----------------------|---|
| Bearing and nonbearing wall-3 hr. Allowable axial load 36600 pounds per foot ³ . | 6 1/4 | 1/2-inch-thick gypsum wallboard, 48 inches wide, fastened to the flanges of cross ties with 2-inch-long gypsum wallboard screws as specified in Table 1. Joints covered with joint compound, covered with tape, and additional coat of joint compound in accordance with GA-216 or ASTM C840. | Not required | No. 4 steel rebars horizontally within cross ties. No. 4 rebars vertically in the center of ICF at 16 in. o.c. |

For SI: 1 lb/ft = 14.5935 N/m; 1 inch = 25.4 mm.

¹Concrete must be normal-weight concrete (145±5 psf) (2323-2404 kg/m³) with a minimum 3000 psi (20.7 MPa) compressive strength at 28 days.

²The wall assembly may be used as either interior or exterior wall. When used as interior wall, both sides of the form must be protected with the interior wallboard as noted in the table.


³Per 10-foot wall height.

7.1.1 – ICC-ES (INTERNATIONAL CODE COUNCIL EVALUATION SERVICE)


CONTINUED

ESR-1642 | Most Widely Accepted and Trusted


Page 7 of 9




PLAN VIEW RIGHT HAND 90° STANDARD
& HALF HEIGHT CORNER BLOCK




SIDE ELEVATION
(full height block
shown)




PLAN VIEW LEFT HAND 90° STANDARD
& HALF HEIGHT CORNER BLOCK




SIDE ELEVATION
(full height block
shown)




PLAN VIEW RIGHT HAND 45° STANDARD
& HALF HEIGHT CORNER BLOCK




SIDE ELEVATION



END VIEW
(full height block
shown)



PLAN VIEW LEFT HAND 45° STANDARD
& HALF HEIGHT CORNER BLOCK



SIDE ELEVATION




FIGURE 1—LOGIX INSULATING CONCRETE FORMS

EVALUATION REPORTS

Good. Solid. Green.™

www.logixicf.com

7-9

LOGIX®
INSULATED CONCRETE FORMS

7.1.1 – ICC-ES (INTERNATIONAL CODE COUNCIL EVALUATION SERVICE)

CONTINUED




FIGURE 2—TYPICAL INSTALLATION DETAILS

7.1.1 – ICC-ES (INTERNATIONAL CODE COUNCIL EVALUATION SERVICE)

CONTINUED

ESR-1642 | Most Widely Accepted and Trusted

Page 9 of 9




FIGURE 3—TYPICAL FLOOR-WALL DETAIL FOR NONCOMBUSTIBLE CONSTRUCTION

www.logixicf.com

Good. Solid. Green.™

7-11

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 30/12

EVALUATION REPORTS

7.1.1 – ICC-ES (INTERNATIONAL CODE COUNCIL EVALUATION SERVICE)

CONTINUED



Most Widely Accepted and Trusted

ICC-ES Evaluation Report

ESR-1642 Supplement

Reissued October 1, 2012

This report is subject to renewal September 1, 2013.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 03 00 00—CONCRETE
Section: 03 11 19—Insulating Concrete Forming

REPORT HOLDER:

LOGIX INSULATED CONCRETE FORMS LTD.
1917 WEST 4TH AVENUE, SUITE 199
VANCOUVER, BRITISH COLUMBIA V6J 1M7
(866) 944-0153
www.logixicf.com
francis@logixicf.com

EVALUATION SUBJECT:

LOGIX INSULATING CONCRETE FORMS

1.0 EVALUATION SCOPE

Compliance with the following codes:

- 2007 Florida Building Code—Residential
- 2007 Florida Building Code—Building

Properties Evaluated:

- Structural
- Surface-burning Characteristics
- Crawl space fire evaluation
- Fire resistance

2.0 PURPOSE OF THIS SUPPLEMENT

This supplement is issued to indicate that the Logix insulating concrete forms (ICFs) described in Sections 2.0 through 7.0 of the master report comply with the 2007 Florida Building Code—Building and the 2007 Florida Building Code—Residential, when designed and installed in accordance with the master evaluation report.

Use of the Logix ICFs described in the master evaluation report for compliance with the High-Velocity Hurricane Zone provisions of the 2007 Florida Building Code—Building and the 2007 Florida Building Code—Residential has not been evaluated, and is outside the scope of this supplement.

For products falling under Florida Rule 9N-3, verification that the report holder's quality assurance program is audited by a quality assurance entity approved by the Florida Building Commission for the type of inspections being conducted is the responsibility of an approved validation entity (or the code official when the report holder does not possess an approval by the Commission).

This supplement expires concurrently with the master report reissued October 1, 2012.

ICC-ES Evaluation Reports are not to be construed as representing aesthetics or any other attributes not specifically addressed, nor are they to be construed as an endorsement of the subject of the report or a recommendation for its use. There is no warranty by ICC Evaluation Service, LLC, express or implied, as to any finding or other matter in this report, or as to any product covered by the report.

Copyright © 2012



Page 1 of 1

www.logixicf.com

Good. Solid. Green.™

7 – 12



7.1.2 – WISCONSIN BUILDING PRODUCTS EVALUATION



Evaluation # 200721-I

Safety & Buildings Division
201 West Washington Avenue
P.O. Box 2658
Madison, WI 53701-2658

Wisconsin Building Products Evaluation

Material

Logix Insulated Concrete Form

Manufacturers

AMC Foam Technologies, Inc.
151 Paramount Rd.
Winnipeg, MB R2X2W6
Canada

Plymouth Foam Inc.
13900 Industry Ave.
Becker, MN 55308
USA

SCOPE OF EVALUATION

GENERAL: This report evaluates the use of the Logix Insulated Concrete Form Wall System, manufactured by AMC Foam Technologies, Inc., and Plymouth Foam Inc., evaluated as permanent form work and insulation system for reinforced concrete beams, lintels, exterior and interior walls, and foundation and retaining walls. The Logix Insulated Concrete Form Wall System was evaluated for safety requirements of the foam plastic and structural requirements for the codes listed below.

This review includes the cited **Comm** code requirements below in accordance with the current **Wisconsin Uniform Dwelling Code for 1 & 2 family dwellings (UDC):**

- **Foam Plastic:** The Logix Insulated Concrete Form Wall System was evaluated in accordance with the fire safety requirements of **s. Comm 21.11**.
- **Structural:** The Logix Insulated Concrete Form Wall System was evaluated in accordance with the structural requirements of **ss. Comm 21.02, and 21.02(3)(c)**.

This review includes the cited **International Building Code (IBC)** requirements below in accordance with the **Wisconsin Amended IBC Code:**

- **Foam Plastic:** The Logix Insulated Concrete Form Wall System was evaluated in accordance with the fire safety requirements **ss. IBC 2603.1, 2603.2, and 2603.3**.
- **Structural:** The Logix Insulated Concrete Form Wall System was evaluated in accordance with the requirements of **IBC Chapter 16**.

SBD-5863 (R. 10/00)

www.logixicf.com

Good. Solid. Green.™

7 – 13



EVALUATION REPORTS

Rev. Sep 23/09

7.1.2 – WISCONSIN BUILDING PRODUCTS EVALUATION CONTINUED

COMMERCE Product Evaluation No. 200721-I (Replaces 200266-I)

Page 2

- **Fire Endurance:** The Logix Insulated Concrete Form Wall System was evaluated in accordance with the requirements of ss. **IBC 2603.4, 2603.5.1, and 2603.5.2.**
- **Fire-Resistance Rating and Fire Tests:** The Logix Insulated Concrete Form Wall System was evaluated in accordance with the requirements of ss. **IBC 703.1 and 703.2 [Comm 62.0703].**

Note: Structural calculations shall be submitted (job-to-job basis) in accordance with IBC Chapter 16 for Live, Ground Snow, Roof, Wind, and Seismic Loads.

DESCRIPTION AND USE

General: The Logix Insulated Concrete Form Wall System consists of expanded polystyrene (EPS) forms which are stacked in running bond and serve as forms for a 4-inch-thick, 6.25-inch-thick, 8-inch-thick, 10-inch-thick or 12-inch-thick reinforced concrete wall. The EPS forms remain in place to provide insulation for the wall. The reinforced concrete wall system may be used as a foundation wall, basement wall, shear wall, exterior load-bearing wall and lintel section.

The Logix EPS forms are 48 inches long and 16 inches high. The 4-inch Logix form for 4-inch-thick reinforced concrete walls is 9 1/2 inches wide. The 6.25-inch Logix form for 6-inch-thick reinforced concrete walls is 11 3/4 inches wide. The 8-inch Logix form for 8-inch-thick reinforced concrete walls is 13 1/2 inches wide. The 10-inch Logix form for 10-inch-thick reinforced concrete walls is 15 1/2 inches wide. The 12-inch Logix form for 12-inch-thick reinforced concrete walls is 17 1/2 inches wide. The forms are available as solid-form blocks or knock-down blocks. The solid-form blocks consist of opposing form panels connected by 6 polypropylene web ties embedded into the panels forming a solid form block. The knock-down blocks consist of opposing form panels connected by 6 polypropylene snap-in-place ties. The polypropylene plastic web ties are spaced 8 inches on center and black in color.

Material: Logix Form Blocks are molded from modified expandable polystyrene beads. Manufacturer include:

| | |
|---|---|
| Product | Manufacturer |
| BFL-422 | BASF Corporation (Beaver Plastics Ltd.) |
| The blocks are manufactured to a nominal density of 1.68 pounds per cubic foot. | |

Concrete: Normal-weight concrete complying with s. **Comm 21.02(3)(b)**, and s. **IBC 1903.1** with maximum aggregate size of 3/4 inch and a minimum compressive strength of 2,500 psi.

Reinforcement: The concrete is reinforced with Nos. 3, 4, 5 and 6 deformed steel reinforcing bars, Type A615, Grade No. 40, with a minimum yield strength of 40,000 psi and Grade No. 60, with a minimum yield strength of 60,000 psi. All steel reinforcement shall be in accordance with s. **IBC 1903.5.**

Each pallet of Logix forms shall bear a label with the manufacturer's name, and the quality control inspection agency (Underwriter's Laboratory Certification).

TESTS AND RESULTS

The tests and results listed below cover both the current WI Building Code **Comm** and future **IBC** requirements:

Intertek Testing Services, ETL SEMKO, conducted testing on the Logix forms. The Logix insulated concrete forms produced by Foam Technologies, Inc., and Plymouth Foam Inc., have been subject to and complied with the following testing:

- EPS has a maximum flame-spread rating of 25 and a maximum smoke-developed rating of 450. Testing was done in accordance with ASTM E 84.
- Meets 4-hour fire rating in accordance with ASTM E119 and CAN/ULC S10 conducted by Underwriter's Laboratories, See Design No. U933 located at the end of this report.

| | |
|--------------------|-----------------------------------|
| Assembly Rating, h | Minimum ICF Cavity Thickness, in. |
|--------------------|-----------------------------------|

Good. Solid. Green.™

www.logixicf.com

7 – 14



Rev. Sep 23/09

7.1.2 – WISCONSIN BUILDING PRODUCTS EVALUATION CONTINUED

COMMERCE Product Evaluation No. 200721-I (Replaces 200266-I)

Page 3

| | |
|---|---------------------------------------|
| 2 | 4 |
| 3 | 6.25 (4-hr. rating with 5/8" drywall) |
| 4 | Greater than or equal to 8 |

NOTE: 1. Unless noted otherwise, ratings are based on wall assembly having 1/2" drywall on fire exposed side.

2. Load bearing during test = 36,000lb/ft.

- Room fire Test Standard for Interior of Foam Plastics Systems in accordance with ASTM D1929, D635 and D2843.
- Crawl Space evaluation conducted in accordance with ICBOES requirements.
- Conforms to ASTM C578, with equivalency CAN/ULC S701 (standard Specification for Rigid, Cellular Polystyrene Thermal Insulation).
- Fastener Withdrawal Evaluation in accordance with ASTM D1761.
- Fastener Lateral Resistance tested in accordance with ASTM D1761.
- Polypropylene web material conforms to CC1 Plastic material when tested in accordance with ASTM D1929, D635, and D2843.

The Rigid Cellular (RCPS) Polystyrene Thermal Insulation was tested for apparent density, compressive properties, and flexural properties in accordance with ASTM C578-95 "Standard Specification for Rigid, Cellular Polystyrene Thermal Insulation," using the following test methods:

- **Apparent Density:** ASTM D1622-98 "Standard Test Method for Apparent Density of Rigid Cellular Plastics".

| Type | Test Result | Minimum Requirement | Status |
|---------|-------------|--------------------------|----------|
| Type II | 1.68 | 1.35 lbs/ft ³ | Complied |

- **Compressive Properties:** ASTM C165-00 "Standard Test Method for Measuring Compressive Properties of Thermal Insulation".

| Type | Test Result | Minimum Requirement | Status |
|---------|-------------|---------------------|----------|
| Type II | 24.5 psi | 15.0 psi | Complied |

- **Flexural Properties:** ASTM C203-99 "Standard Test Method for Breaking Load and Flexural Properties of Block-Type Thermal Insulation"

| Type | Test Result | Minimum Requirement | Status |
|------------|-------------|---------------------|----------|
| SC Type II | 44.9 psi | 40.0 psi | Complied |

Physical properties testing of polypropylene reinforcing web material was performed in general accordance with the following test methods:

- **Screw Withdrawal:** ICBO ES AC 116 (July 2001) "Acceptance Criteria for Nails and Spikes," in conjunction with ASTM D1761-88 (Re-approved 2000) "Standard Test Methods for Mechanical Fasteners in Wood," Sections 1 through 12 (two types of fasteners were tested: a type 'W' coarse thread drywall screw, and a type 'S' fine thread drywall screw)

| | Fastener Type | Withdrawal | Lateral |
|---------|--------------------------------------|----------------|----------------|
| | | Max Load (lbs) | Max Load (lbs) |
| Average | Type 'W' Coarse Thread Drywall Screw | 166 | 367 |
| COV | Type 'W' Coarse Thread Drywall Screw | 10.6 % | 8.4 % |
| Average | Type 'S' Fine Thread Drywall Screw | 169 | 328 |
| COV | Type 'S' Fine Thread Drywall Screw | 8.4 % | 4.1 % |

- **Lateral Screw Resistance:** ICBO ES AC 116 (July 2001) "Acceptance Criteria for Nails and Spikes," in conjunction with ASTM D1761-88 (Re-approved 2000) "Standard Test Methods for Mechanical Fasteners in Wood," Sections 1 through 20

| | Ultimate Tensile Strength (lbs) |
|---------|---------------------------------|
| Average | 842 |
| COV | 1.7 % |

- **Tensile Strength:** ASTM D638-01 "Standard Test Method for Tensile Properties of Plastics"

www.logixicf.com

Good. Solid. Green.™

7 – 15

LOGIX®
INSULATED CONCRETE FORMS

7.1.2 – WISCONSIN BUILDING PRODUCTS EVALUATION CONTINUED

COMMERCE Product Evaluation No. 200721-I (Replaces 200266-I)

Page 4

DISCUSSION: ICBO ES AC 116 references ASTM D1761 for lateral and withdrawal testing. The ASTM D6117 and ASTM D1761 are very similar in methodology, however ASTM D6117 is used for solid sections of plastic members and not for sheets of plastic material. In addition to this, the ICBO ES AC 116 document gives guidance on establishing allowable loads, which ASTM D6117 does not provide. In the absence of a standard that more specifically addresses this issue, ITS recommends that AC 116 is more appropriate.

It is ITS's opinion that it is appropriate to state specific loads for this material. ASTM D5456-99 clause A2.6.1 states, "The equivalent specific gravity is determined from Table 12.21 or Ref. (3) such that the table value for the tested nail does not exceed the average ultimate withdrawal resistance in pounds per inch (N/mm) from A2.4 divided by 5.0..." The safety factor for withdrawal in ASTM D5456 matches that of AC 116, again justifying its applicability to this issue. ASTM D5456 does not have a comparable safety factor for lateral load resistance. In the absence of a standard that more specifically addresses this issue, we suggest that AC 116 is more appropriate.

Given the low C.O.V. of the web tensile test results, it is the opinion of ITS that a safety factor of approximately three is appropriate. We chose to use the lateral resistance factors of AC 116 for consistency.

CALCULATIONS:

1. **Web Tensile:** 842 lbs. x 0.75 = 631 lbs. (Proportional limit assumed to be the same as ultimate load – brittle failure)
842 lbs. ÷ 3.2 = 263 lbs. (Based on average ultimate load)
2. **Fastener Testing:**
 - (A) **Withdrawal Resistance:**

| | |
|----------------|---|
| Type "S" Screw | $F_{allow} = 178 \text{ lbs.} \div 5 = 35 \text{ lbs.}$ |
| Type "W" Screw | $F_{allow} = 166 \text{ lbs.} \div 5 = 33 \text{ lbs.}$ |
 - (B) **Lateral Resistance:**

| | |
|----------------|---|
| Type "S" Screw | $F_{allow} = F \div 3.2 = 328 \text{ lbs.} \div 3.2 = 102.5 \text{ lbs.}$ |
| Type "W" Screw | $F_{allow} = F \div 3.2 = 367 \text{ lbs.} \div 3.2 = 114 \text{ lbs.}$ |

CONCLUSIONS:

1. Physical Properties of Polypropylene Reinforcing Webs

The polypropylene reinforcing webs were found to have the following allowable loads, as recommended by ITS when analyzed in accordance with ICBO ES AC 116 (July 2001) "Acceptance Criteria for Nails and Spikes." (The withdrawal resistance utilized a safety factor of five as per ICBO ES AC 116, Section 4.2. The lateral resistance of both the Type "W" screws and the Type "S" screws utilize a safety factor of 3.2 when analyzed in accordance with ICBO ES AC 116, Section 4.1.):

- Withdrawal resistance of a Type "S" fine thread drywall screw is 35 lbs.
- Withdrawal resistance of a Type "W" coarse thread drywall screw is 33 lbs.
- Lateral resistance of a Type "S" fine thread drywall screw is 102 lbs.
- Lateral resistance of a Type "W" coarse thread drywall screw is 114 lbs.

The polypropylene reinforcing web tensile strength is recommended by ITS to be 263 lbs., based on a safety factor of 3.2 analyzed in accordance with ICBO ES AC 116, Section 4.1. The maximum negative wind pressure for a cladding system attached to the EPS foam plastic panels is based on the maximum fastener values connected into the polypropylene reinforcing webs. For a screwed system into the webs, 8 inches on center vertically, and 6 inches on center horizontally, the allowable negative withdrawal is 99 lbs./ft². This withdrawal capacity can be converted to a wind speed based on the following formula extrapolated from the 1997 Uniform Building Code Table 16-F at a standard height of 33 feet:

$$q_s = Kv^2$$

where: q_s = wind pressure (psf)
and: v = basic wind speed (mph)
and: $K = 0.00256$
thus: $v = (q_s \div 0.00256)^{1/2}$
given: $q_s = 99 \text{ lbs./ft}^2$ (allowable negative withdrawal)
then: $v = 197 \text{ mph}$

- **Three Hour Fire Endurance Test:** ASTM E119-98, "Standard Test Methods for Fire Tests of Building Construction and Materials"

The objective of the test: to determine whether the polypropylene reinforcing web, a component of the form system,

www.logixcf.com

Good. Solid. Green.™

7 – 16

LOGIX®
INSULATED CONCRETE FORMS

7.1.2 – WISCONSIN BUILDING PRODUCTS EVALUATION CONTINUED

COMMERCE Product Evaluation No. 200721-I (Replaces 200266-I)

Page 5

would melt out and cause a loss of support for the non-fire side standard ½-inch gypsum thermal barrier and consequently create a through opening in the concrete wall, and/or flaming of the polypropylene reinforcing web and expanded polystyrene foam on the unexposed side, or create openings in the concrete wall that would result in the ignition of cotton waste.

The fire test sample was constructed to be representative of the code requirements for a foam insulated concrete wall system. The Beaver Plastics Ltd. Insulating concrete form system was tested in accordance with UBC 26-3, Room Fire Test Standard for Interior of Foam Plastic Systems, (refer to ITS/Warnock Hersey report #3020964(a)), and met the conditions of acceptance for a 15 minute index.

- See Design No. U932 located at the end of this report.

LIMITATIONS OF APPROVAL

The limitations below are in accordance with the current **Wisconsin Uniform Dwelling Code (UDC)**, for 1 & 2 family dwellings:

- **Foam Plastic:** The ICF wall system is approved for use with a thermal barrier to separate the blocks from interior spaces in accordance with **s. Comm 21.11(1)**. Where a 1-inch thickness of masonry does not separate the polystyrene blocks from the building interior, including at the top of the wall, a thermal barrier, which has a finish rating of at least 15 minutes, shall be provided.
 1. Logix Form Blocks are approved for use in combustible non-rated construction in accordance with **s. Comm 21.11**. In one- or two-family dwellings, thermal barriers shall be provided to separate the forms from the occupied space of the dwellings per **s. Comm 21.11**.
 2. The exterior face of the blocks shall be finished with an approved weather covering and must be protected from ultraviolet light.
- **Structural:** The Logix Form Blocks are approved as structural building elements.
 1. The units are approved for use as concrete forms for basement walls and exterior walls when the resulting concrete core thickness satisfies **Table 21.18-A** for one- or two-family dwellings, or when structural calculations for the product are submitted for review.
 2. Walls shall be anchored to all floors and roofs. Walls shall be interconnected at corners by embedding and lapping the reinforcement.
 3. Structures are **limited** to two stories in height.
 4. The forms are approved for use as concrete forms for basement walls, exterior walls and retaining walls when structural calculations are submitted to the department by a Wisconsin registered professional engineer or architect.
 5. Below grade walls shall be damp-proofed when required by the local building department.
 6. Damp-proofing and water-proofing materials shall be approved by AMC Foam Technologies, Inc., and Plymouth Foam Inc., and the local building official, and shall be free of solvents that will adversely affect the EPS foam.

NOTE: The Logix Insulated Concrete Form Wall System was **not** evaluated for compliance with the thermal requirements of **Subchapter VI, ss. Comm 22.20, 22.21, 22.23, 22.25, 22.27, 22.28, and 22.31** of the current UDC.

The IBC limitations below are in accordance with the current **Wisconsin Amended IBC 2000 Code**:

- **Foam Plastic:** The Logix ICF wall system is approved for use with a thermal barrier to separate the blocks from interior spaces in accordance with **s. IBC 2603.4**.
 1. In accordance with **s. IBC 2603.4.1.6**, when the Logix ICF is used within the attic or crawl space where entry is made only for service utilities, the foam plastic insulation shall be protected against ignition by 1-1/2" thick mineral fiber insulation, a ¼" thick wood structural panel, particleboard or hardboard, gypsum wallboard, corrosion-resistant steel or other approved material installed so that the foam plastic is not exposed.
 2. The protective covering shall be consistent with the requirements for the type of construction.
 3. The exterior face of the blocks shall be finished with an approved weather covering and must be protected from ultraviolet light.

www.logixicf.com

Good. Solid. Green.™

7 – 17

LOGIX®
INSULATED CONCRETE FORMS

7.1.2 – WISCONSIN BUILDING PRODUCTS EVALUATION CONTINUED

COMMERCE Product Evaluation No. 200721-I (Replaces 200266-I)
Page 6

4. The crawl space shall not be used for storage or air handling purposes, there are no interconnected basement areas and entry to the crawl space is only for service of utilities.
- **Structural:** Design of concrete formed by Logix Forms must comply with **IBC Chapter 19** with the following requirements:
 1. *The forms are approved for use as concrete forms for basement walls, exterior walls and retaining walls when structural calculations are submitted to the department by a Wisconsin registered professional engineer or architect.
 2. *Design calculations of walls must comply with **s. IBC 1901.2**. Use of the empirical design approach specified in **s. 2109.1 [Comm 62.2109(1)]** is prohibited.
 3. Design of lintels shall comply with the applicable provisions of **IBC Chapter 16**.
 4. Wall loading shall be in accordance with **IBC Chapter 16**.
 5. Minimum wall reinforcement shall conform to **s. IBC 1901.2**. When the code requires that vertical and horizontal reinforcement be spaced no further apart than 18 inches or three times the wall thickness, whichever is less, the maximum concrete wall thickness along the length of the wall is permitted to be used to determine rebar spacing.
 6. Walls shall be anchored to floors and roofs in accordance with **s. IBC 1604.8.2**. Walls shall be interconnected at corners by embedding and lapping reinforcement in accordance with the code.
 7. Design of shear walls shall be in accordance with **ss. IBC 1901.2 and 1910**.
 8. Structures are **limited** to two stories in height plus a basement.
 9. Below grade walls shall be damp-proofed when required by the local building department, water-proofed in accordance with **s. IBC 1806**.
 10. Damp-proofing and water-proofing materials shall be approved by AMC Foam Technologies, Inc., and Plymouth Foam Inc., and the local building official, and shall be free of solvents that will adversely affect the EPS foam.
 11. Special inspection is required as noted in **s. IBC 1704**, for placement of reinforcing steel and concrete, and for concrete cylinder testing, except that special inspection is not required for foundation stem walls conforming to **Table 1805.4.2** of the **IBC**.
 - a) Wall systems are a maximum of 8 feet high and are limited to use in single-story construction of Group R-3, or Group U Occupancies.
 - b) Maximum height of a concrete pour is 48 inches. Succeeding lifts must be placed in accordance with **s. IBC 1905.10**.
 - c) Installation is by properly trained installers approved by AMC Foam Technologies, Inc., and Plymouth Foam Inc.
 - d) The installation instructions indicate methods used to verify proper placement of concrete.
 12. Walls constructed with Logix ICF are considered Type V Construction.

***Alternate Design:** In lieu of calculations, the structural design of reinforced concrete formed by Logix Insulated Concrete Form Wall System insulated concrete form blocks for residential construction is permitted to comply with the *Prescriptive Method for Insulating Concrete Forms in Residential Construction* (publication No. EB118), dated May 1998, published by the Portland Cement Association (PCA). Buildings constructed with the Logix Insulated Concrete Form Wall System insulated concrete form system and designed in accordance with the alternate design, will not exceed a height of two stories plus a basement, where the maximum unsupported wall height is 10 feet.

NOTE: The Logix Insulated Concrete Form Wall System was not evaluated for compliance with the thermal requirements of **s. Comm 63.1018**.

Identification: Each package bears a label specifying the name and address of the manufacturer (AMC Foam Technologies, Inc., Winnipeg, MB R2X2W6, Canada or, Plymouth Foam Inc., Becker, MN 55308, USA). Additionally, product labels indicate the Wisconsin Building Product Evaluation Number (**200721-I**), and the name and logo of the quality control agency.

This approval will be valid through December 31, 2012, unless manufacturing modifications are made to the product or a re-examination is deemed necessary by the department. The Wisconsin Building Product Evaluation number must be provided when plans that include this product are submitted for review.

7.1.2 – WISCONSIN BUILDING PRODUCTS EVALUATION CONTINUED

COMMERCE Product Evaluation No. 200721-I (Replaces 200266-I)
Page 7

DISCLAIMER

The department is in no way endorsing or advertising this product. This approval addresses only the specified applications for the product and does not waive any code requirement not specified in this document.

Revision Date:

Approval Date: January 22, 2008

By: _____

Lee E. Finley, Jr.
Product & Material Review
Integrated Services Bureau

200721-I.doc

EVALUATION REPORTS

www.logixcf.com

Good. Solid. Green.™

7 – 19



7.1.3 – LOS ANGELES COUNTY APPROVAL

**BOARD OF
BUILDING AND SAFETY
COMMISSIONERS**

MARSHA L. BROWN
PRESIDENT

VAN AMBATIELOS
VICE-PRESIDENT

VICTOR H. CUEVAS
HELENA JUBANY
ELENORE A. WILLIAMS

**CITY OF LOS ANGELES
CALIFORNIA**



ANTONIO R. VILLARAIGOSA
MAYOR

**DEPARTMENT OF
BUILDING AND SAFETY
201 NORTH FIGUEROA STREET
LOS ANGELES, CA 90012**

ANDREW A. ADELMAN, P.E.
GENERAL MANAGER

RAYMOND CHAN
EXECUTIVE OFFICER

Logix Insulated Concrete Forms Ltd.
1917 West 4th Avenue
Vancouver, BC, Canada, V6J 1M7

Attn: Francis Roma
(866) 944-0153

RESEARCH REPORT: RR 25518
(CSI # 03100)

BASED UPON ICC EVALUATION SERVICE
REPORT NO. ESR-1642

REEVALUATION DUE DATE:
August 1, 2010
Issued Date: August 1, 2009
Code: 2008 LABC

GENERAL APPROVAL - Logix Insulated Concrete Forms

DETAILS

The above assemblies and/or products are approved when in compliance with the description, use, identification and findings of Report No. ESR-1642 dated July 1, 2009, of the ICC Evaluation Services, Incorporated. The report, in its entirety, is attached and made part of this general approval.

The parts of Report No. ESR-1642 marked by asterisk are modified by the Los Angeles Building Department from this approval.

The approval is subject to the following conditions:

1. Complete design and calculation shall be prepared by an engineer licensed in the State of California and approved by the structural plan check.
2. The maximum allowable pour rate of the forms shall be 4 feet per hour.
3. Continuous inspection by Deputy Inspectors shall be provided when the EIFS wall covering system is applied and for the placement of reinforcing steel and concrete as noted in Section 1704 of the City of Los Angeles Building Code. Any exception shall be approved by structural plan check supervisors.

RR 25518
Page 1 of 2

EVALUATION REPORTS

www.logixicf.com

Good. Solid. Green.™

7 – 2 0



7.1.3 – LOS ANGELES COUNTY APPROVAL

CONTINUED

Logix Insulated Concrete Forms Ltd.
Re: Logix Insulated Concrete Forms

DISCUSSION


This report is in compliance with the 2008 City of Los Angeles Building Code.

The approval is based on tests in accordance with ICC-ES Acceptance Criteria for Stay-in-place Foam Plastic Insulating Concrete Form (ICF) Systems for Solid Concrete Walls (AC353), dated October 2007 (editorially revised April 2008).

This general approval will remain effective provided the Evaluation Report is maintained valid and unrevised with the issuing organization. Any revision to the report must be submitted to this Department for review with appropriate fee to continue the approval of the revised report.

Addressee to whom this Research Report is issued is responsible for providing copies of it, complete with any attachments indicated, to architects, engineers and builders using items approved herein in design or construction which must be approved by Department of Building and Safety Engineers and Inspectors.

This general approval of an equivalent alternate to the Code is only valid where an engineer and/or inspector of this Department has determined that all conditions of this Approval have been met in the project in which it is to be used.



YEUAN CHOU, Chief
Engineering Research Section
201 N. Figueroa St., Room 880
Los Angeles, CA 90012
Phone - 213-202-9812
Fax - 213-202-9942

pu BG:slcm
RR25518 /2003 winword
R06/04/09
2C/1910.10/1914.4/1921.6

Attachments: ICC ES Report No. ESR-1642 (10 Pages)

RR 25518
Page 2 of 2

EVALUATION REPORTS

Good. Solid. Green.™

www.logixicf.com

7-21



REPRINTED 2013

Rev. Nov 11/10

7.1.3 – LOS ANGELES COUNTY APPROVAL

CONTINUED



Most Widely Accepted and Trusted

ICC-ES Evaluation Report

ESR-1642

Reissued July 1, 2009

This report is subject to re-examination in one year.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 03—CONCRETE
Section: 03130—Permanent Forms

REPORT HOLDER:

LOGIX INSULATED CONCRETE FORMS LTD.
1917 WEST 4TH AVENUE
VANCOUVER, BRITISH COLUMBIA V6J 1M7
CANADA
(866) 944-0153
www.logixicf.com
francis@logixicf.com

EVALUATION SUBJECT

LOGIX INSULATING CONCRETE FORMS

1.0 EVALUATION SCOPE

Compliance with the following codes:

- 2006 International Building Code® (IBC)
- * ■ 2006 International Residential Code® (IRC)
- * ■ Other Codes (see Section 8.0)

Properties evaluated

- Structural
- Surface burning characteristics
- Crawl space fire evaluation
- Fire resistance
- Noncombustible construction

2.0 USES

The Logix Insulating Concrete Forms (ICFs) are used as stay-in-place formwork for structural concrete, load-bearing and nonload-bearing, below-grade and above-grade walls. The forms are used in construction of plain and reinforced concrete beams, lintels, exterior and interior walls, and foundation and retaining walls. The forms remain in place after placement and curing of concrete and must be covered with approved interior and exterior finish material. The forms may be used in Type V construction; for use in buildings of Type I, II, III and IV construction, installation must be in accordance with Section 4.4.

3.0 DESCRIPTION

3.1 General:

- * The Logix ICFs are classified as a flat ICF wall system in accordance with Section R611.3 of the IRC.

3.2 Materials:

3.2.1 Logix Insulating Concrete Forms: The Logix ICFs consist of two expanded polystyrene (EPS) foam plastic boards separated by injection molded polypropylene cross ties, which are partially embedded into the EPS boards. The polypropylene cross ties, which are spaced 8 inches (203 mm) on center horizontally, maintain the EPS board facings at a fixed clear distance of 4 inches (102 mm), 6 1/4 inches (158 mm), 8 inches (203 mm), 10 inches (254 mm) or 12 inches (305 mm). For the standard forms, the EPS boards are 16 inches (406 mm) high by 48 inches (1219 mm) long. The EPS boards have a maximum thickness of 2 3/4 inches (70 mm). When stacked in a running bond pattern, the Logix ICFs create a cavity where steel reinforcement bars and concrete are placed. In addition to the standard forms, 45-degree angle forms, 90-degree angle corner forms, taper top blocks, brick ledge blocks and transition blocks are also available. See Figure 1 for illustration of the forms.

The 45-degree-angle forms and 90-degree-angle corner forms are used to construct wall intersections. The taper top block is used to construct corbels in the wall at the desired locations. The brick ledge blocks are used to construct corbels that serve as ledges, for supporting exterior brick veneers. The EPS foam boards are molded from beads specified in the approved quality control manuals. The foam plastic has a nominal density of 1.45 pcf (23.2 kg/m³), and has a flame-spread index of 25 or less and a smoke-density index of 450 or less when tested in accordance with ASTM E 84. The foam plastic insulation complies with ASTM C 578 as Type II.

3.2.2 Cross Ties: The cross ties are 8.5 inches (216 mm), 10.75 inches (273 mm), 12.5 inches (318 mm) or 14.5 inches (368 mm) in length and have a 1.25-inch-wide-by-14.25-inch-high (32 mm by 362 mm), 0.1875-inch-thick (4.8 mm) flange. The plastic flanges, embedded 1/2 inch (13 mm) below the outside surface of the EPS foam boards, provide supports for attaching interior and exterior wall coverings. Refer to Figure 1 for details.

3.2.3 Concrete: Concrete must be normal-weight concrete complying with the applicable code, having a maximum aggregate size of 3/4 inch (19 mm) and a maximum slump of 6 inches (152 mm). The maximum water-cementitious materials ratio must be 0.5, unless otherwise approved by the code official. Concrete must have a 28-day minimum compressive strength of 3,000 psi (20.7 MPa). Under the IRC, concrete must comply with IRC Sections R404.4 and R611.6.1.

ICC-ES Evaluation Reports are not to be construed as representing aesthetics or any other attributes not specifically addressed, nor are they to be construed as an endorsement of the subject of the report or a recommendation for its use. There is no warranty by ICC Evaluation Service, Inc., express or implied, as to any finding or other matter in this report, or as to any product covered by the report.

Copyright © 2009

*DELETED BY THE CITY OF LOS ANGELES



Page 1 of 9

Good. Solid. Green.™

www.logixicf.com

7-22



Rev. Nov 11/10

3.2.4 Reinforcement: Walls must be reinforced with deformed steel bars, having a minimum yield stress of 40 ksi (275 MPa). The deformed steel bars must comply with Section 3.5.3.1 of ACI 318-05. ~~If construction is based on the IRC, reinforcement must comply with IRC Sections R404.4.6 and R611.6.2.~~

3.2.5 Other Components: Wood members in contact with concrete for plates of window and door framing must be treated with an approved wood preservative or be a naturally durable species, and must be attached with corrosion-resistant fasteners complying with IBC Section 2304.9.5 ~~or IRC Section R319.3, as applicable.~~ Materials other than wood, such as vinyl, are permitted for window and door framing if approved by the code official.

4.0 DESIGN AND INSTALLATION

4.1 Design:

4.1.1 IBC Design: Concrete walls formed by Logix ICFs must be designed and constructed in accordance with IBC Chapters 16 and 19, as applicable. Footings and foundations must be designed and constructed in accordance with IBC Chapter 18.

~~* 4.1.2 IRC Design: Walls constructed with the Logix ICFs comply with IRC Figure R611.3 as flat ICFs. Wall design, construction and materials must comply with IRC Sections R404.4 and R611, for flat ICF wall systems.~~

~~* 4.1.3 Alternate IRC Design Method: When Logix ICFs are used to construct buildings that do not conform to the applicability limits of the IRC sections R404.4.1 and R611.2, the structural analysis and design of the concrete must be in accordance with ACI 318 and IBC Chapter 19. Use of the empirical design approach specified in Section 4.6.6 of ACI 318 is permitted for the design of concrete walls formed by the Logix ICFs.~~

4.2 Installation:

4.2.1 General: The Logix ICFs must be installed in accordance with the Logix published installation instructions, this report and the applicable code. The published installation instructions and this report must be strictly adhered to, and a copy of these instructions must be available at all times on the jobsite during installation. The Logix ICFs must be supported on concrete footings complying with Chapter 18 of the IBC, ~~or Chapter 4 of the IRC.~~

Vertical reinforcement bars, embedded in the footing, must extend a minimum of 24 inches (610 mm) into the block wall system. The Logix ICFs must be stacked in a running bond pattern such that the cross ties align vertically. Vertical and horizontal reinforcement bars must be placed as required by the design and the applicable code. All horizontal and vertical reinforcement bars must have minimum concrete protection in accordance with the applicable code.

Concrete quality, mixing, and placing must comply with the applicable code. Refer to Figure 2 for typical installation details.

~~* When regulation is under the IRC, reinforcing steel for the Logix ICFs used above grade must comply with Section R611 of the IRC.~~

Pressure-preservative-treated wood ledgers must be attached to the concrete wall by removing the face shell of the EPS units, with the height of the removed portion equal to the depth of the wood ledger. The minimum ambient temperature during placement must be in accordance with ACI 308. When concrete is placed into the wall system, the concrete-filled volume, provided for the anchor bolts, forms

solid corbels that serve as ledges for supporting loads such as brick veneer and heavier floor loads. The transition blocks serve the same function as brick ledge blocks but provide larger bearing lengths to support heavier loads. The spacing and embedment depth of the anchor bolts must comply with the structural design and code requirements. Anchor bolts used to connect the wood ledgers or plates to the concrete must be cast-in-place, with the bolts sized and spaced as required by the design using values as indicated in Section 1912 or Section 1913 of the IBC.

4.2.2 Interior Finish:

4.2.2.1 General: Logix ICFs exposed to the interior of the building must be finished with minimum 1/2-inch-thick (13 mm) regular gypsum wallboard complying with ASTM C 36 or C 1396, attached to the flanges of the cross ties. The wallboard must be installed vertically and attached to the flanges of the cross ties with minimum 2-inch-long (51 mm), No. 6, Type W, coarse thread, gypsum wallboard screws spaced 16 inches (406 mm) on center horizontally, and 12 inches (305 mm) vertically. Gypsum wallboard joints must be taped and filled with joint compound in accordance with GA-216 or ASTM C 840. See Section 4.2.2.2 for installation details when use is as walls of crawl spaces without a covering on the interior face.

4.2.2.2 Crawl Space Installation: Logix ICFs located in under-floor crawl spaces are permitted to be exposed to the crawl space, subject to all of the following conditions:

- Entry to the crawl space is only to service utilities, and heat-producing appliances are not permitted.
- There are no interconnected basement areas.
- Air in the crawl space is not circulated to other parts of the building.
- Under-floor ventilation of the crawl space is provided in accordance with IBC Section 1203.3 ~~or IRC Section R408, as applicable.~~

4.2.3 Exterior Finish:

4.2.3.1 Above Grade: The Logix ICFs must be covered on the exterior with an approved wall covering in accordance with the applicable code. ~~Under the IRC, the walls must be flashed in accordance with IRC Section R703.8.~~ The approved wall covering must be attached to the flanges of the cross ties with the fasteners described in Table 1. The fasteners must be corrosion-resistant and have sufficient length to protrude through the flanges of the cross ties a minimum of 1/4 inch (6.4 mm). The fasteners have the allowable withdrawal and lateral capacities shown in Table 1. The maximum fastener spacing must be designed to support the gravity loads of the wall covering and resist the negative wind pressures. Negative wind pressure capacity of the exterior finish material must be the same as that recognized in the code for generic materials, or in a current ICC-ES evaluation report for proprietary materials.

4.2.3.2 Below-grade: Materials used to dampproof basement walls must be specified by Logix Insulated Concrete Forms, and must comply with the applicable code or a current evaluation report, and must be compatible with foam plastic forms. Applicable dampproofing and waterproofing requirements are in IBC Section 1807 ~~and IRC Section R406.~~ Compliance is required with the drainage requirements in IBC Section 1807.4 ~~or IRC Section R406.4.~~ No backfill is permitted to be applied against the wall until the complete floor system is in place, unless the wall is designed as a freestanding wall that does not rely on the floor system for structural support.

*DELETED BY THE CITY OF LOS ANGELES

7.1.3 – LOS ANGELES COUNTY APPROVAL

CONTINUED

ESR-1642 | Most Widely Accepted and Trusted

Page 3 of 9

4.2.4 Foundation Walls: The Logix ICFs are permitted to be used as a foundation stem wall when supporting wood-framed or concrete construction and when the structure is supported on concrete footings complying with the applicable code. Design and installation of the Logix ICF system as foundation stem walls must comply with IBC Section 1805.5 or IRC Section R404.4, as applicable.

* Section 1805.5 or IRC Section R404.4, as applicable.

4.2.5 Retaining Walls: The Logix ICFs used to form concrete retaining walls are to be reinforced with reinforcement designed in accordance with accepted engineering principles and Section 4.1 of this report.

4.2.6 Protection Against Termites: Where the probability of termite infestation is defined as "very heavy" by the code official, the forms must be installed in accordance with IBC Section 2603.8 or IRC Section R320.6, as applicable. Areas of very heavy termite infestation must be determined in accordance with IBC Section 2603.8 or IRC Figure R301.2(6), as applicable.

* Figure 2603.8 or IRC Figure R301.2(6), as applicable.

4.3 Fire-resistance-rated Construction:

Walls constructed with Logix ICFs have fire-resistance rating for bearing and nonbearing wall assemblies as shown in Table 2.

4.4 Installation in Buildings Required to Be of Type I, II, III and IV Construction:

4.4.1 General: Exterior walls constructed with Logix ICFs are permitted to be used in buildings required to be of Type I, II, III and IV construction, provided the applicable conditions cited below are met. The assemblies described in this section (Section 4.4) comply with IBC Section 1406.2.1.1.

4.4.2 Interior Finish: The forms must be finished on the interior with an approved 15-minute thermal barrier such as 1/2-inch-thick (13 mm) gypsum wallboard as required by the applicable code. The gypsum wallboard must be installed and attached as described in Section 4.2.2.1.

4.4.3 EIFS Exterior Finish: The following EIFS lamina may be installed over the exterior of the forms when applied using their respective reinforcing fabric or lath, base coat and finish coat materials described in their respective evaluation reports:

- Sto Corporation STOTerm Classic EIFS as described in [ESR-1720](#).
- Sto Corporation STOTerm Classic Next[®] EIFS as described in [ESR-1748](#).

4.4.4 Fireblocking: For applications on buildings of any height, floor-to-wall intersections must be fireblocked in accordance with the IBC to prevent the passage of flame, smoke and hot gases from one story to another. The foam plastic insulation on the interior side of the exterior walls and on both sides of interior walls must be discontinuous from one story to another. See Figure 3. Details of typical floor-to-wall intersections must be provided, to the code official, on approved drawings.

4.4.5 One-story Buildings: The following conditions apply:

4.4.5.1 Fire Sprinklers: The building must be equipped throughout with an automatic sprinkler system in accordance with the IBC.

4.4.5.2 Exterior Finish: The foam plastic on the exterior face of the foam wall must be covered with aluminum of a thickness of not less than 0.019 inch (0.48 mm), or corrosion-resistant steel having a base-metal thickness of 0.0160 inch (0.41 mm). Attachment of the metal wall covering must be designed by a registered design professional.

4.4.5.3 Interior Finish: The forms must be finished on the interior with an approved 15-minute thermal barrier such as 1/2-inch-thick (13 mm) gypsum wallboard as required by the applicable code. The gypsum wallboard must be installed and attached as described in Section 4.2.2.1.

4.5 Special Inspection:

4.5.1 IBC: Special inspection is required as noted in IBC Section 1704 for placement of reinforcing steel and concrete, and for concrete cylinder testing.

Special inspections in accordance with IBC Sections 1704.1 and 1704.12 are required when the EIFS wall covering system is applied. Duties of the special inspector include verifying field preparation of materials, expiration dates, installation of components, curing of components, installation of joints and sealants.

~~**4.5.2 IRC:** For walls designed and constructed in accordance with Section 4.1.2 of this report, special inspections are not required. For walls designed in accordance with the Section 4.1.3, special inspection in accordance with Section 4.5.1 is required.~~

5.0 CONDITIONS OF USE

The Logix Insulating Concrete Forms described in this report comply with, or are suitable alternatives to what is specified in, those codes listed in Section 1.0 of this report, subject to the following conditions:

- 5.1 Forms are manufactured, identified and installed in accordance with this report and Logix's published installation instructions. If there is a conflict between the manufacturer's published installation instructions and this report, this report governs.
- 5.2 The forms are separated from the building interior as described in Section 4.2.2.1, except for crawl space construction described in Section 4.2.2.2.
- 5.3 When use is as a part of a fire-resistance-rated assembly, Section 4.3 of this report applies.
- 5.4 Except as described in Section 4.4, concrete walls formed by the Logix ICFs are limited to combustible construction as defined in IBC Chapter 6 and to construction in accordance with the IRC.
- 5.5 When required by the code official, calculations showing compliance with the general design requirements of IBC Chapter 16 must be submitted to the code official for approval, except that calculations are not required when the building design is based on Sections 4.1.2 of this report. The calculations and details must be prepared by a registered design professional where required by the status of the jurisdiction in which the project is to be constructed.
- 5.6 Concrete quality, mixing and placement must comply with IBC Section 1905, or IRC Section R614.6.1, as applicable.
- 5.7 Special inspection must be provided in accordance with Section 4.5.
- 5.8 Logix Insulating Concrete Forms are manufactured by Beaver Plastics Ltd., located in Edmonton, Alberta, Canada, and Chilliwack, British Columbia, Canada; AMC Insulation Corporation, in Winnipeg, Manitoba, Canada; Form Systems Inc., in Hayesville, Kansas; Perma R Products Inc. in Johnson City, Tennessee; and PSC Moulding Corporation in Cobourg, Ontario, Canada. Logix Insulating Concrete Forms are produced under a quality control program with inspections conducted by Underwriters Laboratories Inc. (AA-668).

*DELETED BY THE CITY OF LOS ANGELES

7.1.3 – LOS ANGELES COUNTY APPROVAL

CONTINUED

ESR-1642 | Most Widely Accepted and Trusted

Page 4 of 9

6.0 EVIDENCE SUBMITTED

Data in accordance with the ICC-ES Acceptance Criteria for Stay-in-place Foam Plastic Insulating Concrete Form (ICF) Systems for Solid Concrete Walls (AC308), dated October 2007 (editorially revised April 2008).

7.0 IDENTIFICATION

Each pallet of Logix ICFs must bear a label specifying the company name (Logix Insulating Concrete Forms Ltd.), the evaluation report number (ESR-1642), the manufacturing location, the date of production, and the name and logo of the inspection agency (Underwriters Laboratories Inc.)

When used in buildings required to be of Type I, II, III, or IV construction, as described in Section 4.4, the forms must have at least one label visible in every 160 square feet (14.9 m²) of wall area.

* 8.0 OTHER CODES

* 8.1 Evaluation Scope:

In addition to the codes referenced in Section 1.0, the products in this report were evaluated for compliance with the requirements of the BOCA® National Building Code 1999 (NBBC), the 1999 Standard Building Code (SBC) and the 1997 Uniform Building Code (UBC).

* 8.2 Uses:

See Section 2.0.

* 8.3 Description:

See Section 3.0, except that under the UBC reinforcement must comply with Section 1903 of the UBC, and fastening of wood members in contact with concrete must be in accordance with UBC 2304.3.

* 8.3.1 Concrete: Under the SBC, concrete must comply with SBC Section 1916.6.1; and under the NBBC, concrete must comply with Section 1906.

* 8.3.2 Reinforcement: The deformed steel bars must comply with Section 3.5.3.1 of ACI 318-05 and UBC Section 1903.5 (UBC), Section 3.5.3.1 of ACI 318-05 (NBBC), or SBC Section 1916.6.2, as applicable.

* 8.3.3 Other Components: Wood members in contact with concrete for plates of window and door framing must be treated with an approved wood preservative or be a naturally durable species, and must be attached with corrosion-resistant fasteners complying with the UBC Section 2304.3, NBBC Section 2311.3.3, or SBC Section 2306.3, as applicable.

* 8.4 Design and Installation:

* 8.4.1 UBC or NBBC: Concrete walls formed by Logix ICFs must be designed and constructed in accordance with UBC or NBBC Chapters 16 and 19, as applicable. Footings and foundations must be designed and constructed in accordance with UBC or NBBC Chapter 18, as applicable.

* 8.4.2 Alternate UBC Design Method: Walls limited to a maximum of two stories plus a basement, and a maximum unsupported wall span of 10 feet (3048 mm), may be designed in accordance with Publication No. EB118, Prescriptive Method for Insulating Concrete Forms in Residential Construction, dated May 1998, published by the Portland Cement Association, subject to all applicability limits in Table 1.1 of that document.

* 8.4.3 Design in accordance with SBC: Walls constructed with the Logix Insulating Concrete Forms comply with SBC Figure 1916.3 as flat insulating concrete forms. Wall design, construction and materials must

comply with SBC Sections 1804.6.2 and 1916, as applicable, for flat insulating concrete form wall systems.

* 8.4.4 Alternative SBC design Method: When Logix forms are used to construct buildings that do not conform to the applicability limits of the SBC Sections 1916.2 and 1804.6.2.1, the structural analysis and design of the concrete must be in accordance with ACI 318 and SBC Chapter 19.

* 8.4.5 Installation: The Logix Insulating Concrete Forms must be supported on concrete footings complying with Chapter 18 of the UBC.

Vertical reinforcement bars, embedded in the footing, must extend a minimum of 24 inches (610 mm) into the block wall system. The Logix Insulating Concrete Form blocks must be stacked in a running bond pattern such that the polypropylene webs align vertically. Vertical and horizontal reinforcement bars must be placed as required by the design and the applicable code. All horizontal and vertical reinforcement bars must have minimum concrete protection in accordance with the applicable code. Concrete quality, mixing, and placing must comply with the applicable code. Refer to Figure 2 for typical installation details.

Pressure-preservative treated wood ledgers must be attached to the concrete wall by removing the face shell of the EPS units, with the height of the removed portion equal to the depth of the wood ledger. The minimum ambient temperature during placement must be in accordance with ACI 306. When concrete is placed into the wall system, the concrete-filled volume, provided for the anchor bolts, forms solid corbels that serve as ledgers for supporting loads such as brick veneer and heavier floor loads. The transition blocks serve the same function as brick ledge blocks but provide larger bearing lengths to support heavier loads. The spacing and embedment depth of the anchor bolts must comply with the structural design and code requirements. Anchor bolts used to connect the wood ledgers or plates to the concrete must be cast in place, with the bolts sized and spaced as required by the design using values as indicated in Section 1923 of the UBC.

Anchor bolts used to connect the wood ledgers or plates to the concrete must be cast in place, with the bolts sized and spaced as required by the design using values as indicated in Section 1923 of the UBC.

* 8.4.5.1 Below Grade: Materials used to dampproof basement walls must be specified by Logix Insulating Concrete Forms, and must comply with the applicable code or a current evaluation report, and must be compatible with foam plastic forms. Applicable dampproofing and waterproofing requirements are in UBC Appendix Chapter 18, NBBC Section 1813 and SBC Section 1814. Compliance is required with the drainage requirements in UBC Section 1804.7, NBBC Section 1813.5 or SBC Section 1814. No backfill is permitted to be applied against the wall until the complete floor system is in place, unless the wall is designed as a freestanding wall that does not rely on the floor system for structural support.

* 8.4.5.2 Foundation Walls: The Logix ICFs are permitted to be used as a foundation stem wall when supporting wood framed or concrete construction and when the structure is supported on concrete footings complying with the applicable code. Design and installation of the Logix ICF system as foundation stem walls must comply with NBBC Section 1812 or SBC Section 1804.6.2, as applicable. In jurisdictions adopting the UBC, compliance with Table 18.1-C is required.

* DELETED BY THE CITY OF LOS ANGELES

www.logixicf.com

Good. Solid. Green.™

7-25

LOGIX®
INSULATED CONCRETE FORMS

7.1.3 – LOS ANGELES COUNTY APPROVAL

CONTINUED

ESR-1642 | Most Widely Accepted and Trusted

Page 5 of 9

- * **8.4.6 Protection Against Termites:** For applications governed by the SBC, Logix Insulating Concrete Forms must be installed in accordance with SBC Sections 1916.7.5 and 2603.3, as applicable. Areas of very heavy termite infestation must be determined in accordance with SBC Figure 2304.1.4.
- * **8.4.7 Installation in Buildings Required to be of Noncombustible Construction (UBC, BNBC and SBC):** Exterior walls constructed with Logix ICFs are permitted to be used in noncombustible construction (UBC, BNBC and SBC), provided the applicable conditions cited below are met:
 - * **8.4.7.1 General:** Exterior walls constructed with Logix ICFs are permitted to be used in non-combustible construction (UBC, BNBC and SBC), provided the applicable conditions cited below are met:
 - * **8.4.7.1.1 Interior Finish:** The forms must be finished on the interior with an approved 15-minute thermal barrier such as 1/2-inch-thick (13 mm) gypsum board as required by the applicable code. The gypsum board must be installed and attached as described in Section 4.2.2.1.
 - * **8.4.7.1.2 EIFS Exterior Finish:** The following EIFS lamina may be installed over the exterior of the forms when applied using their respective reinforcing fabric or lath, base coat and finish coat materials described in their respective evaluation reports:
 - ▲ Sto Corporation STOTerm Classic EIFS as described in ESR-1720.
 - ▲ Sto Corporation STOTerm Classic-Next[®] EIFS as described in ESR-1748.
 - * **8.4.7.1.3 Fireblocking:** For applications on buildings of any height, floor-to-wall intersections must be fireblocked in accordance with the applicable code to prevent the passage of flame, smoke and hot gases from one story to another. The foam plastic insulation on the interior side of the exterior walls and on both sides of interior walls must be discontinuous from one story to another. See Figure 3. Details of typical floor-to-wall intersections must be provided to the code official on approved drawings.
 - * **8.4.7.2 One-story Buildings:** The following conditions apply:
 - * **8.4.7.2.1 Fire Sprinklers:** The building must be equipped throughout with an automatic sprinkler system in accordance with the applicable code.
 - * **8.4.7.2.2 Exterior Finish:** The foam plastic on the exterior face of the foam wall must be covered with aluminum of a thickness of not less than 0.019 inch (0.48 mm), or corrosion-resistant steel having a base metal thickness of 0.0160 inch (0.41 mm). Attachment of the metal wall covering must be designed by a registered design professional.
 - * **8.4.7.2.3 Interior Finish:** The forms must be finished on the interior with an approved 15-minute thermal barrier such as 1/2-inch-thick (13 mm) gypsum wallboard as required by the applicable code. The gypsum wallboard must be installed and attached as described in Section 4.2.2.1.
 - * **8.4.8 Special Inspection (UBC):**
 - * **8.4.8.1 UBC:** Special inspection is required as noted in UBC Section 1701 for placement of reinforcing steel and concrete, and for concrete cylinder testing. When approved by the code official, special inspection may be waived when all of the following conditions are met:
 1. Wall systems are a maximum of 8 feet high (2.4 m) and are limited to use in single-story construction of Group R, Division 3, or Group U Occupancies.
 2. Maximum height of a concrete lift is 48 inches (1219 mm). Succeeding lifts must be placed in accordance with Section 1906.10.5 of the UBC.
 3. Installation is by properly trained installers approved by Logix Insulated Concrete Forms Ltd.
 4. The installation instructions indicate methods used to verify proper placement of concrete.
 5. Half the allowable stresses or loads permitted by the UBC are used for the design of the walls.
 - * **8.4.8.2 BNBC:** Special inspection is required as noted in BNBC Section 1704.5, and is to include, but not be limited to, concrete, reinforcing steel and formwork materials; installation of reinforcing steel; formwork installation, bracing and concreting operations.
 - * **8.4.8.3 SBC:** Special inspection is required as noted in SBC Section 1707.1, and is to include, but not be limited to, concrete, reinforcing steel and formwork materials; installation of reinforcing steel; formwork installation, bracing and concreting operations.
 - * **8.5 Conditions of Use:**
 - * **8.5.1** Logix ICFs are manufactured, identified, designed and installed in accordance with this report and the manufacturer's published installation instructions.
 - * **8.5.2** Except as described in Section 8.4.7, concrete walls formed by the Logix ICFs are limited to combustible construction as defined in Chapter 6 of the BNBC, SBC or UBC, as applicable.
 - * **8.5.3** When required by the code official, calculations showing compliance with the general design requirements of Chapter 16 of the BNBC or UBC must be submitted to the code official for approval, except calculations are not required when the building design is based on Sections 8.4.2 or 8.4.3 of this report. The calculations and details must be prepared by a registered design professional where required by the status of the jurisdiction in which the project is to be constructed.
 - * **8.5.4** The ICF forms are separated from the building interior with and must be finished with minimum 1/2-inch-thick (13 mm) regular gypsum wallboard complying attached to the flanges of the cross tie.
 - * **8.5.5** When regulation is under the UBC, BNBC or SBC, special inspection is required in accordance with Section 8.4.8 of this report.
 - * **8.5.6** Concrete quality, mixing and placement must comply with UBC Section 1905, Chapter 5 of ACI 318-95 (BNBC) or SBC Section 1916.6.1, as applicable.
 - * **8.5.7** When use is in buildings required to be of noncombustible construction, as described in Section 8.4.7, the forms must have at least one label as described in Section 7.0 visible in every 160 square feet (14.9 m²) of wall area.
 - * **8.6 Evidence Submitted:**
 - See Section 6.0.
 - * **8.7 Identification:**
 - See Section 7.0.

* DELETED BY THE CITY OF LOS ANGELES

www.logixicf.com

Good. Solid. Green.[™]

7-26

LOGIX[®]
INSULATED CONCRETE FORMS

7.1.3 – LOS ANGELES COUNTY APPROVAL

CONTINUED

ESR-1642 | Most Widely Accepted and Trusted

Page 6 of 9

TABLE 1—ALLOWABLE WITHDRAWAL AND LATERAL CAPACITIES OF SCREWS¹

| SCREW TYPE | ALLOWABLE CAPACITY (pounds) | |
|--|-----------------------------|------------------|
| | Withdrawal Capacity | Lateral Capacity |
| No. 6, Type W, coarse-thread, corrosion-resistant gypsum wallboard screw | 31 | 68 |

For SI: 1 pound = 4.45 N.

¹Screws must be corrosion-resistant and have sufficient length to penetrate the flanges of the cross ties at least $\frac{1}{4}$ inches (6 mm).

TABLE 2—LOGIX INSULATING CONCRETE FORMS IN FIRE-RESISTANCE-RATED ASSEMBLIES^{1,2}

| TYPE-RATING | CAVITY THICKNESS (inches) | INTERIOR WALL FINISH | EXTERIOR WALL FINISH | STEEL REINFORCEMENT |
|--|---------------------------|--|----------------------|---|
| Bearing and nonbearing wall-3 hr. Allowable axial load 36600 pounds per foot ³ . | 6 $\frac{1}{4}$ | $\frac{1}{2}$ -inch-thick gypsum wallboard, 48 inches wide, fastened to the flanges of cross ties with 2-inch-long gypsum wallboard screws as specified in Table 1. Joints covered with joint compound, covered with tape, and additional coat of joint compound in accordance with GA-216 or ASTM C840. | Not required | No. 4 steel rebars horizontally within cross ties. No. 4 rebars vertically in the center of ICF at 16 in. o.c. |

For SI: 1 lbf/ft = 14.5935 N/m; 1 inch = 25.4 mm.

¹Concrete must be normal-weight concrete (145±5 psf) (2323-2404 kg/m³) with a minimum 3000 psi (20.7 MPa) compressive strength at 28 days.

²The wall assembly may be used as either interior or exterior wall. When used as interior wall, both sides of the form must be protected with the interior wallboard as noted in the table.


³Per 10-foot wall height.

7.1.3 – LOS ANGELES COUNTY APPROVAL


CONTINUED

ESR-1642 | Most Widely Accepted and Trusted


Page 7 of 9




PLAN VIEW RIGHT HAND 90° STANDARD
& HALF HEIGHT CORNER BLOCK




SIDE ELEVATION
(full height block
shown)




PLAN VIEW LEFT HAND 90° STANDARD
& HALF HEIGHT CORNER BLOCK




SIDE ELEVATION
(full height block
shown)




PLAN VIEW RIGHT HAND 45° STANDARD
& HALF HEIGHT CORNER BLOCK




SIDE ELEVATION



END VIEW
(full height block
shown)



PLAN VIEW LEFT HAND 45° STANDARD
& HALF HEIGHT CORNER BLOCK



SIDE ELEVATION




FIGURE 1—LOGIX INSULATING CONCRETE FORMS

EVALUATION REPORTS

Good. Solid. Green.™

www.logixicf.com

7-28

LOGIX®
INSULATING CONCRETE FORMS

REPRINTED 2013

Rev. Nov 11/10

CONTINUED

Page 8 of 9



EVALUATION REPORTS

Good. Solid. Green.™

7-29



LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 11/10

7.1.3 – LOS ANGELES COUNTY APPROVAL

CONTINUED

ESR-1642 | Most Widely Accepted and Trusted

Page 9 of 9




FIGURE 3—TYPICAL FLOOR-WALL DETAIL FOR NONCOMUSTIBLE CONSTRUCTION

7.1.3 – LOS ANGELES COUNTY APPROVAL

CONTINUED



Most Widely Accepted and Trusted

ICC-ES Evaluation Report

ESR-1642 Supplement

Issued July 1, 2009

This report is subject to re-examination in one year.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

*

DIVISION: 03—CONCRETE
Section: 03130—Permanent Forms

REPORT HOLDER:

LOGIX INSULATED CONCRETE FORMS LTD.
1917 WEST 4TH AVENUE, SUITE 199
VANCOUVER, BRITISH COLUMBIA V6J 1M7
(866) 944-0153
www.logixicf.com
francis@logixicf.com

EVALUATION SUBJECT:

LOGIX INSULATING CONCRETE FORMS

1.0 EVALUATION SCOPE

Compliance with the following codes:

- 2007 Florida Building Code—Residential
- 2007 Florida Building Code—Building

Properties Evaluated:

- Structural
- * ■ Surface-burning Characteristics
- Crawl space fire evaluation
- Fire resistance

2.0 PURPOSE OF THIS SUPPLEMENT

This supplement is issued to indicate that the Logix insulating concrete forms (ICFs) described in Sections 2.0 through 7.0 of the master report comply with the 2007 Florida Building Code—Building and the 2007 Florida Building Code—Residential, when designed and installed in accordance with the master evaluation report.

Use of the Logix ICFs described in the master evaluation report for compliance with the High-Velocity Hurricane Zone provisions of the 2007 Florida Building Code—Building and the 2007 Florida Building Code—Residential has not been evaluated, and is outside the scope of this supplement.

For products falling under Florida Rule 9B-72, verification that the report holder's quality assurance program is audited by a quality assurance entity approved by the Florida Building Commission for the type of inspections being conducted is the responsibility of an approved validation entity (or the code official when the report holder does not possess an approval by the Commission).

This supplement expires concurrently with the master report issued July 1, 2009.

*

ICC-ES Evaluation Reports are not to be construed as representing aesthetics or any other attributes not specifically addressed, nor are they to be construed as an endorsement of the subject of the report or a recommendation for its use. There is no warranty by ICC Evaluation Service, Inc., express or implied, as to any finding or other matter in this report, or as to any product covered by the report.

Copyright © 2009

EVALUATION REPORTS

www.logixicf.com

Good. Solid. Green.™

7-31




7.1.4 – STATE OF FLORIDA CERTIFICATE OF APPROVAL

02/12/2012

Florida Building Code Online

FLORIDA DEPARTMENT OF



Business & Professional Regulation



Product Approval

USER: Public User

[BCIS Home](#) | [Log In](#) | [User Registration](#) | [Hot Topics](#) | [Submit Surcharge](#) | [Stats & Facts](#) | [Publications](#) | [FBC Staff](#) | [BCIS Site Map](#) | [Links](#) | [Search](#)

[DBPR HOME](#) | [ABOUT DBPR](#) | [DBPR DIVISIONS](#) | [CONTACT DBPR](#)

[License efficiently. Regulate fairly.](#)

[Product Approval Menu](#) > [Product or Application Search](#) > [Application List](#) > **Application Detail**

OFFICE OF THE SECRETARY

| FL # | FL14469 | | | | | | | | | | | | | | |
|--|--|----------|------|-----------|------|---------------------|------|-----------------------|------|-----------|------|-----------|------|----------|------|
| Application Type | New | | | | | | | | | | | | | | |
| Code Version | 2010 | | | | | | | | | | | | | | |
| Application Status | Approved | | | | | | | | | | | | | | |
| | *Approved by DCA. Approvals by DCA shall be reviewed and ratified by the POC and/or the Commission if necessary. | | | | | | | | | | | | | | |
| Comments | | | | | | | | | | | | | | | |
| Archived | <input type="checkbox"/> | | | | | | | | | | | | | | |
| Product Manufacturer | Logix Insulated Concrete Forms | | | | | | | | | | | | | | |
| Address/Phone/Email | 199-1917 W4th Ave Vancouver, FL 33133 (866) 944-0153 francis@logixcf.com | | | | | | | | | | | | | | |
| Authorized Signature | Francis Roma francis@logixcf.com | | | | | | | | | | | | | | |
| Technical Representative | Francis Roma | | | | | | | | | | | | | | |
| Address/Phone/Email | 2755 Columbia Street Vancouver (866) 944-0153 francis@logixcf.com | | | | | | | | | | | | | | |
| Quality Assurance Representative | Francis Roma | | | | | | | | | | | | | | |
| Address/Phone/Email | 106 Perma R Road Johnson City, TN 37063 francis@logixcf.com | | | | | | | | | | | | | | |
| Category | Structural Components | | | | | | | | | | | | | | |
| Subcategory | Insulation Form Systems | | | | | | | | | | | | | | |
| Compliance Method | Certification Mark or Listing | | | | | | | | | | | | | | |
| Certification Agency | Quality Auditing Institute Ltd. | | | | | | | | | | | | | | |
| Validated By | Chris Bowness, P.E. | | | | | | | | | | | | | | |
| | <input checked="" type="checkbox"/> Validation Checklist - Hardcopy Received | | | | | | | | | | | | | | |
| Referenced Standard and Year (of Standard) | <table> <thead> <tr> <th>Standard</th> <th>Year</th> </tr> </thead> <tbody> <tr> <td>ASTM C578</td> <td>2007</td> </tr> <tr> <td>ASTM D1761-88(2000)</td> <td>2000</td> </tr> <tr> <td>ASTM D1929-96(2000)e1</td> <td>2000</td> </tr> <tr> <td>ASTM D635</td> <td>2006</td> </tr> <tr> <td>ASTM E119</td> <td>2007</td> </tr> <tr> <td>ASTM E84</td> <td>2007</td> </tr> </tbody> </table> | Standard | Year | ASTM C578 | 2007 | ASTM D1761-88(2000) | 2000 | ASTM D1929-96(2000)e1 | 2000 | ASTM D635 | 2006 | ASTM E119 | 2007 | ASTM E84 | 2007 |
| Standard | Year | | | | | | | | | | | | | | |
| ASTM C578 | 2007 | | | | | | | | | | | | | | |
| ASTM D1761-88(2000) | 2000 | | | | | | | | | | | | | | |
| ASTM D1929-96(2000)e1 | 2000 | | | | | | | | | | | | | | |
| ASTM D635 | 2006 | | | | | | | | | | | | | | |
| ASTM E119 | 2007 | | | | | | | | | | | | | | |
| ASTM E84 | 2007 | | | | | | | | | | | | | | |
| Equivalence of Product Standards | | | | | | | | | | | | | | | |
| Certified By | | | | | | | | | | | | | | | |
| Product Approval Method | Method 1 Option A | | | | | | | | | | | | | | |
| Date Submitted | 05/22/2012 | | | | | | | | | | | | | | |
| Date Validated | 06/07/2012 | | | | | | | | | | | | | | |

www.floridabuilding.org/pr/pr_app_dtl.aspx?param=wGEVXQwtDquiKNpeAsu%2bZM79cusQpogWD...

1/2

www.logixcf.com

Good. Solid. Green.™

7 – 3 2



7.1.4 – STATE OF FLORIDA CERTIFICATE OF APPROVAL CONTINUED

de Online

http://www.floridabuilding.org/pr/pr_app_dtl.aspx?param=wGEVXQwt..

Product Approval Method

Method 1 Option A

Date Submitted

05/22/2012

Date Validated

06/07/2012

Date Pending FBC Approval

Date Approved

06/19/2012

Summary of Products

| FL # | Model, Number or Name | Description |
|---|--------------------------------|--|
| 14469.1 | Logix Insulated Concrete Forms | Insulated concrete forms |
| Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: Yes Design Pressure: N/A Other: | | Certification Agency Certificate FL14469_R0_C_CAC_LOGIX FBC LISTING LETTER 4 June 2012.pdf Quality Assurance Contract Expiration Date 09/10/2014 Installation Instructions FL14469_R0_II_logix installation guide.pdf Verified By: Quality Auditing Institute Ltd. Created by Independent Third Party: Evaluation Reports Created by Independent Third Party: |

[Back](#)

[Next](#)

Contact Us :: [1940 North Monroe Street, Tallahassee FL 32399](#) Phone: 850-487-1824

The State of Florida is an AA/EEO employer. [Copyright 2007-2010 State of Florida.](#) :: [Privacy Statement](#) :: [Accessibility Statement](#) :: [Refund Statement](#)

Under Florida law, email addresses are public records. If you do not want your e-mail address released in response to a public-records request, do not send electronic mail to this entity. Instead, contact the office by phone or by traditional mail. If you have any questions, please contact 850.487.1395. *Pursuant to Section 455.275(1), Florida Statutes, effective October 1, 2012, licensees licensed under Chapter 455, F.S. must provide the Department with an email address if they have one. The emails provided may be used for official communication with the licensee. However email addresses are public record. If you do not wish to supply a personal address, please provide the Department with an email address which can be made available to the public. To determine if you are a licensee under Chapter 455, F.S., please click [here](#).

Product Approval Accepts:



securityMETRICS

EVALUATION REPORTS

www.logixicf.com

Good. Solid. Green.™

7 – 3 3



7.1.5 – MIAMI-DADE COUNTY



BUILDING CODE COMPLIANCE OFFICE (BCCO)
PRODUCT CONTROL DIVISION

MIAMI-DADE COUNTY, FLORIDA
METRO-DADE FLAGLER BUILDING
140 WEST FLAGLER STREET, SUITE 1603
MIAMI, FLORIDA 33130-1563
(305) 375-2901 FAX (305) 372-6339

www.miamidade.gov/buildingcode

NOTICE OF ACCEPTANCE (NOA)

Logix Insulated Concrete Forms
P.O. Box 5235
Johnson City TN 37602

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code. This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Logix Insulating Concrete Forms

APPROVAL DOCUMENT: Drawing No. **MDSB-1**, titled "Logix ICF Standard Forms", sheet 1 of 1, prepared by Logix Insulated Concrete Forms, signed and sealed by Rahimuddin Rahimi, P.E., bearing the Miami-Dade County Product Control Renewal stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Division.

MISSILE IMPACT RATING: None

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official. This NOA **renews NOA # 03-0319.01** and consists of this page 1, evidence page E-1, as well as approval document mentioned above.

The submitted documentation was reviewed by **Carlos M. Utrera, P.E.**



[Signature]
10/26/09

NOA No 09-0714.03
Expiration Date: September 23, 2014
Approval Date: November 18, 2009
Page 1

EVALUATION REPORTS

Good. Solid. Green.™

www.logixicf.com

7 – 3 4



Logix Insulated Concrete Forms

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

A. DRAWINGS

1. Drawing No. **MDSB-1**, titled "Logix ICF Standard Forms", sheet 1 of 1, prepared by Logix Insulated Concrete Forms, signed and sealed by Rahimuddin Rahimi, P.E.
"Submitted under NOA # 03-0319.01"

B. TESTS

| | <u>Report</u> | <u>Test</u> | <u>Date</u> | <u>Signature</u> |
|----|---------------|-------------|-------------|---------------------|
| 1. | RAD-3015 | ASTM C-303 | April 2002 | J. D. Waldman |
| 2. | RAD-3015 | ASTM C-518 | April 2002 | J. D. Waldman |
| 3. | RAD-3015 | ASTM E-96 | April 2002 | J. D. Waldman |
| 4. | RAD-3015 | ASTM C-272 | April 2002 | J. D. Waldman |
| 5. | RAD-2725 | ASTM D-1929 | Feb 2001 | M. L. Zieman. |
| 6. | UL R-7503 | ASTM E-84 | 06/18/98 | No signature. |
| 7. | UL R-7503 | ASTM E-84 | 06/18/98 | No signature. |
| 8. | ETL 3050535 | ASTM G-21 | 03/17/04 | S. J. Emermas, P.E. |

"Submitted under NOA # 03-0319.01"

C. CALCULATION


1. None.

D. MATERIAL CERTIFICATION

1. None.

E. STATEMENTS

1. No change letter issued by Logix Insulated Concrete Forms, dated 07/06/09, signed Francis Roma, CDT, P.E.
2. Code compliance letter issued by Applied Consumer Services, Inc on 07/15/04, signed by R. Rahimi, P.E. and notarized by G. Tuninskaya.
3. No financial interest letter issued by Applied Consumer Services, Inc on 07/15/04, signed by R. Rahimi, P.E. and notarized by G. Tuninskaya.
"Submitted under NOA # 03-0319.01"


 10/26/09

Carlos M. Utrera, P.E.
 Product Control Examiner
 NOA No 09-0714.03

Expiration Date: September 23, 2014
 Approval Date: November 18, 2009

E - 1

EVALUATION REPORTS

Product Description

The Logix Insulated Concrete Forms consist of expanded polystyrene (EPS) interlocking rigid foam plastic boards that serve as permanent formwork for reinforced concrete, exterior and interior walls, lintel beams, and foundation and retaining walls.

Product Properties of Huntsman




| Description | Properties | Test |
|---------------------------|-------------------------------------|------------|
| Density | 1.39 pcf | ASTM C303 |
| Flame Spread | 5 | ASTM E84 |
| Smoke Development | 400 | ASTM E84 |
| Self Ignition Temperature | 752°F | ASTM D1929 |
| Thermal Conductivity | 0.237 Btu-in/hr-ft ² -°F | ASTM C518 |
| Odor Emission | Not detected | AATCC-112 |
| Water Vapor Transmission | 3.10 perms | ASTM E96 |
| Water Absorption | 0.76% Water abs. vol. | ASTM C272 |
| Fungus Resistance | No bacterial growth | ASTM G21 |

NOTES:

- 1) This approval pertains to the insulation properties of the Logix Insulated Concrete Forms and it does not approve the concrete, the structure and/or the forming capacity of the material and the system.
- 2) The forming system shall comply with the requirements of ACI 347.
- 3) The concrete walls shall comply with the requirements of ACI 318.
- 4) **EPS FOAM TYPE II IS SUPPLIED BY HUNTSMAN CHEMICAL CORPORATION**

| Standard Form | | | | |
|---------------|---------|---------|---------|---------|
| Form Size | 4" | 6" | 8" | 10" |
| | (100mm) | (152mm) | (203mm) | (254mm) |
| A | 4" | 6 1/4" | 8" | 10" |
| B | 9 1/2" | 11 3/4" | 13 1/2" | 15 1/2" |

PRODUCT RENEWED
as complying with the Florida
Building Code
Adoption No. 07-014.03
Expiration Date 07/23/2014
By: [Signature]
Miami-Dade Product Control
Division



END VIEW

SIDE ELEVATION

Approved for compliance with the
Florida Building Code
Date: 09/23/09
By: [Signature]
Miami-Dade Product Control
Division

5/20/04

ENGINEER: RAHEMUDDIN RAHIMT
DISCIPLINE: CIVIL ENGINEERING
NUMBER: 51484

MANUFACTURER: **LOGIX**
P.O. Box 5235
Johnson City, TN
37603
Good. Solid. LogixTM
www.logixcf.com

DWG. TITLE: LOGIX ICF STANDARD FORMS
DWG. NO.: MDSB-1
SHEET NO.: 1 of 1
REV. DATE: JAN 2004

7.1.6 – CITY OF NEW YORK - MEA (MATERIALS & EQUIPMENT ACCEPTANCE)



NYC Department of Buildings
280 Broadway, New York, NY 10007
Patricia Lancaster, FAIA, Commissioner
(212) 566-5000, TTY: (212) 566-4769

Report of Materials and Equipment Acceptance Division

Pursuant to Administrative Code Section 27-131, the following equipment or material has been found acceptable for use subject to the terms and conditions contained herein.

MEA 273-04-M

Manufacturer: Logix Insulated Concrete Forms Ltd., 840 Division Street, Cobourg, Ontario, Canada K9A 4J9.

Trade Name(s): Logix.

Product: Fire rated exterior insulation concrete forms wall assembly for combustible construction.

Pertinent Code Section(s): 27-297, 27-107, 27-133.

Prescribed Test(s): RS 5-5 (ASTM E84), Toxicity, RS 5-2 (ASTM 119).

Laboratory: Intertek Testing Services Ltd.

Test Report(s): Intertek Testing Services Test Report 3020964(b), dated April 24, 2002; Intertek Testing Services Test Report 3020964, dated April 8, 2002; Intertek Testing Services Test Report 3020964(a), dated June 12, 2002. Intertek letter dated November 11, 2003 and SwRI Project No. 01.10935.02.045 dated November 23, 2005.

Description: The Logix Insulated Concrete Forms are stay-in-place concrete forms for reinforced concrete wall systems. The wall system shall be constructed using a minimum ½ inch thick gypsum drywall to achieve the required fire resistance rating, and installed as shown in Figure 1.

| Form Size (Wall Thickness) | Fire Rating |
|----------------------------|-------------|
| 4" | 2 hours |
| 6.25" | 3 hours |
| 8" and larger | 4 hours |

MEA 273-04-M

Page 1 of 2

EVALUATION REPORTS

Good. Solid. Green.™

www.logixicf.com

7-37



7.1.6 – CITY OF NEW YORK - MEA (MATERIALS & EQUIPMENT ACCEPTANCE) CONTINUED




Figure 1. Logix Insulated Concrete Form wall system

1. **Insulated Concrete Forms** – Standard form units comprised of two 48" x 16" x 2.75" thick expanded polystyrene (EPS) panels linked by polypropylene webs spaced at 8" on center. The widths of the wall cavity are 4", 6.25", and 10". Height adjusters consist of 24" long, by 4" high, by 2.75" thick flat EPS panels. End caps are 16", 2.75" thick and range in widths are 4", 6.25", 8" and 10". For a complete listing of products visit the Logix website, www.logixicf.com. Logix ICF's bear the Warnock Hersey certification mark.
2. **Steel Reinforcement** – steel reinforcement shall be placed as per the Logix ICF Product Manual, or as per local engineering design and building code requirements.
3. **Normal Weight Concrete** – 145 ± 5 lb/ft³ density, 2900 psi compressive strength.
4. **Gypsum Board** – Classified or unclassified ½" thick, 48" wide gypsum wallboard fastened to flanges of polypropylene webs with 1.5" long drywall screws spaced on center 12" vertically and 16" horizontally. Minimum weight 1.6 psf. Joints covered with joint compound. Screwheads covered with joint compound.

Terms and Conditions – The above described wall assembly consisting of exterior concrete form and other components be accepted as having fire resistance classification listed above for combustible construction only, when installation complies with the applicable New York City Codes, Rules and Regulations and in particular with Section 27-297A, Tables 3-4, and 4-2 of the Building Code, for 1, 2 or 3 family, when interior and exterior of the concrete form is covered with accepted one hour fire rated material.

This acceptance does not include structural adequacy of wall design, which must be certified by a P.E., or R.A. for particular structures for compliance with the Building Code prior to plan examination by department engineers.

All shipments and deliveries of such materials shall be accompanied by a certificate or label certifying that the materials shipped or delivered are equivalent to those tested and acceptable for use, as provided for in Section 27-131 of the Building Code.

Final Acceptance February 10, 2006
Examined By Sum Derphudam

7.1.7 – QAI FIRE RESISTANCE RATING

Quality Auditing Institute


Listing Book

Standards: ASTM E119 - "Standard Test Methods for Fire Tests of Building Construction and Materials";

CAN/ULC S101 – "Standard Methods of Fire Endurance Tests of Building Construction and Materials"

| | Rating | Product Density | Maximum Cavity Width | Maximum Panel Thickness |
|--------------|--------|-----------------|----------------------|-------------------------|
| ASTM E119 / | 2-Hour | 1.35 pcf | 4 inches | 2 3/4 inches |
| CAN/ULC S701 | 3-Hour | 1.35 pcf | 6 1/8 inches | 2 3/4 inches |
| Ratings: | 4-Hour | 1.35 pcf | 8 inches | 2 3/4 inches |

Structural Rating at above durations for concrete wall at structural design load.



Assembly Details:

1. Insulated Concrete Forms – Standard forms made of two 16" x 48" by 2.75" thick expanded polystyrene (EPS) block panels connected by polypropylene detail webs at 8" O.C. The minimum width of the cavity is 4" as shown in the ratings table above (rating depends on cavity thickness).
2. Reinforcing Steel - No. 4 steel reinforcing bars placed horizontally in each course and vertically at 16" O.C. along centerline of wall cavity thickness.
3. Sand-Limestone Concrete – 145 +/- 5 pcf density, 2900 psi nominal compressive strength concrete.
4. Gypsum Wallboard – Min. 1/2" thick, 1.5 psf minimum density, 48" wide gypsum wallboard fastened to flanges of polypropylene webs with 2" long drywall screws at 16" horizontally and vertically. Joints covered with joint compound, covered with joint tape, and covered with an additional coat of joint compound. Screw heads covered with joint compound.

December 6, 2010

[Go to TABLE OF CONTENTS](#)

Good. Solid. Green.™

www.logixicf.com

7 – 39

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

EVALUATION REPORTS

7.1.8 – NON-COMBUSTIBLE CONSTRUCTION (I-Codes)



February 2, 2006

Francis Roma
Logix Insulated Concrete Forms Ltd.
327 – 801 Klahanie Drive
Port Moody, BC V3H 5K4

Dear Mr. Roma,

RE: Installation of Logix ICF in Non-Combustible Construction, Project # 3091401

INTRODUCTION

Intertek Testing Services NA Ltd. (Intertek) has reviewed, at the request of Logix Insulated Concrete Forms (ICF) Ltd., the requirements for Non-Combustible Construction as it relates to Insulated Concrete Forms (ICFs) under the 2003 International Building Code (IBC). This evaluation is based on past test reports, and Logix ICF Ltd. current application to ICC-ES to include multi-storey construction.

STANDARDS AND CRITERIA

- 2003 International Building Code
- ICC-ES AC12 "Acceptance Criteria for Foam Plastic Insulation"

EVALUATION

Section 3.3 of ICC-ES AC12 states that in some instances foam plastic can be permitted where non-combustible materials are required if conditions of the 2003 IBC, Section 2603.5 are met. This section has been summarized below, and evidence provided to demonstrate how Logix ICF complies for use in non-combustible construction.

1) 2603.5.1 Fire Resistance rated Walls: Where the wall is required to have a fire-resistance rating, data based on tests conducted in accordance with ASTM E119 shall be provided.



This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services NA Ltd.

1500 Brigantine Drive, Coquitlam, BC V3K 7C1 Canada
tel: 604-520-3321 fax: 604-524-9186 Home Page www.intertek-etlsemko.com

www.logixicf.com

Good. Solid. Green.™

7 – 4 0



7.1.8 – NON-COMBUSTIBLE CONSTRUCTION (I-Codes) CONTINUED

Logix Insulated Concrete Forms Ltd.
Project # 3091401

February 2, 2006
Page 2 of 3

The Logix ICFs achieved a 3 hour fire resistance rating when tested by Intertek in Intertek Test Report 3020964(d) dated June 2, 2004. A further study was conducted in which, the Intertek Letter dated November 11, 2003 showed that the presence of plastic ties in the concrete would not affect the ability of the wall to achieve a fire resistance rating of up to 4 hours.

2) 2603.5.2 Thermal Barrier: Any foam plastic insulation shall be separated from the building interior by a thermal barrier meeting the provisions of Section 2603.4.

Section 2603.4 requires that the interior of a building be separated from the foam plastic by an approved thermal barrier of ½ inch (12.7 mm) gypsum wallboard or equivalent thermal barrier that will limit the average temperature rise of the unexposed surface to not more than 250°F (120°C) after 15 minutes of fire exposure. The thermal barrier must also be installed in a manner that will remain in place for 15 minutes based on UL1715 (UBC Standard 26-3).

ASTM E119 testing per Intertek Test Report 3020964(d) was conducted using a ½ inch gypsum wallboard, and results showed that the temperature rise after 15 minutes was less than 60°F on the unexposed side.

A standard room fire test per Intertek Test Report 3020964(a) was also conducted in accordance with UBC Standard 26-3, and results showed that the ½ inch gypsum wallboard remained intact.

3) 2603.5.3 Potential Heat: The potential heat of the foam plastic insulation shall be determined by tests conducted in accordance with NFPA 259.

One of the polystyrene beads used in Logix ICF are Huntsmen Grade 40 and 54, for which Southwest Research Institute conducted testing per NFPA 259 and have reported in SwRI Project No. 01.03049.01.303. Results showed potential heat ratings of 17,293 Btu/lb and 17,269 Btu/lb for Grade 40 and 54 respectively.

4) 2603.5.4 Flame Spread and Smoke Developed Indexes: Foam plastic insulation shall have a flame spread index of 25 or less and a smoke-developed index of 450 or less as determined in accordance with ASTM E84.

Flame Spread and Smoke Developed indexes have been obtained for Huntsmen Grade 40 and 54, one of the main polystyrene beads used in Logix ICF. These results are reported in Underwriters Laboratories Inc. Test Report 96RT6559, which show that various densities of Huntsmen polystyrene beads all achieve flame spread index ratings less than 25 and smoke-developed indices below 450 when tested in accordance to UL 723.

EVALUATION REPORTS

www.logixicf.com

Good. Solid. Green.™

7-41

LOGIX®
INSULATED CONCRETE FORMS

7.1.8 – NON-COMBUSTIBLE CONSTRUCTION (I-Codes) CONTINUED

Logix Insulated Concrete Forms Ltd.
Project # 3091401

February 2, 2006
Page 3 of 3

5) 2603.5.5 Test Standard: The wall assembly shall be tested in accordance with and comply with the acceptance criteria of NFPA 285.

Testing to NFPA 285 is done on the finished wall assembly which includes the cladding (ex. Exterior Insulation and Finish System (EIFS)). This is a test that is primarily done by the cladding manufacturers to show conformance to NFPA 285 per the requirements of Section 3.3.2.1 and 3.3.2.2 of ICC-ES AC12. This is beyond the scope for an ICF manufacturer.

6) 2603.5.6 Label Required: The edge or face of each piece of foam plastic insulation shall bear the label of an approved agency.

Logix ICFs are manufactured under a third party inspection and listing program by Intertek, and all complying Logix ICF are marked with the Intertek – Warnock Hersey Certification Mark.

Each ICF is labeled with the following information: Company Name & Contact Information, Manufacturer's Location, Product Description, Complying Test Standards, Warnock Hersey Certification Mark, and Traceability Information (operator name, date, time).

7) 2603.5.7 Ignition: Exterior walls shall not exhibit sustained flaming when tested in accordance with NFPA 268.

This section lists a few exceptions that result in the foam plastic insulation not requiring testing in accordance to NFPA 268. Logix ICFs meet the exceptions as a thermal barrier (1/2" gypsum wallboard) complying with Section 2603.4 is used.

CONCLUSION

It is Intertek's professional opinion after reviewing Section 2603.5 of the 2003 IBC and the evidence shown above, that the Logix ICF meets the requirements for non-combustible construction for exterior walls of buildings of Type I, II, III or IV construction.

If you have any questions, please do not hesitate to contact us at 604-520-3321.

INTERTEK TESTING SERVICES NA LTD.
Warnock Hersey

Prepared By:



Kal Kooner, EIT
Engineer, Building Products

Reviewed By:



Peter Gildenstern, ASCT
Asst. Mgr., Engineering Services

Enclosure

EVALUATION REPORTS

www.logixicf.com

Good. Solid. Green.™

7 - 4 2



7.1.9 – VAPOR BARRIER (I-Codes)

The following evaluation report, although evaluated to the Canadian Codes, determines the permeance value of LOGIX. (Both I-codes and Canadian Codes determines permeance in accordance with ASTM E96)

The permeance value, as per the report, is noted as 36 ng/Pa-s-m² (or 0.63perms), which meets the requirement as a vapor retarder/barrier, according to the I-codes.

7.1.9 – VAPOR BARRIER (I-Codes) CONTINUED

Logix Insulated Concrete Forms Ltd.
Project No. 3109888-R1

January 30, 2007
Revised: January 31, 2007
Page 2 of 4

1 Introduction

Intertek Testing Services NA Ltd. (Intertek) has conducted an engineering evaluation for Logix Insulated Concrete Forms Ltd., on Logix ICF, to evaluate the vapor permeance properties of the product. The evaluation was conducted to determine if Logix ICF meets the 2005 National Building Code (NBC) for use as a vapor barrier.

2 Sample Description

Logix ICF consists of rigid interlocking expanded polystyrene (EPS) foam plastic boards that serve as permanent formwork for reinforced concrete, exterior and interior walls, and foundation and retaining walls.

3 Reference Documents

- 2005 National Building Code (NBC)
- ASTM E96/96M-05, Standard Test Methods for Water Vapor Transmission of Materials (ASTM E96)
- Intertek Test Report 3048347 dated October 14, 2003
- Intertek Letter dated January 6, 2005

4 Evaluation Method

Vapor barrier properties and installation are described in detail in Section 5.5.1.2 of the 2005 NBC. These details are summarized below:

- 1) The vapor barrier shall have sufficiently low permeance and shall be positioned in the building component or assembly so as to
 - a) minimize moisture transfer by diffusion, to surfaces within the assembly that would be cold enough to cause condensation at the design temperature and humidity conditions, or
 - b) reduce moisture transfer by diffusion, to surfaces within the assembly that would be cold enough to cause condensation at the design temperature and humidity conditions, to a rate that will not allow sufficient accumulation of moisture to cause deterioration or otherwise adversely affect any of
 - i. the health or safety of building users,
 - ii. the intended use of the building, or
 - iii. the operation of building services.
- 2) Coatings applied to gypsum wallboard to provide required resistance to vapour diffusion shall conform to the requirements of Sentence (1) when tested in accordance with CAN/CGSB-1.501-M, "Method for Permeance of Coated Wallboard."

Intertek ETL SEMKO

Testing everywhere for markets anywhere.

www.logixicf.com

Good. Solid. Green.™

7 - 4 4

LOGIX®
INSULATED CONCRETE FORMS

Rev. Sep 23/09

Logix Insulated Concrete Forms Ltd.
Project No. 3109888-R1

January 30, 2007
Revised: January 31, 2007
Page 3 of 4

- 3) Coatings applied to materials other than gypsum wallboard to provide required resistance to vapor diffusion shall conform to the requirements of Sentence (1) when tested in accordance with ASTM E96, "Water Vapor Transmission of Materials" by the desiccant method (dry cup).

Vapor Barrier materials are further discussed in Section 9.25.4.2 of the 2005 NBC under Sentence (1) which is summarized below:

- 1) Vapor barriers shall have a permeance not greater than 60 ng/Pa-s-m² measured in accordance with ASTM E96, "Water Vapor Transmission of Materials" by the desiccant method (dry cup).

Logix ICF fall under Sentence (3) of Section 5.5.1.2 of the 2005 NBC and have been tested by Intertek in accordance with ASTM E96 using the desiccant method. The results were summarized in Intertek Test Report 3048347 dated October 14, 2003 and showed that a 1-inch Logix ICF had a water permeance of 100 ng/Pa-s-m². In the field, Logix ICF is installed with a 2.75-inch thickness and thus the calculated water permeance at this thickness is 36 ng/Pa-s-m². The detailed calculations are shown in Intertek Letter dated January 5, 2005. Based on these results, Logix ICF meets the requirements of Section 9.25.4.2, Sentence (1) of the 2005 NBC and can be installed without the use of a vapor barrier.

5 Conclusion


Intertek has conducted an engineering evaluation for Logix Insulated Concrete Forms Ltd., on Logix ICF, to determine if the Logix ICF meets the 2005 National Building Code as a vapor barrier. The analysis, per Section 4 above, showed that Logix ICF meets the water permeance requirements and can be installed without a vapor barrier.

INTERTEK TESTING SERVICES NA LTD.

Reported by:


Matt Lansdowne, EIT
Engineer, Building Products

Reviewed by:


Kal Kooner, EIT
Team Leader, Engineering Services Canada

 ETL SEMKO
Testing everywhere for markets anywhere.

Good. Solid. Green.™

www.logixicf.com

7-45

LOGIX®
INSULATED CONCRETE FORMS

7.1.10 – GREENGUARD INDOOR AIR QUALITY CERTIFIED



Certificate of Compliance

Certification Details:

Certificate No: 938-00

Status: Certified

Period: 11/2010 - 10/2011

Restrictions: NONE

LOGIX Platinum Series

LOGIX Insulated Concrete Forms, Ltd.

This product has been certified according to the GREENGUARD Indoor Air Quality (IAQ) Certification Program for Low Emitting Products

Reference Standard: GGPS.001 GREENGUARD IAQ Standard for Building Materials, Finishes, and Furnishings

Product Type: Insulation and HVAC Products

| Criteria | Allowable Limits |
|--|--------------------------|
| TVOC ¹ | ≤ 0.5 mg/m ³ |
| Formaldehyde | ≤ 0.05 ppm |
| Total Aldehydes ² | ≤ 0.1 ppm |
| Individual VOCs ³ | ≤ 0.1 TLV |
| Respirable Particles (PM ₁₀) (mg/m ³) | ≤ 0.05 mg/m ³ |
| Listing of measured carcinogens and reproductive toxins as identified by California Proposition 65, the U.S. National Toxicology Program (NTP), and the International Agency on Research on Cancer (IARC) must be provided. | |
| Any pollutant regulated as a primary or secondary outdoor air pollutant must meet a concentration that will not generate an air concentration greater than that promulgated by the National Ambient Air Quality Standard (U.S. EPA, code of Federal Regulations, Title 40, Part 50). | |

See referenced standard for a complete technical explanation.

¹ Defined to be the total response of measured VOCs falling within the C₆-C₁₆ range, with responses calibrated to a toluene surrogate.

² Defined to be the total response of a target list of aldehydes (2-butenal; acetaldehyde; benzaldehyde; 2, 5-dimethylbenzaldehyde, 2-methylbenzaldehyde; 3-and/or 4-methylbenzaldehyde; butanal; 3-methylbutanal; formaldehyde; hexanal; pentanal; propanal), with each individually calibrated to a compound specific standard.

³ Any pollutant not listed must produce an air concentration level no greater than 1/10 the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, Cincinnati, Ohio 45211-4438).

⁴ Particles are applicable to fibrous, particle-releasing products with exposed surface area in air streams.

GREENGUARD Certification affirms that products meet the criteria of the referenced standard and the requirements of the specific certification program. Certification testing is conducted according to a consistent, defined protocol. The testing does not evaluate emissions under usage conditions other than those defined in the protocol and does not address potential environmental impact other than chemical and particle emissions.

The GREENGUARD Environmental Institute (GEI) is an industry independent, third-party certification organization that qualifies products for low chemical emissions. GREENGUARD Certification programs use defined product standards, test methodologies, product sample collection and handling procedures, program application processes and on-going verification procedures. GREENGUARD standards, methods, and procedures are available at www.GREENGUARD.org.

7.1.11 – GREENGUARD CHILDREN AND SCHOOLS CERTIFIED



Certificate of Compliance

Certification Details:

Certificate No: 938-00

Status: Certified

Period: 11/2010 - 10/2011

Restrictions: NONE

LOGIX Platinum Series

LOGIX Insulated Concrete Forms, Ltd.

This product has been certified according to the GREENGUARD Children & Schools Certification Program for Low Emitting Products

Reference Standard: GGPS.002 GREENGUARD Children & SchoolsSM Standard

Product Type: All Products

| Criteria | Allowable Limits |
|--------------------------------|---|
| Individual VOCs ^{1,2} | ≤ 1/100 TLV and ≤ ½ CA chronic REL (Office Seating ≤ 1/100 TLV and ≤ ¼ CA CREL) |
| Formaldehyde | ≤ 0.0135 ppm / 13.5 ppb (Office Seating ≤ 0.0675 ppm / 6.75 ppb) |
| TVOC ³ | ≤ 0.22 mg/m ³ |
| Total Aldehydes ⁴ | ≤ 0.043 ppm / 43 ppb |
| Total Phthalates ⁵ | ≤ 0.01 mg/m ³ |
| Total Particles ⁶ | ≤ 0.02 mg/m ³ |

See referenced standard for a complete technical explanation.

¹Any VOC not listed must produce an air concentration level no greater than 1/100 the Threshold Limit Value (TLV) industrial work place criterion (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, Cincinnati, Ohio 45211-4438) and no greater than 1/2 the CA Chronic Reference Exposure Level (CREL) http://www.oehha.ca.gov/air/chronic_rels/AllChrels.html - (CRELs) Adopted by the State of California Office of Environmental Health Hazard Assessment (OEHHA), December 2008).

²1-Methyl-2-Pyrrolidinone must be ≤ 0.16 mg/m³ for Office Furniture or ≤ 0.080 mg/m³ for Office Seating.

³Defined to be the total response of measured VOCs falling within the C₆-C₁₆ range, with responses calibrated to a toluene surrogate.

⁴Defined to be the total response of a target list of aldehydes (2-butanal; acetaldehyde; benzaldehyde; 2, 5-dimethylbenzaldehyde, 2-methylbenzaldehyde; 3-and/or 4-methylbenzaldehyde; butanal; 3-methylbutanal; formaldehyde; hexanal; pentanal; propanal), with each individually calibrated to a compound specific standard.

⁵Total phthalates include dibutyl (DBP), diethylhexyl (DEHD), diethyl (DEP), butylbenzyl (BBP), di-octyl (DOP), and dimethyl (DMP) phthalates.

⁶Particles are only applicable to fibrous, particle-releasing products with exposed surface area in air streams.

Complies with California Department of Health Services' "Standard Method for the Testing and Evaluation of Volatile Organic Chemical Emissions from Indoor Sources Using Environmental Chambers" Version 1.1 (CA section 01350)

GREENGUARD Certification affirms that products meet the criteria of the referenced standard and the requirements of the specific certification program. Certification testing is conducted according to a consistent, defined protocol. The testing does not evaluate emissions under usage conditions other than those defined in the protocol and does not address potential environmental impact other than chemical and particle emissions.

The GREENGUARD Environmental Institute (GEI) is an industry independent, third-party certification organization that qualifies products for low chemical emissions. GREENGUARD Certification programs use defined product standards, test methodologies, product sample collection and handling procedures, program application processes and on-going verification procedures. GREENGUARD standards, methods, and procedures are available at www.GREENGUARD.org.

www.logixicf.com

Good. Solid. Green.™

7-47



7.1.12 – QAI LISTING REPORT

Quality Auditing Institute

Listing Book

BUILDING PRODUCTS LISTING PROGRAM

Class: Insulation

Customer: LOGIX Insulated Concrete Forms, Ltd.
Location: 199-1917 West 4th Avenue, Vancouver, BC V6J 1M7

Listing No. B1031
Effective Date: September 27, 2010
Last Revised: October 15, 2010
Expires: N/A

Product: Insulated Concrete Forms (ICFs) with expanded polystyrene (EPS) panels and polypropylene web tie connectors.

Bead Types: Only approved bead types meeting certification requirements

Label: Product units are marked with the following: Manufacturer's Name, Trademark or other recognized symbol of identification, Model Designation, Month and Year of Manufacture or equivalent, QAI logo with the "US" and "C" identifier, listing number, and the standard numbers and ratings.

Standard: ASTM E84 - "Standard Test Method for Surface Burning Characteristics of Building Materials"

| Ratings: | Component | Product Density | Maximum Thickness | Flame Spread Index (FSI) | Smoke Developed Index (SDI) |
|----------|------------|-----------------|-------------------|--------------------------|-----------------------------|
| | EPS Panels | 1.35 pcf | 2.75 inches | 25 | 450 |

Standards: ASTM C578 - "Standard Specification for Rigid, Cellular Polystyrene Thermal Insulation";

CAN/ULC S701 - "Standard for Thermal Insulation, Polystyrene, Boards and Pipe Covering"

| | Component | EPS Classification |
|-----------------------|------------|--------------------|
| ASTM C578 Ratings: | EPS Panels | Type II |
| CAN/ULC S701 Ratings: | EPS Panels | Type 2 |

May 18th, 2011

[Go to TABLE OF CONTENTS](#)

EVALUATION REPORTS

Good. Solid. Green.™

www.logixicf.com

7 – 4 8



7.1.12 – QAI LISTING REPORT CONTINUED

Quality Auditing Institute


Listing Book

Standards: ASTM E119 - "Standard Test Methods for Fire Tests of Building Construction and Materials";

CAN/ULC S101 – "Standard Methods of Fire Endurance Tests of Building Construction and Materials"

| | Rating | Product Density | Maximum Cavity Width | Maximum Panel Thickness |
|---|--------|-----------------|----------------------|-------------------------|
| ASTM E119 / CAN/ULC S701 Ratings: | 2-Hour | 1.35 pcf | 4 inches | 2 3/4 inches |
| | 3-Hour | 1.35 pcf | 6 1/8 inches | 2 3/4 inches |
| | 4-Hour | 1.35 pcf | 8 inches | 2 3/4 inches |

Structural Rating at above durations for concrete wall at structural design load.



Assembly Details:

1. Insulated Concrete Forms – Standard forms made of two 16" x 48" by 2.75" thick expanded polystyrene (EPS) block panels connected by polypropylene detail webs at 8" O.C. The minimum width of the cavity is 4" as shown in the ratings table above (rating depends on cavity thickness).
2. Reinforcing Steel - No. 4 steel reinforcing bars placed horizontally in each course and vertically at 16" O.C. along centerline of wall cavity thickness.
3. Sand-Limestone Concrete – 145 +/- 5 pcf density, 2900 psi nominal compressive strength concrete.
4. Gypsum Wallboard – Min. 1/2" thick, 1.5 psf minimum density, 48" wide gypsum wallboard fastened to flanges of polypropylene webs with 2" long drywall screws at 16" horizontally and vertically. Joints covered with joint compound, covered with joint tape, and covered with an additional coat of joint compound. Screw heads covered with joint compound.

May 18th, 2011

[Go to TABLE OF CONTENTS](#)

Good. Solid. Green.™

www.logixicf.com

7 – 49

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 04/11

EVALUATION REPORTS

7.1.12 – QAI LISTING REPORT CONTINUED

Quality Auditing Institute

Listing Book

Standard: ASTM D1761 - "Standard Test Methods for Mechanical Fasteners in Wood"

| | | |
|------------|------------|--|
| | Component | Allowable cladding pressures (based on fastener withdrawal values) |
| ASTM D1761 | ICF System | As per tables below |

ASTM D1761 Allowable fastener values (psf) per fastener spacings for LOGIX ICFs:

| Fastener Type | Fastener Length | Withdrawal Resistance with Factor of Safety of 3.0 | 8" Hor. / 12" Vert. | 8" Hor. / 16" Vert. | 16" Hor. / 16" Vert. |
|-------------------------|-----------------|--|---------------------|---------------------|----------------------|
| #6 Coarse Drywall Screw | 1 5/8 in. | 59 lbs | 88.5 | 66.4 | 33.2 |
| #6 Fine Drywall Screw | 1 5/8 in. | 57 lbs | 86.0 | 64.5 | 32.3 |
| 16 gauge staple | 1 1/2 in. | 9 lbs | 14.0 | 10.5 | 5.3 |
| #8 Wood Screw | 2 in. | 69 lbs | 103.5 | 77.6 | 38.8 |
| #8 Exterior Deck Screw | 2 in. | 70 lbs | 105.0 | 78.8 | 39.4 |
| #10 Wood Screw | 2 in. | 66 lbs | 99.0 | 74.3 | 37.1 |

ASTM D1761 Allowable fastener values (kPa) per fastener spacings for LOGIX ICFs:

| Fastener Type | Fastener Length | Withdrawal Resistance with Factor of Safety of 3.0 | 200mm Hor. / 305 mm Vert. | 200 mm Hor. / 400 mm Vert. | 400 mm Hor. / 400 mm Vert. |
|-------------------------|-----------------|--|---------------------------|----------------------------|----------------------------|
| #6 Coarse Drywall Screw | 41.3 mm | 26.8 kg | 4.24 | 3.18 | 1.59 |
| #6 Fine Drywall Screw | 41.3 mm | 26.0 kg | 4.12 | 3.09 | 1.54 |
| 16 gauge staple | 38.1 mm | 4.2 kg | 0.67 | 0.50 | 0.25 |
| #8 Wood Screw | 50.8 mm | 31.3 kg | 4.96 | 3.72 | 1.86 |
| #8 Exterior Deck Screw | 50.8 mm | 31.8 kg | 5.03 | 3.77 | 1.89 |
| #10 Wood Screw | 50.8 mm | 29.9 kg | 4.74 | 3.56 | 1.78 |

May 18th, 2011

[Go to TABLE OF CONTENTS](#)

Good. Solid. Green.™

www.logixicf.com

7 – 50



Rev. Nov 04/11

7.1.12 – QAI LISTING REPORT CONTINUED

Quality Auditing Institute

Listing Book

Standards: ASTM D635 - "Standard Test Method for Rate of Burning and/or Extent and Time of Burning of Plastics in a Horizontal Position"; ASTM D1929 - "Standard Test Method for Determining Ignition Temperature of Plastics"

| | Component | Rating |
|------------|------------------------|-------------------------|
| ASTM D635 | Polypropylene Web Ties | HB (Horizontal Burning) |
| ASTM D1929 | Polypropylene Web Ties | Pass |

Notes: Also meets Florida Building Code (FBC) High Velocity Hurricane Zone (HVHZ) requirements as per Chapter 26 of the FBC.

These products are subjected to limitations as specified above and must be installed in accordance with the manufacturers' instructions. Authorities having jurisdiction should be consulted regarding allowable applications. See manufacturer's listings for other standards listed under QAI certification programs.

May 18th, 2011

[Go to TABLE OF CONTENTS](#)

Good. Solid. Green.™

www.logixicf.com

7 – 51



7.2 – CANADIAN CODE REPORTS

7.2.1 – CCMC (CANADIAN CONSTRUCTION MATERIALS CENTRE)



Evaluation Report CCMC 13110-R

MASTERFORMAT: 03 11 19.01
Issued: 2003-04-17
Re-evaluated: 2009-07-14
Revised: 2009-12-17
Re-evaluation due: 2012-04-17

Logix™ Insulated Concrete Forms

1. Opinion

It is the opinion of the Canadian Construction Materials Centre (CCMC) that “Logix™ Insulated Concrete Forms” when used as an insulated concrete form in accordance with the conditions and limitations stated in Section 3 of this Report, complies with the National Building Code 2005:

- Clause 1.2.1.1.(1)(a), Division A, using the following acceptable solutions from Division B:
 - Article 3.1.5.12. Combustible Insulations and its Protection
 - Article 4.1.1.3. Design Requirements (structural loads and procedures)
 - Article 4.3.3.1. Design Basis for Plain, Reinforced and Pre-Stressed Concrete
 - Subsection 9.3.1. Concrete
 - Section 9.4. Structural Requirements
 - Article 9.10.17.10. Protection of Foamed Plastics
 - Clause 9.15.1.1.(1)(c) General (footings and foundations)
 - Article 9.15.3.3. Application of Footing Width and Area Requirements
 - Clause 9.15.3.5.(1)(c) Adjustments of Footing Widths for Exterior Walls
 - Subsection 9.15.4. Foundation Walls
 - Clause 9.20.1.1.(1)(b) General (masonry and insulating concrete form walls not in contact with the ground)
 - Clause 9.20.1.1.(2) General (masonry and insulating concrete form walls not in contact with the ground)
 - Article 9.20.1.2. Earthquake Reinforcement
 - Subsection 9.20.17. Above-Ground Flat Insulating Concrete Form Walls

This opinion is based on CCMC's evaluation of the technical evidence in Section 4.1 provided by the Report Holder.

Ruling No. 05-11-135 (13110-R) authorizing the use of this product in Ontario, subject to the terms and conditions contained in the Ruling, was made by the Minister of Municipal Affairs and Housing on 2005-05-13 pursuant to s.29 of the Building Code Act, 1992 (see Ruling for terms and conditions). This Ruling is subject to periodic revisions and updates.

7.2.1 – CCMC (CANADIAN CONSTRUCTION MATERIALS CENTRE) CONTINUED

2. Description

“Logix™ Insulated Concrete Forms” units are modular, interlocking concrete forms consisting of two Type 2 expanded-polystyrene (EPS) panels. The two polystyrene panels are connected by polypropylene webs which are molded into the polystyrene panels and equally spaced at 203 mm. The extremities of the polypropylene connectors are embedded 12.7 mm below the exterior surface of the molds.

The polystyrene panels have a preformed interlocking mechanism along their top and bottom edges to facilitate stacking and to prevent the leakage of freshly placed concrete.

The forms are dry-laid and stacked in a running (staggered) configuration. The stacked units form a rectangular space which, after being filled with concrete, forms an insulated, monolithic concrete wall of uniform thickness.

Reinforcement is placed as required to satisfy strength requirements for above- or below-grade loadbearing walls, beams, lintels and shear walls.

The units have external dimensions of 1220 mm in length and 405 mm in height. The polystyrene panels are 70 mm thick, resulting in an overall wall thickness of 240 mm, 290 mm, 340 mm and 390 mm that in turn, encloses a 100 mm, 150 mm, 200 mm and 250 mm concrete walls.

A standard unit is illustrated in Figure 1. Typical wall section details for residential construction are shown in Figure 2. Additional details are available in the Logix Installation Guide, dated November 8, 2008 and/or at www.logixicf.com.




Figure 1. “Logix™ Insulated Concrete Forms” standard unit

7.2.1 – CCMC (CANADIAN CONSTRUCTION MATERIALS CENTRE) CONTINUED




Figure 2. Typical wall section

7.2.1 – CCMC (CANADIAN CONSTRUCTION MATERIALS CENTRE) CONTINUED

3. Conditions and Limitations

CCMC's compliance opinion in Section 1 is bound by the "Logix™ Insulated Concrete Forms" being used in accordance with the conditions and limitations set out below.

- The use of "Logix™ Insulated Concrete Forms" is permitted in the construction of houses and small buildings up to two storeys high that fall under the provisions of Part 9 of Division B of the NBC 2005, subject to all of the conditions listed below.
- The structural applications of "Logix™ Insulated Concrete Forms" must be in strict accordance with the design analysis as prepared for Logix ICF Ltd. by CHIDIAC & Associated Limited, and included in Report No. 080411.1, dated 13 November 2008, from which Tables 4.1.2.1.1 to 4.1.2.1.19 have been reproduced. When "Logix™ Insulated Concrete Forms" is used in structural applications outside the scope of the referenced design analysis, a registered professional engineer skilled in concrete design must certify the design analysis and the design drawings for such applications. The engineer must certify that the construction provides a level of performance equivalent to that required by Part 4 and/or Part 9 of the NBC 2005.
- The attachment of exterior cladding and interior finishing materials has not been assessed by the present evaluation.
- For load-bearing and shear wall applications, the minimum core thickness of "Logix™ Insulated Concrete Forms" must be 150 mm.
- For non-load-bearing wall applications, the minimum core thickness of "Logix™ Insulated Concrete Forms" must be 100 mm.
- The concrete used in "Logix™ Insulated Concrete Forms" must be Type 10 or Type 30 with a minimum compressive strength of 20 MPa and a maximum slump of 150 mm ± 12 mm.
- The maximum aggregate size to be used in conjunction with "Logix™ Insulated Concrete Forms" must be no greater than 14 mm.
- For the wall heights indicated in Tables 4.1.2.1.1 and 4.1.2.1.2, the pouring of concrete must be made at a rate of 1.3 m per hour in consecutive lifts; each lift is limited to a maximum height of 1.3 m.
- The EPS insulation used in this system must comply with CAN/ULC-S701-97 "Standard For Thermal Insulation, Polystyrene, Boards and Pipe Covering," Type 2. EPS insulation manufactured at the Cobourg, Ontario and Chilliwack, British Columbia plants must be made using BASF BFL 422 beads. EPS insulation manufactured at the Edmonton, Alberta plant must be made using Huntsman S7454 beads, while EPS insulation manufactured at Winnipeg, Manitoba plant must be made using Huntsman 5340 beads.
- "Logix™ Insulated Concrete Forms" EPS insulation panels must be aged for at least three weeks from their date of manufacturing.
- The interior face of "Logix™ Insulated Concrete Forms" panels must be protected from the inside of the building in accordance with Sentence 9.10.17.10.(1) of Division B of the NBC 2005.
- For above-grade installations, the exterior face of "Logix™ Insulated Concrete Forms" must be protected with materials conforming to Article 9.20.6.4., Masonry Veneer, and Sections 9.27., Cladding, and/or 9.28., Stucco, of Division B of the NBC 2005.
- The concrete must be cured a minimum of seven days before backfilling. The top of the foundation wall must be supported by the first floor prior to backfilling.
- For below-grade installations, dampproofing material that is compatible with the EPS insulation must be provided in accordance with Article 9.13.2.2., Material Standards (dampproofing), of Division B of the NBC 2005.
- Where hydrostatic pressure exists, waterproofing that is compatible with the EPS insulation must be provided in accordance with Article 9.13.3.2., of Division B of the NBC 2005.
- For foundation-wall installations, the backfill must be placed in such a way as to avoid damaging the wall, the exterior insulation panel and the waterproofing and dampproofing protection. The backfill material must be well drained and a drainage system must be installed around the footing in accordance with the requirements of the NBC 2005.
- The installation of "Logix™ Insulated Concrete Forms" must be in strict compliance with the Logix Installation Guide, dated

www.logixicf.com

Good. Solid. Green.™

7 – 55

LOGIX®
INSULATED CONCRETE FORMS

7.2.1 – CCMC (CANADIAN CONSTRUCTION MATERIALS CENTRE) CONTINUED

November 8, 2008. Only installers trained and authorized by Logix ICF Ltd. shall be contracted to set up the wall system.

4. Technical Evidence

CCMC's Technical Guide for "Logix™ Insulated Concrete Forms" sets out the nature of the technical evidence required by CCMC to enable it to evaluate a product as an acceptable or alternative solution in compliance with the NBC 2005. The Report Holder has submitted test results and engineering design analyses for CCMC's evaluation. Testing was conducted at independent laboratories recognized by CCMC. The corresponding test results for "Logix™ Insulated Concrete Forms" are summarized below.

4.1 NBC 2005 Compliance Data for "Logix™ Insulated Concrete Forms" on which CCMC Based its Opinion in Section 1

4.1.1 Material Requirements

4.1.1.1 Conformance of the EPS

Compliance of the expanded polystyrene thermal insulation with the requirements of CAN/ULC-S701-01 is covered under Intertek Testing Services NA LTD. certification program.

4.1.2 Design Requirements

4.1.2.1 Conformance of Structural Capacity (Steel Reinforcement Designs)

The design analysis in Report No. 080411.1 (see Conditions and Limitations for complete reference) of walls using "Logix™ Insulated Concrete Forms" provides a level of performance equivalent to that required by applicable provisions in Part 4 and/or Part 9 of Division B of the NBC 2005. The corresponding design analysis is summarized in Tables 4.1.2.1.1 to 4.1.2.1.19. The tables provide steel reinforcement specifications for a number of different wall and lintel applications based on specific structural loads. The design assumptions are indicated below each table.

7.2.1 – CCMC (CANADIAN CONSTRUCTION MATERIALS CENTRE) CONTINUED

Table 4.1.2.1.1 Vertical and horizontal steel reinforcement for below-grade walls⁽¹⁾

| Wall Height (m) | Backfill Height (m) | Max. Spacing for Vertical Reinforcement (mm) | | | Max. Spacing for Horizontal Reinforcement (mm) | | |
|--------------------|------------------------|---|-------------|-------------|---|-------------|-------------|
| | | 150-mm Wall | 200-mm Wall | 250-mm Wall | 150-mm Walls | 200-mm Wall | 250-mm Wall |
| 2.44 | 1.22 | 10M @ 400 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| | 1.52 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| | 1.82 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| | 2.12 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| 3.05 | 1.22 | 10M @ 400 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| | 1.52 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| | 1.82 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| | 2.12 | 15M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| | 2.42 | 15M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| | 2.74 | 15M @ 200 | 15M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| 3.66 | 1.22 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| | 1.52 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| | 1.82 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| | 2.12 | 15M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| | 2.52 | 15M @ 200 | 15M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| | 2.82 | – | 15M @ 200 | 10M @ 200 | – | 10M @ 200 | 10M @ 200 |
| | 3.12 | – | – | 15M @ 200 | – | – | 10M @ 200 |
| | 3.35 | – | – | 15M @ 200 | – | – | 10M @ 200 |

Notes to Table 4.1.2.1.1: Table cells without a value indicate that the spacing is not feasible with respect to the proposed backfill height.

(1) Table 4.1.2.1.1. is based on the following assumptions:

- The design is applicable to seismic zones up to $S_a(1.2)$ for soil Type A.
- Maximum building width is 24.0 m.
- Maximum building length is 18.0 m.
- Maximum clear floor span is 8.0 m.
- Maximum clear roof span is 12.0 m with supports at mid-point.
- Maximum number of storeys above grade is two (2).
- Maximum number of storeys below grade is one (1).
- Roof slope is 1:3.
- Roof dead load is 0.60 kPa.
- Floor dead load is 0.70 kPa.
- Roof live load is 0.50 kPa.
- Floor live load is 1.9 kPa.
- Snow load is 1.9 kPa.
- Loads include earth pressure and surcharge loads, plus gravity load. Gravity load assumes 2 ICF storeys and wood-frame roof.
- Wall height above ground is taken 3.05 m.
- The exterior walls are assumed to be clad with clay bricks.
- Specified compressive strength of concrete, f_c at 28 days is 20 MPa.
- Reinforcing bars shall be hard-grade deformed bars conforming to CAN/CSA G30.12, "Billet-Steel Bars for Concrete Reinforcement," Grade 400. Specified yield strength of reinforcement, f_y , is 400 MPa.
- Wall design detailing bends, placement, spacing, splicing and protection of reinforcement shall be in accordance with CAN/CSA A23.3 (R2000), "Design of Concrete Structures."
- Minimum concrete cover for reinforcement is 20 mm from the inside face of concrete.
- Two 15M bars shall be placed around all openings and extend 600 mm (24") beyond each side of the openings.

7.2.1 – CCMC (CANADIAN CONSTRUCTION MATERIALS CENTRE) CONTINUED

- Minimum 28-day concrete yield strength of 20 MPa. Mix designs in accordance with the manufacturer's recommendations.
- Concrete shall be allowed to cure for a minimum of seven days prior to backfilling.
- Basement walls are considered to be supported by the floor system at the top.
- Floor and roof connections to ICF walls shall be designed to accommodate diaphragm action in seismic zones and zones of high wind pressure.
- All materials and workmanship shall conform to the requirements of the NBC 2005 including any Revisions and Errata that have been released as of the issue date of this table.

Table 4.1.2.1.2 Vertical and horizontal steel reinforcement for above-grade walls⁽²⁾

| Wall Height (m) | Max. Spacing for Vertical Reinforcement (mm) | | | Max. Spacing for Horizontal Reinforcement (mm) | | |
|---|--|-------------|-------------|--|-------------|-------------|
| | 150-mm Wall | 200-mm Wall | 250-mm Wall | 150-mm Wall | 200-mm Wall | 200-mm Wall |
| Single-storey concrete construction supporting a wood-frame roof structure | | | | | | |
| 2.44 | 10M @ 400 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| 3.05 | 10M @ 400 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| 3.66 | 10M @ 400 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| Ground floor concrete construction supporting a second storey wood-frame construction and wood frame roof structure | | | | | | |
| 2.44 | 10M @ 400 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| 3.05 | 10M @ 400 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| 3.66 | 10M @ 400 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| Ground floor concrete construction supporting a second storey concrete construction and a wood-frame roof structure | | | | | | |
| 2.44 | 10M @ 400 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| 3.05 | 10M @ 400 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |
| 3.66 | 10M @ 400 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 | 10M @ 200 |

Notes to Table 4.1.2.1.2:

(2) Table 4.1.2.1.2 is based on the following assumptions:

- The design is applicable to seismic zones up to $S_a(1.2)$ for soil Type A.
- Applicable to a maximum factored wind pressure of 3.15 kPa.
- Loads include all applicable gravity loads and wind loads.
- Specified compressive strength of concrete, f'_c at 28 days is 20 MPa.
- Specified yield strength of reinforcement, f_y , is 400 MPa.
- Two 15M bars should be placed around all openings and shall extend at least 600 mm beyond each corner of the opening.

7.2.1 – CCMC (CANADIAN CONSTRUCTION MATERIALS CENTRE) CONTINUED

Table 4.1.2.1.3 Minimum steel reinforcement of lintels with a 250-mm core made with “Logix™ Insulated Concrete Forms”⁽³⁾

| Opening Width (mm) | Factored Uniformly Distributed Load (kN/m) | | | | | | | | | | | | | |
|-----------------------|--|------------------------|--------------|------------------------|--------------|------------------------|--------------|------------------------|--------------|------------------------|--------------|------------------------|--------------|------------------------|
| | 2.0 | | 5.0 | | 10.0 | | 15.0 | | 20.0 | | 25.0 | | 30.0 | |
| | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) |
| 1000 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 |
| 1500 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 55 |
| 2000 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 167 | 1-15M | 305 |
| 2500 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 208 | 1-15M | 417 | 1-20M | 555 |
| 3000 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 111 | 1-15M | 458 | 1-20M | 667 | 1-20M | 805 |
| 3500 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 361 | 1-20M | 708 | 2-15M | 917 | 1-25M | 1055 |
| 4000 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-20M | 611 | 2-15M | 958 | 1-25M | 1167 | 2-20M | 1305 |
| 4500 | 1-15M | 0 | 1-15M | 0 | 1-20M | 166 | 2-15M | 861 | 1-25M | 1208 | 2-20M | 1417 | 2-25M | 1515 |
| 5000 | 1-15M | 0 | 1-15M | 0 | 1-20M | 416 | 1-25M | 1111 | 2-20M | 1458 | 2-25M | 1667 | 2-25M | 1805 |

Table 4.1.2.1.4 Minimum steel reinforcement of lintels with a 200-mm core made with “Logix™ Insulated Concrete Forms”⁽³⁾

| Opening Width (mm) | Factored Uniformly Distributed Load (kN/m) | | | | | | | | | | | | | |
|-----------------------|--|------------------------|--------------|------------------------|--------------|------------------------|--------------|------------------------|--------------|------------------------|--------------|------------------------|--------------|------------------------|
| | 2.0 | | 5.0 | | 10.0 | | 15.0 | | 20.0 | | 25.0 | | 30.0 | |
| | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) |
| 1000 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 |
| 1500 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 83 | 1-15M | 194 |
| 2000 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 167 | 1-15M | 333 | 1-15M | 444 |
| 2500 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 139 | 1-15M | 417 | 1-15M | 583 | 1-20M | 694 |
| 3000 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 389 | 1-15M | 667 | 1-20M | 833 | 2-15M | 944 |
| 3500 | 1-15M | 0 | 1-15M | 0 | 1-15M | 83 | 1-15M | 639 | 1-20M | 917 | 2-15M | 1083 | 1-25M | 1194 |
| 4000 | 1-15M | 0 | 1-15M | 0 | 1-15M | 333 | 1-20M | 889 | 2-15M | 1167 | 1-25M | 1333 | 2-20M | 1444 |
| 4500 | 1-15M | 0 | 1-15M | 0 | 1-20M | 583 | 2-15M | 1139 | 1-25M | 1417 | 1-30M | 1583 | 2-25M | 1694 |
| 5000 | 1-15M | 0 | 1-15M | 0 | 1-20M | 833 | 1-25M | 1389 | 1-30M | 1667 | 2-25M | 1833 | – | – |

7.2.1 – CCMC (CANADIAN CONSTRUCTION MATERIALS CENTRE) CONTINUED

Table 4.1.2.1.5 Minimum steel reinforcement of lintels with a 150-mm core made with “Logix™ Insulated Concrete Forms”(3)

| Opening Width (mm) | Factored Uniformly Distributed Load (kN/m) | | | | | | | | | | | | | |
|-----------------------|--|------------------------|--------------|------------------------|--------------|------------------------|--------------|------------------------|--------------|------------------------|--------------|------------------------|--------------|------------------------|
| | 2.0 | | 5.0 | | 10.0 | | 15.0 | | 20.0 | | 25.0 | | 30.0 | |
| | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) | Bottom Steel | Stirrup End Dist. (mm) |
| 1000 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 83 |
| 1500 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 125 | 1-15M | 250 | 1-15M | 333 |
| 2000 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 167 | 1-15M | 375 | 1-15M | 500 | 1-15M | 583 |
| 2500 | 1-15M | 0 | 1-15M | 0 | 1-15M | 0 | 1-15M | 417 | 1-15M | 625 | 1-15M | 750 | 1-20M | 833 |
| 3000 | 1-15M | 0 | 1-15M | 0 | 1-15M | 250 | 1-15M | 667 | 1-15M | 875 | 1-20M | 1000 | 2-15M | 1083 |
| 3500 | 1-15M | 0 | 1-15M | 0 | 1-15M | 500 | 1-20M | 917 | 1-20M | 1125 | 2-15M | 1250 | 1-25M | 1133 |
| 4000 | 1-15M | 0 | 1-15M | 0 | 1-15M | 750 | 1-20M | 1167 | 2-15M | 1375 | 1-25M | 1500 | – | – |
| 4500 | 1-15M | 0 | 1-15M | 0 | 1-20M | 1000 | 2-15M | 1417 | 1-25M | 1625 | – | – | – | – |
| 5000 | 1-15M | 0 | 1-15M | 0 | 1-20M | 1250 | 1-25M | 1667 | – | – | – | – | – | – |

Note to Tables 4.1.2.1.3 to 4.1.2.1.5: Table cells without a value indicate that the load is not feasible with respect to the proposed core thickness.

(3) Tables 4.1.2.1.3 to 4.1.2.1.5 are based on the following assumptions:

- The factored uniformly distributed load includes live and dead loads.
- The minimum height of the lintel is 400 mm.
- Stirrups are single leg fabricated from 10M bars spaced at 170 mm on centre.
- Lintel reinforcing is located at the bottom of the lintel and projects 200 mm into the lintel support on each side.
- Specified compressive strength of concrete, at 28 days f'_c , is 20 MPa.
- Specified yield strength of reinforcement, f_y , is 400 MPa.
- Two 15M bars should be placed around all openings and shall extend at least 600 mm beyond each corner of the opening.

7.2.1 – CCMC (CANADIAN CONSTRUCTION MATERIALS CENTRE) CONTINUED

Table 4.1.2.1.6 Minimum solid shear wall length for wind pressure equal to 0.35 kPa⁽⁴⁾

| Wall Length (m) | Wall Width (m) | Wall Thickness (mm) | | | | | | | | | | | |
|-----------------|----------------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|
| | | 150 | | | | 200 | | | | 250 | | | |
| | | 2 nd Floor | | 1 st Floor | | 2 nd Floor | | 1 st Floor | | 2 nd Floor | | 1 st Floor | |
| | | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. |
| 12 | 6 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 15 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 18 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 21 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 24 | 1.50 | 1.50 | 1.50 | 1.62 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| 18 | 6 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 15 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 18 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 21 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 24 | 1.50 | 1.50 | 1.50 | 1.62 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |

Table 4.1.2.1.7 Minimum solid shear wall length for wind pressure equal to 0.45 kPa⁽⁴⁾

| Wall Length (m) | Wall Width (m) | Wall Thickness (mm) | | | | | | | | | | | |
|-----------------|----------------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|
| | | 150 | | | | 200 | | | | 250 | | | |
| | | 2 nd Floor | | 1 st Floor | | 2 nd Floor | | 1 st Floor | | 2 nd Floor | | 1 st Floor | |
| | | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. |
| 12 | 6 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 15 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 18 | 1.50 | 1.50 | 1.50 | 1.56 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 21 | 1.50 | 1.50 | 1.50 | 1.82 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 24 | 1.50 | 1.50 | 1.50 | 2.08 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| 18 | 6 | 1.50 | 1.50 | 1.50 | 1.56 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 1.50 | 1.50 | 1.56 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 15 | 1.50 | 1.50 | 1.50 | 1.56 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 18 | 1.50 | 1.50 | 1.56 | 1.56 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 21 | 1.50 | 1.50 | 1.56 | 1.82 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 24 | 1.50 | 1.50 | 1.56 | 2.08 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |

7.2.1 – CCMC (CANADIAN CONSTRUCTION MATERIALS CENTRE) CONTINUED

Table 4.1.2.1.8 Minimum solid shear wall length for wind pressure equal to 0.55 kPa⁽⁴⁾

| Wall Length (m) | Wall Width (m) | Wall Thickness (mm) | | | | | | | | | | | |
|-----------------|----------------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|
| | | 150 | | | | 200 | | | | 250 | | | |
| | | 2 nd Floor | | 1 st Floor | | 2 nd Floor | | 1 st Floor | | 2 nd Floor | | 1 st Floor | |
| | | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. |
| 12 | 6 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 15 | 1.50 | 1.50 | 1.50 | 1.59 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 18 | 1.50 | 1.50 | 1.50 | 1.90 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 21 | 1.50 | 1.50 | 1.50 | 2.22 | 1.50 | 1.50 | 1.50 | 1.59 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 24 | 1.50 | 1.50 | 1.50 | 2.54 | 1.50 | 1.50 | 1.50 | 1.82 | 1.50 | 1.50 | 1.50 | 1.50 |
| 18 | 6 | 1.50 | 1.50 | 1.50 | 1.90 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 1.50 | 1.50 | 1.90 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 15 | 1.50 | 1.50 | 1.59 | 1.90 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 18 | 1.50 | 1.50 | 1.90 | 1.90 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 21 | 1.50 | 1.50 | 1.90 | 2.22 | 1.50 | 1.50 | 1.50 | 1.59 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 24 | 1.50 | 1.50 | 1.90 | 2.54 | 1.50 | 1.50 | 1.50 | 1.82 | 1.50 | 1.50 | 1.50 | 1.50 |

Table 4.1.2.1.9 Minimum solid shear wall length for wind pressure equal to 0.65 kPa⁽⁴⁾

| Wall Length (m) | Wall Width (m) | Wall Thickness (mm) | | | | | | | | | | | |
|-----------------|----------------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|
| | | 150 | | | | 200 | | | | 250 | | | |
| | | 2 nd Floor | | 1 st Floor | | 2 nd Floor | | 1 st Floor | | 2 nd Floor | | 1 st Floor | |
| | | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. |
| 12 | 6 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 15 | 1.50 | 1.50 | 1.50 | 1.88 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 18 | 1.50 | 1.50 | 1.50 | 2.25 | 1.50 | 1.50 | 1.50 | 1.61 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 21 | 1.50 | 1.50 | 1.50 | 2.63 | 1.50 | 1.50 | 1.50 | 1.88 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 24 | 1.50 | 1.50 | 1.50 | 3.00 | 1.50 | 1.50 | 1.50 | 2.15 | 1.50 | 1.50 | 1.50 | 1.61 |
| 18 | 6 | 1.50 | 1.50 | 1.50 | 2.25 | 1.50 | 1.50 | 1.50 | 1.61 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 1.50 | 1.50 | 2.25 | 1.50 | 1.50 | 1.50 | 1.61 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 15 | 1.50 | 1.50 | 1.88 | 2.25 | 1.50 | 1.50 | 1.50 | 1.61 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 18 | 1.50 | 1.50 | 2.25 | 2.25 | 1.50 | 1.50 | 1.61 | 1.61 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 21 | 1.50 | 1.50 | 2.25 | 2.63 | 1.50 | 1.50 | 1.61 | 1.88 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 24 | 1.50 | 1.50 | 2.25 | 3.00 | 1.50 | 1.50 | 1.61 | 2.15 | 1.50 | 1.50 | 1.50 | 1.61 |

7.2.1 – CCMC (CANADIAN CONSTRUCTION MATERIALS CENTRE) CONTINUED

Table 4.1.2.1.10 Minimum solid shear wall length for wind pressure equal to 0.75 kPa⁽⁴⁾

| Wall Length (m) | Wall Width (m) | Wall Thickness (mm) | | | | | | | | | | | |
|-----------------|----------------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|
| | | 150 | | | | 200 | | | | 250 | | | |
| | | 2 nd Floor | | 1 st Floor | | 2 nd Floor | | 1 st Floor | | 2 nd Floor | | 1 st Floor | |
| | | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. |
| 12 | 6 | 1.50 | 1.50 | 1.50 | 1.73 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 1.50 | 1.73 | 1.73 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 15 | 1.50 | 1.50 | 1.73 | 2.16 | 1.50 | 1.50 | 1.50 | 1.55 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 18 | 1.50 | 1.50 | 1.73 | 2.60 | 1.50 | 1.50 | 1.50 | 1.86 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 21 | 1.50 | 1.51 | 1.73 | 2.03 | 1.50 | 1.50 | 1.50 | 2.17 | 1.50 | 1.50 | 1.50 | 1.63 |
| | 24 | 1.50 | 1.73 | 1.73 | 3.46 | 1.50 | 1.50 | 1.50 | 2.48 | 1.50 | 1.50 | 1.50 | 1.86 |
| 18 | 6 | 1.50 | 1.50 | 1.50 | 2.60 | 1.50 | 1.50 | 1.50 | 1.86 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 1.50 | 1.73 | 2.60 | 1.50 | 1.50 | 1.50 | 1.86 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 15 | 1.50 | 1.50 | 2.16 | 2.60 | 1.50 | 1.50 | 1.55 | 1.86 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 18 | 1.50 | 1.50 | 2.60 | 2.60 | 1.50 | 1.50 | 1.86 | 1.86 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 21 | 1.50 | 1.51 | 2.60 | 3.03 | 1.50 | 1.50 | 1.86 | 2.17 | 1.50 | 1.50 | 1.50 | 1.63 |
| | 24 | 1.50 | 1.73 | 2.60 | 3.46 | 1.50 | 1.50 | 1.86 | 2.48 | 1.50 | 1.50 | 1.50 | 1.86 |

Table 4.1.2.1.11 Minimum solid shear wall length for wind pressure equal to 0.95 kPa⁽⁴⁾

| Wall Length (m) | Wall Width (m) | Wall Thickness (mm) | | | | | | | | | | | |
|-----------------|----------------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|
| | | 150 | | | | 200 | | | | 250 | | | |
| | | 2 nd Floor | | 1 st Floor | | 2 nd Floor | | 1 st Floor | | 2 nd Floor | | 1 st Floor | |
| | | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. |
| 12 | 6 | 1.50 | 1.50 | 1.50 | 2.19 | 1.50 | 1.50 | 1.50 | 1.57 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 1.50 | 2.19 | 2.19 | 1.50 | 1.50 | 1.57 | 1.57 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 15 | 1.50 | 1.50 | 2.19 | 2.74 | 1.50 | 1.50 | 1.57 | 1.96 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 18 | 1.50 | 1.64 | 2.19 | 3.29 | 1.50 | 1.50 | 1.57 | 2.36 | 1.50 | 1.50 | 1.50 | 1.77 |
| | 21 | 1.50 | 1.92 | 2.19 | 3.84 | 1.50 | 1.50 | 1.57 | 2.75 | 1.50 | 1.50 | 1.50 | 2.06 |
| | 24 | 1.50 | 2.19 | 2.19 | 4.39 | 1.50 | 1.57 | 1.57 | 3.14 | 1.50 | 1.50 | 1.50 | 2.35 |
| 18 | 6 | 1.50 | 1.64 | 1.50 | 3.29 | 1.50 | 1.50 | 1.50 | 2.36 | 1.50 | 1.50 | 1.50 | 1.77 |
| | 12 | 1.50 | 1.64 | 2.19 | 3.29 | 1.50 | 1.50 | 1.57 | 2.36 | 1.50 | 1.50 | 1.50 | 1.77 |
| | 15 | 1.50 | 1.64 | 2.74 | 3.29 | 1.50 | 1.50 | 1.96 | 2.36 | 1.50 | 1.50 | 1.50 | 1.77 |
| | 18 | 1.64 | 1.64 | 3.29 | 3.29 | 1.50 | 1.50 | 2.36 | 2.36 | 1.50 | 1.50 | 1.77 | 1.77 |
| | 21 | 1.64 | 1.92 | 3.29 | 3.84 | 1.50 | 1.50 | 2.36 | 2.75 | 1.50 | 1.50 | 1.77 | 2.06 |
| | 24 | 1.64 | 2.19 | 3.29 | 4.39 | 1.50 | 1.57 | 2.36 | 3.14 | 1.50 | 1.50 | 1.77 | 2.35 |

7.2.1 – CCMC (CANADIAN CONSTRUCTION MATERIALS CENTRE) CONTINUED

Table 4.1.2.1.12 Minimum solid shear wall length for wind pressure equal to 1.25 kPa⁽⁴⁾

| Wall Length (m) | Wall Width (m) | Wall Thickness (mm) | | | | | | | | | | | |
|-----------------|----------------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|-----------------------|-----------|
| | | 150 | | | | 200 | | | | 250 | | | |
| | | 2 nd Floor | | 1 st Floor | | 2 nd Floor | | 1 st Floor | | 2 nd Floor | | 1 st Floor | |
| | | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. | Short dir. | Long dir. |
| 12 | 6 | 1.50 | 1.50 | 1.50 | 2.89 | 1.50 | 1.50 | 1.50 | 2.07 | 1.50 | 1.50 | 1.50 | 1.55 |
| | 12 | 1.50 | 1.50 | 2.89 | 2.89 | 1.50 | 1.50 | 2.07 | 2.07 | 1.50 | 1.50 | 1.55 | 1.55 |
| | 15 | 1.50 | 1.80 | 2.89 | 3.61 | 1.50 | 1.50 | 2.07 | 2.58 | 1.50 | 1.50 | 1.55 | 1.94 |
| | 18 | 1.50 | 2.16 | 2.89 | 4.33 | 1.50 | 1.55 | 2.07 | 3.10 | 1.50 | 1.50 | 1.55 | 2.32 |
| | 21 | 1.50 | 2.52 | 2.89 | 5.05 | 1.50 | 1.81 | 2.07 | 3.62 | 1.50 | 1.50 | 1.55 | 2.71 |
| | 24 | 1.50 | 2.89 | 2.89 | 5.77 | 1.50 | 2.07 | 2.07 | 4.13 | 1.50 | 1.55 | 1.55 | 3.10 |
| 18 | 6 | 1.50 | 2.16 | 1.50 | 4.33 | 1.50 | 1.55 | 1.50 | 3.10 | 1.50 | 1.50 | 1.50 | 2.32 |
| | 12 | 1.50 | 2.16 | 2.89 | 4.33 | 1.50 | 1.55 | 2.07 | 3.10 | 1.50 | 1.50 | 1.55 | 2.32 |
| | 15 | 1.80 | 2.16 | 3.61 | 4.33 | 1.50 | 1.55 | 2.58 | 3.10 | 1.50 | 1.50 | 1.94 | 2.32 |
| | 18 | 2.16 | 2.16 | 4.33 | 4.33 | 1.55 | 1.55 | 3.10 | 3.10 | 1.50 | 1.50 | 2.32 | 2.32 |
| | 21 | 2.16 | 2.52 | 4.33 | 5.05 | 1.55 | 1.81 | 3.10 | 3.62 | 1.50 | 1.50 | 2.32 | 2.71 |
| | 24 | 2.16 | 2.89 | 4.33 | 5.77 | 1.55 | 2.07 | 3.10 | 4.13 | 1.50 | 1.55 | 2.32 | 3.10 |

Notes to Tables 4.1.2.1.6 to 4.1.2.1.12:

(4) Table 4.1.2.1.6 to 4.1.2.1.12 are based on the following assumptions:

- Linear interpolation is permitted between hourly wind pressures and building lengths.
- Design applicable to soil Type A.
- Specified compressive strength of concrete, f'_c , at 28 days is 20 MPa.
- Specified yield strength of reinforcement, f_y , is 400 MPa.

Table 4.1.2.1.13 Minimum solid shear wall length for $S_a(0.2) \leq 0.2$ ⁽⁵⁾ and soil Type A

| Wall Length (m) | Wall Width (m) | Wall Thickness (mm) | | | | | |
|-----------------|----------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| | | 150 | | 200 | | 250 | |
| | | 2 nd Floor | 1 st Floor | 2 nd Floor | 1 st Floor | 2 nd Floor | 1 st Floor |
| 12 | 6 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 15 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 18 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 21 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 24 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| 18 | 6 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 15 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 18 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 21 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 24 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |

7.2.1 – CCMC (CANADIAN CONSTRUCTION MATERIALS CENTRE) CONTINUED

Table 4.1.2.1.14 Minimum solid shear wall length for $S_a(0.2)$ equals $0.3^{(5)}$ and soil Type A

| Wall Length (m) | Wall Width (m) | Wall Thickness (mm) | | | | | |
|-----------------|----------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| | | 150 | | 200 | | 250 | |
| | | 2 nd Floor | 1 st Floor | 2 nd Floor | 1 st Floor | 2 nd Floor | 1 st Floor |
| 12 | 6 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 15 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 18 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 21 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 24 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| 18 | 6 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 15 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 18 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 21 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 24 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |

Table 4.1.2.1.15 Minimum solid shear wall length for $S_a(0.2)$ equals $0.45^{(5)}$ and soil Type A

| Wall Length (m) | Wall Width (m) | Wall Thickness (mm) | | | | | |
|-----------------|----------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| | | 150 | | 200 | | 250 | |
| | | 2 nd Floor | 1 st Floor | 2 nd Floor | 1 st Floor | 2 nd Floor | 1 st Floor |
| 12 | 6 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 15 | 1.50 | 1.58 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 18 | 1.50 | 1.80 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 21 | 1.50 | 2.02 | 1.50 | 1.67 | 1.50 | 1.50 |
| | 24 | 1.50 | 2.25 | 1.50 | 1.86 | 1.50 | 1.57 |
| 18 | 6 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 1.80 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 15 | 1.50 | 2.08 | 1.50 | 1.71 | 1.50 | 1.50 |
| | 18 | 1.50 | 2.36 | 1.50 | 1.94 | 1.50 | 1.63 |
| | 21 | 1.50 | 2.64 | 1.50 | 2.16 | 1.50 | 1.81 |
| | 24 | 1.65 | 2.92 | 1.50 | 2.38 | 1.50 | 2.00 |

7.2.1 – CCMC (CANADIAN CONSTRUCTION MATERIALS CENTRE) CONTINUED

Table 4.1.2.1.16 Minimum solid shear wall length for $S_u(0.2)$ equals 0.66⁽⁵⁾ and soil Type A

| Wall Length (m) | Wall Width (m) | Wall Thickness (mm) | | | | | |
|-----------------|----------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| | | 150 | | 200 | | 250 | |
| | | 2 nd Floor | 1 st Floor | 2 nd Floor | 1 st Floor | 2 nd Floor | 1 st Floor |
| 12 | 6 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 2.16 | 1.50 | 1.81 | 1.50 | 1.55 |
| | 15 | 1.50 | 2.52 | 1.50 | 2.10 | 1.50 | 1.79 |
| | 18 | 1.58 | 2.88 | 1.50 | 2.39 | 1.50 | 2.04 |
| | 21 | 1.79 | 3.24 | 1.50 | 2.68 | 1.50 | 2.28 |
| | 24 | 1.99 | 3.60 | 1.61 | 2.97 | 1.50 | 2.52 |
| 18 | 6 | 1.50 | 1.99 | 1.50 | 1.68 | 1.50 | 1.50 |
| | 12 | 1.58 | 2.88 | 1.50 | 2.39 | 1.50 | 2.04 |
| | 15 | 1.85 | 3.33 | 1.50 | 2.74 | 1.50 | 2.33 |
| | 18 | 2.11 | 3.78 | 1.70 | 3.10 | 1.50 | 2.62 |
| | 21 | 2.38 | 4.23 | 1.91 | 3.45 | 1.58 | 2.90 |
| | 24 | 2.65 | 4.67 | 2.11 | 3.80 | 1.75 | 3.19 |

Table 4.1.2.1.17 Minimum solid shear wall length for $S_u(0.2)$ equals 0.75⁽⁵⁾ and soil Type A

| Wall Length (m) | Wall Width (m) | Wall Thickness (mm) | | | | | |
|-----------------|----------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| | | 150 | | 200 | | 250 | |
| | | 2 nd Floor | 1 st Floor | 2 nd Floor | 1 st Floor | 2 nd Floor | 1 st Floor |
| 12 | 6 | 1.50 | 1.72 | 1.50 | 1.50 | 1.50 | 1.50 |
| | 12 | 1.50 | 2.57 | 1.50 | 2.15 | 1.50 | 1.85 |
| | 15 | 1.64 | 3.00 | 1.50 | 2.50 | 1.50 | 2.14 |
| | 18 | 1.88 | 3.43 | 1.53 | 2.84 | 1.50 | 2.42 |
| | 21 | 2.13 | 3.86 | 1.73 | 3.19 | 1.50 | 2.71 |
| | 24 | 2.37 | 4.28 | 1.92 | 3.53 | 1.60 | 3.00 |
| 18 | 6 | 1.50 | 2.36 | 1.50 | 2.00 | 1.50 | 1.73 |
| | 12 | 1.88 | 3.43 | 1.53 | 2.84 | 1.50 | 2.42 |
| | 15 | 2.20 | 3.96 | 1.78 | 3.27 | 1.50 | 2.77 |
| | 18 | 2.52 | 4.50 | 2.02 | 3.69 | 1.68 | 3.11 |
| | 21 | 2.83 | 5.03 | 2.27 | 4.11 | 1.88 | 3.46 |
| | 24 | 3.15 | 5.56 | 2.52 | 4.53 | 2.08 | 3.80 |

7.2.1 – CCMC (CANADIAN CONSTRUCTION MATERIALS CENTRE) CONTINUED

Table 4.1.2.1.18 Minimum solid shear wall length for $S_a(0.2)$ equals 0.94⁽⁵⁾ and soil Type A

| Wall Length (m) | Wall Width (m) | Wall Thickness (mm) | | | | | |
|-----------------|----------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| | | 150 | | 200 | | 250 | |
| | | 2 nd Floor | 1 st Floor | 2 nd Floor | 1 st Floor | 2 nd Floor | 1 st Floor |
| 12 | 6 | 1.50 | 2.16 | 1.50 | 1.84 | 1.50 | 1.59 |
| | 12 | 1.74 | 3.23 | 1.50 | 2.70 | 1.50 | 2.32 |
| | 15 | 2.05 | 3.76 | 1.68 | 3.13 | 1.50 | 2.68 |
| | 18 | 2.36 | 4.30 | 1.92 | 3.57 | 1.61 | 3.04 |
| | 21 | 2.67 | 4.83 | 2.16 | 4.00 | 1.81 | 3.40 |
| | 24 | 2.97 | 5.37 | 2.41 | 4.43 | 2.01 | 3.76 |
| 18 | 6 | 1.56 | 2.96 | 1.50 | 2.51 | 1.50 | 2.17 |
| | 12 | 2.36 | 4.30 | 1.92 | 3.57 | 1.61 | 3.04 |
| | 15 | 2.76 | 4.97 | 2.23 | 4.09 | 1.86 | 3.47 |
| | 18 | 3.15 | 5.63 | 2.54 | 4.62 | 2.11 | 3.90 |
| | 21 | 3.55 | 6.30 | 2.84 | 5.15 | 2.36 | 4.33 |
| | 24 | 3.95 | 6.97 | 3.15 | 5.67 | 2.60 | 4.76 |

Table 4.1.2.1.19 Minimum solid shear wall length for $S_a(0.2) > 0.94 \leq 1.2$ ⁽⁵⁾ and soil Type A

| Wall Length (m) | Wall Width (m) | Wall Thickness (mm) | | | | | |
|-----------------|----------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| | | 150 | | 200 | | 250 | |
| | | 2 nd Floor | 1 st Floor | 2 nd Floor | 1 st Floor | 2 nd Floor | 1 st Floor |
| 12 | 6 | 1.50 | 2.75 | 1.50 | 2.34 | 1.50 | 2.04 |
| | 12 | 2.22 | 4.12 | 1.83 | 3.45 | 1.54 | 2.96 |
| | 15 | 2.62 | 4.80 | 2.14 | 4.00 | 1.80 | 3.42 |
| | 18 | 3.01 | 5.49 | 2.45 | 4.55 | 2.06 | 3.88 |
| | 21 | 3.40 | 6.17 | 2.76 | 5.10 | 2.31 | 4.34 |
| | 24 | 3.80 | 6.85 | 3.07 | 5.66 | 2.57 | 4.80 |
| 18 | 6 | 1.99 | 3.78 | 1.66 | 3.21 | 1.50 | 2.77 |
| | 12 | 3.01 | 5.49 | 2.45 | 4.55 | 2.06 | 3.88 |
| | 15 | 3.52 | 6.34 | 2.84 | 5.22 | 2.37 | 4.43 |
| | 18 | 4.04 | 7.19 | 3.24 | 5.90 | 2.69 | 4.98 |
| | 21 | 4.53 | 8.05 | 3.63 | 6.57 | 3.01 | 5.53 |
| | 24 | 5.04 | 8.90 | 4.02 | 7.24 | 3.32 | 6.08 |

Notes to Tables 4.1.2.1.13 to 4.1.2.1.19:

(5) Table 4.1.2.1.13 to 4.1.2.1.19 are based on the following assumptions:

- Linear interpolation is permitted between hourly wind pressures and building lengths.
- Design applicable to soil Type A.
- Specified compressive strength of concrete, f'_c , at 28 days is 20 MPa.
- Specified yield strength of reinforcement, f_y , is 400 MPa.

7.2.1 – CCMC (CANADIAN CONSTRUCTION MATERIALS CENTRE) CONTINUED

Report Holder: Beaver Plastics Ltd.
Suite 199, 1917 West 4th Ave
Vancouver, BC V6J 1M7
Tel: 1-866-944-0153
604-734-9244
Fax: 604-734-9144

Plant(s): Chilliwack, BC
Cobourg, ON
Edmonton, AB
Winnipeg, MB

This Report is issued by the Canadian Construction Materials Centre, a program of the Institute for Research in Construction at the National Research Council of Canada. The Report must be read in the context of the entire CCMC Registry of Product Evaluations, including, without limitation, the introduction therein which sets out important information concerning the interpretation and use of CCMC Evaluation Reports.

Readers must confirm that the Report is current and has not been withdrawn or superseded by a later issue. Please refer to <http://www.nrc-cnrc.gc.ca/eng/services/irc/ccmc.html>, or contact the Canadian Construction Materials Centre, Institute for Research in Construction, National Research Council of Canada, 1200 Montreal Road, Ottawa, Ontario, K1A 0R6. Telephone (613) 993-6189. Fax (613) 952-0268.

NRC has evaluated the material, product, system or service described herein only for those characteristics stated herein. The information and opinions in this Report are directed to those who have the appropriate degree of experience to use and apply its contents. This Report is provided without representation, warranty, or guarantee of any kind, expressed, or implied, and the National Research Council of Canada (NRC) provides no endorsement for any evaluated material, product, system or service described herein. NRC accepts no responsibility whatsoever arising in any way from any and all use and reliance on the information contained in this Report. NRC is not undertaking to render professional or other services on behalf of any person or entity nor to perform any duty owed by any person or entity to another person or entity.


7.2.2 – QAI FIRE RESISTANCE RATING

Standards: ASTM E119 - “Standard Test Methods for Fire Tests of Building Construction and Materials”;

CAN/ULC S101 – “Standard Methods of Fire Endurance Tests of Building Construction and Materials”

| | Rating | Product Density | Maximum Cavity Width | Maximum Panel Thickness |
|---|--------|-----------------|----------------------|-------------------------|
| ASTM E119 / CAN/ULC S701 Ratings: | 2-Hour | 1.35 pcf | 4 inches | 2 3/4 inches |
| | 3-Hour | 1.35 pcf | 6 1/8 inches | 2 3/4 inches |
| | 4-Hour | 1.35 pcf | 8 inches | 2 3/4 inches |

Structural Rating at above durations for concrete wall at structural design load.



Assembly Details:

1. Insulated Concrete Forms – Standard forms made of two 16” x 48” by 2.75” thick expanded polystyrene (EPS) block panels connected by polypropylene detail webs at 8” O.C. The minimum width of the cavity is 4” as shown in the ratings table above (rating depends on cavity thickness).
2. Reinforcing Steel - No. 4 steel reinforcing bars placed horizontally in each course and vertically at 16” O.C. along centerline of wall cavity thickness.
3. Sand-Limestone Concrete – 145 +/- 5 pcf density, 2900 psi nominal compressive strength concrete.
4. Gypsum Wallboard – Min. ½” thick, 1.5 psf minimum density, 48” wide gypsum wallboard fastened to flanges of polypropylene webs with 2” long drywall screws at 16” horizontally and vertically. Joints covered with joint compound, covered with joint tape, and covered with an additional coat of joint compound. Screw heads covered with joint compound.

December 6, 2010

[Go to TABLE OF CONTENTS](#)

7.2.3 – NON-COMBUSTIBLE CONSTRUCTION (NATIONAL BUILDING CODE OF CANADA)

Intertek Testing Services, an independent, nationally accredited testing agency, conducted a fire evaluation and determined the products listed below meets clause 3.2.3.8 when used with LOGIX for exterior walls for building over 3 storeys.

Copies of the evaluation reports can be downloaded at www.logixicf.com.

Products evaluated:

- Dryvit Exsulation 2000 System
- Dryvit Infinity System
- Dryvit Exsulation 2000 System
- Dryvit Fedderlite 2000 System
- Dryvit Outsulation System
- Dryvit Outsulation MD System
- Sto EIFS
- Sto Signature System
- Sto CLASSIC NExT
- Sto CLASSIC NExT NC
- Sto SIGNATURE SYSTEM NC
- Standard ADEX System
- Standard ADEX RF System
- Durock ICF Finish System

7.2.4 – VAPOUR BARRIER (NATIONAL BUILDING CODE OF CANADA)

Logix Insulated Concrete Forms Ltd.
Project No. 3109888-R1

January 30, 2007
Revised: January 31, 2007
Page 2 of 4

1 Introduction

Intertek Testing Services NA Ltd. (Intertek) has conducted an engineering evaluation for Logix Insulated Concrete Forms Ltd., on Logix ICF, to evaluate the vapor permeance properties of the product. The evaluation was conducted to determine if Logix ICF meets the 2005 National Building Code (NBC) for use as a vapor barrier.

2 Sample Description

Logix ICF consists of rigid interlocking expanded polystyrene (EPS) foam plastic boards that serve as permanent formwork for reinforced concrete, exterior and interior walls, and foundation and retaining walls.

3 Reference Documents

- 2005 National Building Code (NBC)
- ASTM E96/96M-05, Standard Test Methods for Water Vapor Transmission of Materials (ASTM E96)
- Intertek Test Report 3048347 dated October 14, 2003
- Intertek Letter dated January 6, 2005

4 Evaluation Method

Vapor barrier properties and installation are described in detail in Section 5.5.1.2 of the 2005 NBC. These details are summarized below:

- 1) The vapor barrier shall have sufficiently low permeance and shall be positioned in the building component or assembly so as to
 - a) minimize moisture transfer by diffusion, to surfaces within the assembly that would be cold enough to cause condensation at the design temperature and humidity conditions, or
 - b) reduce moisture transfer by diffusion, to surfaces within the assembly that would be cold enough to cause condensation at the design temperature and humidity conditions, to a rate that will not allow sufficient accumulation of moisture to cause deterioration or otherwise adversely affect any of
 - i. the health or safety of building users,
 - ii. the intended use of the building, or
 - iii. the operation of building services.
- 2) Coatings applied to gypsum wallboard to provide required resistance to vapour diffusion shall conform to the requirements of Sentence (1) when tested in accordance with CAN/CGSB-1.501-M, "Method for Permeance of Coated Wallboard."

Intertek ETL SEMKO
Testing everywhere for markets anywhere.

Good. Solid. Green.™

www.logixicf.com

7-71

LOGIX®
INSULATED CONCRETE FORMS

7.2.4 – VAPOUR BARRIER (NATIONAL BUILDING CODE OF CANADA) CONTINUED

Logix Insulated Concrete Forms Ltd.
Project No. 3109888-R1

January 30, 2007
Revised: January 31, 2007
Page 3 of 4

- 3) Coatings applied to materials other than gypsum wallboard to provide required resistance to vapor diffusion shall conform to the requirements of Sentence (1) when tested in accordance with ASTM E96, "Water Vapor Transmission of Materials" by the desiccant method (dry cup).

Vapor Barrier materials are further discussed in Section 9.25.4.2 of the 2005 NBC under Sentence (1) which is summarized below:

- 1) Vapor barriers shall have a permeance not greater than 60 ng/Pa-s-m² measured in accordance with ASTM E96, "Water Vapor Transmission of Materials" by the desiccant method (dry cup).


Logix ICF fall under Sentence (3) of Section 5.5.1.2 of the 2005 NBC and have been tested by Intertek in accordance with ASTM E96 using the desiccant method. The results were summarized in Intertek Test Report 3048347 dated October 14, 2003 and showed that a 1-inch Logix ICF had a water permeance of 100 ng/Pa-s-m². In the field, Logix ICF is installed with a 2.75-inch thickness and thus the calculated water permeance at this thickness is 36 ng/Pa-s-m². The detailed calculations are shown in Intertek Letter dated January 5, 2005. Based on these results, Logix ICF meets the requirements of Section 9.25.4.2, Sentence (1) of the 2005 NBC and can be installed without the use of a vapor barrier.

5 Conclusion


Intertek has conducted an engineering evaluation for Logix Insulated Concrete Forms Ltd., on Logix ICF, to determine if the Logix ICF meets the 2005 National Building Code as a vapor barrier. The analysis, per Section 4 above, showed that Logix ICF meets the water permeance requirements and can be installed without a vapor barrier.

INTERTEK TESTING SERVICES NA LTD.

Reported by:


Matt Lansdowne, EIT
Engineer, Building Products

Reviewed by:


Kal Kooner, EIT
Team Leader, Engineering Services Canada

Intertek ETL SEMKO
Testing everywhere for markets anywhere.

Good. Solid. Green.™

www.logixicf.com

7-72

LOGIX®
INSULATED CONCRETE FORMS

7.2.4 – VAPOUR BARRIER (NATIONAL BUILDING CODE OF CANADA) CONTINUED

Logix Insulated Concrete Forms Ltd.
Project No. 3109888-R1

January 30, 2007
Revised: January 31, 2007
Page 4 of 4

REVISION SUMMARY

| DATE | SUMMARY |
|------------------|---|
| February 1, 2007 | Added additional reference to 2005 NBC and maximum permeance requirements |
| | |
| | |

EVALUATION REPORTS

Intertek ETL SEMKO
Testing everywhere for markets anywhere.

Good. Solid. Green.™

www.logixicf.com

7 – 73

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Sep 23/09

7.2.5 – GREENGUARD INDOOR AIR QUALITY CERTIFIED



Certificate of Compliance

LOGIX Platinum Series

LOGIX Insulated Concrete Forms, Ltd.

This product has been certified according to the GREENGUARD Indoor Air Quality (IAQ) Certification Program for Low Emitting Products

Certification Details:

Certificate No: 938-00

Status: Certified

Period: 11/2010 - 10/2011

Restrictions: NONE

Reference Standard: GGPS.001 GREENGUARD IAQ Standard for Building Materials, Finishes, and Furnishings

Product Type: Insulation and HVAC Products

| Criteria | Allowable Limits |
|--|--------------------------|
| TVOC ¹ | ≤ 0.5 mg/m ³ |
| Formaldehyde | ≤ 0.05 ppm |
| Total Aldehydes ² | ≤ 0.1 ppm |
| Individual VOCs ³ | ≤ 0.1 TLV |
| Respirable Particles (PM ₁₀) (mg/m ³) | ≤ 0.05 mg/m ³ |
| Listing of measured carcinogens and reproductive toxins as identified by California Proposition 65, the U.S. National Toxicology Program (NTP), and the International Agency on Research on Cancer (IARC) must be provided. | |
| Any pollutant regulated as a primary or secondary outdoor air pollutant must meet a concentration that will not generate an air concentration greater than that promulgated by the National Ambient Air Quality Standard (U.S. EPA, code of Federal Regulations, Title 40, Part 50). | |

See referenced standard for a complete technical explanation.

¹ Defined to be the total response of measured VOCs falling within the C₆-C₁₆ range, with responses calibrated to a toluene surrogate.

² Defined to be the total response of a target list of aldehydes (2-butenal; acetaldehyde; benzaldehyde; 2, 5-dimethylbenzaldehyde, 2-methylbenzaldehyde; 3-and/or 4-methylbenzaldehyde; butanal; 3-methylbutanal; formaldehyde; hexanal; pentanal; propanal), with each individually calibrated to a compound specific standard.

³ Any pollutant not listed must produce an air concentration level no greater than 1/10 the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, Cincinnati, Ohio 45211-4438).

⁴ Particles are applicable to fibrous, particle-releasing products with exposed surface area in air streams.

GREENGUARD Certification affirms that products meet the criteria of the referenced standard and the requirements of the specific certification program. Certification testing is conducted according to a consistent, defined protocol. The testing does not evaluate emissions under usage conditions other than those defined in the protocol and does not address potential environmental impact other than chemical and particle emissions.

The GREENGUARD Environmental Institute (GEI) is an industry independent, third-party certification organization that qualifies products for low chemical emissions. GREENGUARD Certification programs use defined product standards, test methodologies, product sample collection and handling procedures, program application processes and on-going verification procedures. GREENGUARD standards, methods, and procedures are available at www.GREENGUARD.org.

7.2.6 – GREENGUARD CHILDREN AND SCHOOLS CERTIFIED



Certificate of Compliance

Certification Details:

Certificate No: 938-00

Status: Certified

Period: 11/2010 - 10/2011

Restrictions: NONE

LOGIX Platinum Series

LOGIX Insulated Concrete Forms, Ltd.

This product has been certified according to the GREENGUARD Children & Schools Certification Program for Low Emitting Products

Reference Standard: GGPS.002 GREENGUARD Children & SchoolsSM Standard

Product Type: All Products

| Criteria | Allowable Limits |
|--------------------------------|---|
| Individual VOCs ^{1,2} | ≤ 1/100 TLV and ≤ ½ CA chronic REL (Office Seating ≤ 1/100 TLV and ≤ ¼ CA CREL) |
| Formaldehyde | ≤ 0.0135 ppm / 13.5 ppb (Office Seating ≤ 0.0675 ppm / 6.75 ppb) |
| TVOC ³ | ≤ 0.22 mg/m ³ |
| Total Aldehydes ⁴ | ≤ 0.043 ppm / 43 ppb |
| Total Phthalates ⁵ | ≤ 0.01 mg/m ³ |
| Total Particles ⁶ | ≤ 0.02 mg/m ³ |

See referenced standard for a complete technical explanation.

¹Any VOC not listed must produce an air concentration level no greater than 1/100 the Threshold Limit Value (TLV) industrial work place criterion (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, Cincinnati, Ohio 45211-4438) and no greater than 1/2 the CA Chronic Reference Exposure Level (CREL) http://www.oehha.ca.gov/air/chronic_rels/AllChrels.html - (CRELs) Adopted by the State of California Office of Environmental Health Hazard Assessment (OEHHA), December 2008).

²1-Methyl-2-Pyrrolidinone must be ≤ 0.16 mg/m³ for Office Furniture or ≤ 0.080 mg/m³ for Office Seating.

³Defined to be the total response of measured VOCs falling within the C₆-C₁₆ range, with responses calibrated to a toluene surrogate.

⁴Defined to be the total response of a target list of aldehydes (2-butenal; acetaldehyde; benzaldehyde; 2, 5-dimethylbenzaldehyde, 2-methylbenzaldehyde; 3-and/or 4-methylbenzaldehyde; butanal; 3-methylbutanal; formaldehyde; hexanal; pentanal; propanal), with each individually calibrated to a compound specific standard.

⁵Total phthalates include dibutyl (DBP), diethylhexyl (DEHD), diethyl (DEP), butylbenzyl (BBP), di-octyl (DOP), and dimethyl (DMP) phthalates.

⁶Particles are only applicable to fibrous, particle-releasing products with exposed surface area in air streams.

Complies with California Department of Health Services' "Standard Method for the Testing and Evaluation of Volatile Organic Chemical Emissions from Indoor Sources Using Environmental Chambers" Version 1.1 (CA section 01350)

GREENGUARD Certification affirms that products meet the criteria of the referenced standard and the requirements of the specific certification program. Certification testing is conducted according to a consistent, defined protocol. The testing does not evaluate emissions under usage conditions other than those defined in the protocol and does not address potential environmental impact other than chemical and particle emissions.

The GREENGUARD Environmental Institute (GEI) is an industry independent, third-party certification organization that qualifies products for low chemical emissions. GREENGUARD Certification programs use defined product standards, test methodologies, product sample collection and handling procedures, program application processes and on-going verification procedures. GREENGUARD standards, methods, and procedures are available at www.GREENGUARD.org.

www.logixicf.com

Good. Solid. Green.™

7-75



7.2.7 – QAI LISTING REPORT

Quality Auditing Institute

Listing Book

BUILDING PRODUCTS LISTING PROGRAM

Class: Insulation

Customer: LOGIX Insulated Concrete Forms, Ltd.
Location: 199-1917 West 4th Avenue, Vancouver, BC V6J 1M7

Listing No. B1031
Effective Date: September 27, 2010
Last Revised: October 15, 2010
Expires: N/A

Product: Insulated Concrete Forms (ICFs) with expanded polystyrene (EPS) panels and polypropylene web tie connectors.

Bead Types: Only approved bead types meeting certification requirements

Label: Product units are marked with the following: Manufacturer's Name, Trademark or other recognized symbol of identification, Model Designation, Month and Year of Manufacture or equivalent, QAI logo with the "US" and "C" identifier, listing number, and the standard numbers and ratings.

Standard: ASTM E84 - "Standard Test Method for Surface Burning Characteristics of Building Materials"

| Ratings: | Component | Product Density | Maximum Thickness | Flame Spread Index (FSI) | Smoke Developed Index (SDI) |
|----------|------------|-----------------|-------------------|--------------------------|-----------------------------|
| | EPS Panels | 1.35 pcf | 2.75 inches | 25 | 450 |

Standards: ASTM C578 - "Standard Specification for Rigid, Cellular Polystyrene Thermal Insulation";

CAN/ULC S701 – "Standard for Thermal Insulation, Polystyrene, Boards and Pipe Covering"

| | Component | EPS Classification |
|-----------------------|------------|--------------------|
| ASTM C578 Ratings: | EPS Panels | Type II |
| CAN/ULC S701 Ratings: | EPS Panels | Type 2 |

May 18th, 2011

[Go to TABLE OF CONTENTS](#)

EVALUATION REPORTS

Good. Solid. Green.™

www.logixicf.com

7 – 7 6



7.2.7 – QAI LISTING REPORT CONTINUED

Quality Auditing Institute


Listing Book

Standards: ASTM E119 - "Standard Test Methods for Fire Tests of Building Construction and Materials";

CAN/ULC S101 – "Standard Methods of Fire Endurance Tests of Building Construction and Materials"

| | Rating | Product Density | Maximum Cavity Width | Maximum Panel Thickness |
|---|--------|-----------------|----------------------|-------------------------|
| ASTM E119 / CAN/ULC S701 Ratings: | 2-Hour | 1.35 pcf | 4 inches | 2 3/4 inches |
| | 3-Hour | 1.35 pcf | 6 1/8 inches | 2 3/4 inches |
| | 4-Hour | 1.35 pcf | 8 inches | 2 3/4 inches |

Structural Rating at above durations for concrete wall at structural design load.



Assembly Details:

1. Insulated Concrete Forms – Standard forms made of two 16" x 48" by 2.75" thick expanded polystyrene (EPS) block panels connected by polypropylene detail webs at 8" O.C. The minimum width of the cavity is 4" as shown in the ratings table above (rating depends on cavity thickness).
2. Reinforcing Steel - No. 4 steel reinforcing bars placed horizontally in each course and vertically at 16" O.C. along centerline of wall cavity thickness.
3. Sand-Limestone Concrete – 145 +/- 5 pcf density, 2900 psi nominal compressive strength concrete.
4. Gypsum Wallboard – Min. 1/2" thick, 1.5 psf minimum density, 48" wide gypsum wallboard fastened to flanges of polypropylene webs with 2" long drywall screws at 16" horizontally and vertically. Joints covered with joint compound, covered with joint tape, and covered with an additional coat of joint compound. Screw heads covered with joint compound.

May 18th, 2011

[Go to TABLE OF CONTENTS](#)

Good. Solid. Green.™

www.logixicf.com

7-77

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 04/11

EVALUATION REPORTS

7.2.7 – QAI LISTING REPORT CONTINUED

Quality Auditing Institute

Listing Book

Standard: ASTM D1761 - "Standard Test Methods for Mechanical Fasteners in Wood"

| | | |
|------------|------------|--|
| | Component | Allowable cladding pressures (based on fastener withdrawal values) |
| ASTM D1761 | ICF System | As per tables below |

ASTM D1761 Allowable fastener values (psf) per fastener spacings for LOGIX ICFs:

| Fastener Type | Fastener Length | Withdrawal Resistance with Factor of Safety of 3.0 | 8" Hor. / 12" Vert. | 8" Hor. / 16" Vert. | 16" Hor. / 16" Vert. |
|-------------------------|-----------------|--|---------------------|---------------------|----------------------|
| #6 Coarse Drywall Screw | 1 5/8 in. | 59 lbs | 88.5 | 66.4 | 33.2 |
| #6 Fine Drywall Screw | 1 5/8 in. | 57 lbs | 86.0 | 64.5 | 32.3 |
| 16 gauge staple | 1 1/2 in. | 9 lbs | 14.0 | 10.5 | 5.3 |
| #8 Wood Screw | 2 in. | 69 lbs | 103.5 | 77.6 | 38.8 |
| #8 Exterior Deck Screw | 2 in. | 70 lbs | 105.0 | 78.8 | 39.4 |
| #10 Wood Screw | 2 in. | 66 lbs | 99.0 | 74.3 | 37.1 |

ASTM D1761 Allowable fastener values (kPa) per fastener spacings for LOGIX ICFs:

| Fastener Type | Fastener Length | Withdrawal Resistance with Factor of Safety of 3.0 | 200mm Hor. / 305 mm Vert. | 200 mm Hor. / 400 mm Vert. | 400 mm Hor. / 400 mm Vert. |
|-------------------------|-----------------|--|---------------------------|----------------------------|----------------------------|
| #6 Coarse Drywall Screw | 41.3 mm | 26.8 kg | 4.24 | 3.18 | 1.59 |
| #6 Fine Drywall Screw | 41.3 mm | 26.0 kg | 4.12 | 3.09 | 1.54 |
| 16 gauge staple | 38.1 mm | 4.2 kg | 0.67 | 0.50 | 0.25 |
| #8 Wood Screw | 50.8 mm | 31.3 kg | 4.96 | 3.72 | 1.86 |
| #8 Exterior Deck Screw | 50.8 mm | 31.8 kg | 5.03 | 3.77 | 1.89 |
| #10 Wood Screw | 50.8 mm | 29.9 kg | 4.74 | 3.56 | 1.78 |

May 18th, 2011

[Go to TABLE OF CONTENTS](#)

EVALUATION REPORTS

Good. Solid. Green.™

www.logixicf.com

7 – 7 8

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 04/11

7.2.7 – QAI LISTING REPORT CONTINUED

Quality Auditing Institute

Listing Book

Standards: ASTM D635 - "Standard Test Method for Rate of Burning and/or Extent and Time of Burning of Plastics in a Horizontal Position"; ASTM D1929 – "Standard Test Method for Determining Ignition Temperature of Plastics"

| | Component | Rating |
|------------|------------------------|-------------------------|
| ASTM D635 | Polypropylene Web Ties | HB (Horizontal Burning) |
| ASTM D1929 | Polypropylene Web Ties | Pass |

Notes: Also meets Florida Building Code (FBC) High Velocity Hurricane Zone (HVHZ) requirements as per Chapter 26 of the FBC.

These products are subjected to limitations as specified above and must be installed in accordance with the manufacturers' instructions. Authorities having jurisdiction should be consulted regarding allowable applications. See manufacturer's listings for other standards listed under QAI certification programs.

May 18th, 2011

[Go to TABLE OF CONTENTS](#)

Good. Solid. Green.™

www.logixicf.com

7 – 79

LOGIX®
INSULATED CONCRETE FORMS

REPRINTED 2013

Rev. Nov 04/11

7.3 – LEED EVALUATION

7.3.1 – LEED EVALUATION (U.S.)

July 17, 2009

Francis Roma
LOGIX
Suite 199, 1917 West 4th Ave
Vancouver, BC, Canada
V6J 1M7

Dear Francis,

Re: LOGIX ICF Technical Bulletins No's. 18 and 19

I have reviewed the above referenced Technical Bulletins in order to verify the accuracy of claims made with respect to the potential for LOGIX ICFs to help earn LEED points.

Technical Bulletin No. 18 which deals with LEED NC v3 makes fair and valid claims as to how the use of LOGIX ICFs can help projects earn LEED points under the LEED NC v3 guidelines. I reviewed this Technical Bulletin using the CaGBC's LEED NC v.1 guidelines which are very similar, but not identical to the USGBC's guidelines for new construction and major renovations.

Technical Bulletin No. 19 which deals with LEED for Schools v3 makes fair and valid claims as to how the use of LOGIX ICFs can help projects earn LEED points under the LEED for Schools v3 guidelines. It should be noted that I reviewed this Technical Bulletin using the USGBC's LEED for Schools v3 online guidelines. This online resource is not detailed but provides sufficient information to convince me that the claims made in Bulletin No. 19 are fair and reasonable.

For further clarification on how LOGIX ICFs contribute to LEED projects please contact me at the coordinates below.

Sincerely,



Alastair Moore, MRM, LEED AP
D&A Planning Inc.
Tel: 778 239 1965

EVALUATION REPORTS

www.logixicf.com

Good. Solid. Green.™

7 – 80



7.3.1 – LEED EVALUATION (U.S.) CONTINUED

TECHNICAL BULLETIN No.18 - 071009

LOGIX Potential LEED Contribution - LEED for New Construction & Major Renovations v3 (LEED-NC v3)

The United States Green Building Council (USGBC) has recently released the latest version of the LEED Rating System for New Construction & Major Renovations - LEED-NC v3. Beginning in June 2009 all new LEED projects in the United States are required to comply to the latest LEED rating systems.

Below is a summary of the LEED-NC v3 credits to which LOGIX can potentially contribute. In total, LOGIX can potentially help to earn 27* of the 40 points required to achieve LEED-NC certification. Under Building Reuse Credit, 4 additional points may apply to projects wherein ICFs, found in an existing building, are salvaged during de-construction and included in a new building constructed on the same site.

For information on the new LEED Rating Systems see LOGIX Technical Bulletin No.17, "LEED 2009 Rating System - Major Differences Between v2.2 & v3" at www.logixicf.com or visit www.usgbc.gov.

POTENTIAL LEED POINTS WITH LOGIX ICF*: LEED-NC v3

| Sustainable Sites | Points | Comments |
|--|--------|--|
| Site Development: Protect or Restore Habitat | 1 | <ul style="list-style-type: none"> Although the points may not apply to LOGIX, wall bracing for LOGIX is one of a combination of actions that, together with other procedures, can result in proper protection or restoration of natural areas around the job site. LOGIX is typically placed within the building perimeter. This type of assembly avoids disturbance to existing natural areas and keeps construction activity close to the building perimeter. |

| Energy & Atmosphere | Points | Comments |
|-----------------------------|----------|---|
| Optimize Energy Performance | Up to 19 | <p>Improved building energy can be enhanced by the combination of foam insulation and the thermal mass properties of the insulated concrete. LOGIX panels provide:</p> <ul style="list-style-type: none"> high thermal resistance for a LOGIX wall system – R24 (35+ effective Rvalue). Larger Rvalues can be achieved when using LOGIX XRV panels which have thicknesses of up to 8 inches. reduction in the peak heating and cooling loads on the building air tight structure which reduces air leakage and energy use. |

| Materials & Resources | Points | Comments |
|--|---------|--|
| Construction Waste Management: Divert 50% to 75% from Disposal | Up to 2 | Any on-site waste can be fully recycled. |
| Recycled Content: 10% to 20% (post-consumer + 1/2 pre-consumer) | Up to 2 | LOGIX foam panels are made from a maximum of 10% recycled EPS. The webs are made of 100% recycled polypropylene. |
| Regional Materials: 10% to 20% Extracted, Processed & Manufactured Regionally | Up to 2 | LOGIX currently has 8 manufacturing facilities throughout North America. The concrete is obtained through local suppliers. |
| 4 additional points may apply to projects wherein ICFs, found in an existing building, are salvaged during de-construction and included in a new building constructed on the same site. Under the Building Reuse Credit, points are achieved as follows: Maintain 55% to 95% of existing walls, floors and roofs (3 points); Maintain 50% of interior non-structural elements (1 point). | | |

| Indoor Envir. Quality | Points | Comments |
|--|-----------|---|
| Thermal Comfort: Design | 1 | ICFs are air tight structures, which make air flow and ventilation easier to control and monitor. The end result is a healthier, comfortable environment for occupants, and a reduction in HVAC capacity. |
| Minimum Indoor Air Quality Performance is a pre-requisite under LEED. Therefore, there are no points to be achieved. However, LOGIX can still contribute to improved Minimum Indoor Air Quality Performance. | | |
| TOTAL LEED-NC V3* | 27 | |

*The total LEED point contribution from LOGIX is a best estimate based on available information and test data. The actual LEED point contribution may change based on project specifics, and should be determined by a LEED Accredited Professional for each project seeking LEED accreditation.

TECHNICAL BULLETIN NO. 18 - JUL 2009
EVALUATION REPORTS

www.logixicf.com

Good. Solid. Green.™

7 – 8 1



7.3.1 – LEED EVALUATION (U.S.) CONTINUED

TECHNICAL BULLETIN No.19 - 071009

LOGIX Potential LEED Contribution - LEED for Schools v3

The United States Green Building Council (USGBC) has recently released the latest version of the LEED Rating System for Schools v3. Beginning in June 2009 all new LEED projects for schools in the United States are required to comply to the latest LEED for Schools rating systems.

Below is a summary of the LEED-NC v3 credits to which LOGIX can potentially contribute. In total, LOGIX can potentially help to earn 28* of the 40 points required to achieve LEED for schools certification. Under Building Reuse Credit, 4 additional points may apply to projects wherein ICFs, found in an existing building, are salvaged during de-construction and included in a new building constructed on the same site.

For information on the new LEED Rating Systems see LOGIX Technical Bulletin No.17, "LEED 2009 Rating System - Major Differences Between v2.2 & v3" at www.logixicf.com or visit www.usgbc.gov.

POTENTIAL LEED POINTS WITH LOGIX ICF*: LEED for Schools v3

| Sustainable Sites | Points | Comments |
|--|--------|--|
| Site Development: Protect or Restore Habitat | 1 | <ul style="list-style-type: none"> Although the points may not apply to LOGIX, wall bracing for LOGIX is one of a combination of actions that, together with other procedures, can result in proper protection or restoration of natural areas around the job site. LOGIX is typically placed within the building perimeter. This type of assembly avoids disturbance to existing natural areas and keeps construction activity close to the building perimeter. |

| Energy & Atmosphere | Points | Comments |
|-----------------------------|----------|---|
| Optimize Energy Performance | Up to 19 | <p>Improved building energy performance can be enhanced by the combination of foam insulation and the thermal mass properties of the insulated concrete. LOGIX panels provide:</p> <ul style="list-style-type: none"> high thermal resistance for a LOGIX wall system – R24 (35+ effective Rvalue). Larger Rvalues can be achieved when using LOGIX XRV panels which have thicknesses of up to 8 inches. reduction in the peak heating and cooling loads on the building air tight structure which reduces air leakage and energy use. |

| Materials & Resources | Points | Comments |
|--|---------|--|
| Construction Waste Management: Divert 50% to 75% from Disposal | Up to 2 | Any on-site waste can be fully recycled. |
| Recycled Content: 10% to 20% (post-consumer + 1/2 pre-consumer) | Up to 2 | LOGIX foam panels are made from a maximum of 10% recycled EPS. The webs are made of 100% recycled polypropylene. |
| Regional Materials: 10% to 20% Extracted, Processed & Manufactured Regionally | Up to 2 | LOGIX currently has 8 manufacturing facilities throughout North America. The concrete is obtained through local suppliers. |
| 4 additional points may apply to projects wherein ICFs, found in an existing building, are salvaged during de-construction and included in a new building constructed on the same site. Under the Building Reuse Credit, points are achieved as follows: Maintain 55% to 95% of existing walls, floors and roofs (3 points); Maintain 50% of interior non-structural elements (1 point). | | |

| Indoor Envir. Quality | Points | Comments |
|--|-----------|---|
| Thermal Comfort: Design | 1 | ICFs are air tight structures, which make air flow and ventilation easier to control and monitor. The end result is a healthier, comfortable environment for occupants, and a reduction in HVAC capacity. |
| Enhanced Acoustical Performance | 1 | LOGIX can provide walls with STC50+, which is well above the required STC35. |
| Minimum Indoor Air Quality Performance is a pre-requisite under LEED. Therefore, there are no points to be achieved. However, LOGIX can still contribute to improved Minimum Indoor Air Quality Performance. | | |
| TOTAL LEED-NC V3* | 28 | |

*The total LEED point contribution from LOGIX is a best estimate based on available information and test data. The actual LEED point contribution may change based on project specifics, and should be determined by a LEED Accredited Professional for each project seeking LEED accreditation.

www.logixicf.com

Good. Solid. Green.™

7 – 82



7.3.2 – LEED EVALUATION (CANADA)

July 17, 2009

Francis Roma
LOGIX
Suite 199, 1917 West 4th Ave
Vancouver, BC, Canada
V6J 1M7

Dear Francis,

Re: LOGIX ICF Technical Bulletins No's. 18 and 19

I have reviewed the above referenced Technical Bulletins in order to verify the accuracy of claims made with respect to the potential for LOGIX ICFs to help earn LEED points.

Technical Bulletin No. 18 which deals with LEED NC v3 makes fair and valid claims as to how the use of LOGIX ICFs can help projects earn LEED points under the LEED NC v3 guidelines. I reviewed this Technical Bulletin using the CaGBC's LEED NC v.1 guidelines which are very similar, but not identical to the USGBC's guidelines for new construction and major renovations.

Technical Bulletin No. 19 which deals with LEED for Schools v3 makes fair and valid claims as to how the use of LOGIX ICFs can help projects earn LEED points under the LEED for Schools v3 guidelines. It should be noted that I reviewed this Technical Bulletin using the USGBC's LEED for Schools v3 online guidelines. This online resource is not detailed but provides sufficient information to convince me that the claims made in Bulletin No. 19 are fair and reasonable.

For further clarification on how LOGIX ICFs contribute to LEED projects please contact me at the coordinates below.

Sincerely,



Alastair Moore, MRM, LEED AP
D&A Planning Inc.
Tel: 778 239 1965

EVALUATION REPORTS

www.logixicf.com

Good. Solid. Green.™

7 – 83

LOGIX®
INSULATED CONCRETE FORMS

7.3.2 – LEED EVALUATION (CANADA)

CONTINUED

TECHNICAL BULLETIN
No.25 - 012211
Revised 030912

LEED Canada for New Construction & Major Renovations 2009 - LOGIX Potential LEED Contribution

The Canada Green Building Council (CaGBC) released the latest version of the LEED Rating System for New Construction & Major Renovations - LEED Canada NC 2009. Since June 2010 all new LEED projects in the Canada are required to comply to the latest LEED rating systems.

LEED Canada NC 2009 is based on the United States Green Building Council (USGBC) LEED-NC v3 rating system. The Canadian version, however, also includes one point for "Durable Building" requirements. Below is a summary of the LEED Canada NC 2009 credits to which LOGIX can potentially contribute. In total, LOGIX can potentially help to earn 28* of the 40 points required to achieve LEED-NC certification. Under Building Reuse Credit, 4 additional points may apply to projects wherein ICFs, found in an existing building, are salvaged during de-construction and included in a new building constructed on the same site.

POTENTIAL LEED POINTS WITH LOGIX ICF*: LEED Canada NC 2009

| Sustainable Sites | Points | Comments |
|--|--------|---|
| Site Development: Protect or Restore Habitat | 1 | <ul style="list-style-type: none">Although the points may not apply to LOGIX, wall bracing for LOGIX is one of a combination of actions that, together with other procedures, can result in proper protection or restoration of natural areas around the job site.LOGIX is typically placed within the building perimeter. This type of assembly avoids disturbance to existing natural areas and keeps construction activity close to the building perimeter. |

| Energy & Atmosphere | Points | Comments |
|-----------------------------|----------|--|
| Optimize Energy Performance | Up to 19 | Improved building energy can be enhanced by the combination of foam insulation and the thermal mass properties of the insulated concrete. LOGIX panels provide: <ul style="list-style-type: none">high thermal resistance for a LOGIX wall system – R24 (35+ effective Rvalue). Larger Rvalues can be achieved when using LOGIX XRV or LOGIX Platinum Series (upto R77 can be achieved).reduction in the peak heating and cooling loads on the buildingair tight structure which reduces air leakage and energy use. |

| Materials & Resources | Points | Comments |
|--|---------|--|
| Construction Waste Management: Divert 50% to 75% from Disposal | Up to 2 | Any on-site waste can be fully recycled. |
| Recycled Content: 10% to 20% (post-consumer + 1/2 pre-consumer) | Up to 2 | LOGIX foam panels are made from a maximum of 10% recycled EPS. The webs are made of 100% recycled polypropylene. |
| Regional Materials: 10% to 20% Extracted, Processed & Manufactured Regionally | Up to 2 | LOGIX currently has 9 manufacturing facilities throughout North America. The concrete is obtained through local suppliers. |
| 4 additional points may apply to projects wherein ICFs, found in an existing building, are salvaged during de-construction and included in a new building constructed on the same site. Under the Building Reuse Credit, points are achieved as follows: Maintain 55% to 95% of existing walls, floors and roofs (3 points); Maintain 50% of interior non-structural elements (1 point). | | |

EVALUATION REPORTS

TECHNICAL BULLETIN NO. 25 - JAN 2011

www.logixicf.com

Good. Solid. Green.™

7 – 84



7.3.2 – LEED EVALUATION (CANADA)

CONTINUED

TECHNICAL BULLETIN
No.25 - 012211
Revised 030912

LEED Canada for New Construction & Major Renovations 2009 - LOGIX Potential LEED Contribution

| Indoor Envir. Quality | Points | Comments |
|--|--------|--|
| Minimum Indoor Air Quality Performance | n/a | Minimum Indoor Air Quality Performance is a pre-requisite under LEED. Therefore, there are no points to be achieved. However, LOGIX can still contribute to improved Minimum Indoor Air Quality Performance. |
| Thermal Comfort: Design | 1 | ICFs are air tight structures, which make air flow and ventilation easier to control and monitor. The end result is a healthier, comfortable environment for occupants, and a reduction in HVAC capacity. |

| Regional Priority | Points | Comments |
|--------------------------|-----------|--|
| Durable Building | 1 | Concrete is one of the most durable building materials available and is known to last for decades. With the protected layer of ICF foam panels, a LOGIX wall system can last indefinitely and will not promote the growth of mold or mildew. |
| TOTAL LEED-NC V3* | 28 | |

*The total LEED point contribution from LOGIX is a best estimate based on available information and test data. The actual LEED point contribution may change based on project specifics, and should be determined by a LEED Accredited Professional for each project seeking LEED accreditation.

Related articles:

- [Technical Bulletin No.09: "LEED Rating System with Logix Insulated Concrete Forms"](#)
- [Technical Bulletin No.18: "LEED for New Construction & Major Renovations v3 \(US version\) - LOGIX Potential LEED Contribution"](#)
- [Technical Bulletin No.19: "LEED for Schools v3 - LOGIX Potential LEED Contribution"](#)

TECHNICAL BULLETIN NO. 25 - JAN 2011

EVALUATION REPORTS

Good. Solid. Green.™

www.logixicf.com

7 – 85



8.0 – TECHNICAL SPECIFICATIONS + REFERENCES

TABLE OF CONTENTS

| | |
|---|---------|
| 8.1 – TECHNICAL SPECIFICATIONS..... | P. 8-3 |
| 8.2 – MATERIAL SAFETY DATA SHEET..... | P. 8-20 |
| 8.3 – RECOMMENDED INDUSTRY PRACTICE FOR PLACING REINFORCING BARS | P. 8-23 |
| 8.4 – STANDARD PRACTICE - SPLICING & DOWELS.... | P. 8-24 |
| 8.5 – LOGIX R-VALUES..... | P. 8-27 |

T E C H N I C A L S P E C I F I C A T I O N S + R E F E R E N C E S

8.1 – TECHNICAL SPECIFICATIONS

(CSI Specifications for LOGIX are available at www.logixicf.com)



Updated 07/20/11

Good. Solid. Green.™

LOGIX INSULATED CONCRETE FORMS GENERAL SPECIFICATIONS SHEET

This document is intended for general information purposes only regarding specifications for Logix Insulated Concrete Forms (herein referred to as Logix ICF). Technical specification sheet, as per Construction Specifications institute (CSI) formatting, can be downloaded at www.logixicf.com.

1 PRODUCT DESCRIPTION

- Logix ICF consists of two flame-resistant EPS boards separated by polypropylene webs.
- Logix ICF consists of solid form units (LOGIX Pro Forms) or knock-down forms (LOGIX KD Forms) or a combination of both Logix form and Logix KD forms, referred to as LOGIX Hybrid Forms.
- The EPS foam boards are a minimum 70 mm (2.75 inch) thick, and can range in thickness of 70 (2.75 inches), 102 (4 inches), 127 (5 inches), 152 (6 inches), 178 (7 inches) and 203 mm (8 inches), which gives a total EPS foam board thickness of 140 (5.50 inches), 203 (8 inches), 254 (10 inches), 305 (12 inches), 356 (14 inches) and 406 mm (16 inches), respectively.
- The webs separate the EPS boards to form 102 mm (4 inch), 159 mm (6.25 inc), 203 mm (8 inch), 254 mm (10 inch) and 305 mm (12 inch) cavities, which create the concrete wall thicknesses. With Logix Xtenders the concrete wall thickness can be increased to virtually any thickness.
- The webs are spaced every 203 mm (8 inch) on centre horizontally and 406 mm (16 inch) on centre vertically, and contain a 32 mm (1.25 inch) wide furring strip that extends the height of each ICF block. The furring strips shall facilitate fasteners for attachment of both exterior and interior finishes.
- A furring strip is located in the corners of corner forms. The furring strip consists of both a vertical and horizontal component. The vertical component extends nearly the full height of the form, extends a minimum of 64 mm (2.5 inches) from both sides of the corner, and a minimum of 5 mm (0.2 inches) thick. The horizontal component is a minimum 51mm (2 inches) in height, extend a minimum of 152 mm (6 inches) from both sides of the corner, and a minimum of 5 mm (0.2 inches) thick.
- The webs facilitate rebar placement in accordance with CAN/CSA A23.1, and ACI 318

www.logixicf.com

Pg.1 of 16

Good. Solid. Green.™

www.logixicf.com

8 – 3



REPRINTED 2013

Rev. Nov 04/11

8.1 – TECHNICAL SPECIFICATIONS CONTINUED



Updated 07/20/11

Good. Solid. Green.™

LOGIX INSULATED CONCRETE FORMS GENERAL SPECIFICATIONS SHEET, CONT'D

2 CODE/CERTIFICATION APPROVALS

- International Code Council Evaluation Report No. 1642
- CCMC Report No. 13110-R
- City of Los Angeles Research Report No. 25518
- Miami-Dade County Approval No.09-0714.03
- State of Florida Certification of Approval No.FL14109
- Wisconsin Building Products Evaluation No.200266-I
- City of New York Materials and Equipment Acceptance – MEA 273-04-M
- QAI listed QM0503

3 DESIGN/PERFORMANCE OF LOGIX ICF

A brief description of each test is outlined in the attached Appendix. Test reports are available upon request.

| Test Description | Result | Pass/Fail Criteria | Referenced Standard Test Method |
|--|--|---|---------------------------------|
| R-Value (Thermal Resistance of EPS) per inch (per 25.4mm) | R 4.13 (RSI 0.72) | Min. R 4.00 (RSI 0.70) | ASTM C518 |
| U-Value (Thermal Conductance of EPS) per inch (per 25.4mm) | $1/R = 1/4.13 = 0.242$ (1.39) | N/A | N/A |
| Water Absorption | 0.18% | Max. 3.0% | ASTM D2842 |
| Water Vapor Presence | 94.0ng/Pa-s-m2 (1.64perm-in.) | Max. 201 ng/Pa-s-m2 (3.5perm-in.) | ASTM E96 |
| Compressive Strength | 165kPa (23.9psi) | Min. 104kPa (15.0psi) | ASTM D1621 & ASTM C165 |
| Flexural Strength | 365kPa (53.0psi) | Min. 240kPa (35.0psi) | ASTM C203 |
| Dimensional Stability – Thermal & Humid Aging | 0.5% | Max. 2.0% | ASTM D2126 |
| Density | 27.5kg/m3 (1.72pcf) | Min. 22 kg/m3 (1.35pcf) | ASTM C1622 & ASTM C303 |
| Dimensions | Min. length variation = 0.0% Max. length variation = 0.4% Min. width variation = 0.1% Max. width variation = 0.4% Min. thickness variation = -0.3mm Max. thickness variation = 0.9mm Max. squareness = 3mm | Min. -0.2% Max. 0.4% Min. -0.2% Max. 0.4% Max. -2mm Max. 4mm Max. 3mm | ASTM C303 |
| Limiting Oxygen Index | 29.1% | Min. 24.0% | ASTM D2863 |
| Formaldehyde Emission | No formaldehyde detected | N/A* | AATTC-112 |
| Fungi Resistance | No fungal growth detected | N/A* | ASTM G21 |
| Flame Spread Rating | < 25 | N/A* | ASTM E84/CAN ULC S102 |

www.logixicf.com

Pg.2 of 16

www.logixicf.com

Good. Solid. Green.™

8 – 4



8.1 – TECHNICAL SPECIFICATIONS CONTINUED



Updated 07/20/11

Good. Solid. Green.™

LOGIX INSULATED CONCRETE FORMS GENERAL SPECIFICATIONS SHEET, CONT'D

| Test Description | Result | Pass/Fail Criteria | Referenced Standard Test Method |
|-------------------------|--|--|--|
| Smoke Developed Rating | < 450 | N/A* | ASTM E84/CAN ULC S102 |
| Fire Endurance Test | See Fire Resistance Rating table | N/A* | ASTM E119/CAN ULC S101 |
| Standard Room Fire Test | w/in acceptable limits | Met conditions required for exposure to fire for 15 minutes. | UBC 26-3/CAN ULC 1715 |
| Concrete Pour-in-place | Observations of deflection recorded. | N/A* | CCMC Masterformat 03131 |
| Sound Transmission | STC 56 for 6.25" Logix wall system (2 layers of 5/8" drywall & 2x2 wood strips on one side, 1/2" drywall on the other side) STC 50 for 4" Logix wall system (1/2" drywall & 2x2 wood strips on one side, 1/2" drywall on the other side). | N/A* | ASTM E90 |
| UPITT Toxicity | Pass | LC50 < 19.7g | University of Pittsburgh Toxicity Test |

*Code body or referenced test standard required reporting test results only - no Pass/Fail criteria specified.

TESTS CONDUCTED ON POLYPROPYLENE WEB

| Test Description | Result | US Requirements | Referenced Standard Test Method |
|--|--|--|------------------------------------|
| Flammability | Flame Front Distance = 100mm (4") Avg. Linear Burn Rate = 17.9mm/min (0.70in/min) | Max. linear burn rate = 40.0mm/min (1.57in/min) for Flame Front Dist. = 100mm (4") | ASTM D635 |
| Smoke Density Rating | 19.1% | Max. 75% | ASTM D2843 |
| Average Lateral Fastener Resistance of Drywall Screws | 1.63kN (367lbs) | N/A* | ASTM D1761 |
| Average Withdrawal Fastener Resistance of Drywall Screws | 0.75kN (169lbs) | N/A* | ASTM D1761 |
| Shear Strength of Polypropylene Web | 26.1MPa (37.9psi) | N/A* | ASTM D732, CCMC Masterformat 03131 |
| Average Tensile Strength of Polypropylene Web | 3.75kN (842lbs) | N/A* | ASTM D638 |

www.logixicf.com

Pg.3 of 16

Good. Solid. Green.™

www.logixicf.com

8 – 5



Rev. Nov 04/11

REPRINTED 2013

8.1 – TECHNICAL SPECIFICATIONS CONTINUED



Updated 07/20/11

Good. Solid. Green.™

LOGIX INSULATED CONCRETE FORMS GENERAL SPECIFICATIONS SHEET, CONT'D

| Test Description | Result | US Requirements | Referenced Standard Test Method |
|--|---------------|-----------------|--|
| Average Withdrawal Resistance of Staples 1.59mm 16ga. | 105N (24lbs) | N/A* | ASTM D1761 (under cyclic temperatures) |
| Average Withdrawal Resistance of Plane Shank 1.5" long, 3/8" head | 155N (35lbs) | N/A* | ASTM D1761 (under cyclic temperatures) |
| Average Withdrawal Resistance of Ring Shank 1.5" long, 3/8" head | 431N (97lbs) | N/A* | ASTM D1761 (under cyclic temperatures) |
| Average Withdrawal Resistance of Spiral Shank 1.5" long, 3/8" head | 135N (30lbs) | N/A* | ASTM D1761 (under cyclic temperatures) |
| Average Lateral Resistance of Staples 1.59mm 16ga. | 169N (38lbs) | N/A* | ASTM D1761 (under cyclic temperatures) |
| Average Lateral Resistance of Plane Shank 1.5" long, 3/8" head | 520N (117lbs) | N/A* | ASTM D1761 (under cyclic temperatures) |
| Average Lateral Resistance of Ring Shank 1.5" long, 3/8" head | 378N (85lbs) | N/A* | ASTM D1761 (under cyclic temperatures) |
| Average Lateral Resistance of Spiral Shank 1.5" long, 3/8" head | 200N (45lbs) | N/A* | ASTM D1761 (under cyclic temperatures) |
| Average Withdrawal Resistance of Corrosion Resistance No.8-18 x 0.323 HD x 1.5/8" | 567N (127lbs) | N/A* | ASTM D1761 |
| Average Withdrawal Resistance of Corrosion Resistance 6d (0.113" shank x 0.267 HD x 2" long) | 93N (21lbs) | N/A* | ASTM D1761 |
| #6 Coarse Drywall Screw, 1-5/8" long** | 787N (177lbs) | N/A* | ASTM D1761 |
| #6 Fine Drywall Screw, 1-5/8" long** | 765N (172lbs) | N/A* | ASTM D1761 |
| 16ga. Staple, 1-1/2" long** | 124N (28lbs) | N/A* | ASTM D1761 |
| Galvanized Ringed Wallboard Nail, 1-1/2" long** | 462N (104lbs) | N/A* | ASTM D1761 |
| Hot-dipped Galvanized Spiral Nail, 2" long** | 226N (51lbs) | N/A* | ASTM D1761 |
| #8 Wood Screw, 2" long** | 920N (207lbs) | N/A* | ASTM D1761 |

www.logixicf.com

Pg.4 of 16

TECHNICAL SPECIFICATIONS + REFERENCES

www.logixicf.com

Good. Solid. Green.™

8 – 6



REPRINTED 2013

Rev. Nov 04/11



Updated 07/20/11

Good. Solid. Green.™

LOGIX INSULATED CONCRETE FORMS GENERAL SPECIFICATIONS SHEET, CONT'D

| Test Description | Result | US Requirements | Referenced Standard Test Method |
|-----------------------------------|---------------|-----------------|---------------------------------|
| #8 Exterior Deck Screw, 2" long** | 934N (210lbs) | N/A* | ASTM D1761 |
| #10 Wood Screw, 2" long** | 880N (198lbs) | N/A* | ASTM D1761 |

*Code body or referenced test standard required reporting test results only - no Pass/Fail criteria specified.

**Applicable to corner web only.

FIRE RESISTANCE RATING

| Form Size (Concrete Wall Thickness) | Rating with ½" drywall |
|-------------------------------------|----------------------------------|
| 100mm (4") | 2hrs |
| 159mm (6.25") | 3hrs (4hrs if 5/8" drywall used) |
| 203mm (8") and above | 4hrs |

*Bearing load applied to wall = 360,000lbs (360kips)

4 MANUFACTURED UNITS

LOGIX manufactures both assembled and unassembled insulated concrete form units. LOGIX assembled forms, known simply as "LOGIX Pro", are delivered to the job site as assembled form blocks. LOGIX unassembled forms (or knock-down forms), known as "LOGIX KD", are delivered to the job site in components that make up the form blocks - the form panels and KD Connectors. LOGIX KD are assembled on the job site.

Below is a summary of the types of LOGIX and LOGIX KD forms available.

LOGIX (assembled form blocks)

| | Description |
|------------------------------------|--|
| LOGIX Pro | White in color |
| LOGIX Pro Platinum ³ | Grey in color. Offers higher R-value ¹ than LOGIX Pro. |
| LOGIX Pro TX | LOGIX Pro with termite resistant additive Preventol ² . |
| LOGIX Pro Platinum ³ TX | LOGIX Platinum with Preventol. |

8.1 – TECHNICAL SPECIFICATIONS CONTINUED



Updated 07/20/11

Good. Solid. Green.™

LOGIX INSULATED CONCRETE FORMS GENERAL SPECIFICATIONS SHEET, CONT'D

LOGIX KD (unassembled form blocks)

| | Description |
|-----------------------------------|--|
| LOGIX KD | White in color |
| LOGIX KD Platinum ³ | Grey in color. Offers higher R-value ¹ than LOGIX Pro. |
| LOGIX KD TX | LOGIX Pro with termite resistant additive Preventol ² . |
| LOGIX KD Platinum ³ TX | LOGIX Platinum with Preventol. |

Notes:

1. See Section 8.5 for LOGIX R-values.
2. Preventol is an effective termite resistant additive.
3. Care should be taken to protect exposed foam surfaces from reflected sunlight and prolonged solar exposure until wall cladding or finish material is applied. Shade exposed foam areas, or remove sources of reflective surfaces, where heat build up onto exposed foam might occur. For more information refer to BASF Technical Leaflet N-4 Neopor, "Recommendations for packaging, transporting, storing and installing building insulation products made from Neopor EPS foam." (The BASF Technical Leaflet is attached to every bundle of LOGIX Platinum forms delivered to a job site).

8.1 – TECHNICAL SPECIFICATIONS CONTINUED



Updated 07/20/11

Good. Solid. Green.™

LOGIX INSULATED CONCRETE FORMS GENERAL SPECIFICATIONS SHEET, CONT'D

STRAIGHT FORMS

| LOGIX FORM PANELS | STANDARD | TAPER TOP | BRICK LEDGE | TRANSITION |
|-------------------------|--------------------------|--------------------------|------------------------------------|------------------------------------|
| STANDARD | | | | |
| Conc. Core Thickness | 4 6.25 8 10 12 | 4 6.25 8 10 12 | 4 6.25 8 10 12 | 4 6.25 8 10 12 |
| Width Top ¹ | 9.5 11.75 13.5 15.5 17.5 | 9.5 11.75 13.5 15.5 17.5 | 13.375 15.625 17.375 19.375 21.375 | 11.25 13.5 15.25 17.25 19.25 |
| Width Bot. ¹ | 9.5 11.75 13.5 15.5 17.5 | 9.5 11.75 13.5 15.5 17.5 | 9.5 11.75 13.5 15.5 17.5 | 9.5 11.75 13.5 15.5 17.5 |
| Form Type ² | KD/P KD/P KD/P KD/P KD | KD KD/P KD/P KD/P KD | KD/P KD/P KD/P KD/P KD | KD/P KD/P KD/P KD KD |
| TAPER TOP | | | | |
| Conc. Core Thickness | | 4 6.25 8 10 12 | 4 6.25 8 10 12 | 4 6.25 8 10 12 |
| Width Top ¹ | | 9.5 11.75 13.5 15.5 17.5 | 13.375 15.625 17.375 19.375 21.375 | 11.25 13.5 15.25 17.25 19.25 |
| Width Bot. ¹ | | 9.5 11.75 13.5 15.5 17.5 | 9.5 11.75 13.5 15.5 17.5 | 9.5 11.75 13.5 15.5 17.5 |
| Form Type ² | | KD KD KD KD KD | KD KD KD KD KD | KD KD KD KD KD |
| BRICK LEDGE | | | | |
| Conc. Core Thickness | | | 4 6.25 8 10 12 | 4 6.25 8 10 12 |
| Width Top ¹ | | | 17.25 19.5 21.25 23.25 25.25 | 15.125 17.375 19.125 21.125 23.125 |
| Width Bot. ¹ | | | 9.5 11.75 13.5 15.5 17.5 | 9.5 11.75 13.5 15.5 17.5 |
| Form Type ² | | | KD KD KD KD KD | KD KD KD KD KD |
| TRANSITION | | | | |
| Conc. Core Thickness | | | | 4 6.25 8 10 12 |
| Width Top ¹ | | | | 13 15.25 17 19 21 |
| Width Bot. ¹ | | | | 9.5 11.75 13.5 15.5 17.5 |
| Form Type ² | | | | KD KD KD KD KD |

1. Width at Top and Bottom is measured from outside face to outside face of forms.

TECHNICAL SPECIFICATIONS + REFERENCES

www.logixicf.com

Good. Solid. Green.™

8 – 9



REPRINTED 2013

Rev. Nov 04/11

8.1 – TECHNICAL SPECIFICATIONS CONTINUED



Updated 07/20/11

Good. Solid. Green.™

LOGIX INSULATED CONCRETE FORMS GENERAL SPECIFICATIONS SHEET, CONT'D

STRAIGHT FORMS WITH XRV

| LOGIX FORM PANELS | XRV4 | | | | | XRV5 | | | | | XRV6 | | | | | XRV7 | | | | | XRV8 | | | | |
|----------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| STANDARD | | | | | | | | | | | | | | | | | | | | | | | | | |
| Conc. Core Thickness | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 |
| Width Top¹ | 10.75 | 13 | 14.75 | 16.75 | 18.75 | 11.75 | 14 | 15.75 | 17.75 | 19.75 | 12.75 | 15 | 16.75 | 18.75 | 20.75 | 13.75 | 16 | 17.75 | 19.75 | 21.75 | 14.75 | 17 | 18.75 | 20.75 | 22.75 |
| Width Bot.¹ | 10.75 | 13 | 14.75 | 16.75 | 18.75 | 11.75 | 14 | 15.75 | 17.75 | 19.75 | 12.75 | 15 | 16.75 | 18.75 | 20.75 | 13.75 | 16 | 17.75 | 19.75 | 21.75 | 14.75 | 17 | 18.75 | 20.75 | 22.75 |
| Form Type² | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD |
| TAPER TOP | | | | | | | | | | | | | | | | | | | | | | | | | |
| Conc. Core Thickness | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 |
| Width Top¹ | 10.75 | 13 | 14.75 | 16.75 | 18.75 | 11.75 | 14 | 15.75 | 17.75 | 19.75 | 12.75 | 15 | 16.75 | 18.75 | 20.75 | 13.75 | 16 | 17.75 | 19.75 | 21.75 | 14.75 | 17 | 18.75 | 20.75 | 22.75 |
| Width Bot.¹ | 10.75 | 13 | 14.75 | 16.75 | 18.75 | 11.75 | 14 | 15.75 | 17.75 | 19.75 | 12.75 | 15 | 16.75 | 18.75 | 20.75 | 13.75 | 16 | 17.75 | 19.75 | 21.75 | 14.75 | 17 | 18.75 | 20.75 | 22.75 |
| Form Type² | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD |
| BRICK LEDGE | | | | | | | | | | | | | | | | | | | | | | | | | |
| Conc. Core Thickness | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 |
| Width Top¹ | 14.625 | 16.875 | 18.625 | 20.625 | 22.625 | 15.625 | 17.875 | 19.625 | 21.625 | 23.625 | 16.625 | 18.875 | 20.625 | 22.625 | 24.625 | 17.625 | 19.875 | 21.625 | 23.625 | 25.625 | 18.625 | 20.875 | 22.625 | 24.625 | 26.625 |
| Width Bot.¹ | 10.75 | 13 | 14.75 | 16.75 | 18.75 | 11.75 | 14 | 15.75 | 17.75 | 19.75 | 12.75 | 15 | 16.75 | 18.75 | 20.75 | 13.75 | 16 | 17.75 | 19.75 | 21.75 | 14.75 | 17 | 18.75 | 20.75 | 22.75 |
| Form Type² | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD |
| TRANSITION | | | | | | | | | | | | | | | | | | | | | | | | | |
| Conc. Core Thickness | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 | 4 | 6.25 | 8 | 10 | 12 |
| Width Top¹ | 12.5 | 14.75 | 16.5 | 18.5 | 20.5 | 13.5 | 15.75 | 17.5 | 19.5 | 21.5 | 14.5 | 16.75 | 18.5 | 20.5 | 22.5 | 15.5 | 17.75 | 19.5 | 21.5 | 23.5 | 16.5 | 18.75 | 20.5 | 22.5 | 24.5 |
| Width Bot.¹ | 10.75 | 13 | 14.75 | 16.75 | 18.75 | 11.75 | 14 | 15.75 | 17.75 | 19.75 | 12.75 | 15 | 16.75 | 18.75 | 20.75 | 13.75 | 16 | 17.75 | 19.75 | 21.75 | 14.75 | 17 | 18.75 | 20.75 | 22.75 |
| Form Type² | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD | KD |

- Width at Top and Bottom is measured from outside face to outside face of forms.
- "KD" and "P" denotes LOGIX KD (unassembled forms) and LOGIX PRO (assembled forms), respectively.

www.logixicf.com

Pg.8 of 16

www.logixicf.com

Good. Solid. Green.™

8 – 10



Rev. Nov 04/11

8.1 – TECHNICAL SPECIFICATIONS CONTINUED



Updated 07/20/11

Good. Solid. Green.™

LOGIX INSULATED CONCRETE FORMS GENERAL SPECIFICATIONS SHEET, CONT'D

XRV FORMS

| LOGIX FORM PANELS | XRV4 | XRV5 | XRV6 | XRV7 | XRV8 |
|----------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| XRV4 | | | | | |
| Conc. Core Thickness | 4 6.25 8 10 12 | 4 6.25 8 10 12 | 4 6.25 8 10 12 | 4 6.25 8 10 12 | 4 6.25 8 10 12 |
| Width Top¹ | 12 14.25 16 18 20 | 13 15.25 17 19 21 | 14 16.25 18 20 22 | 15 17.25 19 21 23 | 16 18.25 20 22 24 |
| Width Bot.¹ | 12 14.25 16 18 20 | 13 15.25 17 19 21 | 14 16.25 18 20 22 | 15 17.25 19 21 23 | 16 18.25 20 22 24 |
| Form Type² | KD KD KD KD KD | KD KD KD KD KD | KD KD KD KD KD | KD KD KD KD KD | KD KD KD KD KD |
| XRV5 | | | | | |
| Conc. Core Thickness | | 4 6.25 8 10 12 | 4 6.25 8 10 12 | 4 6.25 8 10 12 | 4 6.25 8 10 12 |
| Width Top¹ | | 14 16.25 18 20 22 | 15 17.25 19 21 23 | 16 18.25 20 22 24 | 17 19.25 21 23 25 |
| Width Bot.¹ | | 14 16.25 18 20 22 | 15 17.25 19 21 23 | 16 18.25 20 22 24 | 17 19.25 21 23 25 |
| Form Type² | | KD KD KD KD KD | KD KD KD KD KD | KD KD KD KD KD | KD KD KD KD KD |
| XRV6 | | | | | |
| Conc. Core Thickness | | | 4 6.25 8 10 12 | 4 6.25 8 10 12 | 4 6.25 8 10 12 |
| Width Top¹ | | | 16 18.25 20 22 24 | 17 19.25 21 23 25 | 18 20.25 22 24 26 |
| Width Bot.¹ | | | 16 18.25 20 22 24 | 17 19.25 21 23 25 | 18 20.25 22 24 26 |
| Form Type² | | | KD KD KD KD KD | KD KD KD KD KD | KD KD KD KD KD |
| XRV7 | | | | | |
| Conc. Core Thickness | | | | 4 6.25 8 10 12 | 4 6.25 8 10 12 |
| Width Top¹ | | | | 18 20.25 22 24 26 | 19 21.25 23 25 27 |
| Width Bot.¹ | | | | 18 20.25 22 24 26 | 19 21.25 23 25 27 |
| Form Type² | | | | KD KD KD KD KD | KD KD KD KD KD |
| XRV8 | | | | | |
| Conc. Core Thickness | | | | | 4 6.25 8 10 12 |
| Width Top¹ | | | | | 20 22.25 24 26 28 |
| Width Bot.¹ | | | | | 20 22.25 24 26 28 |
| Form Type² | | | | | KD KD KD KD KD |

- Width at Top and Bottom is measured from outside face to outside face of forms.
 - "KD" and "P" denotes LOGIX KD (unassembled forms) and LOGIX PRO (assembled forms), respectively.
- www.logixicf.com

Pg.9 of 16

www.logixicf.com

Good. Solid. Green.™

8 – 11



8.1 – TECHNICAL SPECIFICATIONS CONTINUED



Good. Solid. Green.™

Updated 07/20/11

LOGIX INSULATED CONCRETE FORMS
GENERAL SPECIFICATIONS SHEET, CONT'D

CORNER FORMS

| | Left Hand Corner Form | Right Hand Corner Form |
|-----------------------------------|-----------------------|------------------------|
| 4 inch Concrete Core Thickness | | |
| Form Type ¹ | KD/P | KD/P |
| 6.25 inch Concrete Core Thickness | | |
| Form Type ¹ | KD/P | KD/P |
| 8 inch Concrete Core Thickness | | |
| Form Type ¹ | KD/P | KD/P |
| 10 inch Concrete Core Thickness | | |
| Form Type ¹ | KD/P | KD/P |
| 12 inch Concrete Core Thickness | | |
| Form Type ¹ | KD | KD |

1. "KD" and "P" denotes LOGIX KD (unassembled forms) and LOGIX PRO (assembled forms), respectively.
www.logixicf.com





Updated 07/20/11

Good. Solid. Green.™

LOGIX INSULATED CONCRETE FORMS
GENERAL SPECIFICATIONS SHEET, CONT'D

45° FORMS

| | Left Hand 45° Form | Right Hand 45° Form |
|-----------------------------------|--------------------|---------------------|
| 4 inch Concrete Core Thickness | | |
| Form Type¹ | KD/P | KD/P |
| 6.25 inch Concrete Core Thickness | | |
| Form Type¹ | KD/P | KD/P |
| 8 inch Concrete Core Thickness | | |
| Form Type¹ | KD/P | KD/P |

TECHNICAL SPECIFICATIONS + REFERENCES

www.logixicf.com

Good. Solid. Green.™



8.1 – TECHNICAL SPECIFICATIONS CONTINUED



Updated 07/20/11

Good. Solid. Green.™

LOGIX INSULATED CONCRETE FORMS GENERAL SPECIFICATIONS SHEET, CONT'D

HALF HEIGHT FORMS

| HALF HEIGHT STANDARD FORMS ¹ | | |
|---|--------------------------------------|-----------------------------------|
| 4 inch Concrete Core Thickness | 6.25 inch Concrete Core Thickness | 8 inch Concrete Core Thickness |
| | | |

| | HALF HEIGHT CORNER FORMS ¹ | | HALF HEIGHT 45° FORMS ¹ | |
|--|---------------------------------------|---------------------|------------------------------------|---------------------|
| | Left Hand 45° Form | Right Hand 45° Form | Left Hand 45° Form | Right Hand 45° Form |
| | | | | |
| | | | | |
| | | | | |

1. Height of forms for Half Height Forms = 8 inches
www.logixicf.com

Good. Solid. Green.™

www.logixicf.com

8 – 14





Updated 07/20/11

Good. Solid. Green.™

LOGIX INSULATED CONCRETE FORMS GENERAL SPECIFICATIONS SHEET, CONT'D

ACCESSORIES

LOGIX ACCESSORIES

| | | |
|-----------|-----------------------------|---------|
| | | |
| Flex Bars | Height Adjuster | End Cap |
| | | |
| Pilaster | Horizontal & Vertical Hooks | Xtender |

FURRING STRIP DIMENSIONS

| | Block Size | | | | |
|-----------------------------|-----------------|-----------------|-----------------|-----------------|-----------------|
| | 100mm (4") | 159mm (6.25") | 203mm (8") | 254mm (10") | 305mm (12") |
| Height (full height blocks) | 362mm (14.25") | 362mm (14.25") | 362mm (14.25") | 362mm (14.25") | 362mm (14.25") |
| Height (half height blocks) | 159mm (6.25") | 159mm (6.25") | 159mm (6.25") | n/a | n/a |
| Width | 32mm (1.25") | 32mm (1.25") | 32mm (1.25") | 32mm (1.25") | 32mm (1.25") |
| Thickness | 4.8mm (0.1875") | 4.8mm (0.1875") | 4.8mm (0.1875") | 4.8mm (0.1875") | 4.8mm (0.1875") |

8.1 – TECHNICAL SPECIFICATIONS CONTINUED



Updated 07/20/11

Good. Solid. Green.™

LOGIX INSULATED CONCRETE FORMS GENERAL SPECIFICATIONS SHEET, CONT'D

90° CORNER FURRING STRING DIMENSIONS (full height blocks)

| | Block Size | | | | |
|---|-----------------|-----------------|-----------------|-----------------|-----------------|
| | 100mm (4") | 159mm (6.25") | 203mm (8") | 254mm (10") | 305mm (12") |
| Height (Vertical Strip) | 362mm (14.25") | 362mm (14.25") | 362mm (14.25") | 362mm (14.25") | 362mm (14.25") |
| Height (Horizontal Strip) | 50mm (2") | 50mm (2") | 50mm (2") | 50mm (2") | 50mm (2") |
| Width (Vertical Strip – one side of corner) | 48mm (1.875") | 48mm (1.875") | 48mm (1.875") | 48mm (1.875") | 48mm (1.875") |
| Width (Horizontal Strip – one side of corner) | 147mm (5.75") | 147mm (5.75") | 147mm (5.75") | 147mm (5.75") | 147mm (5.75") |
| Thickness | 4.8mm (0.1875") | 4.8mm (0.1875") | 4.8mm (0.1875") | 4.8mm (0.1875") | 4.8mm (0.1875") |

5 DESIGN PROPERTIES OF STEEL

| Property | Value |
|------------------|---------------------|
| Yield Stress, fy | Min. 276Mpa (40ksi) |

6 DESIGN PROPERTIES OF CONCRETE

| Properties | Value for each Block Size | | | | |
|---------------------------------|---------------------------|----------------------|----------------------|----------------------|----------------------|
| | 100mm (4") | 159mm (6.25") | 203mm (8") | 254mm (10") | 305mm (12") |
| 28day Compressive Strength | 20Mpa (2900psi) | 20Mpa (2900psi) | 20Mpa (2900psi) | 20Mpa (2900psi) | 20Mpa (2900psi) |
| Recommended Max. Aggregate Size | 9.5mm (0.375") | 9.5mm (0.375") | 9.5mm (0.375") | 9.5mm (0.375") | 9.5mm (0.375") |
| Recommended Slump | 127-178mm (5 – 7in.) | 127-178mm (5 – 7in.) | 127-178mm (5 – 7in.) | 127-178mm (5 – 7in.) | 127-178mm (5 – 7in.) |
| Min. Concrete Cover Attainable | 25mm (1in.) | 25mm (1in.) | 25mm (1in.) | 25mm (1in.) | 25mm (1in.) |

7 QUALITY ASSURANCE

Manufacturers of Logix ICF are certified under QAI carrying the QAI labels. Unannounced quality control inspections are conducted by QAI at least 4 times a year to ensure strict compliance with established quality control procedures.



Good. Solid. Green.™

Updated 07/20/11

LOGIX INSULATED CONCRETE FORMS
GENERAL SPECIFICATIONS SHEET, CONT'D

APPENDIX

TEST DESCRIPTIONS

To be read in reference to the tabulated test results in Section 3

www.logixicf.com

Pg.15 of 16

TECHNICAL SPECIFICATIONS + REFERENCES

Good. Solid. Green.™

www.logixicf.com

8 – 17



8.1 – TECHNICAL SPECIFICATIONS CONTINUED



Updated 07/20/11

Good. Solid. Green.™

LOGIX INSULATED CONCRETE FORMS GENERAL SPECIFICATIONS SHEET, CONT'D

Compressive Strength – indication of the amount of pressure required to compress the EPS to its yield point or by 10% of its original dimension, whichever occurs first.

Concrete Pour-in-place – assembly of a Logix ICF wall in which observations were recorded visually for the behaviour of the ICF wall during concrete pouring. Deflections before, during and after the pour were recorded. In addition, the form was structurally inspected to check for any structural damage caused to the ICF form during the pour. Using 203mm (8in) Logix ICF blocks, the wall size was 3.66m (12ft) high by 2.44m (8ft) wide.

Density – a measure of the weight of EPS per unit volume.

Dimensions – length, width and thickness of full size (finished product) EPS panels measured to ensure the final dimensions are within acceptable tolerances.

Dimensional Stability, Thermal & Humid Aging – a measure of dimensional change in EPS after exposure to hot and cold temperatures at high relative humidity for seven days. The EPS is normally exposed to temperatures of 70°C (158°F) and -40°C (-40°F) for seven days at 97% or ambient humidity. After exposure the dimensions of the EPS samples are measured at room temperature. The tabulated value is expressed as a percent change in dimensions before and after exposure. The smaller the percent change the smaller the change in dimensions.

Fire Endurance Test – fire test of a wall assembly, with cast-in-place concrete. The non-fire exposed side of the wall has no cover or protective barrier; the fire exposed side is covered with 25.4mm (1½") drywall over the EPS. The wall assembly is subjected to a bearing load of 360kips while exposed to fire until a certain temperature on the wall is reached. The time to reach that temperature including observations are recorded. After the fire test the wall assembly is subjected to the impact, cooling and erosion effects of a hose stream – the hose stream test.

Flammability – fire test on the polypropylene web to determine the burning characteristics of the web material. With the web supported in a horizontal position, a flame is applied at one end. The flame front distance is the distance the flame travels from the applied end to the point the flame goes out. The linear burn rate is the rate it takes to travel the flame front distance.

Flame Spread & Smoke Developed Rating – flame spread and smoke developed rating is determined from a fire test. Flame spread and smoke developed rating is a surface burning characteristic of a material and is not related to the fire resistance of a material. Flame spread rating is an indication of how fast fire will spread over the EPS from the original flame source. Smoke developed rating is an indication of how much smoke is generated during the fire test. The tabulated values are relative numbers based on calculations from the fire test results. The number is compared to asbestos and red oak, which have a rating of 0 and 100, respectively. Flame spread ratings provide an indication, particularly useful for fire officials, of how fast fire may spread in a building based on the building's materials. The National Fire Protection Agency (NFPA) classifies a material's suitability for use in construction based on its flame spread index.

Flexural Strength – measured as the amount of pressure it takes to reach the breaking load of EPS samples in bending. Samples are supported at the ends and a concentrated load is applied at the mid-span of the samples. The load is gradually increased until the samples fail.

Formaldehyde Emission – a measure of the amount of formaldehyde released from the EPS when heated to 120°F (49°C).

Fungi Resistance – a measure of the amount of fungi growth on the EPS when exposed to certain types of fungi.

Lateral Fastener Resistance – test to determine the lateral strength of Type S and Type W drywall screws fastened to the web. A concentrated load is applied perpendicular to the axis of the screw, which is fastened to the web. The load is gradually increased and tested to failure. Deflections are recorded during the duration of the tests.

www.logixicf.com

Pg.16 of 16

www.logixicf.com

Good. Solid. Green.™

8 – 18





Updated 07/20/11

Good. Solid. Green.™

LOGIX INSULATED CONCRETE FORMS GENERAL SPECIFICATIONS SHEET, CONT'D

Limiting Oxygen Index – a measure of the EPS to sustain a flame. The measurement is described as the amount of oxygen required (expressed as a percentage) to just support flaming combustion of the EPS when exposed to a flowing mixture of nitrogen and oxygen. The tabulated value is the amount of oxygen in the nitrogen/oxygen mixture required to just keep the EPS aflame.

Shear Strength – test to determine the shear strength of the polypropylene web.

Smoke Density Rating – a measure of the relative amount of smoke produced by the burning of the polypropylene web. The tabulated value is the amount of loss of light transmission through the smoke produced from the burning of the web, expressed as a percentage.

Smoke Developed Rating – see Flame Spread Rating.

Standard Room Fire Test – fire test of a room assembly where one corner of the room is built with Logix ICF blocks with cast-in-place concrete, and covered with ½" drywall. The room is exposed to a column of fire originating in the corner of the room adjacent to the ICF. The ICF is exposed to the fire for 15 minutes and observations recorded. The tabulated value is based on observations that showed melting of the EPS did not extend outside of the column of fire, smoke generated was not excessive, and since there was no damage to the concrete the structural integrity of the wall remained in place. Using 159mm (6.25in) ICF blocks, the size of the corner built with ICF was 2.44m (8ft) long in one direction, 2.44m (8ft) long in the other direction, and 2.44m (8ft) high.

Tensile Strength – test to determine the tensile strength of the polypropylene web.

Thermal Resistance – a measure of a materials resistance to heat flow through the EPS. The higher the R-value the greater the resistance to heat flow, the better the insulator.

Water Absorption – a measure of the ability of the EPS to absorb water. The tabulated value is a ratio of the weight of water absorbed by the EPS to the weight of the EPS dry, expressed as a percentage. The smaller the value the less water absorbed by the EPS.

Water Vapour Permeance – the rate at which water vapour will pass through the EPS. During the test, a vapour pressure difference between the two sides of the EPS is produced. The tabulated value is the rate at which the vapour passes through the EPS. The smaller the value the lower the water vapour permeance of the EPS.

Withdrawal Fastener Resistance – test to determine the withdrawal strength (or pullout strength) of Type S and Type W drywall screws fastened to the web. A concentrated load was applied parallel to the axis of the screw, which is fastened to the web. The load is gradually increased and tested to failure.

8.2 – MATERIAL SAFETY DATA SHEET



Material Safety Data Sheet - Expanded Polystyrene (EPS)
in Logix Insulated Concrete Forms

Issue Date: July, 2010

MATERIAL SAFETY DATA SHEET

**Material Safety Data Sheet – Expanded Polystyrene (EPS)
in Logix Insulated Concrete Forms**

SECTION 1 - PRODUCT INFORMATION

Manufacturer Name: LOGIX INSULATED CONCRETE FORMS LTD.

Address: 199 – 1917 West 4th Ave
Vancouver, British Columbia, Canada
V6J 1M7

Emergency Phone: 604-831-8528

Product Use: Stay-In-Place Insulated Concrete Forms

Suppliers: Flint Hills Resources
PO Box 2917
Wichita, Kansas 67201
316-828-3477

SECTION 2 - PREPARATION INFORMATION

Contact Name: Francis B Roma

Phone: 1-866-944-0153

Date Issued: July 31, 2010

SECTION 3 - HAZARDOUS INGREDIENTS

| Chemical Name | CAS No. | Content |
|--|-----------|---------|
| Benzene Ethenyl-Homopolymer (Common Name: Polystyrene) | 9003-53-6 | 99% |
| Pentane | 109-66-0 | <1% |

SECTION 4 - PHYSICAL DATA

Physical State: Solid

Odour & appearance: Slight Hydrocarbon Odour, White In Color

Specific Gravity: (Water = 1) 0.02 To 0.03

Vapour Pressure: N/A

Evaporation Rate: None

Boiling Point: N/A

Freezing Point: N/A

Melting Point: Softens at 100°C (212°F) & begins melting at higher temperatures.

Page 1 of 3

Good. Solid. Green.™

www.logixicf.com

8 – 2 0



Rev. Nov 04/11

8.2 – MATERIAL SAFETY DATA SHEET

CONTINUED



Material Safety Data Sheet - Expanded Polystyrene (EPS)
in Logix Insulated Concrete Forms

Issue Date: July, 2010

SECTION 5 - FIRE OR EXPLOSION HAZARDS

Explosive Hazards: Fire gives off black smoke consisting of carbon monoxide (< 10ppm), carbon dioxide (500ppm), oxides of nitrogen (4ppm), including trace of amounts of pentane, aldehydes and ketones. Fire hazards increase with presence of ignition sources or high concentrations of dust from work sites.

Means of Extinction: Use water spray, dry chemical, foam or carbon dioxide to extinguish flames.

Flash Point: 698°F (370°C)

Auto Ignition Temperature: 880°F (471°C)

SECTION 6 - REACTIVITY DATA

Unstable Conditions: Unstable when exposed to high temperatures. Recommended maximum use temperature of 165°F (75°C).

Incompatible materials: Not compatible with materials containing primarily of hydrocarbons, aldehydes, esters and amines

Hazardous Polymerization: Does not occur

Hazardous Decomposition: High heat or combustion produces black smoke consisting of carbon monoxide (< 10ppm), carbon dioxide (500ppm), oxides of nitrogen (4ppm), including trace of amounts of pentane, aldehydes and ketones.

Conditions of reactivity: Products react to high temperatures and strong oxidizers.

SECTION 7 - PREVENTATIVE MEASURES

Personal Protective Equipment:

Eye Protection: Approved safety goggles when applying fasteners, sanding or sawing.

Skin protection: Approved gloves and/or sleeves should be worn if sensitive to material composition of products.

Respiratory Protection: Approved dust mask when sanding, sawing or when working in high dust/particulates environment. In areas of high dust, vapor or mist content exceeding safe exposure limits use NIOSH or MSHA approved air purifiers or air supplied respirators.

Ventilation: Maintain proper ventilation in areas prone to static discharge (high dust environment) or products prone to combustion. Wear approved dust masks and maintain proper ventilation when hot-knifing product in enclosed areas.

Leaks or Spills: Loose material can be vacuumed or swept and placed in disposal containers.

Waste disposal: This material can be disposed of in accordance with local, state/provincial and federal regulations. This material is not considered a hazardous waste.

Handling: Take special precautions in handling and unloading product onto the construction site. When loading or unloading from trucks use either proper lifting equipment or use a minimum of 2 persons when manually loading or unloading pallets from trucks.

Page 2 of 3

Good. Solid. Green.™

www.logixicf.com

8-21



REPRINTED 2013

Rev. Nov 04/11

TECHNICAL SPECIFICATIONS + REFERENCES

8.2 – MATERIAL SAFETY DATA SHEET

CONTINUED



Material Safety Data Sheet - Expanded Polystyrene (EPS)
in Logix Insulated Concrete Forms

Issue Date: July, 2010

Storage: Storage locations should be in an area that will minimize damage or soiling to products. Protection should be provided in cases where stored products could be exposed, for more than 2 weeks, to UV or freezing rain or snow conditions. Keep products away from heat, sparks, flames or other ignition sources.

SECTION 8 - FIRST AID MEASURES

Eyes: Flush eyes with water for several minutes. Get medical attention if eye irritation persists or particulates are difficult to remove from the eye.

Skin: This material is not considered to be a skin irritant. In cases where irritation may occur to extra sensitive skin, wash with soap and water for several minutes. Get medical attention if skin irritation develops or persists.

Ingestion: This material is not considered to be hazardous when ingested but may cause blockage of air passage if large pieces are ingested. Get medical attention and apply proper first aid for persons with air passage blocked.

SECTION 9 - TOXICOLOGICAL PROPERTIES

Primary Route of Entry: Eyes, Skin, Inhalation

Effects of Acute Exposure:

Eyes: When hot-knifing material, vapors may cause irritation to eyes.

Skin: This material is not considered to be a skin irritant. Products may contain small particulates of dust accumulated naturally from surrounding environment, which may cause skin irritation with possible mild discomfort on extra sensitive skin.

Inhalation: When hot-knifing vapors may be cause irritation to nose and throat. Dizziness may occur in poorly ventilated areas when hot-knifing.

Effects of Chronic Exposure: Exposure to vapors may aggravate existing respiratory conditions, such as asthma, bronchitis and inflammatory or fibrotic respiratory disease.

TO THE BEST OF OUR KNOWLEDGE THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE. HOWEVER, NEITHER THE ABOVE NAMED MANUFACTURER OR SUPPLIER NOR ANY OF ITS SUBSIDIARIES ASSUMES ANY LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Page 3 of 3

Good. Solid. Green.™

www.logixicf.com

8 – 22



Rev. Nov 04/11

8.3 – RECOMMENDED INDUSTRY PRACTICE FOR PLACING REINFORCING BARS

Reprinted from: THE MANUAL OF STANDARD PRACTICE by the Concrete Reinforcing Steel Institute, January 1997.

RECOMMENDED INDUSTRY PRACTICE FOR PLACING REINFORCING BARS*

1. Introduction

These recommendations for placing reinforcing bars are partially based upon the ACI Building Code.

2. General

Reinforcing bars should be accurately placed in the positions shown on the placing drawings and adequately tied and supported before concrete is placed, and secured against displacement within the tolerances recommended in Section 8.

Welding of crossing bars (tack welding) should not be permitted for assembly of reinforcement unless authorized by the Architect/Engineer.

3. Surface Condition of Reinforcement

At the time of concrete placement, all reinforcing bars should be free of mud, oil, or other deleterious materials. Reinforcing bars with rust, mill scale, or a combination of both should be considered as satisfactory, provided the minimum dimensions, weight, and height of deformations of a hand-wire-brushed test specimen are not less than the applicable ASTM specification requirements.

4. Bending

Reinforcing bars should not be bent or straightened in a manner that will injure the material. Bars with kinks or improper bends should not be used. Except for realignment of #7 through #18 rebar up to about 30° bend and #3 through #6 rebar up to about a 45° bend, no bars partially embedded in concrete should be field bent, except as shown on the project drawings or permitted by the Architect/Engineer.

5. Spacing of Reinforcement

The clear distance between parallel reinforcing bars in a layer should not be less than the nominal diameter of the bars, nor 1 in. Clear distance should also not be less than one and one-third times the nominal maximum size of the coarse aggregate, except if in the judgement of the Architect/Engineer, workability and methods of consolidation are such that concrete can be placed without honeycomb or voids.

Where parallel reinforcement is placed in two or more layers, the bars in the upper layers should be placed directly above those in the bottom layer with the clear distance between layers not less than 1 in.

Groups of parallel reinforcing bars bundled in contact, assumed to act as a unit, not more than four in any one bundle may be used only when stirrups or ties enclose the bundle. Bars larger than #11 should not be

bundled in beams or girders. Individual bars in a bundle cut off within the span of flexural members should terminate at different points with at least 40 bar diameters stagger. Where spacing limitations and minimum clear cover are based on bar size, a unit of bundled bars should be treated as a single bar of a diameter derived from the equivalent total area.

In walls and slabs other than concrete joist construction, the principal reinforcement should not be spaced farther apart than three times the wall or slab thickness, nor more than 18 in.

In spirally reinforced and tied columns, the clear distance between longitudinal bars should not be less than one and one-half times the nominal bar diameter, nor 1½ in.

The clear distance limitation between bars should also apply to the clear distance between a contact lap splice and adjacent splices or bars.

6. Splices in Reinforcement**

6.1 General

Splicing of reinforcing bars should be either by lapping, mechanical connections, or by welding.

Splices of reinforcing bars should be made only as required or permitted on the project drawings or in the project specifications, or as authorized by the Architect/Engineer. All welding should conform to the current edition of "Structural Welding Code—Reinforcing Steel" (ANSI/AWS D1.4).

6.2 Lap Splices

Lap splices of #14 and #18 bars should not be used, except in compression only to #11 and smaller bars.

Lap splices of bundled bars should be based on the lap splice length recommended for individual bars of the same size as the bars spliced, and such individual splices within the bundle should not overlap each other. The length of lap should be increased 20 percent for a 3-bar bundle and 33 percent for a 4-bar bundle.

Bar laps placed in contact should be securely wired together in such a manner as to maintain the alignment of the bars and to provide minimum clearances.

Bars spliced by noncontact lap splices in flexural members should not be spaced transversely farther apart than one-fifth the required length of lap nor 6 in.

*For more complete recommendations on bar placement, see *Placing Reinforcing Bars* available from the Concrete Reinforcing Steel Institute.

**See *Reinforcement: Anchorages, Lap Splices and Connections* by the Concrete Reinforcing Steel Institute.

8.4 – STANDARD PRACTICE - SPLICING & DOWELS

Lap Splices




Figure 1a: Contact lap splices

A lap is when two pieces of rebar overlap to form a continuous line. This helps transfer loads properly throughout the structure. There are two types of lap splices: contact lap and non-contact lap splices (see Figure 1a and 1b). The lapped sections of contact lap splices are wired together. Lapped sections of non-contact lap splices do not touch and are permitted in practice provided the distance between lap sections meet the specified code requirements.

When using LOGIX ICFs non-contact lap splices can be used in lieu of contact lap splices.




Figure 1b: Non-contact lap splices

Lap Splices in Horizontal Rebar

In traditional construction methods, contact lap splices are more commonly used because it offers the most reliable method of ensuring the lapped sections are secure against displacement, especially during concrete pours. LOGIX ICFs can accommodate contact lap splices. However, the rebar slots in the LOGIX webs are also designed to accommodate non-contact lap splices,

8.4 – STANDARD PRACTICE - SPLICING & DOWELS CONTINUED




Figure 2a: Contact lap splices




Figure 2b: Non-contact lap splices




Figure 3: Vertical rebar in LOGIX ICF wall system

ensuring the horizontal rebar stays in place (see **Figure 2a** and **2b**). This minimizes the need to wire tie lapped sections and reduces labor.

The length of a lapped section (or lap length) varies depending mainly on the loading conditions, rebar size, rebar spacing, rebar grade and concrete strength. As a general rule, LOGIX recommends a lap length of 40d or 24", whichever is greater, for residential construction (see **Figure 1a** and **1b**).

Lap Splices in Vertical Rebar

For the same reason as horizontal rebar, contact lap splices are also more commonly used in traditional construction methods. However, contact lap splices are not necessary when using LOGIX ICFs. The LOGIX web ties, which are spaced horizontally every 8" (203mm) and about 5.25" (133mm) vertically per block, provides enough stability for placement of vertical rebar. Vertical rebar can be further secured if it is slid through a staggered pattern of horizontal rebar. The slots in the webs have been designed to accommodate this (see **Figure 3**).

8.4 – STANDARD PRACTICE - SPLICING & DOWELS CONTINUED

Footing Dowels





Figure 4: Wall/Footing connection

Footing dowels connects the wall to the footing (see **Figure 4**). This prevents wall movement at the wall/footing joint caused mainly by soil loads. In residential construction, the vertical rebar in the wall itself does not contribute to the strength of the wall/footing connection and hence is not required to splice with the footing or match the spacing of the footing dowels. In cases, where lap splice may be required, non-contact lap splices are permitted.



R611.7.1.4

Lap Splices –Building & Design Code References

International Building Code 2003 (IBC 2003),
R611.7.1.4:

“R611.7.1.4 Lap Splices. Where lap splicing of vertical or horizontal reinforcing steel is necessary, the lap splice shall be in accordance with Figure R611.7.1.4 and a minimum of $40d_b$, where d_b is the diameter of the smaller. The maximum distance between noncontact parallel bars at a lap splice shall not exceed $8d_b$.”

National Building Code 1995 (NBC 1995), 4.3.3.1:

Clause 4.3.3.1 references concrete design code, CSA A23.3 (specifically CSA A23.3, 12.14.2.3):

“12.14.2.3

Bars spliced by lap splices in flexural members shall have a transverse spacing not exceeding the lesser of one-fifth of the required lap splice length or 150mm.”

8.5 – LOGIX R-VALUES

| LOGIX FORM PANELS | STANDARD | TAPER TOP | BRICK LEDGE | TRANSITION |
|-------------------|---|---|---|---|
| STANDARD | | | | |
| | LOGIX R1/R2 (RSI) ¹ 23/24 (4/4.25) | LOGIX PLATINUM 26/27 (4.56/4.81) | LOGIX R1/R2 (RSI) ¹ 23/24 (4/4.25) | LOGIX PLATINUM 26/27 (4.56/4.81) |
| TAPER TOP | | | | |
| | | LOGIX R1/R2 (RSI) ¹ 23/24 (4/4.25) | LOGIX PLATINUM 26/27 (4.56/4.81) | LOGIX R1/R2 (RSI) ¹ 23/24 (4/4.25) |
| BRICK LEDGE | | | | |
| | | | LOGIX R1/R2 (RSI) ¹ 23/24 (4/4.25) | LOGIX PLATINUM 26/27 (4.56/4.81) |
| TRANSITION | | | | |
| | | | | LOGIX R1/R2 (RSI) ¹ 23/24 (4/4.25) |
| | | | | LOGIX PLATINUM 26/27 (4.56/4.81) |

1. R1 denotes total R-value of form panels only (per ASTM C518 at average mean temperature of 75deg F.). R2 denotes total R-value of a wall assembly consisting of form panels, 4 inch concrete core, 1/2 inch drywall and interior airfilm. R1 and R2 are based on imperial units. R-values are based on independent testing conducted by Intertek Testing Services.

8.5 – LOGIX R-VALUES CONTINUED

| LOGIX FORM PANELS | XRV4 | XRV5 | XRV6 | XRV7 | XRV8 | | | | | |
|--------------------------|----------------------|---------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| STANDARD | | | | | | | | | | |
| | LOGIX | LOGIX PLATINUM | LOGIX | LOGIX PLATINUM | LOGIX | LOGIX PLATINUM | LOGIX | LOGIX PLATINUM | | |
| R1/R2 (RSI) ¹ | 28/29 (4.91/5.16) | 32/33 (5.6/5.85) | 32/33 (5.64/5.89) | 37/38 (6.43/6.68) | 36/38 (6.36/6.61) | 41/43 (7.26/7.51) | 40/42 (7.09/7.34) | 46/47 (8.09/8.34) | 44/46 (7.82/8.07) | 51/52 (8.92/9.17) |
| TAPER TOP | | | | | | | | | | |
| | LOGIX | LOGIX PLATINUM | LOGIX | LOGIX PLATINUM | LOGIX | LOGIX PLATINUM | LOGIX | LOGIX PLATINUM | LOGIX | LOGIX PLATINUM |
| R1/R2 (RSI) ¹ | 28/29 (4.91/5.16) | 32/33 (5.6/5.85) | 32/33 (5.64/5.89) | 37/38 (6.43/6.68) | 36/38 (6.36/6.61) | 41/43 (7.26/7.51) | 40/42 (7.09/7.34) | 46/47 (8.09/8.34) | 44/46 (7.82/8.07) | 51/52 (8.92/9.17) |
| BRICK LEDGE | | | | | | | | | | |
| | LOGIX | LOGIX PLATINUM | LOGIX | LOGIX PLATINUM | LOGIX | LOGIX PLATINUM | LOGIX | LOGIX PLATINUM | LOGIX | LOGIX PLATINUM |
| R1/R2 (RSI) ¹ | 28/29 (4.91/5.16) | 32/33 (5.6/5.85) | 32/33 (5.64/5.89) | 37/38 (6.43/6.68) | 36/38 (6.36/6.61) | 41/43 (7.26/7.51) | 40/42 (7.09/7.34) | 46/47 (8.09/8.34) | 44/46 (7.82/8.07) | 51/52 (8.92/9.17) |
| TRANSITION | | | | | | | | | | |
| | LOGIX | LOGIX PLATINUM | LOGIX | LOGIX PLATINUM | LOGIX | LOGIX PLATINUM | LOGIX | LOGIX PLATINUM | LOGIX | LOGIX PLATINUM |
| R1/R2 (RSI) ¹ | 28/29 (4.91/5.16) | 32/33 (5.6/5.85) | 32/33 (5.64/5.89) | 37/38 (6.43/6.68) | 36/38 (6.36/6.61) | 41/43 (7.26/7.51) | 40/42 (7.09/7.34) | 46/47 (8.09/8.34) | 44/46 (7.82/8.07) | 51/52 (8.92/9.17) |

1. R1 denotes total R-value of form panels only (per ASTM C518 at average mean temperature of 75deg F). R2 denotes total R-value of a wall assembly consisting of form panels, 4 inch concrete core, 1/2 inch drywall and interior airfilm. R1 and R2 are based on imperial units. R-values are based on independent testing conducted by Intertek Testing Services.

8.5 – LOGIX R-VALUES CONTINUED

| LOGIX FORM PANELS | XRV4 | XRV5 | XRV6 | 7XRV | XRV8 | | | | | |
|-------------------|--------------------------------------|--|--------------------------------------|--|--|--|--|--|--|--|
| XRV4 | | | | | | | | | | |
| | LOGIX R1/R2 (RSI) ¹ | LOGIX PLATINUM 38/39 (6.64/6.89) | LOGIX 37/39 (6.55/6.8) | LOGIX PLATINUM 42/44 (7.47/7.72) | LOGIX 41/43 (7.27/7.52) | LOGIX PLATINUM 47/49 (8.29/8.54) | LOGIX 45/47 (8/8.25) | LOGIX PLATINUM 52/53 (9.12/9.37) | LOGIX 50/51 (8.73/8.98) | LOGIX PLATINUM 57/58 (9.95/10.2) |
| XRV5 | | | | | | | | | | |
| | | | LOGIX R1/R2 (RSI) ¹ | LOGIX PLATINUM 41/43 (7.27/7.52) | LOGIX 45/47 (8/8.25) | LOGIX PLATINUM 52/53 (9.12/9.37) | LOGIX 50/51 (8.73/8.98) | LOGIX PLATINUM 57/58 (9.95/10.2) | LOGIX 54/55 (9.46/9.71) | LOGIX PLATINUM 61/63 (10.78/11.03) |
| XRV6 | | | | | | | | | | |
| | | | | LOGIX R1/R2 (RSI) ¹ | LOGIX PLATINUM 50/51 (8.73/8.98) | LOGIX 54/55 (9.46/9.71) | LOGIX PLATINUM 61/63 (10.78/11.03) | LOGIX 58/59 (10.18/10.43) | LOGIX PLATINUM 66/67 (11.61/11.86) | |
| XRV7 | | | | | | | | | | |
| | | | | | | LOGIX R1/R2 (RSI) ¹ | LOGIX PLATINUM 58/59 (10.18/10.43) | LOGIX 62/63 (10.91/11.16) | LOGIX PLATINUM 71/72 (12.44/12.69) | |
| XRV8 | | | | | | | | | | |
| | | | | | | | | LOGIX R1/R2 (RSI) ¹ | LOGIX PLATINUM 66/67 (11.64/11.89) | LOGIX PLATINUM 75/77 (13.27/13.52) |

1. R1 denotes total R-value of form panels only (per ASTM C518 at average mean temperature of 75deg F.). R2 denotes total R-value of a wall assembly consisting of form panels, 4 inch concrete core, 1/2 inch drywall and interior airfilm. R1 and R2 are based on imperial units. R-values are based on independent testing conducted by Intertek Testing Services.

